

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 16-03-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DCW990 41		843050000002 5 / BOOT DMS SIZE 6S		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 6S GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 6S	item as per specification
2	DCW990 50		843050000157 6 / BOOT DMS SIZE 13 LARGE		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 13 LARGE GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 13 LARGE	ITEM AS PER SPECIFIATI ON
3	DCC991 28		840570326640 2 / DRESS NO 3 WHITE HALF SLEEVES SIZE 2 WAIST 30" COLLAR 15"		160 / EACH/N UMBER						TECHNICAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 2 WAIST 30" COLLAR 15" GENERAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 2 WAIST 30"COLLAR 15"	THE ITEM IS PROCURE D AGAINST TENDER SAMPLE, AS PER SPECIFICA TION.
4	DCC991 33		840570326640 7 / DRESS NO 3 WHITE HALF SLEEVES SIZE 7 WAIST 40" COLLAR 16.5"		160 / EACH/N UMBER						TECHNICAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 7 WAIST 40" COLLAR 16.5" GENERAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 7 WAIST 40"COLLAR 16.5"	THE ITEM IS PROCURE D AGAINST TENDER SAMPLE, AS PER SPECIFICA TION.
5	DCC991 31		840570326640 5 / DRESS NO		160 / EACH/N						TECHNICAL SPECIFICATION - DRESS NO 3 WHITE HALF	THE ITEM IS

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			3 WHITE HALF SLEEVES SIZE 5 WAIST 36" COLLAR 16"		UMBER						SLEEVES SIZE 5 WAIST 36" COLLAR 16" GENERAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 5 WAIST 36" COLLAR 16"	PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.
6	DCC991 27		840570326640 1 / DRESS NO 3 WHITE HALF SLEEVES SIZE 1 WAIST 28" COLLAR 14.5"		160 / EACH/NUMBER						TECHNICAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 1 WAIST 28" COLLAR 14.5" GENERAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 1 WAIST 28" COLLAR 14.5"	the item is procured against tender sample, as per specification.
7	SCF9834 3		834559004023 1 / FLAG ALPHA U RECT NO 4 FITTED SZ 5.00X3.75FT		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG ALPHA U RECT NO 4 FITTED SZ 5.00X3.75FT GENERAL SPECIFICATION - FLAG ALPHA U RECT NO 4 FITTED SZ 5.00X3.75FT	
8	SCF9860 4		834559571588 5 / FLAG NUMERAL ONE RECT NO 4 FITTED		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NUMERAL ONE RECT NO 4 FITTED GENERAL SPECIFICATION - FLAG NUMERAL ONE RECT NO 4 FITTED	
9	SCF9843 0		834559571593 4 / FLAG NUMERAL ZERO RECT NO 4 FITTED SZ 5.00X3.75FT		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NUMERAL ZERO RECT NO 4 FITTED SZ 5.00X3.75FT GENERAL SPECIFICATION - FLAG NUMERAL ZERO RECT NO 4 FITTED SZ 5.00X3.75FT	
10	DCW990 43		843050000003 3 / BOOT DMS SIZE 8L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8L	ITEM AS PER SPECIFICATION
11	DCC991 38		840570326641 2 / DRESS NO 3 WHITE HALF SLEEVES SIZE 12 WAIST 50" COLLAR 18.5"		160 / PAIR						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	THE ITEM IS PROCURED AGAINST TENDER SAMPLE,

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
12	DCC99135		8405703266409 / DRESS NO 3 WHITE HALF SLEEVES SIZE 9 WAIST 44" COLLAR 17.5"		160 / PAIR						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	AS PER SPECIFICATION. THE ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.
13	DCC99134		8405703266408 / DRESS NO 3 WHITE HALF SLEEVES SIZE 8 WAIST 42" COLLAR 17"		160 / EACH/NUMBER						TECHNICAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 8 WAIST 42" COLLAR 17" GENERAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 8 WAIST 42" COLLAR 17"	THE ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.
14	DCW99053		8430500001578 / BOOT DMS SIZE 14 LARGE		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE	ITEM AS PER SPECIFICATION
15	DCW99048		8430500000034 / BOOT DMS SIZE 9S		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S	ITEM AS PER SPECIFICATION
16	DCW99046		8430500000036 / BOOT DMS SIZE 9L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L	ITEM AS PER SPECIFICATION
17	SCF98680		8345595715861 / FLAG NUMERAL SIX REC NO 4 FITTED SZ 5.00X3.75FT		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NUMERAL SIX REC NO 4 FITTED SZ 5.00X3.75FT GENERAL SPECIFICATION - FLAG NUMERAL SIX REC NO 4 FITTED SZ 5.00X3.75FT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
18	DCC99132		840570326640 6 / DRESS NO 3 WHITE HALF SLEEVES SIZE 6 WAIST 38" COLLAR 16.5"		160 / EACH/NUMBER						TECHNICAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 6 WAIST 38" COLLAR 16.5" <u>GENERAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 6 WAIST 38" COLLAR 16.5"</u>	THE ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.
19	DCC98670		840550069257 9 / OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II		120 / EACH/NUMBER						TECHNICAL SPECIFICATION - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II <u>GENERAL SPECIFICATION - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II</u>	ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.
20	DCC99180		840550069257 9 / OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II		120 / EACH/NUMBER						TECHNICAL SPECIFICATION - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II <u>GENERAL SPECIFICATION - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II</u>	ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.
21	DCC99181		840550069258 0 / OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III		120 / EACH/NUMBER						TECHNICAL SPECIFICATION - OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III <u>GENERAL SPECIFICATION - OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III</u>	ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.
22	DCC98671		840550069258 0 / OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III		120 / EACH/NUMBER						TECHNICAL SPECIFICATION - OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III <u>GENERAL SPECIFICATION - OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III</u>	ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
23	DCW99045		843050000003 1 / BOOT DMS SIZE 8S		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8S <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8S	ITEM AS PER SPECIFIATI ON
24	DCC99136		840570326641 0 / DRESS NO 3 WHITE HALF SLEEVES SIZE 10 WAIST 46" COLLAR 17.5"		160 / PAIR						TECHNICAL SPECIFICATION - null <u>GENERAL SPECIFICATION -</u> null	THE ITEM IS PROCURE D AGAINST TENDER SAMPLE, AS PER SPECIFICA TION.
25	SCF98683		834559571583 7 / FLAG NUMERAL THREE RECT NO 4 FITTED SZ 5.00X3. 75FT		30 / EACH/N UMBER						TECHNICAL SPECIFICATION - FLAG NUMERAL THREE RECT NO 4 FITTED SZ 5.00X3.75FT <u>GENERAL SPECIFICATION - FLAG</u> NUMERAL THREE RECT NO 4 FITTED SZ 5.00X3.75FT	
26	DCW99044		843050000003 2 / BOOT DMS SIZE 8 M		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8 M <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8 M	ITEM AS PER SPECIFIATI ON
27	DCW99042		843050000002 9 / BOOT DMS SIZE 7		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7 <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7	ITEM AS PER SPECIFIATI ON
28	DCW99047		843050000003 5 / BOOT DMS SIZE 9 MEDIUM		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9 MEDIUM <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9 MEDIUM	ITEM AS PER SPECIFIATI ON
29	DCW99056		843050000157 7 / BOOT DMS SIZE 14 MEDIUM		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 MEDIUM <u>GENERAL SPECIFICATION - BOOT</u> DMS WITH FABRIC LACE 200 CM	ITEM AS PER SPECIFIATI ON

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SIZE 14 MEDIUM	
30	DCC99130		840570326640 / DRESS NO 3 WHITE HALF SLEEVES SIZE 4 WAIST 34" COLLAR 16"		160 / EACH/NUMBER						TECHNICAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 4 WAIST 34" COLLAR 16" GENERAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 4 WAIST 34" COLLAR 16"	THE ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.
31	SCF98682		8345595715840 / FLAG NUMERAL FOUR RECT NO 4 FITTED SZ 5.00X3.75FT		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NUMERAL FOUR RECT NO 4 FITTED SZ 5.00X3.75FT GENERAL SPECIFICATION - FLAG NUMERAL FOUR RECT NO 4 FITTED SZ 5.00X3.75FT	
32	SCF98681		8345595715843 / FLAG NUMERAL FIVE RECT NO 4 FITTED SZ 5.00X3.75FT		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NUMERAL FIVE RECT NO 4 FITTED SZ 5.00X3.75FT GENERAL SPECIFICATION - FLAG NUMERAL FIVE RECT NO 4 FITTED SZ 5.00X3.75FT	
33	SCF98684		8345595715834 / FLAG NUMERAL TWO RECT NO 4 FITTED SZ 5.00X3.75FT		43 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NUMERAL TWO RECT NO 4 FITTED SZ 5.00X3.75FT GENERAL SPECIFICATION - FLAG NUMERAL TWO RECT NO 4 FITTED SZ 5.00X3.75FT	
34	DCC99137		8405703266411 / DRESS NO 3 WHITE HALF SLEEVES SIZE 11 WAIST 48" COLLAR 18"		160 / PAIR						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	THE ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION.
35	DCC99129		8405703266403 / DRESS NO 3 WHITE HALF SLEEVES SIZE 3 WAIST 32" COLLAR 15.5"		160 / EACH/NUMBER						TECHNICAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 3 WAIST 32" COLLAR 15.5" GENERAL SPECIFICATION - DRESS NO 3 WHITE HALF SLEEVES SIZE 3	THE ITEM IS PROCURED AGAINST TENDER SAMPLE,

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WAIST 32"COLLAR 15.5"	AS PER SPECIFICATION.
36	DCW99049		8430500000045 / BOOT DMS SIZE 12L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L	ITEM AS PER SPECIFICATION
37	DNF99022	HTS-SFP-850	5915705248696 / SFP MODULE		2 / EACH/NUMBER	SFP-850				ITRF	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
38	DNF99222	SURT6000XLI	7021715030585 / 6KVA UPS	USE SELF	2 / SET						TECHNICAL SPECIFICATION - Power requirement 230v AC, 50 Hz Frequency 50/60 Hz Output current rating Power output 6 KVA front panel Sockets up to 03 back panel sockets up to 03 rixed/removable input supply cable unput & output power supply meters OR Apc ups SURT 5000xli, standard backup time 20/30 mins OR Avr 6000 VA with Standard Backup Time GENERAL SPECIFICATION - Power requirement 230v AC, 50 Hz Frequency 50/60 Hz Output current rating Power output 6 KVA front panel Sockets up to 03 back panel sockets up to 03 rixed/removable input supply cable unput & output power supply meters OR Apc ups SURT 5000xli, standard backup time 20/30 mins OR Avr 6000 VA with Standard Backup Time	
39	DNF99023	197/FLUKE 87	6625705045345 / MULTIMETER DIGITAL		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
40	DNF99126	ST4000NM0053/ST4000VX000	7025785207849 / 4TB SURVEILLANCE HARD DISK-SATA FOR NVR	CCTV System CHINA	1 / EACH/NUMBER	ST4000VX000	NA	Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888		CHINA	TECHNICAL SPECIFICATION - Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32 GENERAL SPECIFICATION - Marketing Name: Surveillance HDD Cache	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32	
41	DNF99197	BAT 12200 / WPG 200-12 AN	6130775153454 / MAINTENANCE FREE MARINE BATTERY 12V 200H	GRP POLICE BOAT (BATTERY CHARGER SYS)	2 / EACH/NUMBER	BAT 12200		M/S VETUS N.V. FOKKERSTRAAT 571 SCHIEDAM NETHERLANDS 3125 BD 010-4377700 / 010-4152634 KVK 24219798 0000 SALES@VETUS.NL		VETUS HOLLAND	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
42	DNO99029	13509102	4810775237127 / (C), CHECK VALVE, 1207, STORM TYPE, RIGHT-ANGLES, DN65, FLANGE, PN 10, FL;PN 10, CAST IRON GG 40.3 (ENJS 1020), COATED, WITH LOCKING DE		1 / EACH/NUMBER	Not Known					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
43	DNF99020	SERVO COTROL STAC JAPAN	6110705045037 / STABILIZER 3KVA I/P50-130V/160-240VAC50/60HZ O/P110/220V STAC	ELECTRICAL GENERAL USE	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DNO99030	3213-600GPD	4620705345046 / 600gpd commercial ro water purifier with pressure gauge and indicator board		1 / EACH/NUMBER	3213-600gpd					TECHNICAL SPECIFICATION - NAME: 600GPD COMMERCIAL RO WATER PURIFIER WITH PRESSURE GAUGE AND INDICATOR BOARD MODEL: 3213-600GPD SALT REJECTION RATE: 99.0% CAPACITY: 600GPD BRAND: HELLOPURE TYPE: 600GPD FLOW:95L/H TANK: 11G STEEL TANK GENERAL SPECIFICATION - NAME: 600GPD COMMERCIAL RO WATER PURIFIER WITH PRESSURE GAUGE AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											INDICATOR BOARD MODEL: 3213-600GPD SALT REJECTION RATE: 99.0% CAPACITY: 600GPD BRAND: HELLOPURE TYPE: 600GPD FLOW:95L/H TANK: 11G STEEL TANK	
45	DNF99024	SRX-300 / 210	701071520702 1 / JUNIPER FIREWALL SRX300	UFFAQ	1 / EACH/N UMBER	SRX-300 / 210		Juniper Networks, Inc. 1194 North Mathilda Avenue Sunnyvale, CA 94089 USA Phone: 888.JUNIPER (888.586.4737) or 408.745.2000 Fax: 408.745.2100 www.juniper.net	Juniper Networks. inc	ITRF	<u>TECHNICAL SPECIFICATION - As Attached</u> <u>GENERAL SPECIFICATION - As Attached</u>	
46	DNV99035	r1-e-9-26	674070527479 3 / THERMAL PRINTER		2 / EACH/N UMBER	THERMA L PRINTER					<u>TECHNICAL SPECIFICATION - 1.2 TB SSD</u> <u>GENERAL SPECIFICATION - 1.2 TB SSD</u>	
47	DNF99120	MD231 (CROWN) /EH1504 /EH1418	444079510254 4 / PREMI-AIR DEHUMIDIFIE RS,300W, 220/240V SIZE: 350X452X275 MM	DEHUMIDIFIE RS	4 / EACH/N UMBER	MD231 (CROWN) /EH1504/ EH1418					<u>TECHNICAL SPECIFICATION -</u> Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <u>GENERAL SPECIFICATION</u> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG	
48	DNF99123	SRT1000R MXLI/SRT 1000RML / EP- 1000T Elen Brand or equivalent	6130PK507263 7 / UPS 1 KVA WITH BATTERY ON LINE (10 Mint Backup time)		2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> AUTHORITY:SANCTION OF OFFICE EQUIPMENT-F22P CELL AT PN DOCKYARD.VIDE NHQ LETTER ST-S/3277/1014 DT 14 OCT 2010. <u>GENERAL</u> <u>SPECIFICATION - AUTHORITY:</u> SANCTION OF OFFICE EQUIPMENT-F22P CELL AT PN DOCKYARD.VIDE NHQ LETTER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ST-S/3277/1014 DT 14 OCT 2010.	
49	DNJ99202	55125-93L00-0EP	2895765222453 / TAB, TRIM (BLACK)	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN	CINS INSPECTIO N	<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
50	DNF95070	RG-NBS3100-24GT4SFP /RUIJIE/J9776A / J9772A+j4859c/RG-NBS3100-24GT4SFP	5895785207833 / NETWORK SWITCH HP 2530 24G/48G WITH 2/4 SFP MODULES	NETWORK SWITCH J9772A CHINA	1 / EACH/NUMBER	RG-NBS5200-48GT4xS/R8N88A-HP/J9776A/J9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA		<u>TECHNICAL SPECIFICATION - ATTACHED</u> <u>GENERAL SPECIFICATION - ATTACHED</u>	
51	DNF99125	DCC/HFB M/HW/120	6730705213201 / HDMI CABLE 30M DVI TO HDMI	OPERATOR CONSOLE DCC-2012016 PAKISTAN	10 / EACH/NUMBER	DCC-2012016	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, KHI 021-35363212	DATA COMM		<u>TECHNICAL SPECIFICATION - Make: Dell or HP DISPLAY</u> <u>CABLE</u> <u>GENERAL SPECIFICATION - Make: Dell or HP DISPLAY CABLE</u>	
52	DNF99186	SURT6000 XLI/SRV6KI	6130715194943 / 06 KVA ON LINE UPS	SMART-UPS ON-LINE5	1 / EACH/NUMBER	Smart-UPS On-Line SRC 220 V		Schneider Electric Industries SAS USA www.schneider-electric.com 998-1269702_US + 971 4 7099333 USA	APC by Schneider Electric		<u>TECHNICAL SPECIFICATION - Power Rating : 06KVA/3500 W</u> Nominal Output Voltage : 220 Vac single-phase UPS Nominal Input Voltage : 220/230 Vac single-phase UPS Input Frequency Range : 40 ? 70 Hz Output Frequency : 50/60 Hz Topology : Double-conversion Online Backup time : MINIMUM OF 05 MINUTES AND MAXIMUM FOR 15 MINUTES. <u>GENERAL SPECIFICATION - Power Rating : 06KVA/3500 W</u> Nominal Output Voltage : 220 Vac single-phase UPS Nominal Input Voltage : 220/230 Vac single-phase UPS Input Frequency Range : 40 ? 70 Hz Output Frequency : 50/60 Hz Topology : Double-conversion Online Backup time : MINIMUM OF 05 MINUTES AND MAXIMUM FOR 15 MINUTES.	
53	DNJ99117	55125-93L00-Y5S	2895765222454 / TAB, TRIM (WHITE)	SUZUKI DF300AP 300 HP OBM	6 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
54	DNJ99028	38890-98J00	2815765221422 /	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ACTUATOR, SHIFT								NIL	
55	DNF99004	DEFSTAN 61-3PT1	0562799101155 / BATTERY DRY LECLANCHET YPE 90 1.5V 4.125X3.187X8.703IN		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DNF99124	87-III/fluke 87-v	6625715088738 / FLUKE-87 DIGITAL MULTIMETER RANGE 1000V AC/DC USA	TEST EQUIPMENT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DNF98988	320623770280	5995705312146 / ufone 4g blaze device		1 / EACH/NUMBER	MF920U					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
58	DNF99199	rb2011 uias-rm / L009UIGS-RM	5915705246336 / mikrotik router		1 / EACH/NUMBER	rb2011 uias-rm					TECHNICAL SPECIFICATION - brocher is attached for detials GENERAL SPECIFICATION - brocher is attached for detials spec	
59	DNF99121	CC-01-00017	5935785232786 / CAT6A STP RJ45 CONNECTOR FOR ETHERNET CABLE		100 / EACH/NUMBER	RJ45					TECHNICAL SPECIFICATION - AS PER BROUCHER ENCLOSED a. Schneider Electric/Actassi Cat-6 RJ45 connectors/China/Rs 2700/50 Pcs . b. 3M Micro link /Cat-6 RJ45 Connectors/China/Rs 1999/100 Pcs. c. Black copper/Cat-6 RJ45 connectors/China/Rs 1350/100 Pcs. GENERAL SPECIFICATION - AS PER BROUCHER ENCLOSED a. Schneider Electric/Actassi Cat-6 RJ45 connectors/China/Rs 2700/50 Pcs . b. 3M Micro link /Cat-6 RJ45 Connectors/China/Rs 1999/100 Pcs. c. Black copper/Cat-6 RJ45 connectors/China/Rs 1350/100 Pcs.	
60	DNF95127	Kronos 15KVA / ST151	5836705172778 / UPS 15KVA/12KW	PCBRF	1 / EACH/NUMBER	Kronos 15KVA/A PC		M/s ALI BUISNESS MACHINES PVT.LTD.No-1-16.2nd Floor,Mujahid Plaza. Blue Area.Islamabad.ph 051-2870212	CHINA		TECHNICAL SPECIFICATION - Make/Model/Brand: APC Smart-RT 15KVA RMUPS-12KW-15000VA GENERAL SPECIFICATION - Make/Model/Brand: APC Smart-RT 15KVA RMUPS-12KW-15000VA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
61	DNF96135	MSII 10000 RT/ABLER EX UPS 10 KVA / GXT-10000MTP LUSC230	702579525879 2 / UPS 10 KVA with battery Pack for 17 mints Back Up Emerson/ABLE REX with accessories		3 / EACH/NUMBER	ABLEREX UPS 10 KVA / LiebertITA 10KVA/9KW UPS 230V/400 V					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
62	DNF99162	CS-FP3S52D-SC-SC-06	601571531193 6 / Optical Fiber patch Cord SM 9/125um OS2 G.652 LSZH Simplex 06M		8 / EACH/NUMBER	CS-FP3S52D-SC-SC-06					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
63	DNJ97509	6E5-11325-00	299076509964 3 / ANODE	E140JMH, YAMAHA ENGINE	23 / EACH/NUMBER	E140JMH	60CL100410G	YAMAHA LTD. 2500 SHINGAIWATA, SHIZUOKA, JAPAN Tel : +81 538 32 1115 Fax : +81 538 32 1634 Email/URL : info@seaquest.biz	YAMAHA LTD. 2500 SHINGAIWATA, SHIZUOKA, JAPAN Tel : +81 538 32 1115 Fax : +81 538 32 1634 Email/URL : info@seaquest.biz		TECHNICAL SPECIFICATION - MARINE GRADE ALUMINUM 0.20 KG TO 0.40 KG (200 G - 400 G) LENGTH 100 MM - 203 MM WIDTH 47MM - 60 MM HEIGHT /THICKNESS 6 MM - 20 MM M6 OR M10 THREAD GENERAL SPECIFICATION - MARINE GRADE ALUMINUM 0.20 KG TO 0.40 KG (200 G - 400 G) LENGTH 100 MM - 203 MM WIDTH 47MM - 60 MM HEIGHT /THICKNESS 6 MM - 20 MM M6 OR M10 THREAD	
64	DNF95462	0102-034021-226	482078515446 5 / OIL TEMPERATUR E CONTROLLER RANGE 0-300 C	L PAC /AC/PLANT	2 / EACH/NUMBER	OMRON ESC4	100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674.	CHINA		TECHNICAL SPECIFICATION - DIGITAL TEMPERATURE CONTROLLER /INDICATOR THERMOCOUPLE rtd OFTEN 199.9 TO 900c LED /LCD PANEL INDICATING RELAY OR SSR DRIVE (ALARM /CONTROL) 100-240 VAC (PANEL MOUNT) GENERAL SPECIFICATION - DIGITAL TEMPERATURE CONTROLLER /INDICATOR THERMOCOUPLE rtd OFTEN 199.9 TO 900c LED /LCD PANEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											INDICATING RELAY OR SSR DRIVE (ALARM /CONTROL) 100-240 VAC (PANEL MOUNT)	
65	DNF9627 2	AS-MP5E-17	692070520865 4 / AIMING SENSOR	G-3 SIMULATOR 2017	1 / ASSEM BLY	AS- MP5E-17	NA	M/S SOFT INOVATION SYSTEM 34-A/2, 1ST FLOOR LUXURY HOTEL, LALAZAR. MT KHAN ROAD KARACHI +9221385610277	M/S SOFT INNOVAT IVE SYSTEM S		TECHNICAL SPECIFICATION - AIMING SENSOR AS-MP5E-17 TECHNOLOGY INFRA RED VOLTAGE 3.0 VDC-4.0 VDC +-10% CURRENT 100 MA +-20% GENERAL SPECIFICATION - AIMING SENSOR AS-MP5E-17 TECHNOLOGY INFRA RED VOLTAGE 3.0 VDC-4.0 VDC +-10% CURRENT 100 MA +-20%	
66	DNF9627 3	AS- PISTOLE- 17	692070520865 6 / AIMING SENSOR	G-3 SIMULATOR 2017 PAK	1 / ASSEM BLY	AS- PISTOLE- 17	NA	M/S SOFT INOVATION SYSTEM 34-A/2, 1ST FLOOR LUXURY HOTEL, LALAZAR. MT KHAN ROAD KARACHI +9221385610277	M/S SOFT INNOVAT IVE SYSTEM S		TECHNICAL SPECIFICATION - AIMING SENSOR AS PISTOLE-17 TECHONOLGY INFRA RED VOLTAGE 3.0 VDC -4.0 VDC+-10% CURRENT 100 mA +-20% GENERAL SPECIFICATION - AIMING SENSOR AS PISTOLE-17 TECHONOLGY INFRA RED VOLTAGE 3.0 VDC -4.0 VDC+-10% CURRENT 100 mA +-20%	
67	DNJ9767 7	6CE- 12411-00	668576520249 9 / THERMOSTAT	OBM YAMAHA ENGINE FL300BETX JAPAN	4 / EACH/N UMBER	FL300BE TX	6CF- 1009814	YAMAHA MOTO CO LTD. 2500 SHINGAI IWATA SHIZUOKA JAPAN	YAMAHA JAPAN		TECHNICAL SPECIFICATION - OBM YAMAHA ENGINE FL300BETX JAPAN GENERAL SPECIFICATION - OBM YAMAHA ENGINE FL300BETX JAPAN	
68	SNF9930 7	SM-170- 380	594573522833 4 / PHASE SEQUENCE RELAY	STEERING CONTROL	8 / EACH/N UMBER	SM-170- 380	NIL	M/S FATEK AUTOMATION CORPORATION 26FL, No 29, Sec.2, jung,jeng E Road Danshuei Dist, New Taipei city 25170, Taiwan, R.O.C. TEL : +886-2-2808-2192 FAX : +886-2-2809-2618.	FATEK TAIWAN		TECHNICAL SPECIFICATION - M/S FATEK AUTOMATION CO TAIWAN GENERAL SPECIFICATION - M/S FATEK AUTOMATION CO TAIWAN	
69	SNF9930 4	LC1-D32- BL	599973522833 7 / CONTACTOR	STEERING CONTROL	5 / EACH/N UMBER	LC1-D32- BL	NIL	M/S FATEK AUTOMATION CORPORATION 26FL, No 29, Sec.2, jung,jeng E Road Danshuei Dist, New Taipei city 25170, Taiwan, R.O.C. TEL : +886-2-2808-2192 FAX : +886-2-2809-2618.	FATEK TAIWAN		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DNS975 25	5268375	432001603876 8 / PUMP SEA WATER	CUMMINS MAIN ENGINE CUMMINS	2 / EACH/N UMBER	QSB6.7- 305MD		M/s Cummins Inc 500 Jackson Street Columbus	M/s IMPEX NINE INC		TECHNICAL SPECIFICATION - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				MODEL QSB6. 7?305MD USA				IN, USA			USA CAGE 65KD2 USA <u>GENERAL SPECIFICATION</u> - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565 USA CAGE 65KD2 USA	
71	DNF96579	YSAPL22-DL24RHG / 153060718	621073520465 5 / INDICATION LIGHT (R-GREEN)	MONITORING & ALARM SYSTEM YSAPL22-DL24RHG KOREA	6 / EACH/NUMBER	YSAPL22-DL24RHG	NIL	87, HWANGMUL-RO, DONGDAEMUN-GU, SEOUL, KOREA		YONGSUNG KOREA	<u>TECHNICAL SPECIFICATION</u> - PANNEL INDICATION LIGHT IT'S A NORMAL INDICATION LIGHT THAT IS USED IN ELECTRICAL SWITCH BOARD. <u>GENERAL SPECIFICATION</u> - PANNEL INDICATION LIGHT IT'S A NORMAL INDICATION LIGHT THAT IS USED IN ELECTRICAL SWITCH BOARD.	
72	DNZ90597	D100801	431079513881 0 / CYLINDER LINER	MAIN AIR COMPRESSOR	2 / EACH/NUMBER	NO DATA AVAILABLE		UK		COMPAIR UK LTD	<u>TECHNICAL SPECIFICATION</u> - - <u>GENERAL SPECIFICATION</u> - -	
73	DNJ96980	8M010248 4 / 8M011724 9	304071521497 3 / GEAR HOUSING ASSEMBLY Complete, Silver (Counter Rotation X-Long)(1.75:1)	Mercury OBM Engine	1 / EACH/NUMBER	300 HP Mercury	2B469929	Murcery Marine W6250 Pioneer Road Fond du Lac Wisconsin USA		Murcery Marine USA	<u>TECHNICAL SPECIFICATION</u> - COMPLETE GEAR HOUSING ASSEMBLY SILVER (FACTORY FINISH) ROTATION: COUNTER ROTATION LENGTH: X - LONG GEAR RATIO: 1.75:01 (REDUCTION RATIO) HOUSING MATERIAL: ALUMINUM ALLOY BEARING: TAPERED ROLLER OR PRECISION ROLLER BEARINGS <u>GENERAL SPECIFICATION</u> - COMPLETE GEAR HOUSING ASSEMBLY SILVER (FACTORY FINISH) ROTATION: COUNTER ROTATION LENGTH: X - LONG GEAR RATIO: 1.75:01 (REDUCTION RATIO) HOUSING MATERIAL: ALUMINUM ALLOY BEARING: TAPERED ROLLER OR PRECISION ROLLER BEARINGS	
74	DNF96294	ML-1102S-A/ML-1102S-B (RJ-45 PORTS) /4V1D	609978516657 5 / FIBER MEDIA CONVERTER FOR IP CAMERAS	CCTV SYSTEM (PSS)	1 / PAIR	ML-1102S-A RJ45/4V1D		CETC Mansion No 5 walatong north street, Xicheng District, Beijing China 100120		M/S CETC international Co.Ltd	<u>TECHNICAL SPECIFICATION</u> - Optical Transceiver model number: ML-1102S-A ML-1102S-B (2 RJ-45 Ports sPEC: transceivers HAVING 100/1000 MBPS (GB) oem: MICROLINK <u>GENERAL SPECIFICATION</u> - Optical Transceiver model number: ML-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											1102S-A ML-1102S-B (2 RJ-45 Ports sPEC: transceivers HAVING 100/1000 MBPS (GB) oem: MICROLINK	
75	DNJ96180	8M010248 2 / 8M011724 7	304071521497 1 / GEAR HOUSING ASSEMBLY Complete, Silver (Standard XX-Long)(1.75:1)	Mercury OBM Engine	1 / EACH/NUMBER	300 HP Mercury	2B469929	Murcery Marine W6250 Pioneer Road Fond du Lac Wisconsin USA		Murcery Marine USA	TECHNICAL SPECIFICATION - 12 teeth with corresponding spline connection gear ratio: 1.75:01 for verado height case: 8.75 (222 mmm) width: 31 (787 mm) length : 53 (1346) weight : 56-62 kg (123-136 lbs) GENERAL SPECIFICATION - 12 teeth with corresponding spline connection gear ratio: 1.75:01 for verado height case: 8.75 (222 mmm) width: 31 (787 mm) length : 53 (1346) weight : 56-62 kg (123-136 lbs)	
76	DNJ96979	8M010248 2 / 8M011724 7	304071521497 1 / GEAR HOUSING ASSEMBLY Complete, Silver (Standard XX-Long)(1.75:1)	Mercury OBM Engine	1 / EACH/NUMBER	300 HP Mercury	2B469929	Murcery Marine W6250 Pioneer Road Fond du Lac Wisconsin USA		Murcery Marine USA	TECHNICAL SPECIFICATION - 12 teeth with corresponding spline connection gear ratio: 1.75:01 for verado height case: 8.75 (222 mmm) width: 31 (787 mm) length : 53 (1346) weight : 56-62 kg (123-136 lbs) GENERAL SPECIFICATION - 12 teeth with corresponding spline connection gear ratio: 1.75:01 for verado height case: 8.75 (222 mmm) width: 31 (787 mm) length : 53 (1346) weight : 56-62 kg (123-136 lbs)	
77	DNF96274	AS-G3E-17	299070520757 5 / AIMING SENSOR	G-3 SIMULATOR 2017 PAKISTAN	1 / EACH/NUMBER	AS-G3E-17	NA	M/S SOFT INOVATIVE SYSTEM 34-A/2, 1ST FLOOR,OPP LUXURY HOTEL, LALAZAR OFF. MT KHAN ROAD KARACHI TEL: +922135610429 +9221385610277		M/S SOFT INNOVATIVE SYSTEM S	TECHNICAL SPECIFICATION - TECHNOLOGY = INFRE RED VOLTAGE = 3 Vdc -4 Vdc +- 10 % CURRENT = 100 mA +- 20 % COLOR = BLACK WEIGHT = .025 KG WITH CLAMP GENERAL SPECIFICATION - TECHNOLOGY = INFRE RED VOLTAGE = 3 Vdc -4 Vdc +- 10 % CURRENT = 100 mA +- 20 % COLOR = BLACK WEIGHT = .025 KG WITH CLAMP	
78	DNS97525	5268375	432001603876 8 / PUMP SEA WATER	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD USA	2 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA		CUMMINS	TECHNICAL SPECIFICATION - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565 USA CAGE 65KD2 USA GENERAL SPECIFICATION - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											NAPERVILLE, IL 60565 USA CAGE 65KD2 USA	
79	DNZ9774 5	A12150	253078515898 0 / BRAKE LINING MATERIAL SIZE. 5/8	PORT DRAG HEAD WINCH	100 / FOOT			M/S CSTC CHINA/ABBASI TRADERS LTD	M/S CSTC CHINA..		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
80	DNZ9658 2	A12150	253078515898 0 / BRAKE LINING MATERIAL SIZE. 5/8	PORT DRAG HEAD WINCH	80 / FOOT			M/S CSTC CHINA/ABBASI TRADERS LTD	M/S CSTC CHINA..		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
81	DNF9733 8	2080/G	596375520732 5 / SMART LOOP MODULE 2080/G	FIRE ALARM 2080/G ITALY	1 / EACH/N UMBER	2080/G	NA	INIM ELECTRONICS ITLAY TEL +39 0735705007 FAX +390735704910	INIM ELECTR ONICS		TECHNICAL SPECIFICATION - OPERATING VOLTAGE: 230V AC -15% +10% 50/60 HZ MAX INTERNAL POWER CURRENT: 4A BATTERY SPECIFICATIONS: 12V @7AH OR 12V @17AH OPERATING TEMPERATURE: DA -5 A +40C DIMENSION: 48CM X 47CM X 13.5 CM WEIGHT: 8 KG MAKE: ITALY GENERAL SPECIFICATION - OPERATING VOLTAGE: 230V AC -15% +10% 50/60 HZ MAX INTERNAL POWER CURRENT: 4A BATTERY SPECIFICATIONS: 12V @7AH OR 12V @17AH OPERATING TEMPERATURE: DA -5 A +40C DIMENSION: 48CM X 47CM X 13.5 CM WEIGHT: 8 KG MAKE: ITALY	
82	DNZ9778 4	3973493	281578522379 9 / CYLINDER HEAD	120 KW MAIN DG # 1 & 2	1 / EACH/N UMBER	6CTA 8.3 GM155	78588535 & 78588536	CUMMINS ENGINE Co, LTD	CUMMIN S		TECHNICAL SPECIFICATION - DIESEL ENGINE CYLINDER HAD HIGH STRENGTH CAST IRON VALVE COUNT 12 VALVES (06 CYCLE 02 VALVES PER CYLINDER) WEIGHT: 78-85 KG (172-188 IBS) 950 M X 390 MM * 260MM GENERAL SPECIFICATION _DIESEL ENGINE CYLINDER HAD HIGH STRENGTH CAST IRON VALVE COUNT 12 VALVES (06 CYCLE 02 VALVES PER CYLINDER) WEIGHT: 78-85 KG (172-188 IBS) 950 M X 390 MM *	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											260MM	
83	DNS96456	3161223	471027035535 4 / OIL PIPE	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	1 / EACH/N UMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60	AB Volvo Penta Sweden		<u>TECHNICAL SPECIFICATION -</u> MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT) <u>GENERAL SPECIFICATION</u> _MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)	
84	DNF97170	05-00- 0049-00	635071519706 1 / 160 KV CONTROLLER	SCANNING MACHINE XIS- 6545 USA	1 / EACH/N UMBER	XIS-6545	ASTNC16 0SS2299	INC. 21481 FERRERO PARKWAY CITY OF INDUSTRY, CA-91789USA	ASTROP HYSICS USA		<u>TECHNICAL SPECIFICATION -</u> Used for Luggage Mail / Baggage Scanning <u>GENERAL</u> <u>SPECIFICATION -</u> Used for Luggage Mail / Baggage Scanning	
85	DNF96300	DCC/HFB M/HW/127	662570521320 2 / HEADPHONES WITH MIC	OPERATOR CONSOLE DCC-2012016 PAKISTAN	20 / EACH/N UMBER	DCC- 2012016	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212	DCC		<u>TECHNICAL SPECIFICATION -</u> Headphones with Mic DRIVER DIAMETER: 40MM EAR CUP OUTER 80-100 MM CABLE LENGTH 1.2 - 1.5 M 100G -300G 4 MM DIA MIC SIZE <u>GENERAL</u> <u>SPECIFICATION -</u> Headphones with Mic DRIVER DIAMETER: 40MM EAR CUP OUTER 80-100 MM CABLE LENGTH 1.2 - 1.5 M 100G -300G 4 MM DIA MIC SIZE	
86	DNF95463	5133311	291573513331 1 / OIL PRESSURE SENSOR	150KVA GENSET	2 / EACH/N UMBER	150KVA GENSET	OC		RA ELECTR ONICS GROUP ENGINEE RING SERVICE S SUIT 216 2ND FLOOR MASHRIQ UE CENTRE GULSHA N-E- IQBAL KARACHI		<u>TECHNICAL SPECIFICATION -</u> PART OF DIESEL GENERATOR PORT CATTERPILLER 55 KW CONTROL SYSTEM <u>GENERAL</u> <u>SPECIFICATION -</u> PART OF DIESEL GENERATOR PORT CATTERPILLER 55 KW CONTROL SYSTEM	
87	DNF96578	ED-786D/ Ed-D787	666570522104	DESTO EXPLOSIVE	1 / EACH/N	ED-786D/ d787		DESTO (HQ) CHAKLALA CANTT, RAWALPINDI-	DESTO (DEFENC		<u>TECHNICAL SPECIFICATION - 1.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			0 / HAND HELD EXPLOSIVE DETECTOR	DETECTOR PAKISTAN	UMBER			46200, PAKISTAN PHONE NO +92-51-9280507, FAX +92-51-92-9280502 EMAIL desto@isbpaknet.com.pk	E & SCIENCE TECHNO LOGY ORGANIZ ATION)		<p>Principle: Ions concentration 2. Respective Time: Immediate 3. Operating Voltage: 14.5VDC + Volts 4. Battery Type: Li-ion recharged 5. Battery life: 04 Hours 6. Max Charging Time: 02 hrs 30 minutes 7. Low Voltage Alarms: 09 Volts + 1 Volt 8. Audio Indicators: Beep 9. Visual Indicators: LED 10. Operating Temp Range: +5 C to +55 C 11. Storage Temp Range: +5 C to 80 C Range of ED-D787 has been designed to detect the presence Explosives of various from the following explosive substances: Detector 1. TNT (Tri Nitro Toluene) 2. NG (Nitro Gtyceone) 3. Dynamite 4. ANFO (Ammonium Nitrate Fuel Oil) 5. Tetryl MANUAL ZERO 10 SEC FROM SWITCH ON RESPONSE TIME IMMIDIATE BATTERY VOLTAGE TYPE +-12V, AA SIZE CELL INDICATOR PEIZO BUZZER VISUAL INDICATOR LED TEMP 0-60C <u>GENERAL SPECIFICATION -</u> 1. Principle: Ions concentration 2. Respective Time: Immediate 3. Operating Voltage: 14.5VDC + Volts 4. Battery Type: Li-ion recharged 5. Battery life: 04 Hours 6. Max Charging Time: 02 hrs 30 minutes 7. Low Voltage Alarms: 09 Volts + 1 Volt 8. Audio Indicators: Beep 9. Visual Indicators: LED 10. Operating Temp Range: +5 C to +55 C 11. Storage Temp Range: +5 C to 80 C Range of ED-D787 has been designed to detect the presence Explosives of various from the following explosive substances: Detector 1. TNT (Tri Nitro Toluene) 2. NG (Nitro Gtyceone) 3. Dynamite 4. ANFO (Ammonium Nitrate Fuel Oil) 5. Tetryl MANUAL ZERO 10 SEC FROM SWITCH ON RESPONSE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											TIME IMMEDIATE BATTERY VOLTAGE TYPE +-12V, AA SIZE CELL INDICATOR PEIZO BUZZER VISUAL INDICATOR LED TEMP 0- 60C	
88	DNF9707 8	N1537	611070515526 0 / ENERGY SAVER 220V- 240V ,11W. (screw type)	SELF, FOR DISTRIBUTION SYS.	25 / EACH/N UMBER			SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI.	PHILIPS CO LTD.		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220- 240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/I,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi 'GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220- 240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/I,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi '	
89	DNF9647 3	N1537	611070515526 0 / ENERGY SAVER 220V- 240V ,11W. (screw type)	SELF, FOR DISTRIBUTION SYS.	24 / EACH/N UMBER			SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI.	PHILIPS CO LTD.		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220- 240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/I,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi 'GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/I,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi	
90	DNF97970	A/p SPECCS pak cable/ Allied Cable	614570513268 3 / POWER CABLE 2 CORE 3/29 P. V.C WIRE 220/440 VOLTS	CCTV SYSTEM	450 / METER	PAK CABLE		PK		M/S AYUB ENGINEERING MANUFACTURES, REPAIRING & GENERAL SUPPLIER GROUND FLOOR, NORTH WING, MULES MANSION, KEAMARI, KARACHI	TECHNICAL SPECIFICATION - brand: pakistan cable equivalent: Allied Cable ;1.5mm 2 core flat pvc insulated 300/500v (brochure Attached) 2. 2 core 3 strains copper wire per core with cross sectional area .646 mm2 outer daimeter: 0.282 ohm/km pure copper wire 99% current carrying capicity: 11 aMps acceptance criteria: item should satisfied all mentioned specifications testing: testing is to be performed to verify all the mentioned specs. GENERAL SPECIFICATION - brand: pakistan cable equivalent: Allied Cable ;1.5mm 2 core flat pvc insulated 300/500v (brochure Attached) 2. 2 core 3 strains copper wire per core with cross sectional area .646 mm2 outer daimeter: 0.282 ohm/km pure copper wire 99% current carrying capicity: 11 aMps acceptance criteria: item should satisfied all mentioned specifications testing: testing is to be performed to verify all the mentioned specs.	
91	DNF98268	0582-16063 (999235744)	058259923574 4 / COMBINED-BOW-LIGHT ITEMS REQ/LENS, RED, GREEN, M/NAVIGATIONAL	GRP BOATS	11 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DNF95989	CHINA A/P DESCRIPT	056579900569 1 /	SOLDING EQUIP.	11 / EACH/NUMBER	CHINA BRAND					TECHNICAL SPECIFICATION - 25W 110/220V TIP PENCIL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		ION	SOLDERING IRON ELECTRIC 25W 110/220V TIP PENCIL (CHINA BRAND)		UMBER						GENERAL USE GENERAL SPECIFICATION - 25W 110/220V TIP PENCIL GENERAL USE	
93	DNF95487	1001-7928-01	0561UK5061888 / RADIATORY WIRE BOTTOM (SINGLE CORE)	ANTENNA MC/LP NTS LANDHI	250 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DNG96722	1108833	2920715060537 / STARTER SELF 12V-CW-MODEL-1990472-TEETH 11 BASE SIZE 110X110	GM DETRIOT D/E-4-71 (MODEL 1042-5000)	1 / EACH/NUMBER	1042-5000					TECHNICAL SPECIFICATION - STARTER MOTOR SELF STARTER 12V DC TEETH 11 BASE SIZE 110X110 05 KG UPTO 15 KG (POWER) SEALED ELECTRICAL GENERAL SPECIFICATION - STARTER MOTOR SELF STARTER 12V DC TEETH 11 BASE SIZE 110X110 05 KG UPTO 15 KG (POWER) SEALED ELECTRICAL	
95	DNZ97931		4540CH5076895 / SUPPORT FOR WASH BASIN FOR JALALAT-II	JALALAT-II	25 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
96	DNZ95340		4820CH5074917 / GLOBE VALVE SIZE 3"	SPARES RETURN FROM D/YARD FOR JALALAT-II	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - GENERAL SPEC: KSI BRAND PN 16 CHINA GENERAL SPECIFICATION - GENERAL SPEC: KSI BRAND PN 16 CHINA	
97	DNF95534	654018	6130997425711 / CHARGER MODULE	STATIC FREQUENCY CHANGER & ACCESSORIES	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - country of origin uk. BATTERY CHARGER /DC POWER SUPPLY AC (110/220 VAC AT 50/60 HZ DC FOR CHARGING LEAD ACID POWER TRANSFORMER RECTIFIER /REGULATOR CIRCUITRY GENERAL SPECIFICATION - country of origin uk. BATTERY CHARGER /DC POWER SUPPLY AC (110/220 VAC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AT 50/60 HZ DC FOR CHARGING LEAD ACID POWER TRANSFORMER RECTIFIER /REGULATOR CIRCUITRY	
98	DNF9774 4	PP3 , 6F22, (6135-00- 900-2139)	613570100411 8 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGI Z 047X25. 75X017MM	AVO METER	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
99	DNF9497 9	1354-01	625000299596 2 / STARTER FLUORESCEN T 2PINS 110/220V	TUBE LIGHTES	300 / EACH/N UMBER						TECHNICAL SPECIFICATION - STARTER FLUORESCENT LAMP a. TERMINAL QTY: 2 b. BODY DIAMETER: 0.810 INCHES c. BODY LENGTH: 1.500 INCHES. d. LAMP WATAGE RATING WATTS: 4.0 AND 6.0 AND 8.0 e. LAMP CURRENT TYPE: AC. f. LAMP VOLTAGE RATING IN VOLTS: 118.0 MINIMUM AND 120.0 MAXIMUM g. STARTER TYPE: GLOW h. TERMINAL TYPE: TWIST TYPE. GENERAL SPECIFICATION - STARTER FLUORESCENT LAMP a. TERMINAL QTY: 2 b. BODY DIAMETER: 0.810 INCHES c. BODY LENGTH: 1.500 INCHES. d. LAMP WATAGE RATING WATTS: 4.0 AND 6.0 AND 8.0 e. LAMP CURRENT TYPE: AC. f. LAMP VOLTAGE RATING IN VOLTS: 118.0 MINIMUM AND 120.0 MAXIMUM g. STARTER TYPE: GLOW h. TERMINAL TYPE: TWIST TYPE.	
100	DNA973 40	NO DATA AVAILABL E	6685UK507204 0 / GAUGE TEMPRATURE 20-240 F	MAIN ENGINE	5 / EACH/N UMBER						TECHNICAL SPECIFICATION - TEMPERATURE GUAGE (ENGINE COOLANT /ENGINE TEMP INDICATOR) 20 F TO 240 F ANALOG DIAL GUAGE WITH NEEDLE POINTER GENERAL SPECIFICATION - TEMPERATURE GUAGE (ENGINE COOLANT /ENGINE TEMP INDICATOR) 20 F	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											TO 240 F ANALOG DIAL GUAGE WITH NEEDLE POINTER	
101	DNF92651	380V/ 2500W LOCAL	7310PK507571 8 / COOKING PLATE 380V 2500W LG 11.5" W 11.5"	COOCKING SYS.	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
102	DNF96730	STEEL/ME TAL LOCAL	492073512072 4 / PEINCE TABLE STAND	PA SYSTEM	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - Heavy duty speaker stand. Light weight aluminum construction. Adjustable up to 6 feet in height. 65 Kg handling capacity. Samson, USA GENERAL SPECIFICATION - Heavy duty speaker stand. Light weight aluminum construction. Adjustable up to 6 feet in height. 65 Kg handling capacity. Samson, USA	
103	DNF95322	XR-800 FT/DC- CMS2200- 3-MIG	142071512071 1 / PRO AUDIO MIXER DYNACORD CMS- 1600/2200-3 16/22- CHANNEL	PA SYSTEM	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - Main voltage 100 to 240VAC, 50/60 Hz, battery power supply 48 V DC, 12 Mic/Line +4 Mic/Stereo inputs. 15 Hz-70KHz Freq response. master EQ 11 Band. XR-800 FT/DC-CMS2200-3-MIG OEM: DYNACORD ORIGIN: USA GENERAL SPECIFICATION - Main voltage 100 to 240VAC, 50/60 Hz, battery power supply 48 V DC, 12 Mic/Line +4 Mic/Stereo inputs. 15 Hz-70KHz Freq response. master EQ 11 Band. XR-800 FT/DC-CMS2200-3-MIG OEM: DYNACORD ORIGIN: USA	
104	DNG97605	ACB/MCC B 600A	000050000082 7 / AIR CIRCUIT BREAKER 600AMPS 500 VOLTS AC3PHASE 60HZ FUJIEA60		1 / EACH/N UMBER	EG603C					TECHNICAL SPECIFICATION - 600 AMP (03 PHASE) 500 VOLTS AC (50/60 HZ) OVERLAD SHORT CIRCUIT TRIP (AIR BREAKER) TRIP TYPE: THERMAL MAGNETIC OR ELECTRONIC TRIP UNIT PANEL OR SWITCHBOARD MOUNT IEC/UL TYPE PROTECTION GENERAL SPECIFICATION - 600 AMP (03 PHASE) 500 VOLTS AC (50/60 HZ) OVERLAD SHORT CIRCUIT TRIP (AIR BREAKER) TRIP TYPE:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											THERMAL MAGNETIC OR ELECTRONIC TRIP UNIT PANEL OR SWITCHBOARD MOUNT IEC/UL TYPE PROTECTION	
105	DCW94674		843050000002 9 / BOOT DMS SIZE 7		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7 <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7	ITEMS AS PER SPECIFICA TION
106	DCW94680		843050000003 5 / BOOT DMS SIZE 9 MEDIUM		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9 MEDIUM <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9 MEDIUM	ITEMS AS PER SPECIFICA TION
107	DCW94686		843050000157 7 / BOOT DMS SIZE 14 MEDIUM		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 MEDIUM <u>GENERAL SPECIFICATION -</u> BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 MEDIUM	ITEMS AS PER SPECIFICA TION
108	DNC96164	5321420215	299072531913 4 / FLANGE		3 / EACH/N UMBER	BR2000 CR					TECHNICAL SPECIFICATION - null <u>GENERAL SPECIFICATION -</u> null	
109	DNO97978	GP-0183	723077524105 1 / SHOWER CURTAIN		8 / EACH/N UMBER	Ecomotive 6.66					TECHNICAL SPECIFICATION - Not Know <u>GENERAL SPECIFICATION -</u> Not Know	
110	DNO97803	417-2406	536577526682 6 / SPRING		1 / EACH/N UMBER	3516E					TECHNICAL SPECIFICATION - COIL SPRING HIGH GRADE SPRING STEEL HEAT TREATED ABSORBS SHOCK 0.1361 KG APPROX CATERPILLAR <u>GENERAL</u> SPECIFICATION - COIL SPRING HIGH GRADE SPRING STEEL HEAT TREATED ABSORBS SHOCK 0.1361 KG APPROX CATERPILLAR	
111	DCW94683		843050000004 5 / BOOT DMS SIZE 12L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L	ITEMS AS PER SPECIFICA TION
112	DCW94673		843050000002 5 / BOOT DMS		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE	items as per specification

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE 6S								160CM) SIZE 6S <u>GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 6S</u>	
113	DNF96972	P19720-B21	702579525519 6 / HPE PROLIANT DL380 SERVER WITH ACCESSORIE S		1 / EACH/ UMBER	GEN 10 8sFF NC Configure to order					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
114	DCW94678		843050000003 1 / BOOT DMS SIZE 8S		90 / PAIR						<u>TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8S</u> <u>GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8S</u>	ITEMS AS PER SPECIFICATION
115	DNO97801	450-5413	531077526688 4 / BRIDGE		16 / EACH/ UMBER	3516E					<u>TECHNICAL SPECIFICATION - COMPONENT TYPE : VALVE BRIDGE MATERIAL: FORGED /MACHINED ALLOY STEEL HARDNESS: APPROX 50*60 HRC LUBRICATION: SPALASH OP TEMP: 200-250C</u> <u>GENERAL SPECIFICATION - COMPONENT TYPE : VALVE BRIDGE MATERIAL: FORGED /MACHINED ALLOY STEEL HARDNESS: APPROX 50*60 HRC LUBRICATION: SPALASH OP TEMP: 200-250C</u>	
116	DCW94679		843050000003 6 / BOOT DMS SIZE 9L		90 / PAIR						<u>TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L</u> <u>GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L</u>	ITEMS AS PER SPECIFICATION
117	DCW94682		843050000003 4 / BOOT DMS SIZE 9S		90 / PAIR						<u>TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S</u> <u>GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S</u>	ITEMS AS PER SPECIFICATION
118	DNO96480	349-7378/369-7561	662077524994 1 / SENSOR GP-		1 / EACH/ UMBER	C9.3					<u>TECHNICAL SPECIFICATION - SENSOR GP-PRESSURE</u> <u>GENERAL SPECIFICATION - SENSOR GP-</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PRESSURE								PRESSURE	
119	DN096651	0610.155050.4.0	2815FP3030508 / O-RING		2 / EACH/NUMBER	TBD620V12					TECHNICAL SPECIFICATION - O-RING circular cross - section sealing ring nbr / fluorocarbon (viton) NBR (-30 TO +100 c) VITON (-20 + 200c) GENERAL SPECIFICATION - O-RING circular cross - section sealing ring nbr / fluorocarbon (viton) NBR (-30 TO +100 c) VITON (-20 + 200c)	
120	DNO96482	424-4490	3414775262396 / GEAR		1 / EACH/NUMBER	C 9.3					TECHNICAL SPECIFICATION - GEAR GENERAL SPECIFICATION - GEAR	
121	DCW94685		8430500001578 / BOOT DMS SIZE 14 LARGE		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE	ITEMS AS PER SPECIFICATION
122	DCW94676		8430500000033 / BOOT DMS SIZE 8L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8L	ITEMS AS PER SPECIFICATION
123	DNF97737	05-00-5497-00 / 05-00-3395-00	5810715300651 / PC AVATAR - PC Based with Windows OS 7, Intel Core i7		1 / EACH/NUMBER	XIS-100XD					TECHNICAL SPECIFICATION - MACHINE LENGTH: 1524 MM, WIDTH: 770 MM, HEIGHT: 1212 MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM GENERAL SPECIFICATION - MACHINE LENGTH: 1524 MM, WIDTH: 770 MM, HEIGHT: 1212 MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM	
124	DNC96163	X59414500018/87	2815725300671 / EXHAUST PIPE BELOWS		3 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - WEIGHT: 13.500KG GENERAL SPECIFICATION - WEIGHT: 13.500 KG	
125	DCD976		844050423907		750 /						TECHNICAL SPECIFICATION -	item

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	45		4 / CAP BARRET NAVY BLUE WOOLLEN 6- 5/8 INCH (15CM)		EACH/N UMBER						COLOR PANTONE SHADE BLUE: 19-3924 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDEGENERAL SPECIFICATION - COLOR PANTONE SHADE BLUE: 19-3924 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE	required as per tender sample
126	DCD975 51		845550120202 6 / SOFT POOL INSIGNIA FOR COMMAND MASTER CHIEF PETTY OFFICER (CMCPO) WIDTH 1.6CM AND HEIGHT 2.5CM		100 / EACH/N UMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
127	DCW946 84		843050000157 6 / BOOT DMS SIZE 13 LARGE		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 13 LARGE GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 13 LARGE	ITEMS AS PER SPECIFICA TION
128	DCW946 77		843050000003 2 / BOOT DMS SIZE 8 M		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8 M GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8 M	ITEMS AS PER SPECIFICA TION