

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 24-03-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|----------------------|--|---------------------------------------|--------------------------|--------------------------|-------------|-----------|--------------|----------------|---|-----------|
| 1 | DNG95843 | NO DATA AVAILAB E | 592000851473 7 / FUSE NORMAL BLOW, CERAMIC BODY, 2AMP250V,7.1 X32MM | | 150 / EACH/N UMBER | | | | | | TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE | |
| 2 | DNF96746 | DL 160 G9 | 702579525879 0 / HP Server with accessories as per Part Catalog | | 1 / EACH/N UMBER | DL 160 G9 | | | | | TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null | |
| 3 | DNN97332 | 5310-031- 963.5 | 2030FP102000 2 / LAMP 031- 963.5 SERIES 31, 36V-30mA | SR662 TENFJORD STEERING GEAR | 10 / EACH/N UMBER | NO DATA AVAILAB LE | | | | | TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE | |
| 4 | DNO95852 | 109-6507 | 593001466480 2 / SWITCH AS-PUSH BUTTON (ENGINE SHUTOFF) | | 2 / EACH/N UMBER | 3516E | | | | | TECHNICAL SPECIFICATION - SWITCH AS-PUSH BUTTON (ENGINE SHUTOFF) GENERAL SPECIFICATION - SWITCH AS- PUSH BUTTON (ENGINE SHUTOFF) | |
| 5 | DNT96211 | 110- 244.101 | 599872535055 8 / Outer Sphere PCB of gyro std 22nx | | 1 / EACH/N UMBER | 110- 244.101 | | | | | TECHNICAL SPECIFICATION - OUTTER SPHERE PCB OF GYRO STD 22 NX 101-244.101 GENERAL SPECIFICATION - OUTTER SPHERE PCB OF GYRO STD 22 NX 101-244.101 | |
| 6 | DNO96938 | 13509102 | 481077523712 7 / (C), CHECK | | 3 / EACH/N | Not Known | | | | | TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|-------------------------------|---|-----------------------------------|------------------|-------------------|--------------------------|---|--------------|----------------|--|-----------|
| | | | VALVE, 1207, STORM TYPE, RIGHT-ANGLES, DN65, FLANGE, PN 10, FL;PN 10, CAST IRON GG 40.3 (EN-JS 1020), COATED, WITH LOCKING DE | | UMBER | | | | | | null | |
| 7 | DNJ95511 | 6CE-12411-00 | 668576520249 9 / THERMOSTAT | OBM YAMAHA ENGINE FL300BETX JAPAN | 9 / EACH/NUMBER | FL300BETX | 6CF-1009814 | YAMAHA MOTO CO LTD. 2500 SHINGAI IWATA SHIZUOKA JAPAN | YAMAHA JAPAN | | TECHNICAL SPECIFICATION - OBM YAMAHA ENGINE FL300BETX JAPAN GENERAL SPECIFICATION - OBM YAMAHA ENGINE FL300BETX JAPAN | |
| 8 | DNO94693 | 447-8639 | 662077526343 3 / DETECTOR GP-OIL MIST | | 10 / EACH/NUMBER | 3516E | | | | | TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null | |
| 9 | DNF96137 | 05-00-5497-00 / 05-00-3395-00 | 581071530065 1 / PC AVATAR - PC Based with Windows OS 7, Intel Core i7 | | 1 / EACH/NUMBER | XIS-100XD | | | | | TECHNICAL SPECIFICATION - MACHINE LENGTH: 1524 MM, WIDTH: 770 MM, HEIGHT: 1212 MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM GENERAL SPECIFICATION - MACHINE LENGTH: 1524 MM, WIDTH: 770 MM, HEIGHT: 1212 MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM | |
| 10 | DNJ97080 | 6CB-13016-00 | 531076520336 0 / O-RING | YAMAHA OBM | 2 / EACH/NUMBER | NO DATA AVAILABLE | 6CE-1029885, 6CF-1009814 | YAMAHA MOTOR CO. LTD JAPAN | JAPAN | | TECHNICAL SPECIFICATION - GENERAL SPECIFICATION - | |
| 11 | DNF97169 | 05-00-5497-00 / 05-00-3395-00 | 581071530065 1 / PC AVATAR - PC Based with Windows OS 7, Intel | | 1 / EACH/NUMBER | XIS-100XD | | | | | TECHNICAL SPECIFICATION - MACHINE LENGTH: 1524 MM, WIDTH: 770 MM, HEIGHT: 1212 MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|-------------------|---|-------------|------------------|--------------|-------------|-----------|---------------|--|--|-----------|
| | | | Core i7 | | | | | | | | WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM <u>GENERAL SPECIFICATION</u> -MACHINE LENGTH: 1524 MM, WIDTH: 770 MM, HEIGHT: 1212 MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM | |
| 12 | DNJ96031 | 64J-24560-00. | 289576534461 2 / FILTER ASSY | | 3 / EACH/NUMBER | 64J-24560-00 | | | | | <u>TECHNICAL SPECIFICATION - FILTER ASSY</u> <u>GENERAL SPECIFICATION - FILTER ASSY</u> | |
| 13 | DNO97306 | 349-7378/369-7561 | 662077524994 1 / SENSOR GP-PRESSURE | | 2 / EACH/NUMBER | C9.3 | | | | | <u>TECHNICAL SPECIFICATION - SENSOR GP-PRESSURE</u> <u>GENERAL SPECIFICATION - SENSOR GP-PRESSURE</u> | |
| 14 | DNF96061 | 6500K (E27) | 611078514190 0 / ENERGY SAVER DAY LIGHT 220V/20W | LIGHTING | 15 / EACH/NUMBER | 6500K (E27) | | CH | | OEM ADDRESS: HUNGARY ZRT, H-1340 BUDAPEST, E-MAIL: VACI UT 77.WWW.GELIGHTING.COM, COUNTRY CHINA. | <u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u> | |
| 15 | DNF97348 | B19 | 056579923819 7 / POLISHER FLOOR ELECT DOUBLE BRUSH 220V/240V AC/DC | | 1 / EACH/NUMBER | | | | | | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u> | |
| 16 | DNF95140 | 3632273 | 292001498129 1 / STARTING MOTOR VDC24 VOLTS INPUT VOLTAGES 24 | | 1 / EACH/NUMBER | 3632273 | | | | | <u>TECHNICAL SPECIFICATION - STARTING MOTOR vDC24 VOLTS</u> input voltages 24vdc rotation clockwise power : 9 kw mount type : sae 3 pinion : teeth 11 pinion pitch: 6/8 weight 15.9kg dimm 78 cm x 22.9 | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|--------------|-----------------------|--|-------------------------|------------------------|---|-------------|-----------|---------------|----------------|---|-----------|
| | | | VDC ROTATION CLOCK WISE 11 teeth | | | | | | | | cmx 27.6 cm ALTERNATIVE PART NUMBERS DELCO REMY 10479339 PRESTOLITE M128R3850SE GENERAL SPECIFICATION - STARTING MOTOR vDC24 VOLTS input voltages 24vdc rotation clock wise power : 9 kw mount type : sae 3 pinion : teeth 11 pinion pitchv: 6/8 weight 15.9kg dimm 78 cm x 22.9 cmx 27.6 cm ALTERNATIVE PART NUMBERS DELCO REMY 10479339 PRESTOLITE M128R3850SE | |
| 17 | DNF9605 4 | MA3000C- 48/BL820E | 444079506152 4 / DEHUMIDIFIE R PORTABLE | (YSD) GENERAL USE | 2 / EACH/N UMBER | PREM-I- AIR ELITE EH1418 XTREEM | | | | | TECHNICAL SPECIFICATION - IP Rating: IP 21 or above Voltage RATING: 110/220 V 50/60 Hz Power Rating: 470 Watts Over-current PROTECTION: Should be installed with circuit breaker/ fuse protection against over-current and short-circuit Grounding/ Earthing: Must comply with Unit's earthing system Cable/ Plug Design: Special electrical cable with fol properties: ∠ Extra flexible ∠ Tough outer covering Flame retardant with 3 Pin Plug Material Body: Special Plastic/ Composite with Fire Retardant Additives Refrigerant: R-22 Water Tank Capacity: 6 Liters Weight: 21 Kg Size: 455 mm x 350 mm x 603mm Dehumidifying Capacity: 28-35 Ltrs per day D/fying capc(Ltrs):28-35 per day Power input (Watt): 510 D/fying: 4.8 Refrigerent: R22 W/tank cap (Ltr): 06 Rated power:470W Rated current: 4.1A Opertaing Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600WGENERAL SPECIFICATION - IP Rating: IP 21 or above Voltage RATING: 110/220 V 50/60 Hz Power Rating: 470 Watts | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|---------------------------|---|------------------|----------------|-----------|-------------|---------------------------|--------------|----------------|---|-----------|
| | | | | | | | | | | | Over-current PROTECTION: Should be installed with circuit breaker/ fuse protection against over-current and short-circuit Grounding/ Earthing: Must comply with Unit's earthing system Cable/ Plug Design: Special electrical cable with fol properties: ζ Extra flexible ζ Tough outer covering Flame retardant with 3 Pin Plug Material Body: Special Plastic/ Composite with Fire Retardant Additives Refrigerant: R-22 Water Tank Capacity: 6 Liters Weight: 21 Kg Size: 455 mm x 350 mm x 603mm Dehumidifying Capacity: 28-35 Ltrs per day D/fying capc(Ltrs):28-35 per day Power input (Watt): 510 D/fying: 4.8 Refrigrent: R22 W/tank cap (Ltr): 06 Rated power:470W Rated current: 4.1A Opertaing Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600W | |
| 18 | DNF96923 | MCTX-CAT6 | 5915705248710 / CAT 6 networkig cable | | 375 / METER | MCTX-CAT6 | | | | | TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null | |
| 19 | DNJ95275 | HF101224 | 4720735289428 / HOSE FUEL A-2 2*3/8 INCH | | 4 / FOOT | MB10054 | | | | | TECHNICAL SPECIFICATION - HOSE FUEL A-2 2*3/8 INCH GENERAL SPECIFICATION - HOSE FUEL A-2 2*3/8 INCH | |
| 20 | DNF95640 | COM-FDPSM9-ST/PC-ST/PC-03 | 6015715103128 / FIBER OPTICL PATCH CORD ST/PC - ST/PC SM9/125UM OS2 D.652D LSZH DUPLEX SC-SC, 3M COLOR YELLOW | COMPUTER NETWORK | 7 / EACH/UMBER | | | | | | TECHNICAL SPECIFICATION - ST/PC - ST/PC SM9/125UM OS2 D. 652D LSZH DUPLEX SC-SC, 3M COLOR YELOW OEM COMBRIDGE WWW.COMBRIDGENETWORKS. COMGENERAL SPECIFICATION - ST/PC - ST/PC SM9/125UM OS2 D. 652D LSZH DUPLEX SC-SC, 3M COLOR YELOW OEM COMBRIDGE WWW.COMBRIDGENETWORKS. COM | |
| 21 | DNF9796 | CMS-118 | 599870521930 | SM RACK | 6 / | CMS-118 | NA | Commercially Of The Shelf | COTS | | TECHNICAL SPECIFICATION - | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|--------------------------|--|-------------------------------|-------------------|---------------------|-------------|---|--------------|----------------|--|---|
| | 9 | | 4 / POWER EXTENSION BOARD CAMELLION MODEL CMS-118 | | EACH/NUMBER | (CAMELLION) | | (COTS)/Local Market | | | 220V Power Connection Board. Used in mounting racks.pakistan GENERAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan | |
| 22 | DNF95131 | CMS-118 | 599870521930 4 / POWER EXTENSION BOARD CAMELLION MODEL CMS-118 | SM RACK | 2 / EACH/NUMBER | CMS-118 (CAMELLION) | NA | Commercially Of The Shelf (COTS)/Local Market | COTS | | TECHNICAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan GENERAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan | |
| 23 | DNF97973 | ST4000NM0053/ST4000VX000 | 702578520784 9 / 4TB SURVEILLANCE HARD DISK-SATA FOR NVR | CCTV System ST4000VX000 CHINA | 4 / EACH/NUMBER | ST4000VX000 | NA | Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888 | CHINA | | TECHNICAL SPECIFICATION - Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32 GENERAL SPECIFICATION - Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32 | |
| 24 | DCC99495 | | 841550168204 3 / WAIST COAT FOR KHATEEB & SOR SIZE-S | | 200 / EACH/NUMBER | | | | | | TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null | the item is procured against tender sample. |
| 25 | DCC99462 | | 840550069257 9 / OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II | | 120 / EACH/NUMBER | | | | | | TECHNICAL SPECIFICATION - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II GENERAL SPECIFICATION - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II | ITEM IS PROCURED AGAINST TENDER SAMPLE, AS PER SPECIFICATION. |
| 26 | DCC99522 | | 841550168204 5 / WAIST COAT FOR KHATEEB & SOR SIZE-L | | 200 / EACH/NUMBER | | | | | | TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null | the item is procured against tender sample. |
| 27 | DCC99463 | | 840550069258 0 / OVERALL BLUE | | 120 / EACH/NUMBER | | | | | | TECHNICAL SPECIFICATION - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% | ITEM IS PROCURED AGAINST |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|---------|---|-------------|--------------------|-------|-------------|-----------|---------------|----------------|---|--|
| | | | PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III | | | | | | | | COTTON SIZE-III <u>GENERAL SPECIFICATION - OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III</u> | TENDER SAMPLE, AS PER SPECIFICA TION. |
| 28 | DCW95602 | | 8430500759140 / BATH ROOM CHAPPLE FOR SURGEON | | 350 / PAIR | | | | | | <u>TECHNICAL SPECIFICATION - BATH ROOM CHAPPLE FOR SURGEON</u> <u>GENERAL SPECIFICATION - BATH ROOM CHAPPLE FOR SURGEON</u> | items on required as per specification s |
| 29 | DCC99523 | | 8415501682046 / WAIST COAT FOR KHATEEB & SOR SIZE-XL | | 200 / EACH/NUMBER | | | | | | <u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u> | the item is procured against tender sample. |
| 30 | SCF97510 | | 8345505711988 / FLAG ALPHABATIC A-Z SIZE 4 FITED 26 FLAGS | | 2 / SET | | | | | | <u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u> | |
| 31 | DCC96965 | | 8440500901014 / HANDKERCHIEF WHITE COTTON SAILORS SIZE 17 X 17 INCH | | 7000 / EACH/NUMBER | | | | | | <u>TECHNICAL SPECIFICATION - HANDKERCHIEF WHITE COTTON SAILORS SIZE 17 X 17 INCH</u> <u>GENERAL SPECIFICATION - HANDKERCHIEF WHITE COTTON SAILORS SIZE 17 X 17 INCH</u> | ITEM IS PROCURE D AS PER TENDER SAMPLE. |
| 32 | DCC99496 | | 8415501682044 / WAIST COAT FOR KHATEEB & SOR SIZE-M | | 200 / EACH/NUMBER | | | | | | <u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u> | the item is procured against tender sample. |
| 33 | DCC99722 | | 8405501200202 / BAND DRESS SUMMER CEREMONIAL WHITE WITH EMBROIDRY SIZE40 (WITH WAIST BAND & SHOULDER EPPLETS) | | 13 / PAIR | | | | | | <u>TECHNICAL SPECIFICATION - BAND DRESS SUMMER CEREMONIAL WHITE WITH EMBROIDRY SIZE40 (WITH WAIST BAND & SHOULDER EPPLETS)</u> <u>GENERAL SPECIFICATION - BAND DRESS SUMMER CEREMONIAL WHITE WITH EMBROIDRY SIZE40 (WITH WAIST BAND & SHOULDER EPPLETS)</u> | the item is procured against tender sample, as per specification . |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|--------------|--|---|---|------------------------|---------------------------|-------------|-----------|--------------|--|--|---|
| 34 | DCC997 23 | | 840550120047 4 / BAND DRESS SUMMER CEREMONIAL WHITE WITH EMBROIDRY (WITH WAIST BAND & SHOULDER EPPLETS) (AS PER MEASUREME NTS) | | 10 / PAIR | | | | | | TECHNICAL SPECIFICATION - BAND DRESS SUMMER CEREMONIAL WHITE WITH EMBROIDRY (WITH WAIST BAND & SHOULDER EPPLETS) (AS PER MEASUREMENTS) GENERAL SPECIFICATION - BAND DRESS SUMMER CEREMONIAL WHITE WITH EMBROIDRY (WITH WAIST BAND & SHOULDER EPPLETS) (AS PER MEASUREMENTS) | the item is procured against tender sample as per specification |
| 35 | DNF9964 3 | (Cannon EOS R- 100)/Nikon Z50II /D3500 /D- 3000 | 671076508744 7 / NIKON DIGITAL STILL CAMERA WITH FLASH GUN SB-900 /NIKON Z50II | DIGITAL CAMERA | 1 / EACH/N UMBER | (Cannon EOS R- 100) | | | | | TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null | |
| 36 | DNF9964 4 | 525502 | 665012157956 0 / BINOCULAR 7X50B/7X50c | BINOCULAR 7X50B OEM: ZEISS,CARL POB 1380 | 3 / EACH/N UMBER | 7x50b/7X 50c | | | | | TECHNICAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germanyGENERAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germany | |
| 37 | DNC982 12 | WBCL000 636 | 482074513314 6 / DENFOS EXPANSION VALVE TCBE1 | A/C SYSTEM PNS KARRAR | 2 / EACH/N UMBER | NO DATA AVAILAB LE | | FR | | WEBAST O MARINE COMFOR T FRANCE | TECHNICAL SPECIFICATION - brass /stainless steel single flow -40c to +10c tube length 750-800 mm 34 bar pressure 1/4 -3/8 (odf /flare) GENERAL SPECIFICATION - brass /stainless steel single flow -40c to +10c tube length 750-800 mm 34 bar pressure 1/4 -3/8 (odf /flare) | |
| 38 | DNF9486 8 | 1106 | 582570511832 3 / BATTERY CHARGER I/P220V 50HZ 1PH O/P 48V (12X4) 20A WITH ACCE | | 1 / EACH/N UMBER | GZL30A- 6/48V | | | | | TECHNICAL SPECIFICATION - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC: OEM: Nanchang Shuguang Eledricd Equipment Factory GENERAL SPECIFICATION - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|--|---|-----------------------|-----------------|----------------------|---------------|------------------------------|-----------------|---|--|-----------|
| | | | | | | | | | | | 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC: OEM: Nanchang Shuguang Eledricd Equipment Factory | |
| 39 | SNF97637 | AALR6 | 613573528152 4 / AA2 ENERGIZER LITHIUM BATTERY 1.5V RECHARGEABLE SIZE H: 145mm | | 500 / PAIR | ENERGIZER LITHIUM | | | | | <u>TECHNICAL SPECIFICATION - (2 PACK)</u> <u>GENERAL SPECIFICATION - (2 PACK)</u> | |
| 40 | DNC96165 | X00003420 | 293012386012 0 / ELBOW TO PLATE-CORE COOLE | | 4 / EACH/NUMBER | 8V 2000 M84 | | | | | <u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u> | |
| 41 | DNF94501 | A/p SPECCS pak cable/ Allied Cable | 614570513268 3 / POWER CABLE 2 CORE 3/29 P. V.C WIRE 220/440 VOLTS | CCTV SYSTEM | 200 / METER | PAK CABLE | | PK | | M/S AYUB ENGINEER RING MANUFACTURES, REPAIRING &GENERAL SUPPLIER GROUND FLOOR, NORTH WING, MULES MANSION , KEAMARI , KARACHI | <u>TECHNICAL SPECIFICATION - brand: pakistan cable equivalent: Allied Cable ;1.5mm 2 core flat pvc insulated 300/500v (brochure Attached) 2. 2 core 3 strains copper wire per core with cross sectional area .646 mm2 outer daimeter: 0.282 ohm/km pure copper wire 99% current carrying capicity: 11 aMps acceptance criteria: item should satisfied all mentioned specifications testing: testing is to be performed to verify all the mentioned specs.</u> <u>GENERAL SPECIFICATION - brand: pakistan cable equivalent: Allied Cable ;1.5mm 2 core flat pvc insulated 300/500v (brochure Attached) 2. 2 core 3 strains copper wire per core with cross sectional area .646 mm2 outer daimeter: 0.282 ohm/km pure copper wire 99% current carrying capicity: 11 aMps acceptance criteria: item should satisfied all mentioned specifications testing: testing is to be performed to verify all the mentioned specs.</u> | |
| 42 | DNJ99386 | 38890-98J00 | 281576522142 2 / | SUZUKI DF300AP 300 | 2 / EACH/NUMBER | DF300AP | 30002P-712896 | SUZUKI MOTOR CO LTD JAPAN | SUZUKI JAPAN | | <u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION -</u> | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|---------------------------------|--|-------------------------------------|-------------------|----------------------------|----------------|---|-----------------------------------|--|--|-----------|
| | | | ACTUATOR, SHIFT | HP OBM | UMBER | | | | | | NIL | |
| 43 | DNJ99388 | 15440-93J00-000/15440-93J00 | 2940765221800 / FILTER, FUEL (EPI) | SUZUKI DF300AP 300 HP OBM | 13 / EACH/NUMBER | DF300AP | 30002P-712896 | SUZUKI MOTOR CO LTD JAPAN | SUZUKI JAPAN | | TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL | |
| 44 | DNF96063 | 05-00-0049-00 | 6350715197061 / 160 KV CONTROLLER | SCANNING MACHINE XIS-6545 USA | 1 / EACH/NUMBER | XIS-6545 | ASTNC160SS2299 | INC. 21481 FERRERO PARKWAY CITY OF INDUSTRY, CA-91789USA | ASTROP HYSICS USA | | TECHNICAL SPECIFICATION - Used for Luggage Mail / Baggage Scanning GENERAL SPECIFICATION - Used for Luggage Mail / Baggage Scanning | |
| 45 | DNF93144 | RTAC-01 | 7025580002969 / DIGITIZER, DATA ENTRY | PORTAL CRANE M-4 TURKEY | 2 / EACH/NUMBER | M-4 | 21338-100 | Nisantepi Mh. Fabrikalar Sk. No:8 Alemdag Umraniye 34794 Istanbul TURKEY Phone: +90(216) 585 1818 Fax +90(216) 585 1819 Website: esitscale.com | ISTANBU L EURO CRANE (IEC) TURKEY | | TECHNICAL SPECIFICATION - OUTPUT VOLTAGE 1: +24VDC OUTPUT VOLTAGE 2: +15VDC MAX POWER CONSUMPTION : 140mA(5v)+55mA(24v) GENERAL SPECIFICATION - OUTPUT VOLTAGE 1: +24VDC OUTPUT VOLTAGE 2: +15VDC MAX POWER CONSUMPTION : 140mA(5v)+55mA(24v) | |
| 46 | DNF97552 | zkx8s | 5815151717958 / zk-teco zk-8s/ZKTECO G3 PLUS biometric finger print reader | | 1 / EACH/NUMBER | zkx8s/ZK Teco G3 Plus | | | | ONLY REQUIRED (ZKTECO G3 PLUS BIOMETRIC FINGER PRINT ReADER MODEL) | TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null | |
| 47 | SNG96434 | NO DATA AVAILAB LE | 5306546014933 / BOLT WITH NUT STAINLESS STEEL SZ DIA 1/2" LENTH 2 | WALCON FALANKS AS&AS P30 BABUR/BADR | 500 / EACH/NUMBER | NO DATA AVAILAB LE | | | | | TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE | |
| 48 | DNF96922 | ZDGgv30 | 5895795280757 / YACHT MARINE ais gps antenna | | 2 / EACH/NUMBER | gv30 combo ais gps antenna | | | | | TECHNICAL SPECIFICATION - ENCLOSED GENERAL SPECIFICATION - ENCLOSED | |
| 49 | DNF99654 | RG-NBS3200-24SFP/8GT4XS/3C17300 | 5930715102968 / SUPER STACK SWITCH 4226 WITH24 PORT | COMPUTER NETWORK, PNS RAZA | 1 / EACH/NUMBER | | | | | | TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|--------------|---|--|--|--------------------------|-----------------------------------|-------------|-----------|--|--|--|-----------|
| | | | 10/100 | | | | | | | | | |
| 50 | DNF9954 2 | NCB- FS09D- LCSC-10 | 599570524636 5 / D-LINK SC- LC SINGLEMODE OS2 DUPLEX PATCH CORD 10m | | 10 / EACH/N UMBER | NCB- FS09D- LCSC-10 | | | | | TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null | |
| 51 | DNF9949 3 | n150 exide | 614070514769 7 / BATTERY 12V 110 AH | R&S 3MR RADIO (PROJECT BURQ) | 2 / EACH/N UMBER | N150 EXIDE | | PK | M/S RODHE & SWARZ GERMAN Y | | TECHNICAL SPECIFICATION - MAKE: EXIDE EQUIVALANT: AGS 12 VOLTS(90 AH)GENERAL SPECIFICATION - MAKE: EXIDE EQUIVALANT: AGS 12 VOLTS(90 AH) | |
| 52 | DNF9755 4 | RG- NBS3100- 48GT4SFP -P / J9627A | 593073511469 1 / HP JL322A Aruba 2930M 48 Ports PoE+ 1 + slot + Switch + Layer 3 +managed | AT-8300 SERIES | 1 / EACH/N UMBER | RG- NBS3100- 48GT4SF P-P | | | | REQUIRED ONLY (HP JL322A Aruba 2930M 48Ports PoE+ 1 + slot + Switch +Layer 3 +managed) | TECHNICAL SPECIFICATION - Brand: HP Product: Family ProCurve Product: Series E2620 Product: Name 2620-48-PoE+ Product Code / Part No: J9627A Category: Network SwitchGENERAL SPECIFICATION - Brand: HP Product: Family ProCurve Product: Series E2620 Product: Name 2620-48-PoE+ Product Code / Part No: J9627A Category: Network Switch | |
| 53 | DNF9733 3 | CLIPSAL/A VAYA | 614570511899 7 / NETWORKING I/O (NETWORK BOX+FACE PLATE+I/O WITH 02 I/O CAPAC | NETWORKING I/O (CLIPSAL, AMP,AVAYA, 3M) | 190 / EACH/N UMBER | | | | | | TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE | |
| 54 | DNF9939 7 | NO DATA AVAILABL E | 613071511934 9 / UPS STABIMATIC 7KVA / UPS APC 7KVA WITH ACCESS7.5 KVA | UPS | 1 / EACH/N UMBER | UPS 7KVA | | | | | TECHNICAL SPECIFICATION - UPS STABIMATIC 7KVA UPS 7KVA back up time : 30 minuts GENERAL SPECIFICATION - UPS STABIMATIC 7KVA UPS 7KVA back up time : 30 minuts | |
| 55 | DNF9531 8 | KFAE-55C | 610570504423 6 / BLOWER EXHAUST 1.5 | EXHAUST BLOWER STEERING | 18 / EACH/N UMBER | | | | | | TECHNICAL SPECIFICATION - 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3 PHASEGENERAL | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|--|--|-------------------------------------|------------------------|---|-------------|---|--------------|----------------|---|-----------|
| | | | KW 380-420V 5AMP RPM 2950 50HZ 3PHASE | COMPART | | | | | | | <u>SPECIFICATION</u> - 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE | |
| 56 | DNF96064 | ST4000NM0053/ST4000VX000 | 702578520784 9 / 4TB SURVEILLANCE HARD DISK-SATA FOR NVR | CCTV System ST4000VX000 CHINA | 6 / EACH/ NUMBER | ST4000VX000 | NA | Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888 | CHINA | | <u>TECHNICAL SPECIFICATION</u> - Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32 <u>GENERAL SPECIFICATION</u> - Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32 | |
| 57 | DNF95584 | sc-615/ sc-630m/ TC15ML/T C10ML TOA | 951270003000 4 / LOUD- SPEAKER HORN TYPE | PA SYSTEM/SRE SYSTEM | 2 / EACH/ NUMBER | TC15ML/ TC10ML TOA sc- 615 | | | | | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE | |
| 58 | DNF99646 | MA3000C-48/BL820E | 444079506152 4 / DEHUMIDIFIER PORTABLE | (YSD) GENERAL USE | 2 / EACH/ NUMBER | PREM-I- AIR ELITE EH1418 XTREEM | | | | | <u>TECHNICAL SPECIFICATION</u> - IP Rating: IP 21 or above Voltage RATING: 110/220 V 50/60 Hz Power Rating: 470 Watts Over-current PROTECTION: Should be installed with circuit breaker/ fuse protection against over-current and short-circuit Grounding/ Earthing: Must comply with Unit's earthing system Cable/ Plug Design: Special electrical cable with fol properties: 2 Extra flexible 2 Tough outer covering Flame retardant with 3 Pin Plug Material Body: Special Plastic/ Composite with Fire Retardant Additives Refrigerant: R-22 Water Tank Capacity: 6 Liters Weight: 21 Kg Size: 455 mm x 350 mm x 603mm Dehumidifying Capacity: 28-35 Ltrs per day D/fying capc(Ltrs):28-35 per day Power input (Watt): 510 D/fying: 4.8 Refrigrent: R22 W/tank cap (Ltr): 06 Rated power:470W Rated current: 4.1A Opertaing Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: | |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS | Dimension |
|-------|----------|-------------------------------------|---|-------------|-----------------|-------------------------|-------------|-----------|--------------|----------------|---|-----------|
| | | | | | | | | | | | <p>455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600WGENERAL SPECIFICATION - IP Rating: IP 21 or above Voltage RATING: 110/220 V 50/60 Hz Power Rating: 470 Watts Over-current PROTECTION: Should be installed with circuit breaker/ fuse protection against over-current and short-circuit Grounding/ Earthing: Must comply with Unit's earthing system Cable/ Plug Design: Special electrical cable with fol properties: ζ Extra flexible ζ Tough outer covering Flame retardant with 3 Pin Plug Material Body: Special Plastic/ Composite with Fire Retardant Additives Refrigerant: R-22 Water Tank Capacity: 6 Liters Weight: 21 Kg Size: 455 mm x 350 mm x 603mm Dehumidifying Capacity: 28-35 Ltrs per day D/fying capc(Ltrs):28-35 per day Power input (Watt): 510 D/fying: 4.8 Refrigrent: R22 W/tank cap (Ltr): 06 Rated power:470W Rated current: 4.1A Opertaing Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600W</p> | |
| 59 | DNF99382 | N250 PLUS EXIDE / OSAKA OR EQUALENT | 0562795620006 / BATTERY LEAD ACID 12V 200AH | DG USED | 4 / EACH/NUMBER | N250 PLUS EXIDE / OSAKA | | | | | <p>TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA SIZE: 511X280X246MM EXIDE PAKISTAN.GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA SIZE:511X280X246MM EXIDE PAKISTAN.</p> | |