

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 04-03-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE971 77	NO DATA AVAILABL E	035059923357 5 / FENDER MARINE ROUND SISAL WT.32 LBS. OVERALL DIA 2",INTERNAL DIA 8" FOR HARBOUR LAUNCHES		8 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - δ MEDIUM SIZE: δ 1000 MM LENGHT δ 500 MM DIAMETER δ 1550 MM CIRCUMFERENCE δ MATERIAL EVA FOAM AND NATURAL RUBBER δ IYPE: FLANGE TYPE AND ROPE TYPE δ ISO 9001 COMPLIANCE δ ENERGY ABSORPTION 08 K NM δ FORCE RECTION 71 KN</p> <p><u>GENERAL SPECIFICATION - δ MEDIUM SIZE:</u> δ 1000 MM LENGHT δ 500 MM DIAMETER δ 1550 MM CIRCUMFERENCE δ MATERIAL EVA FOAM AND NATURAL RUBBER δ IYPE: FLANGE TYPE AND ROPE TYPE δ ISO 9001 COMPLIANCE δ ENERGY ABSORPTION 08 K NM δ FORCE RECTION 71 KN</p>	
2	DGB974 15	aqs101	413070534447 0 / ac flapper rag size 6 inch dia		30 / EACH/N UMBER	AQS101					<p>TECHNICAL SPECIFICATION - AC FLAPPER VENT GRILLE SIZE: 6" X6" MATERIAL: ALUMINUM (POWDER COATED) BLADE TYPE: FIXED HORIZONTAL LOUVERS INSTALLATION :CELLING/WALL SURFACE MOUNT WARRANTY; 1 YEAR</p> <p><u>GENERAL SPECIFICATION - AC FLAPPER VENT GRILLE SIZE: 6"X6" MATERIAL: ALUMINUM (POWDER COATED) BLADE TYPE: FIXED HORIZONTAL LOUVERS</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											INSTALLATION :CELLING/WALL SURFACE MOUNT WARRANTY; 1 YEAR	
3	DGB963 57		028359571150 5 / ROD COPPER RD ANNEALED DIA 1.50 INCH WT PER FT6. 849LBS		11 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
4	DGB970 45		028350283152 1 / CADMIUM ANODE ROLLED LG 12 WTH 8 TH 3/8		7.25 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm GENERAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm	
5	DGB972 91		028359571121 3 / ALUMINIUM BRONZE RoD ROUND SOLUTION HEAT TREATED, DIA 3 inch, running LENGTH 6-10 feet, wt. per pound 25.500 (lbs).		3 / METER						TECHNICAL SPECIFICATION - DEF STAN 02-833. DIA: 3 INCH. RUNNING LENGTH: 6-10 FEET. WT. PER POUND: 25.500 (LBS). GENERAL SPECIFICATION - DEF STAN 02-833. DIA: 3 INCH. RUNNING LENGTH: 6-10 FEET. WT. PER POUND: 25.500 (LBS).	
6	DGB971 29		028359571121 3 / ALUMINIUM BRONZE RoD ROUND SOLUTION HEAT TREATED, DIA 3 inch, running LENGTH 6-10 feet, wt. per pound 25.500 (lbs).		4 / METER						TECHNICAL SPECIFICATION - DEF STAN 02-833. DIA: 3 INCH. RUNNING LENGTH: 6-10 FEET. WT. PER POUND: 25.500 (LBS). GENERAL SPECIFICATION - DEF STAN 02-833. DIA: 3 INCH. RUNNING LENGTH: 6-10 FEET. WT. PER POUND: 25.500 (LBS).	
7	DGB963 66		028359571145 5 / ROD		6 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NAVAL BRASS DIA 2 INCH (WT PER FT 11.72 LB)								GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance. <u>GENERAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.</u>	
8	DGB963 65		028359571145 6 / ROD NAVAL BRASS RD DIA 2.12 INCH WT.13.14 PER FOOT(LB)	SP.BS 2874,CZ 112M	6 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
9	DGB971 28		028359571145 9 / ROD NAVAL BRASS RD DIA.2.50 INCH WT PER MTR 27.49 KG		10 / METER						<u>TECHNICAL SPECIFICATION - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU zN 39 SN 1</u> <u>GENERAL SPECIFICATION - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU zN 39 SN 1</u>	
10	DGB972 85		027479910545 3 / HAMMER HAND COAL BREAKING 6.00LBS LG 3.000IN		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
11	DGB973 84		026759923510 4 / ELBOW ROUND BLACK 2.50 IN		12 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
12	DGB973 89	BS949, 1G579 (5136-99- 122-7414)	027170122741 4 / TAP THREAD CUTTING I.S.O P/S12.00X01. 75X29.00X07. 50X89.00MM		72 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
13	DGB973 49	LENGTH. 1,50 INCH PAK PATTERN NO	021459003560 3 / BOLT MACHINE STEEL BLACK BSW HEX HD		20 / TEN						<u>TECHNICAL SPECIFICATION - Material Grade EN4140</u> <u>GENERAL SPECIFICATION - Material Grade EN4140</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SZ 1.500X0.187 IN									
14	DGE97175	0330-1225	035059923386 8 / FENDER MARINE LENGTH 9.0 INCHES WIDTH 5.0 INCHES		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT. GENERAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT.	
15	DGB97350		021459003566 1 / BOLT MACHINE STEEL BSW HEX HD SZ 4.000X0.375 IN		20 / TEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
16	DGB97284		026559423327 0 / NAIL COPPER BOAT 4"X0.198" ROUND POINT FLAT CSK HEAD		8 / KILOGRAMME						TECHNICAL SPECIFICATION - sPECS: √ Material: Copper √ Round Point Flat CSK Head √ Size: 4"X0.198" a. Complete item/ store description: 4 Inch Nail Copper b. Packing Details :10 in One Pack, 6.34 x 4.02 x 0.43 inches c. Availability: Available in local market GENERAL SPECIFICATION - sPECS: √ Material: Copper √ Round Point Flat CSK Head √ Size: 4"X0.198" a. Complete item/ store description: 4 Inch Nail Copper b. Packing Details :10 in One Pack, 6.34 x 4.02 x 0.43 inches c. Availability: Available in local market	
17	DGB97383		027379000411 4 / CUTTER INSULATION REMOVING DIAMETER CAPACITY 0.744IN	USE; PYROTENAX CABLE	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
18	DGB973 62		021450214079 2 / NUT MILD STEEL FOR BOLT HEX .SZ 1.250 IN		220 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
19	DGB973 81		027359910446 3 / CALIPER INSIDE SPRING JOINT 06IN (LOCAL)		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
20	DGB973 88		024750247001 4 / RING-FOR- HOT-PLATES		54 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
21	DGB973 82		026459124068 6 / CHESTTOOLKI T		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DGB973 92	BS 3628 &K0851& DEFSTAN 47-11	025470420308 8 / CLAMP HOSE TERRY BRAND SZ 2.750 TO 3.500"WD . 505"XTHK 0.038"		113 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DGB973 86	(SIM)	025770941150 4 / NUT-PLAIN- HEXAGON (BRASS) THREAD UNF SZ .375"LH . 350"		32 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
24	DGB973 87	Material Grade EN 4140	025770941150 6 / NUT-PLAIN- HEXAGON- THREAD-SIZE. 625LH.550"		29 / DOZEN						TECHNICAL SPECIFICATION - material specs AISI 4140(PD 970: 2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED GENERAL SPECIFICATION - material specs AISI 4140(PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
25	DGB973 91		512073100059 1 / WRENCH (ALLEN)KEY		12 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			1.5-12MM 10PCS SET								AVAILABLE	
26	DGT973 99	NO DATA AVAILABL E	553070504293 3 / PLY WOOD NATURAL TEAK FINISH ONE SIDE (NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W= 4' TH=03mm to 04mm	PRESENTATIO N BOXES FOR VVIPS	160 / SQ FEET						TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm GENERAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm	
27	DGB971 30	NO DATA AVAILABL E	024850000147 8 / CHEST 6 LEVER LOCK 33-5/8X26- 3/4X24-5/8 INCH THICK 3/8 INCH		4 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB GENERAL SPECIFICATION - NO DATA AVAILABLE	
28	DGE971 74		8340PK507382 7 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIE S		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE AND WITH ROT-PROOF, WATERPROOF AND VAT-DYED TREATMENT. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. THE PARTICIPANT OF THE TENT TO BE PROVIDED A CERTIFICATE OF MEMBERSHIP FROM PCTMEA (PAKISTAN CANVAS AND TENTS MANUFACTURERS AND EXPORTERS ASSOCIATION) OR AN AUTHORITY LETTER FROM MEMBER ALONG WITH TECHNICAL QUOTATION. 7. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. GENERAL</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE AND WITH ROT-PROOF, WATERPROOF AND VAT-DYED TREATMENT. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. THE PARTICIPANT OF THE TENT TO BE PROVIDED A CERTIFICATE OF MEMBERSHIP FROM PCTMEA (PAKISTAN CANVAS AND TENTS MANUFACTURERS AND EXPORTERS ASSOCIATION) OR AN AUTHORITY LETTER FROM MEMBER ALONG WITH TECHNICAL QUOTATION. 7. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p>	
29	DGE971 73	O/FLY 23X19FT. I/FLY 20X19FT	8340PK509764 1 / 400 LBS TENT/IP DOUBLE FLY MILITARY PATTERN, WITH GALVANIZED STEEL FRAME AND COMPLETE ACCESSORIE S	MANZOOR SONS KARACHI PAKISTAN	2 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	---------------	----------------	------------------	-----------

											<p>Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p> <p><u>GENERAL SPECIFICATION - SPECIFICATION:</u> OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS</p> <p>manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p>	
--	--	--	--	--	--	--	--	--	--	--	--	--

30	DGT971 64	NO DATA AVAILABL E	010050000001 8 / Ply Wood GD-1, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4',	SPECEFCATI ON.IM-2581 (E)	608 / SQ FEET	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 :</p>	
----	--------------	--------------------------	--	------------------------------	---------------------	--------------------------	--	--	--	--	---	--

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			TH=12MM								1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 GENERAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
31	DGT974 00	NO DATA AVAILABL E	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	700 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 GENERAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
32	DGT973 98	NO DATA AVAILABL E	010050000002 8 / PLY WOOD MARINE ALL SHESHAM	2.440X1. 220MTRX6. 35MM) SPECE/BS-	384 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLYS OF SHESHAM WOOD) 5-PLY	1088							BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M ³ . 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, <u>GENERAL SPECIFICATION -</u> 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M ³ . 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,	
33	DGT92809	NO DATA AVAILAB LE	010050000002 8 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLYS OF SHESHAM WOOD) 5-PLY	2.440X1. 220MTRX6. 35MM) SPECE/BS- 1088	352 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M ³ . 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, <u>GENERAL SPECIFICATION -</u> 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											KG/M ³ . 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,	
34	DGE970 60		830570100083 2 / CALICO CLOTH UNBLEACHED 36 " WIDE		80 / METER						<u>TECHNICAL SPECIFICATION</u> - a. Width: 91.4 cm + 1 cm (36") b. Weight/ sq meter: 115 to 130 gram c. Thread/ cm Warp = 24/25 Weft = 17/18 d. Count of yarn: 20/21 s e. Shrinkage ; 2 % (Max) f. Scouring loss: 1 % (Max) <u>GENERAL SPECIFICATION</u> - a. Width: 91.4 cm + 1 cm (36") b. Weight/ sq meter: 115 to 130 gram c. Thread/ cm Warp = 24/25 Weft = 17/18 d. Count of yarn: 20/21 s e. Shrinkage ; 2 % (Max) f. Scouring loss: 1 % (Max)	
35	DGT971 65	NO DATA AVAILABL E	933070507970 4 / PLASTIC FORMICA DULL COLOUR OFF WHITE SIZE 8'X4' , THICKNESS 1.50mm		17 / SHEET						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILAB <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
36	DGB973 46	NO DATA AVAILABL E	021479013081 4 / BOLT MACHINE STEEL BSF HEX HD SZ 0.500X3. 500X1.000 IN	BR 320 D 78	20 / TEN	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILAB <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
37	DGB973 20	nl-fr-02	534050530180 3 / solar frames		7 / EACH/N UMBER	00					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
38	DGE971 76	NO DATA AVAILABL E	035059923357 6 / FENDER MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6 INTERNAL DIA 10"	MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6	8 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10" <u>GENERAL SPECIFICATION</u> - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
39	DGE975 12	CKM	5640705140378 / FALSE CEILING GYPSUM WITH LIGHT BOXES & FIXING	OFFICE CUBICAL, METTALIC	850 / EACH/N UMBER	NO DATA AVAILAB LE		PK	PAKISTA N		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
40	DGE974 35	SCOTCH 88	5970996648764 / Tape, insulation, Electrical	0	90 / EACH/N UMBER	0	0	3M CENTRE, CAIN ROAD, BRACKNELL	3M UNITED KINGDO M PLC		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
41	DGE972 71	10MM	5970705133476 / GLASS SLEEVEING 10MM	MOTOR WINDING FOR CABLE	126 / EACH/N UMBER	NO DATA AVAILAB LE		PK	GREEN WAY ELECTRI C STORE SHOP NO.1-5 ARAMBA GH KARACHI		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
42	DGE975 58	MIL-T-52809	9611795165359 / HYDRAULIC TROLLEY 02 TONS	HYDRAULIC TROLLEY 02 TONS	2 / EACH/N UMBER	AMEISE 2200	NIL	JUNGHEINRICH UK LTD, HEAD OFFICE SHERBOURNE HOUSE, SHEBOURNE DRIVE, TILBROOK MILTON KEYNES MK7 8HX, PHONE: 01908363100, FAX: 01908363150	JUNGHEI NRICH UK LTD		<u>TECHNICAL SPECIFICATION - MIL-T-52809</u> <u>GENERAL SPECIFICATION - MIL-T-52809</u>	
43	DGE973 23	MIL-T-52809	9611795165359 / HYDRAULIC TROLLEY 02 TONS	HYDRAULIC TROLLEY 02 TONS	2 / EACH/N UMBER	AMEISE 2200	NIL	JUNGHEINRICH UK LTD, HEAD OFFICE SHERBOURNE HOUSE, SHEBOURNE DRIVE, TILBROOK MILTON KEYNES MK7 8HX, PHONE: 01908363100, FAX: 01908363150	JUNGHEI NRICH UK LTD		<u>TECHNICAL SPECIFICATION - MIL-T-52809</u> <u>GENERAL SPECIFICATION - MIL-T-52809</u>	
44	DGE972 45	ASTM D 6413	7210505155171 / FIRE RETARDANT SPRING MATTRESS (L6.5"XW2XH6)	MATRESSES FOR BED	10 / EACH/N UMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		<u>TECHNICAL SPECIFICATION -</u> <u>MATERIAL SPRING: IMPORTED</u> <u>STEEL WIRE(BONNEL/HELICAL)</u> <u>SPRING STRENGTH: 1500-</u> <u>1800N/MM2 COVERING FABRIC:</u> <u>FIRE RETARDANT FOAM: GOOD</u> <u>QUALITY FOAM FELT SHEET</u> <u>(NAMDA): GOOD QUALITY FELT</u> <u>STEEL INTERNAL FABRIC:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	---------------	----------------	------------------	-----------

45	DGE975 23		721050515517 2 / FIRE RETARDANT SPRING MATRESS (L6'XW2'XH6)	MATRESSES FOR BED	25 / EACH/N UMBER			LOCAL ADDRESS:AL- KHAIR HOUSE-43-T,AL- KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL- KHAIR HOUSE- 43-T		IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL) GENERAL SPECIFICATION - MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500- 1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL)	
46	DGE958 35	100-65F	792099300899 7 / CLEANING LINT FREE CLOTH (GUC ITEM)	CLEANING CLOTH	215 / EACH/N UMBER	NO DATA AVAILAB LE		UK	MEMO HCG/MS D/03/336 DT 2/7/08		TECHNICAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413GENERAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 TECHNICAL SPECIFICATION - Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy).	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>GENERAL SPECIFICATION - Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy).</p>	
47	DGE972 68	100-65F	792099300899 7 / CLEANING LINT FREE CLOTH (GUC ITEM)	CLEANING CLOTH	66 / EACH/N UMBER	NO DATA AVAILAB LE		UK		MEMO HCG/MS D/03/336 DT 2/7/08	<p>TECHNICAL SPECIFICATION - Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy).</p> <p>GENERAL SPECIFICATION - Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy).</p>	
48	DGE974 80		042270515841 1 / PVC MAT (SHEET)	SELF	2000 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA	M/S ANWAR PLASTIC		<p>TECHNICAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)					JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	S, SADDAR KARACHI		GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
49	DGE973 80		042270515841 1 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	2250 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTIC S, SADDAR KARACHI		TECHNICAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
50	DGE972 49	L10/11610	534077516837 7 / FLAT POLYSTER WEBBING SLING, SF 6:1	POLICE BOAT LIFTING	2 / EACH/NUMBER			EUROTEX HOLLAND	EUROTE X HOLLAN D		TECHNICAL SPECIFICATION - 10 INCH WIDE 20M LONG PLY 3 VERTICAL LIFT 150000KG U-LIFT 30000KG PLOT 122-C KEMARI TOWNSHIP KEMARI KARACHI PH 0333-2114658 GENERAL SPECIFICATION - 10 INCH WIDE 20M LONG PLY 3 VERTICAL LIFT 150000KG U-LIFT 30000KG PLOT 122-C KEMARI TOWNSHIP KEMARI KARACHI PH 0333-2114658	
51	DGT975 46	NO DATA AVAILAB LE	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTABLISHMENT	5 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE		TECHNICAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM GENERAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									0322-2578654.			
52	DGH95781	LUKUF90105210OM	7125705206257 / FRAME 10' X 3.5'	Racking	15 / EACH/NUMBER	NA		M/s Habib & Sons 3rd Floor, 83-C, Phase II Extension, Main National Highway, Defense Housing Society Karachi-Pakistan	M/s Habib & Sons		<p>TECHNICAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated</p> <p>GENERAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated</p>	
53	DGH95975	LUKUF90105210OM	7125705206257 / FRAME 10' X 3.5'	Racking	15 / EACH/NUMBER	NA		M/s Habib & Sons 3rd Floor, 83-C, Phase II Extension, Main National Highway, Defense Housing Society Karachi-Pakistan	M/s Habib & Sons		<p>TECHNICAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated</p> <p>GENERAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated</p>	
54	DGH96290	LUKUF90105210OM	7125705206257 / FRAME 10' X 3.5'	Racking	5 / EACH/NUMBER	NA		M/s Habib & Sons 3rd Floor, 83-C, Phase II Extension, Main National Highway, Defense Housing Society Karachi-Pakistan	M/s Habib & Sons		<p>TECHNICAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated</p> <p>GENERAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated</p>	
55	DGH96265	LCKHB1081182B	3020705202580 / BEAM PR 2740X240	RACKS	35 / EACH/NUMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726	HABIB & SONS		<p>TECHNICAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Lugs/nut bolt:4 Load safety factor: 01:01.5 <u>GENERAL SPECIFICATION</u> - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
56	DGH96286	LCKHB1081182B	3020705202580 / BEAM PR 2740X240	RACKS	35 / EACH/NUMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726		HABIB & SONS	<u>TECHNICAL SPECIFICATION</u> - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5 <u>GENERAL SPECIFICATION</u> - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
57	DGH95905	LCKHB1081182B	3020705202580 / BEAM PR 2740X240	RACKS	35 / EACH/NUMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726		HABIB & SONS	<u>TECHNICAL SPECIFICATION</u> - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5 <u>GENERAL SPECIFICATION</u> - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
58	DGH959	LCKHB108	302070520258	RACKS	35 /			OFFICE:3RD FLOOR 83 C,		HABIB &	<u>TECHNICAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Avallability	Tender Remarks	TECH / GEN SPECS	Dimension
	63	1182B	0 / BEAM PR 2740X240		EACH/ UMBER			PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021- 5388726	SONS		Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l- type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5GENERAL SPECIFICATION _Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l- type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
59	DGH957 80	LCKHB108 1182B	302070520258 0 / BEAM PR 2740X240	RACKS	35 / EACH/ UMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021- 5388726	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l- type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5GENERAL SPECIFICATION _Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l- type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
60	DGB975 04		028370571116 5 / SHEET- ALUMINIUM- LH-144- WIDTH-48- TH0.080"		25 / EACH/ UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DGB959 08		028370000160 6 / ELECTRODE MONO METAL 08 SWG		80 / METER						TECHNICAL SPECIFICATION - a. Size 3.25 x 350 mm b. Current 90- 120 c. Polarity DC Electrode Negative (DCEN) d. Position Flat, Horizontal, Vertical, Overhead e. Type of Arc Medium, Moderate,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											Penetration f. Material Low Carbon Steels g. Technique Use short Arc length with electrode angle 30o + 15o , to the line of weld. h. (8SWG) Mild Steel (HYUNDAI)GENERAL SPECIFICATION - a. Size 3.25 x 350 mm b. Current 90-120 c. Polarity DC Electrode Negative (DCEN) d. Position Flat, Horizontal, Vertical, Overhead e. Type of Arc Medium, Moderate, Penetration f. Material Low Carbon Steels g. Technique Use short Arc length with electrode angle 30o + 15o , to the line of weld. h. (8SWG) Mild Steel (HYUNDAI)	
62	DGB974 92	SPC BS 1470/NS4 -0;DES STAN 95-4	028399525866 1 / SHEET-ALUMINIUM ALLOY LENGTH 2500 MM WITH 1250 MM SPEC 1.6	PNS BABUR	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
63	DGB974 91		028370571126 0 / ANGLE-ALUMINIUM-LH-2.50-3.50-TH-0.31INCH		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DGB974 90		028370571126 6 / ALUMINIUM ARGLE SIZE 6X3X3"/8		30 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DGE970 53	0413/8568	041359924350 3 / FIBER SHEET, VULCANISED, LG,54"WD.42" THICKNESS 0.031"	FOR AIR COMPRESSOR	100 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
66	DGE971 42		041359923932 9 / WASHER FLAT RUBBER RD;RD HOLE SZ.1.000X1.938X0.188IN		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
67	DGE958 65	0413-8532 &0413_92 3_8899, BS1154	041359923889 9 / RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 HARDNESS RATING 42- 50°,TENSILE STRENGTH : 2500 PSI		200 / KILOGR AMME						TECHNICAL SPECIFICATION - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 GENERAL SPECIFICATION - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21	
68	DGE974 88	9-27061 (NSN 6260-01- 074-4230)	047350473015 9 / LIGHT, CHEMILUMINE SCENT YELLOW	LIGHT STICK (SAFETY LIGHT)- YELLOW	403 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
69	DGE972 47	NO DATA AVAILABL E	047659943474 3 / TUFF GRADE 1" PAINT BRUSH	HANGAR DOOR	157 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inchGENERAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch	
70	DGE974 33	NO DATA AVAILABL E	047659943474 3 / TUFF GRADE 1"	HANGAR DOOR	35 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PAINT BRUSH								25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch <u>GENERAL SPECIFICATION - 1.</u> Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch	
71	DGE974 27	NO DATA AVAILAB LE	055979020048 5 / INSULATION- TAPE- POLYETHYLE NE TERAPHALAT E(TERYLENE) W/0.75		40 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
72	DGE975 19		041459923069 7 / PACKING ASSEMBLIES EXT.DIA 1- 23/32" I.DIA 1- 1/8"NO.PER SET 2		38 / SET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
73	DGE972 64	U1901 AND P35M	041459923069 9 / PACKING ASSY MICA SZ.1.5/32,OD. 3/4,I/D 13/64 2 PERSET SQ. C/S		22 / SET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
74	DGE976 67	NO DATA AVAILAB LE	055979002055 2 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	52 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
75	DGE958 21	NO DATA AVAILAB LE	055979002055 2 / INSULATION	GENERAL ELECTRIC USE	35 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER								AVAILABLE	
76	DGE97141		041359923875 2 / WASHER RUBBER 0.500X0.875IN		12 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DGE97438	0.75X0.007INCH-50MTR-	055979001524 4 / INSULATION-TAPE-VARNISHED WOVEN GLASS-FIBRE-(STRAIGHT CUT)		40 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
78	DGE97653		041459923099 7 / WASHER ASBESTOS COPPER 1.000X0.250X1.000X0.500IN		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DGE97669	NO DATA AVAILAB LE	046254600578 4 / TAPE-BROWN-PAPER-GUMMED (DTLD. NSD/TD/19/286 , DT.09		90 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
80	DGE97248	NIL	047659000775 8 / GLOVES SEAMLESS DIPPED RUBBER		13 / PAIR	202-GNFG					TECHNICAL SPECIFICATION - a. Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc GENERAL SPECIFICATION - a. Product Code:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc	
81	DGE972 67	NO DATA AVAILABL E	046159000098 0 / CLOTH ABRASIVE 9		57 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DGE972 46	047694305 57, BS2992TABLE8ITEM 8/5	047659943055 7 / BRUSH VARNISH TYNEX FIBER FLAT SQUIRE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	122 / EACH/NUMBER						TECHNICAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable GENERAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
83	DGE972 69	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		11 / EACH/NUMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
84	DGE972 56	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		120 / EACH/NUMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
85	DGE97270	NIL	0559794444898 / INSULATION SLEEV ELEC INT DIA 3MM THICK0.500 MATER CERAMIC	GENERAL ELECTRIC USE	145 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DGE97405	NO DATA AVAILAB L E	0350595713132 / ROPE NYLON, 3-STRAND, CIRC: 4-INCH, DIA: 32MM		120 / FATHO M	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI	
87	DGB95909	AWS S-8018-B2	0283700011838 / ELECTRODE WELDING 2.6 MM AWS S-8018-B2	WELDING SYSTEMS	120 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
88	DGE97140	NO DATA AVAILABLE	0413546004794 / EAR DEFENDER LARGE SIZE		25 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
89	DGE97591	0415-2502	0415599231450 / CORK AND RUBBER SHEET, LG.01 MTR WIDTH 01 MTR THICK 3.175MM. SYNTHETIC RUBBER DEF 22		18 / SHEET						TECHNICAL SPECIFICATION - CORK AND RUBBER SHEET, Item Specification: DEF-22, THIC=3.175mm, LG=01 MTR WIDTH 01 MTR Synthetic Rubber. GENERAL SPECIFICATION - CORK AND RUBBER SHEET, Item Specification: DEF-22, THIC=3.175mm, LG=01 MTR WIDTH 01 MTR Synthetic Rubber.	
90	DGE97262	0415-2502	0415599231450 / CORK AND RUBBER SHEET, LG.01 MTR WIDTH 01 MTR THICK 3.175MM. SYNTHETIC RUBBER DEF 22		4 / SHEET						TECHNICAL SPECIFICATION - CORK AND RUBBER SHEET, Item Specification: DEF-22, THIC=3.175mm, LG=01 MTR WIDTH 01 MTR Synthetic Rubber. GENERAL SPECIFICATION - CORK AND RUBBER SHEET, Item Specification: DEF-22, THIC=3.175mm, LG=01 MTR WIDTH 01 MTR Synthetic Rubber.	
91	DGB97497		0283595711459 / ROD		4 / METER						TECHNICAL SPECIFICATION - BS EN-12163 DESIGNATION: CW-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NAVAL BRASS RD DIA.2.50 INCH WT PER MTR 27.49 KG								719R, R-340 SYMBOL: CU zN 39 SN 1GENERAL SPECIFICATION - BS EN-12163 DESIGNATION: CW- 719R, R-340 SYMBOL: CU zN 39 SN 1	
92	DGE975 21	0414-5162	041459923093 5 / ASBESTOS SHEET COMPRESSE D, LENGTH: 63-INCH, WIDTH: 54- INCH, THICKNESS: 0.125 INCH	GENERL PERPOSE	20 / KILOGR AMME						TECHNICAL SPECIFICATION - a. Standard/ Grade: BS 2815, Grade A b. Length (inch) 63 Inch c. Width (inch) 54 d. Thickness (inch) 1/8 (0.125 INCH) e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS- 2815GENERAL SPECIFICATION - a. Standard/ Grade: BS 2815, Grade A b. Length (inch) 63 Inch c. Width (inch) 54 d. Thickness (inch) 1/8 (0.125 INCH) e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS-2815	
93	DGE975 40	NO DATA AVAILABL E	043452000015 6 / LEAD WEIGHT IKG WITH CLAMP TYPE LOCK,T- 40761	DIVING BREATHING APPARATUS T-9651 LARIII	34 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DGE972 63	NIL	041359923892 3 / RUBBER SHEET SOLID NATURAL (CLOTH INSERT)		148 / KILOGR AMME						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCRL: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43- INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL. GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SPECIFICATION OF ITEM AS PER NMCRL: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.</p>	
95	DGE972 65	NIL	041359923892 4 / RUBBER SHEET SOLID NATURAL		167 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - BS 1154 OF 1992 COMPUND Y2 COMPOUND CLASSIFICATION Y-50 Cloth insert, also known as rubber insertion, Thick: 0.063 inch, width: 43 inch, No of PLY: 01 Approx, wt per sq ft: ½ Lbs, tensile strength 17Mpa, Hardness: 50+5-4. Spec: BS 1154</u> <u>GENERAL SPECIFICATION - BS 1154 OF 1992 COMPUND Y2 COMPOUND CLASSIFICATION Y-50 Cloth insert, also known as rubber insertion, Thick: 0.063 inch, width: 43 inch, No of PLY: 01 Approx, wt per sq ft: ½ Lbs, tensile strength 17Mpa, Hardness: 50+5-4. Spec: BS 1154</u></p>	
96	DGE975 92	0413-8553	041359923892 6 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		60 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"</u> <u>GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPU ND Y2, HARDNESS RATING= 42-50"	
97	DGE976 54		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN TRANSPAREN T L X W X THIC 48"X48"X0. 250"		54 / SHEET						TECHNICAL SPECIFICATION - Manfr/Tech.Sponcer Code reference: DTD 5592GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference:DTD 5592	
98	DGB960 20		026659000039 0 / HAND CUFFS BRIGHT STEEL LARGE SIZE WITH KEY		2 / PAIR						TECHNICAL SPECIFICATION - made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kgGENERAL SPECIFICATION - made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg	
99	DGB943 45		026759521328 0 / PIPING STEEL GALVANIZED SEAMLESS (EXT DIA 1.906		100 / METER						TECHNICAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P- 265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0.128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtrGENERAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P-265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0. 128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr	
100	DGB943 42		026759521328 1 / PIPING	GENERAL USE	60 / METER						TECHNICAL SPECIFICATION - 1. BSEN:10216-2 OF 2019 2. BS EN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			STEEL GALV SEAMLESS, EXT DIA: 60.3 mm,WALL THKNESS: 3.6 mm,N/BORE: 50.8mm, running length 6 meter								ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships. <u>GENERAL SPECIFICATION - 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships.</u>	
101	DGB940 95		026759521328 1 / PIPING STEEL GALV SEAMLESS, EXT DIA: 60.3 mm,WALL THKNESS: 3.6 mm,N/BORE: 50.8mm, running length 6 meter	GENERAL USE	60 / METER						<u>TECHNICAL SPECIFICATION - 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships.</u> <u>GENERAL SPECIFICATION - 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships.</u>	
102	DGB943 46		026759521328 2 / PIPING STEEL GALVANIZED SEAMLESS	LENGHT BULK SUPPLY EXT DIA 76.1MM(3	100 / METER						<u>TECHNICAL SPECIFICATION - SIZES: EXT DIA 03 INCH, WALL THICKNESS; 0.144" AND NOMINAL BORE: 2.5" (AS PER BR 320 D) RUNNING LENGTH: 06 METERS STANDARD SPECIFICATION 1- BS EN 10216-2 of 2019 2. BS EN ISO 10240 Thickness of 55 um on inside and outside of pipe is recommended FOR GALVANIZATION. GENERAL SPECIFICATION - SIZES: EXT DIA 03 INCH, WALL THICKNESS; 0.144" AND NOMINAL BORE: 2.5" (AS PER</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											BR 320 D) RUNNING LENGTH: 06 METERS STANDARD SPECIFICATION 1- BS EN 10216-2 of 2019 2. BS EN ISO 10240 Thickness of 55 um on inside and outside of pipe is recommended FOR GALVANIZATION.	
103	DGT975 42	NIL	010050100011 7 / PLY WOOD MARINE SHESHAM GRADE-I		64 / SQ FEET						<p><u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: 1. PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 5 PLY. TYPE OF BOND WBP CLASS-II BS EN 314-2 TREATED WITH PRESERVATIVE AS PER SPECS. 2. BS 1088 PART 1 & 2. 3. DENSITY OF TEMBER (SHEESHAM) AS PER INTERNATIONAL STANDARD. 4. SIZES: LENGTH: 8 FEET, WIDTH: 4 FEET, THICKNESS: 3/8 INCH, THICKNESS OF VEENER (FACE&BACK): 06MM (MIN).</p> <p><u>GENERAL SPECIFICATION -</u> SPECIFICATION: 1. PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 5 PLY. TYPE OF BOND WBP CLASS-II BS EN 314-2 TREATED WITH PRESERVATIVE AS PER SPECS. 2. BS 1088 PART 1 & 2. 3. DENSITY OF TEMBER (SHEESHAM) AS PER INTERNATIONAL STANDARD. 4. SIZES: LENGTH: 8 FEET, WIDTH: 4 FEET, THICKNESS: 3/8 INCH, THICKNESS OF VEENER (FACE&BACK): 06MM (MIN).</p>	
104	DGB960 49	NO DATA AVAILABL E	026659128262 8 / SCREW MACHINE STEEL (zinc		200 / TEN						<p><u>TECHNICAL SPECIFICATION -</u> Screw Machine Steel (MS Zinc coated): Length: 1 inch Dia : 4 mm Thread Type: BA <u>GENERAL</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			coated)								SPECIFICATION - Screw Machine Steel (MS Zinc coated): Length: 1 inch Dia : 4 mm Thread Type: BA	
105	DGH963 93	BS1449 PART 1 HR37/23P	021159237188 4 / STEEL SHEET 08.X04. X0.064 16 SWG NSN 9515-99-525-9254		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DGB960 23	BS 1127	027179910134 4 / DIE THREAD CUTTING CS BSF12.0 TPI SZ 0.750X2. 250X0.687"	P/N BS 1127	89 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DGH956 94	NO DATA AVAILAB L E	022359423410 9 / CHAIN MOORING ANCHOR LENGTH 27.4 MTR DIAMETER 20.0MM		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
108	DGE931 40	NIL	035059923712 8 / ROPE NYLON, HAWSERLAID, Z-LAY, 3-STRANDS, NOM DIA: 20MM, CIRC: 2.50 INCH, TYPE: 1, MINIMUM BREAKING LOAD: 8.3 TONS	MIN BRKG STRENGTH UNIT OF AVAILABILITY	120 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	---------------	----------------	------------------	-----------

											<p>TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
--	--	--	--	--	--	--	--	--	--	--	---	--

109	DGB959 10	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	150 / KILOGR AMME						<p><u>TECHNICAL SPECIFICATION - a.</u> Dia: 3.2mm b. Length: 350 mm- 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface<u>GENERAL SPECIFICATION</u> - a. Dia: 3.2mm b. Length: 350 mm- 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface</p>	
110	DGB928 34		021459941001 9 / BOLT	BR-320 D/78	296 / EACH/N						<p><u>TECHNICAL SPECIFICATION - AISI PD 970:2005, MATERIAL GRADE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MACHINE STEEL UNC class 2a HEX HD SZ 0.625 X3.000X1.500 IN		UMBER						708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED GENERAL SPECIFICATION - AISI PD 970: 2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED	
111	DGE946 01	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	410 / FATHOM						<p><u>TECHNICAL SPECIFICATION - 1.</u> 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
112	DGB96233		025850258120 3 / COPPER-WIRE-2-MM-DIA		22 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION -</u> Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER</p> <p><u>GENERAL SPECIFICATION -</u> Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
113	DGB96234		026559423318 2 / NAIL-STEEL-TINNED-FLAT-HEAD-0.50 INCH		100 / KILOGRAMME						<p>TECHNICAL SPECIFICATION - Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm² Length related weight: 26.5 kg/1000 m cOPPER : 99.9 % copper purity with 2mm diameter</p> <p>GENERAL SPECIFICATION - Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm² Length related weight: 26.5 kg/1000 m cOPPER : 99.9 % copper purity with 2mm diameter</p>	
114	DGB97042	1473	024879129614 8 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE, DOOR NOT LESS THAN 3/8" THK-	2 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03</p> <p>GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03</p>	
115	DGB95943		025770128376 9 / BOLT MACHINE BRASS BSW HEX HD SZ 0.375X1.000X1.500 IN		42.5 / DOZEN						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</p> <p>GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
116	DGB95562	NTER SUNK SLOT DRIVE SPEC BS1210	026659000022 6 / SCREW WOOD BRASS27 TONS/SQUARE FALT CSK SLOT IN MTS DRIVE HD 7G LG 0.750 IN		1931 / DOZEN						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</p> <p>GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
117	DGB97498	NO DATA AVAILABLE	021259571062 3 / LATHE MACHINE CUTTING TOOL STEEL	LATHE MACHINE	5 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - Material: steel high speed square' hot rolled dimension : 3/4" x 3/4"x "6.</p> <p>GENERAL SPECIFICATION - Material: steel high speed square' hot</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HIGH SPEED SQ HOT ROLLED								rolled dimension : 3/4" x 3/4"x "6.	
118	SGB973 16		132572335001 0 / BLADE POWER HACK SAW HSS 18X1-1/2X0. 075" 6TPI		65 / EACH/N UMBER	AISI M2 HSS (Super Hardened)					TECHNICAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 ½ x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened)GENERAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 ½ x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened)	
119	DGE876 71		209050503923 3 / GROUND SHEET- CANVAS LG- 2M 35CM WITH85CM THK 0.75MM		50 / EACH/N UMBER						TECHNICAL SPECIFICATION - Specifications: √ Material: Polyester-cotton canvas with PU/ PVC coating. √ Weight: 450-550 GSM √ Size: 5m x 8m (standard) √ Coating: Waterproof, anti-fungal, UV-resistant √ Color: Olive green/ khaki/ brown √ Edges: Reinforced with rust proof eyelets. √ Finish: Mildew resistant Technical Data: √ Waterproofing: 2000 mm hydrostatic head √ Tensile Strength: 350 N/ cm (warp), 300 N/ cm (weft). √ Tear Strength: 50N √ UV Resistance: 500 hrs exposure without degradation √ Abrasion: 30,000 rubs √ Shrinkage: 3% √ Temp Range: -100 C to + 550 √ Flame Retardant: NFPA 701/ BS 5852 compliant Testing Criteria : √ Hydrostatic pressure (ISO 811) √ Tensile & tear strength (ISO 13934-1, ISO 13937-2) √ UV resistance √ Mildew test √ Abrasion (ISO Standard) √ Shrinkage (ISO Standard) √ Fire resistance Accepting Criteria: √ Waterproof 2000 mm √ Tensile 350/300 N/cm √ Tear Strength > 50N √ No mildew growth (7 days) √ UV degradation 15% √ Abrasion > 30,000 rubs √ Shrinkage 3% √ Must pass flame test dimension: Width = 4 feet Height = 3 feet GENERAL SPECIFICATION - Specifications: √ Material: Polyester-cotton canvas with PU/ PVC coating. √ Weight: 450-550 GSM √ Size: 5m x	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	---------------	----------------	------------------	-----------

8m (standard) ∩ Coating: Waterproof, anti-fungal, UV-resistant ∩ Color: Olive green/ khaki/ brown ∩ Edges: Reinforced with rust proof eyelets. ∩ Finish: Mildew resistant Technical Data: ∩ Waterproofing: 2000 mm hydrostatic head ∩ Tensile Strength: 350 N/ cm (warp), 300 N/ cm (weft). ∩ Tear Strength: 50N ∩ UV Resistance: 500 hrs exposure without degradation ∩ Abrasion: 30,000 rubs ∩ Shrinkage: 3% ∩ Temp Range: -100 C to + 550 ∩ Flame Retardant: NFPA 701/ BS 5852 compliant Testing Criteria : ∩ Hydrostatic pressure (ISO 811) ∩ Tensile & tear strength (ISO 13934-1, ISO 13937-2) ∩ UV resistance ∩ Mildew test ∩ Abrasion (ISO Standard) ∩ Shrinkage (ISO Standard) ∩ Fire resistance Accepting Criteria: ∩ Waterproof 2000 mm ∩ Tensile 350/300 N/cm ∩ Tear Strength > 50N ∩ No mildew growth (7 days) ∩ UV degradation 15% ∩ Abrasion > 30,000 rubs ∩ Shrinkage 3% ∩ Must pass flame test dimension: Width = 4 feet Height = 3 feet

120	DGH954 67		056159000974 3 / CABLE ELECT LEAD 3CORE COND1/.036		200 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
121	DGH954 64		056159018066 7 / CABLE ELECTRIC NO. OF CORES_2, SIZE OF COND. (IN) 162/.0076,		200 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DGE972 66	NO DATA AVAILABL E	047259425973 5 / FABRIC RUBBERIZED 2PLY RH BIAS COLOUR		40 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			BLUE									
123	DGE972 61	.BS 7344,1990.	0462592202400 / TUBING PLASTIC POLYETHYLE NE FLAT	PACKAGING /PRESERVATI ON	88 / KILOGR AMME						TECHNICAL SPECIFICATION - a. THICKNESS: 0.005 (127 MICRON) b. WIDTH: 15 INCHES c. APPEARANCE: CLEAR/ WHITE/ PLAIN d. Testing/ Acceptance Clear/ White/ Plan CriteriaGENERAL SPECIFICATION - a. THICKNESS: 0.005 (127 MICRON) b. WIDTH: 15 INCHES c. APPEARANCE: CLEAR/ WHITE/ PLAIN d. Testing/ Acceptance Clear/ White/ Plan Criteria	
124	DGH954 65		0561590002533 / CABLE ELECT R.I N.S. A 2CORE COND 7/0.036 500LG		200 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
125	DGE971 08		4220705046424 / AIRCRAFT MARSHALLER S IDENTIFICATI ON JACKET	TO USED BY GROUND PERSONEL DEPLOYED	24 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
126	DGE974 85	NSN 1370-99-9629136	4220725055198 / HAND FLARE RED P MK 3 (USE ONLY WHEN AIRCRAFT)	SURVIVAL PACK USED FOR 20MEN LIFERAFT	10 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DGB753 54	FAG 6330M	3110001568288 / BEARING BALL ANNULAR FAG 6330M SZ 150.00 X320.00X65.00MM		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
128	DGB955 50	CH50-10	4030705039310 / CHAIN BLOCK 5TON CAPACITY WITH 45 FEET	FOR GENERAL PURPOSE-	1 / EACH/N UMBER	CH50-10					TECHNICAL SPECIFICATION - Make: ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 Inch Weight: 84 LBS Type: Manual	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			DRIFT LINE DIA 9MM-								Acceptance CRITERIA : lifting OF 5 Tons Load GENERAL SPECIFICATION - Make: ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 Inch Weight: 84 LBS Type: Manual Acceptance CRITERIA : lifting OF 5 Tons Load	
129	DGB955 51	ANT COUPLIN G-	472070505711 2 / FIRE HOSE SIZE 2-1/2" X100 FEET DURLANE 500 LIGHT ALLOY INST-	FOR FIRE FIGHTING	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
130	DGE958 25		535000235013 7 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE 2/0		160 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
131	DGE971 15		535099461682 9 / STEEL WOOL 1 LB PER BALLS 50 BALLS PER CARTOON GRADE-3	FOR GENERAL USE	6 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
132	DGE972 57		535099461682 9 / STEEL WOOL 1 LB PER BALLS 50 BALLS PER CARTOON GRADE-3	FOR GENERAL USE	16 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
133	DGE958 24	A-A-1201, P-P-121, ANSIB74-18	535000186882 0 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE 110-A		160 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
134	DGB84165	NO DATA AVAILAB LE	534576501638 5 / DISC CUTTING SIZE 300MM X 3.0 MM X 22.23MM		50 / EACH/N UMBER						TECHNICAL SPECIFICATION - Make:Rhodius Model: Alphaline ST21 Made:EU Dimensions: 300mm x 3.0mm x 22.23mm Diameter : 300 mm Thickness: 3.0 mm Hole: 22.23 mm GENERAL SPECIFICATION - Make:Rhodius Model: Alphaline ST21 Made:EU Dimensions: 300mm x 3.0mm x 22.23mm Diameter : 300 mm Thickness: 3.0 mm Hole: 22.23 mm	
135	DGE95671	P 51241/S	6150GR506607 5 / CABLE TIES200/5MM	MAN AUX MARINE DIESEL GENERATOR 300KW	200 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
136	DGE95830	1756654	597000184200 2 / TAPE- INSLATION		30 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
137	DGE97432	81349 MIL- 1-46852	597000955997 6 / TAP INSULATING BLACK ADHESIVE RUBBER W 1		6 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
138	DGE97429		597000543115 4 / TAPE INSULATION WOVEN GLASS WIDTH 13MM,THICK 0.18MM,LG. 50MTR		50 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
139	DGE92856	NO DATA AVAILAB LE	042250000003 3 / CARPET WOOLEN.		768 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm GENERAL SPECIFICATION - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
140	DGE97250	NO DATA AVAILABLE	042250000003 3 / CARPET WOOLEN.		400 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm GENERAL SPECIFICATION - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm	
141	DGE72389	NO DATA AVAILABLE	042250000003 4 / CARPET WOOLEN DARK GRAY B-92		536 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
142	DGE95862		834070504571 2 / CLOTH COVER BEIGE FOR CHAIRS	FOR WARD ROOM	100 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
143	DGE95858		813570506488 2 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	55 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
144	DGT95622	NO DATA AVAILABLE	010000000000 3 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	174 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DGE94009	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	2 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAGE					TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p> <p><u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON</p> <p>BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
146	DGE939 31	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATIO N	2 / EACH/N UMBER	OPTICAL INFRARE D CAMOUF LAGE NET. ANTI RADAR CAMOUF LAG					<p>TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI- SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25- INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p> <p>GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI- SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE=</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
147	DGT97602	NO DATA AVAILAB LE	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	960 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 <u>GENERAL SPECIFICATION</u> - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
148	DGT97506	NO DATA AVAILAB LE	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	1482 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 GENERAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993</p>	
149	DGT976 62	NO DATA AVAILABL E	010050000003 0 / PLY WOOD NATURAL TEAK FINISH BOTH SIDE (NOT ARTIFICIAL) GRADE-1, 9- PLY, LENGTH= 8- FEET, WIDTH= 4- FEET, THICKNESS= 16mm ±2	2.44X1. 22MTRX19. 05MM) SPECE/BS656 6 OF1985	64 / SQ FEET	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - SPECIFICATION: bs-1088 part-1&II, density of PLY WOOD TEAK= 500 TO 850 KG/M3, thickness of face back venEer should be 0.6 mm (min) GENERAL SPECIFICATION - SPECIFICATION: bs-1088 part-1&II, density of PLY WOOD TEAK= 500 TO 850 KG/M3, thickness of face back venEer should be 0.6 mm (min)</p>	
150	DGT976 60	NO DATA AVAILABL E	010050000001 1 / Ply Wood GD-I, 13 ply (core and inner plies of Poplar Size:L = 8'W = 4'Th = 25 MM		64 / SQ FEET	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - SPECIFICATION:(1)BS-6566 OF 1985. PART 1-8. TYPE-INT. WOOD PRESERVATION AS PER BS-6566, Part-7,appendex.GENERAL SPECIFICATION - SPECIFICATION: (1)BS-6566 OF 1985. PART 1-8. TYPE-INT. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex.</p>	
151	DGE973 90	NO DATA AVAILABL E	8415PK506744 2 / CLOTH PARASHUTE GRAY		100 / METER						<p>TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											proof colour of item is gray end user acceptance required on delivery	
152	DGE976 20	NO DATA AVAILABL E	8415PK506744 2 / CLOTH PARASHUTE GRAY		400 / METER						<u>TECHNICAL SPECIFICATION</u> - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery <u>GENERAL SPECIFICATION</u> - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
153	DGE973 21	NO DATA AVAILABL E	8415PK506744 2 / CLOTH PARASHUTE GRAY		400 / METER						<u>TECHNICAL SPECIFICATION</u> - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery <u>GENERAL SPECIFICATION</u> - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
154	DGB960 50	NO DATA AVAILABL E	026550000130 2 / HINGES- PYANO- STEEL- LG 6 FT 0.750-INCH WIDTH		199 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION</u> - NO DATA AVAILABLE	
155	DGE974 31	NO DATA AVAILABL E	045150000002 1 / CLOTH TICKEN BLUE STRIPS WIDTH 58 INCHES		1621 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - a. WIDTH:58 INCH(1,473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT;40 d.COUNT OF YARN WARP;2/206 WEFT2/206 e. SHRINKAGE- WARP; 2%(MAX) WEFT;2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS) <u>GENERAL SPECIFICATION</u> - a. WIDTH:58 INCH(1,473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT;40 d.COUNT OF YARN WARP;2/206 WEFT2/206 e. SHRINKAGE- WARP; 2%(MAX) WEFT;2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS)	
156	DGE952 68	PLATILON C	933099225122 3 / PLASTIC SHEET,TRAN	STRUCTURE CASING FORGINS	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION</u> - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SPIRIT ,200M ROL,1.8M WIDE								AVAILABLE	
157	DGT97544	NO DATA AVAILAB LE	010050000003 9 / TIMBER FIR HIMALAYA/ SPRUCE SLEEPER, WELL SEASONED LOCAL/ IMPORTED, SIZE: L=8'-15', W=8"-14", h=4"-10"	(3.05MTR X254 MM X127 MM) SPECE/PSG 69	25 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%, <u>GENERAL SPECIFICATION -</u> SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%,	
158	DGE78683		933099224609 0 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4. X0.60 to 0.70 MM	GENERAL USE	2 / SHEET						<u>TECHNICAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 <u>GENERAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
159	DGE78063		933099224609 0 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4. X0.60 to 0.70 MM	GENERAL USE	3 / SHEET						<u>TECHNICAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 <u>GENERAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
160	DGE81009		933099224609 0 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4. X0.60 to 0.70 MM	GENERAL USE	9 / SHEET						<u>TECHNICAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 <u>GENERAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
161	DGE79090		933099224609 0 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4.	GENERAL USE	2 / SHEET						<u>TECHNICAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 <u>GENERAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			X0.60 to 0.70 MM								Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
162	DGD974 03	NO DATA AVAILABL E	732070501321 6 / POTATOES PEELER MACHINE 15 to 20 kg CAPACITY s/steel		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market GENERAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market	
163	DGE976 50		731070505462 5 / ICE BOX SIZE 3'.X2'. X2'(FEET). WALL THICK 46MM SHEET GALVANIZED	HOUSE HOLD	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - size: 3 ft x 2ft x 2ft GENERAL SPECIFICATION - size: 3 ft x 2ft x 2ft	
164	DGE958 20	BS 419/156	055954600536 2 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
165	DGE876 63	IS8021	047654600478 5 / Coated Rigger Gloves with Rubberized Cuff		130 / PAIR						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
166	DGD974 02	NO DATA AVAILABL E	003250000013 8 / KNIFE BUTTER PN CRESTED (AS PER STOCK SAMPLE)	RADAR 1006	20 / EACH/N UMBER	LOCAL					TECHNICAL SPECIFICATION - Material Stainless steel non magnetic & non reactive, food grade stainless stell (AS PER STOCK SAMPLE) GENERAL SPECIFICATION - Material Stainless steel non magnetic & non reactive, food grade stainless stell (AS PER STOCK SAMPLE)	
167	DGE974 30	MIL-I-46852	597000177162 7 / TAPE INSULATION ELECTRICAL NOMINAL WD 1.5		96 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - PVC TAPE OSAKA Tape insulation electrical ADHES plastic BLK WD 19 mm thickness 0.2mm GENERAL SPECIFICATION - PVC TAPE OSAKA Tape insulation electrical	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ADHES plastic BLK WD 19 mm thickness 0.2mm	
168	DGH95573	NO DATA AVAILABLE	5305ZO6568045 / LAWN MOVER MACHINE		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
169	DGH95530	NO DATA AVAILABLE	5305ZO6568045 / LAWN MOVER MACHINE		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
170	DGE79971	0413-8553,	0413599238926 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		59 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"</u> <u>GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"</u>	
171	DGT97947	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"		4400 / FOOT	NO DATA AVAILABLE		PK		TAWAKAL BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI	<u>TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required</u> <u>GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required</u>	
172	DGE97680	Nil	8415705228017 / PARACHUTE CLOTH FOR WEAPONS AND SENSORS	Cloth	300 / METER	NIL		AL MUSTAFA TRADERS F-41/F-42, Iqbal Center, M. A. Jinnah Road, Karachi-74200	AL MUSTAFA TRADERS		<u>TECHNICAL SPECIFICATION - Type of cloth: Parachute Cloth Code: D-16-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof. with good quality gauge to withstand humid and hot environment.</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - Type of cloth: Parachute Cloth Code: D-16-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof. with good quality gauge to withstand humid and hot environment.	
173	DGE977 13	B2315512	471070517796 0 / FLEXIBLE PIPE 1 INCH DIA	CNA LAN NETWORK	1320 / METER			ADAMJEE PAKISTAN		ADAMJEE PAKISTAN	TECHNICAL SPECIFICATION - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter GENERAL SPECIFICATION - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter	
174	DGE974 84	0413-8532 &0413_92 3_8899, BS1154	041359923889 9 / RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42- 50°,TENSILE STRENGTH : 2500 PSI		300 / KILOGR AMME						TECHNICAL SPECIFICATION - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 GENERAL SPECIFICATION - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											21	
175	DGE976 71		047659000006 2 / GLOVES LEATHER LEFT HAND.		55 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable</p> <p>GENERAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable</p>	
176	DGE976 12	047694305 57, BS2992TA BLE8ITEM 8/5	047659943055 7 / BRUSH VARNISH TYNEX FIBER FLAT SQUIRE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	28 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable</p> <p>GENERAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable</p>	
177	DGE976 16	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		60 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8</p> <p>GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8</p>	
178	DGE976 68	0415-9061	041559923141 9 / SAFETY WALK TREAD NONMETALIC, NON-SKID, LENGTH= 2- FEET, WIDTH= 6-INCH,		202 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. Make / Model / Brand / Equivalent be endorsed: Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated : Anti-Skid Safety Walk Used Over Stairs, 4. Detailed specifications / Technical data Testing : Safety Walk Thread Nonmetallic Nonskid SIZE: Length 2- FEET, Width 6-INCH</p> <p>GENERAL SPECIFICATION - 1. Make / Model / Brand / Equivalent be endorsed: Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated : Anti-Skid Safety Walk Used Over Stairs, 4. Detailed specifications / Technical data Testing : Safety Walk Thread</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Nonmetallic Nonskid SIZE: Length 2- FEET, Width 6-INCH	
179	DGE976 52		041459924180 8 / PAPER GASKET OIL PROOF JOINTING 100YD ROLLS WD.42"TH. 1/64".		72 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
180	DGB974 87		026659000039 0 / HAND CUFFS BRIGHT STEEL LARGE SIZE WITH KEY		10 / PAIR						<u>TECHNICAL SPECIFICATION -</u> made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg <u>GENERAL SPECIFICATION -</u> made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg	
181	DGT977 98	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD- II (CORE INNER & OUTER PLYS OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIV E		280 / SQ FEET						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS- 4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB- 2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) <u>GENERAL SPECIFICATION</u> - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
182	DGT978 62	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD- II (CORE INNER & OUTER PLYS		280 / SQ FEET						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS- 4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB- 2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE								(±1MM)GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
183	DGB977 19		026759571170 5 / PIPING STEEL GALV 6.00X6.500X0.176IN		14 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
184	DGB978 44	NO DATA AVAILABL E	026559423350 3 / PAD LOCK , 1 INCH JAPANNE D STEEL OR GALVANISE D CASE BRASS INTERIOR WITH 2 KEYS		24 / EACH/N UMBER						TECHNICAL SPECIFICATION - PAD LOCK, 1 INCH JAPANNE D STEEL OR GALVANISE D CASE BRASS INTERIOR WITH 2 KEYS. FORMER NS CAT. NO. 6964 SPEC NO: DGS 45. DWG XC11/104/4106GENERAL SPECIFICATION - PAD LOCK, 1 INCH JAPANNE D STEEL OR GALVANISE D CASE BRASS INTERIOR WITH 2 KEYS. FORMER NS CAT. NO. 6964 SPEC NO: DGS 45. DWG XC11/104/4106	
185	DGB974 86		027370910421 6 / CHISEL COLD HAND SPEARHEAD OVERALL LG 6.50IN		40 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
186	DGB978 49	1473	024879129614 8 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE,DOOR NOT LESS THAN3/8"THK-	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03	
187	DGB976 81	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS)	NIL	150 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR								UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
188	DGB977 25	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	100 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
189	DGE975 93	NO DATA AVAILABL E	055979900471 5 / INSULATION- SLEEVING- RED-17MM		1 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
190	DGB974 89	C60	047450448149 7 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	FOUNDRY USE OEM MORGANITE UK FAX NO	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
191	DGE974 81	GRADE40 0	5350PK510407 1 / WATER PROOF SAND PAPER GRADE400	WOODEN & GRP BOATS,, AQUATIC CLUB D/YARD	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
192	DGT978 64	NO DATA AVAILABL E	553070504293 3 / PLY WOOD NATURAL TEAK FINISH ONE SIDE	PRESENTATIO N BOXES FOR VVIPS	96 / SQ FEET						TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			(NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W=4' TH=03mm to 04mm								back ply should of hard wood Thickness of face and back veneer = 0.6mm <u>GENERAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm</u>	
193	DGE979 71		543070504426 5 / TANK WATER FIBRE GLASS CAPACITY 1000 GALLONS LENGTH 9 FEET, 6 INCH.		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
194	DGE978 54		543070504426 5 / TANK WATER FIBRE GLASS CAPACITY 1000 GALLONS LENGTH 9 FEET, 6 INCH.		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
195	DGD981 32	LG-MP-9482 SR	731073511893 9 / MICROWAVE OVEN-LG SHARP WAVES/DAWLANCE & TOSHIBA	MICROWAVE OVEN LG	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - capacity: 36 LITTERs</u> <u>GENERAL SPECIFICATION - capacity: 36 LITTERs</u>	
196	DGB975 31	NO DATA AVAILAB LE	026850000004 6 / SALTER-CHECKWEIGH ER-MODLE 652-CAPACITY 30KG WITH HANGING PAN	30 KG X100G DIVISION DIAL 12" FITTTED	2 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
197	DGE976 11	NO DATA AVAILAB LE	841570504570 5 / CLOTH	CEREMONAL ACCOMODATI	60 / METER						<u>TECHNICAL SPECIFICATION - a. Nylon 1680D, PU Coating, Water</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		E	PARASHUTE WHITE	ON SCREEN							Proof (Packing 50 yard per Roll, Width 5 Ft) b. $\pm 2\%$ tolerance is acceptable GENERAL SPECIFICATION - a. Nylon 1680D, PU Coating, Water Proof (Packing 50 yard per Roll, Width 5 Ft) b. $\pm 2\%$ tolerance is acceptable	
198	DGT977 59	NO DATA AVAILAB L E	01005000002 9 / Ply wood, Marine All Shesham, 13-Ply, GD-II, (WBP, Treated with Preservative) Size: L=8FT, W=4FT, TH=25MM, (Core inner plies & veneer) (Wood Should be all Shesham)		320 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER GENERAL SPECIFICATION - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER	
199	DGE975 84	NO DATA AVAILAB L E	8415PK506744 2 / CLOTH PARASHUTE GRAY		400 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
200	DGE974 83	60-501-001	615076502401 1 / TIE WRPA (CABLE TIE) P/N 60-501-001	GRADIOMETE R SYSTEM	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held GENERAL SPECIFICATION - a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held	
201	DGD787 08		732070501321 4 / TOASTER TWO SLOT 220V 50HZ 01	FOR DOMASTIC USE	3 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Make/ Model / Brand/ Equivalent be endorsed: Panasonic/ Dawlance/ West point a. Make/ Model of item	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PHASE 920W								Moulinex LT 140827 Black & Decker ET 222 Philips HD 2637/90 b. OEM COC/ authorized dealer certificate/ mill test certificate (MTC): Not required GENERAL SPECIFICATION - a. Make/ Model / Brand/ Equivalent be endorsed: Panasonic/ Dawlance/ West point a. Make/ Model of item Moulinex LT 140827 Black & Decker ET 222 Philips HD 2637/90 b. OEM COC/ authorized dealer certificate/ mill test certificate (MTC): Not required	
202	DGD98134	T52254 / E-6228	7320705045236 / MINCING MACHINE NO 22 WITH 2HP MOTOR BASE FRAME RPM 1420		2 / EACH/NUMBER	pakistan					TECHNICAL SPECIFICATION - Frame of Machine Material: Mild Steel, MATERIAL OF Motor body and Mincing Machine: Cast Iron NOTE: ITEMS MADE IN PAKISTAN TECHNICALY ACCEPTENCE BY END USER GENERAL SPECIFICATION - Frame of Machine Material: Mild Steel, MATERIAL OF Motor body and Mincing Machine: Cast Iron NOTE: ITEMS MADE IN PAKISTAN TECHNICALY ACCEPTENCE BY END USER	
203	DGD97875		0035500000520 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		9 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER GENERAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
204	DGE97700	NO DATA AVAILAB LE	5920006443167 / TAP INSULATING		15 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
205	DGE97482	NO DATA AVAILAB LE	0461546004602 / BOX FIRST		3 / EACH/N						TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		E	AID 728 MS		UMBER						SPECIFICATION - NO DATA AVAILABLE	
206	DGD981 37	B-650	733070526967 5 / VEGETABLE CUTTER		2 / EACH/N UMBER	b-650					TECHNICAL SPECIFICATION - stainless steel body, motor: 1 h/p, bottom frame: 1/1 angle 3mm thickness, high efficient blade GENERAL SPECIFICATION - stainless steel body, motor: 1 h/p, bottom frame: 1/1 angle 3mm thickness, high efficient blade	
207	DGD981 33	MJ-DJ31	733070527066 5 / PANASONIC JUICER BLENDER 3 IN 1		1 / EACH/N UMBER	MJ-DJ31					TECHNICAL SPECIFICATION - BRAND PANASONIC, CAPACITY: 1LTR, VOLTAGE: 800W, JAR MATERIAL TYPE GLASS, OPERAING MODE MANUAL, SKLI 227669609, PK-1447852121, 2 LTR CAPACITY GENERAL SPECIFICATION - BRAND PANASONIC, CAPACITY: 1LTR, VOLTAGE: 800W, JAR MATERIAL TYPE GLASS, OPERAING MODE MANUAL, SKLI 227669609, PK-1447852121, 2 LTR CAPACITY	
208	DGT977 58	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	104 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
209	DGE976 48	23-53-21-17-01SA	047670520731 9 / SHOOTER GLOVES	GLOVE	7 / EACH/N UMBER	X-PRO by Alif	NA	M SADIQ ALI & SONS, 217/15, SALEH MARKET, ADAMJEE ROAD, SADDAR, RAWALPINDI. 051-5527252 051-5513958		M SADIQ ALI & SONS	TECHNICAL SPECIFICATION - goatskin leather (abrasion resistant) reinforced palm and double stitching for heavy duty protection from abrasion reinforced digital leather layer with antislip feature and grip for tactical applications durable, lightweight, breathable and comfortable adjustable wrist design	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(X-PRO by Alif).GENERAL SPECIFICATION - goatskin leather (abrasion resistant) reinforced palm and double stitching for heavy duty protection from abrasion reinforced digital leather layer with antislip feature and grip for tactical applications durable, lightweight, breathable and comfortable adjustable wrist design (X-PRO by Alif).	