

**LOCAL PURCHASE DIVISION – PAKISTAN NAVY**

**TERMS & CONDITIONS FOR INVITATION TO TENDER TO BE OPENED ON 13-05-2026**

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 50/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER / CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
  
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION
  
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
  
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELVES REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: [clp@paknavy.gov.pk](mailto:clp@paknavy.gov.pk), [localpurchasedivision@gmail.com](mailto:localpurchasedivision@gmail.com)

PHONE: 021-48508828, 021-48508924

WHATSAPP NO. 092-322-0188121 (MESSAGE ONLY)

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE99929	PLATILON C	9330992251223 / PLASTIC SHEET, TRAN SPIRIT, 200M ROL, 1.8M WIDE	STRUCTURE CASING FORGINS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
2	DGE98451	PLATILON C	9330992251223 / PLASTIC SHEET, TRAN SPIRIT, 200M ROL, 1.8M WIDE	STRUCTURE CASING FORGINS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
3	DGB97346	NO DATA AVAILABLE	0214790130814 / BOLT MACHINE STEEL BSF HEX HD SZ 0.500X3.500X1.000 IN	BR 320 D 78	20 / TEN	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
4	DGE97483	60-501-001	6150765024011 / TIE WRPA (CABLE TIE) P/N 60-501-001	GRADIOMETER SYSTEM	100 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held GENERAL SPECIFICATION - a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held	
5	DGE100167	BS 419/156	0559546005362 / TAPE INSULATING		40 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR								AVAILABLE	
6	DGE981 81		045154600445 8 / ROLLER- RING PLASTIC FOR CURTAIN LG 11MM O/D 11.7 X11 MM		5 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
7	DGD989 42		003554600066 1 / STRAINERSRI CE FOR POTS ALU 20X10 INCH		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
8	DGE100 163	NO DATA AVAILABL E	055978000018 5 / SLEEVE PLASTIC		5 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DGE977 00	NO DATA AVAILABL E	592000644316 7 / TAP INSULATING		15 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
10	DGE100 237		834570511986 2 / SATTON CLOTH WHITE	PRESENTATIO N VIP ITEM	15 / METER						TECHNICAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches GENERAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches	
11	DGD990 37	NO DATA AVAILABL E	003350000020 0 / JUGS WATER GLASS 1 QT		4 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
12	DGD989 74	NO DATA AVAILABL E	003550000037 9 / LADLE S/S HANDLE (L- 13") WITH WOODEN GRIP,POT WD 3.5".		3 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
13	DGE974 82	NO DATA AVAILABL E	046154600460 2 / BOX FIRST AID 728 MS		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
14	DGE100268	LOCALLY DEVELOPED	4220546013157 / REPAIR KIT (FOR LIFE RAFT) CONTENTS OF 07 ITEMS, SHELF LIFE 05.		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
15	DGE64951	CTLBS12202003	5340735267409 / BASE 4' (1220 X 200 X 3MM)		96 / FOOT RUN	BASE 4' CTLBS12202003					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
16	DGE100027	ASTM D-120-87	8415011589454 / Gloves electrical workers		10 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A	
17	DGE64921	CTLCS15011016	5340735267412 / CROSS (1500 X 1100 X 1.6MM)		40 / EACH/NUMBER	CROSS CTLCS15011016					TECHNICAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500 X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500 X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
18	DGB97383		0273790004114 / CUTTER INSULATION REMOVING DIAMETER CAPACITY 0.744IN	USE: PYROTENAX CABLE	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
19	DGE99524	NIL	0350599237135 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MM, TYPE-1								<p>ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
20	DGE988 10	NIL	035059923713	H 41.200 TONS UNIT OF	120 / FATHO						<u>TECHNICAL SPECIFICATION - 1.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	AVAILABILITY 726	M						<p>TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021.</p> <p>2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED. 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021.</p> <p>2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
21	DGB974 86		027370910421 6 / CHISEL COLD HAND SPEARHEAD OVERALL LG 6.50IN		40 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DGB973 81		027359910446 3 / CALIPER INSIDE SPRING JOINT 06IN (LOCAL)		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DGB973 88		024750247001 4 / RING-FOR- HOT-PLATES		54 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
24	DGB970 42	1473	024879129614 8 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE.DOOR NOT LESS THAN3/8"THK-	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03 GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03	
25	DGD989 48	NO DATA AVAILABLE	003550000045 1 / UTENSILS COOKINGALU M O/D5.35" H2. 5" TH 18 SWG WITH COVER		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) GENERAL SPECIFICATION - Material Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD)	
26	DGH990 67	WT PER FT 0.84 LB SPEC: DNC/S 23	021259571071 2 / ANGLE STEEL CARBON BLACK 0.750" X 0.750" X 0.187"		66 / METER						TECHNICAL SPECIFICATION - bs en 10025-2 of 2004 grade s 275 jr GENERAL SPECIFICATION - bs en 10025-2 of 2004 grade s 275 jr	
27	DGB973 97		026759521327 8 / PIPING STEEL	UTS LENGTH. BULK SUPPLY	228 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GALVANIZED SEAMLESS, L : 6.1 M, E/DIA 26.9MM, TH 2.6 MM, N/BORE:19.1 MM								EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS GENERAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS	
28	DGB986 50	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	126 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS: 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS: 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
29	DGB946 52	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	130 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS: 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS: 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
30	DGB974 98	NO DATA AVAILABL E	021259571062 3 / LATHE MACHINE CUTTING TOOL STEEL HIGH SPEED SQ HOT ROLLED	LATHE MACHINE	5 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material: steel high speed square' hot rolled dimension : 3/4" x 3/4"x "6. GENERAL SPECIFICATION - Material: steel high speed square' hot rolled dimension : 3/4" x 3/4"x "6.	
31	DGB984 24		021450214062 0 / BOLT AND		4 / EACH/N						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NUTS STEEL HEX HD THD LG 1.25" TPI12SZ6. 000X0.750 IN		UMBER						SPECIFICATION - NO DATA AVAILABLE	
32	DGE876 71		209050503923 3 / GROUND SHEET- CANVAS LG- 2M 35CM WITH85CM THK 0.75MM		50 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION -</u>  Specifications: ∩ Material: Polyester-cotton canvas with PU/ PVC coating. ∩ Weight: 450-550 GSM ∩ Size: 5m x 8m (standard) ∩ Coating: Waterproof, anti-fungal, UV-resistant ∩ Color: Olive green/ khaki/ brown ∩ Edges: Reinforced with rust proof eyelets. ∩ Finish: Mildew resistant Technical Data: ∩ Waterproofing: 2000 mm hydrostatic head ∩ Tensile Strength: 350 N/ cm (warp), 300 N/ cm (weft). ∩ Tear Strength: 50N ∩ UV Resistance: 500 hrs exposure without degradation ∩ Abrasion: 30,000 rubs ∩ Shrinkage: 3% ∩ Temp Range: -100 C to + 550 ∩ Flame Retardant: NFPA 701/ BS 5852 compliant Testing Criteria : ∩ Hydrostatic pressure (ISO 811) ∩ Tensile &amp; tear strength (ISO 13934-1, ISO 13937-2) ∩ UV resistance ∩ Mildew test ∩ Abrasion (ISO Standard) ∩ Shrinkage (ISO Standard) ∩ Fire resistance Accepting Criteria: ∩ Waterproof 2000 mm ∩ Tensile 350/300 N/cm ∩ Tear Strength &gt; 50N ∩ No mildew growth (7 days) ∩ UV degradation 15% ∩ Abrasion &gt; 30,000 rubs ∩ Shrinkage 3% ∩ Must pass flame test dimension: Width = 4 feet Height = 3 feet</p> <p><u>GENERAL SPECIFICATION -</u>  Specifications: ∩ Material: Polyester-cotton canvas with PU/ PVC coating. ∩ Weight: 450-550 GSM ∩ Size: 5m x 8m (standard) ∩ Coating: Waterproof, anti-fungal, UV-resistant ∩ Color: Olive green/ khaki/ brown ∩ Edges: Reinforced with rust proof eyelets. ∩ Finish: Mildew resistant Technical</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Data: √ Waterproofing: 2000 mm hydrostatic head √ Tensile Strength: 350 N/ cm (warp), 300 N/ cm (weft). √ Tear Strength: 50N √ UV Resistance: 500 hrs exposure without degradation √ Abrasion: 30,000 rubs √ Shrinkage: 3% √ Temp Range: -100 C to + 550 √ Flame Retardant: NFPA 701/ BS 5852 compliant Testing Criteria : √ Hydrostatic pressure (ISO 811) √ Tensile &amp; tear strength (ISO 13934-1, ISO 13937-2) √ UV resistance √ Mildew test √ Abrasion (ISO Standard) √ Shrinkage (ISO Standard) √ Fire resistance Accepting Criteria: √ Waterproof 2000 mm √ Tensile 350/300 N/cm √ Tear Strength &gt; 50N √ No mildew growth (7 days) √ UV degradation 15% √ Abrasion &gt; 30,000 rubs √ Shrinkage 3% √ Must pass flame test dimension: Width = 4 feet Height = 3 feet</p>	
33	DGE986 73	X-6131	204070511070 9 / TRAPEZOID SHAPE FENDER WITH THE CIRCULAR BORE	NIL.M/S K.R RUBBER GARDEN MARKET KARACHI	10 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. MATERIAL: A. EPDM NATURAL AND SYNTHETIC RUBBER. 2. DIMENSION A. LENGTH: 1820 MM B. WIDTH (BASE OF TRAPEZOID): 100 MM C. WIDTH (TOP OF TRAPEZOID): 75 MM D. HEIGHT: 75 MM E. DISTANCE BETWEEN HOLES: 405 MM F. SIZE OF HOLE FROM TOP: 32 MM G. SIZE OF HOLE FROM BOTTOM: 13 MM H. STAINLESS STEEL STRIP (WIDTH: 32MM, THICKNESS:03MM) BE INSERTED ALL ALONG LENGTH OF TRAPEZOID SHAPE FENDER AS PER ORIGINAL SAMPLE. 3. TRAPEZOID SHAPE FENDER SHOULD QUALIFY FOLLOWING PARAMETERS: S NO. PROPERTIES REQUIRED VALUES TEST METHOD A. HARDNESS (IRHD) 65-80 BS 903 PART: A26</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>METHOD N B. TENSILE STRESS STRAINS BS 903 PART: A2 TYPE 2 DUMB-BELL TEST PIECES (1) TENSILE STRENGTH(MN/M2) MINIMUM 10 SIX TEST PIECES PER COMPOSITION (2) ELONGATION AT BREAKING MINIMUM 250 STRENGTH (%) C. COMPRESSION SET AT 70 + DEG 25 MAXIMUM BS 903 PART: A6 TYPE 1 TEST PIECE AT 70+ 1 DEG C FOR 24 C FOR 24 HOURS (%) HOURS D. SPECIFIC GRAVITY 1.4 G/CMP - E. EFFECT OF TEMPERATURE AT A. 100C NO EFFECT B. 150C NO EFFECT F. EFFECT OF CHEMICALS (1). SODIUM HYDROXIDE 50% NOT EFFECTED (2). LUBE OIL NOT EFFECTED G. TEAR STRENGTH (M/MM2) MINIMUM 30 BS 903 PART: A3 J. ACCELERATED AIR (B HRS AT 70 DEG C) - BS 903 PARTS: A2, A19, A26 I. HARDNESS CHANGE IRHD +10 TO -10 II. TENSILE STRENGHT CHANGE (% OF ORIGINAL VALUE) III.CHANGE IN ELONGATION (% OF ORIGINAL VALUE NOTE: DESIGN AND CONSTRUCTION OF EACH ITEM WILL BE AS PER ORIGINAL SAMPLE.GENERAL SPECIFICATION - 1. MATERIAL: A. EPDM NATURAL AND SYNTHETIC RUBBER. 2. DIMENSION A. LENGTH: 1820 MM B. WIDTH (BASE OF TRAPEZOID): 100 MM C. WIDTH (TOP OF TRAPEZOID): 75 MM D. HEIGHT: 75 MM E. DISTANCE BETWEEN HOLES: 405 MM F. SIZE OF HOLE FROM TOP: 32 MM G. SIZE OF HOLE FROM BOTTOM: 13 MM H. STAINLESS STEEL STRIP (WIDTH:32MM, THICKNESS:03MM) BE INSERTED</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>ALL ALONG LENGTH OF TRAPEZOID SHAPE FENDER AS PER ORIGINAL SAMPLE. 3. TRAPEZOID SHAPE FENDER SHOULD QUALIFY FOLLOWING PARAMETERS: S NO. PROPERTIES REQUIRED VALUES TEST METHOD A. HARDNESS (IRHD) 65-80 BS 903 PART: A26 METHOD N B. TENSILE STRESS STRAINS BS 903 PART: A2 TYPE 2 DUMB-BELL TEST PIECES (1) TENSILE STRENGTH(MN/M2) MINIMUM 10 SIX TEST PIECES PER COMPOSITION (2) ELONGATION AT BREAKING MINIMUM 250 STRENGTH (%) C. COMPRESSION SET AT 70 + DEG 25 MAXIMUM BS 903 PART: A6 TYPE 1 TEST PIECE AT 70+ 1 DEG C FOR 24 C FOR 24 HOURS (%) HOURS D. SPECIFIC GRAVITY 1.4 G/CMP - E. EFFECT OF TEMPERATURE AT A. 100C NO EFFECT B. 150C NO EFFECT F. EFFECT OF CHEMICALS (1). SODIUM HYDROXIDE 50% NOT EFFECTED (2). LUBE OIL NOT EFFECTED G. TEAR STRENGTH (M/MM2) MINIMUM 30 BS 903 PART: A3 J. ACCELERATED AIR (B HRS AT 70 DEG C) - BS 903 PARTS: A2, A19, A26 I. HARDNESS CHANGE IRHD +10 TO -10 II. TENSILE STRENGHT CHANGE (% OF ORIGINAL VALUE) III.CHANGE IN ELONGATION (% OF ORIGINAL VALUE NOTE: DESIGN AND CONSTRUCTION OF EACH ITEM WILL BE AS PER ORIGINAL SAMPLE.</p>	
34	DGE97593	NO DATA AVAILAB E	055979900471 5 / INSULATION- SLEEVING-		1 / METER						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILAB <u>GENERAL SPECIFICATION</u> - NO DATA AVAILAB</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			RED-17MM									
35	DGE97146	NO DATA AVAILABLE	0559799004675 / INSULATION-SLEEVING-ELECT-1.5MM-RED DIA 1.500		1 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
36	DGE98126	NO DATA AVAILABLE	0476546005947 / BRUSH SABLE HAIR NO.4.		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DGE97266	NO DATA AVAILABLE	0472594259735 / FABRIC RUBBERIZED 2PLY RH BIAS COLOUR BLUE		40 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DGB97489	C60	0474504481497 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	FOUNDRY USE OEM MORGANITE UK FAX NO	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
39	DGE98572	NO DATA AVAILABLE	0461500006792 / CHALK WHITE SOFT	W/T DOORS & FIT	20 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
40	DGE78220		4220505101929 / LIFE JACKETS (Orange/Camouflage)	FOR PERSONNAL SAFETY,PNS QASIM,PRIZE ENT	65 / EACH/NUMBER						TECHNICAL SPECIFICATION - (1) Buoyancy: 7.5kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003 GENERAL SPECIFICATION - (1) Buoyancy: 7.5 kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											DRAWING NO TD-1688/2003	
41	DGE97108		4220705046424 / AIRCRAFT MARSHALLER S IDENTIFICATI ON JACKET	TO USED BY GROUND PERSONEL DEPLOYED	24 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DGE98575	IN70046	4710795103409 / SIKAFLEX WHITE TUBES	HOVER CRAFT GRIFFON UK	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
43	DGE98306	FEC-32-5113	4240705112409 / GAS MASK RESPIRATOR 3M		200 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DGE99892		5330006183221 / PACKING MATERIAL SIZE 3/16".		10 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DGE98119		5330006183221 / PACKING MATERIAL SIZE 3/16".		10 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DGE97811		5330001790050 / SHEET RUBBER SLD/CLOTH		4 / KILOGRAMME						TECHNICAL SPECIFICATION - Heavy Duty Rubber Sheet, High Temperature Heat Protection Water Proof and Weather resistant, peroxide cured for increased temperature resistance. Size: Length : 40" Width : 40" Thickness: 2-MM GENERAL SPECIFICATION - Heavy Duty Rubber Sheet, High Temperature Heat Protection Water Proof and Weather resistant, peroxide cured for increased temperature resistance. Size: Length : 40" Width : 40" Thickness: 2-MM	
47	DGE98358	nil	5330000382922 / PACKING-MATERIAL	FUEL OIL SERVICE PMP	75 / METER						TECHNICAL SPECIFICATION - SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C GENERAL SPECIFICATION - SPECIFIATION: CROSS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C	
48	DGE971 15		535099461682 9 / STEEL WOOL 1 LB PER BALLS 50 BALLS PER CARTOON GRADE-3	FOR GENERAL USE	6 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DGE972 57		535099461682 9 / STEEL WOOL 1 LB PER BALLS 50 BALLS PER CARTOON GRADE-3	FOR GENERAL USE	16 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
50	DGE974 81	GRADE40 0	5350PK510407 1 / WATER PROOF SAND PAPER GRADE400	WOODEN & GRP BOATS., AQUATIC CLUB D/YARD	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
51	DGT978 64	NO DATA AVAILABL E	553070504293 3 / PLY WOOD NATURAL TEAK FINISH ONE SIDE (NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W= 4' TH=03mm to 04mm	PRESENTATIO N BOXES FOR VVIPS	96 / SQ FEET						TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm GENERAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm	
52	DGE983 53	MIL-P- 15280	564000237482 7 / INSULATION SLEEVING THERMAL		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - mil- p-15280 Sleeve Sizes: LENGTH: 72- INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p>	
53	DGE983 54	MIL-P- 15280	564000237482 8 / INSULATION SLEEVING THERMAL		10 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p>	
54	DGE999 23	MIL-P- 15280	564000237482 8 / INSULATION SLEEVING THERMAL		20 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
55	DGE99055	P 51241/S	6150GR506607 5 / CABLE TIES200/5MM	MAN AUX MARINE DIESEL GENERATOR 300KW	100 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DGE97432	81349 MIL-1-46852	597000955997 6 / TAP INSULATING BLACK ADHESIVE RUBBER W 1		6 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DGE100179	NO DATA AVAILABLE	597070504085 6 / SLEEVING GLASS DIA 25 MM THICKNESS 1.1MM	D/GENERATOR STATER	50 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DGE96024	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		13 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
59	DGE97429		597000543115 4 / TAPE INSULATION		50 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WOVEN GLASS WIDTH 13MM,THICK 0.18MM,LG. 50MTR								AVAILABLE	
60	DGB792 23	CH50-10	024650000106 5 / BLOCK CHAIN 5 TON 5 METER CHAIN (ORIGINAL ELEPHANT JAPAN)		2 / EACH/N UMBER	CH50-10					<u>TECHNICAL SPECIFICATION -</u> MADE /Brand: Elephant Japan Model: CH50-10. 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn). Maximum working load is 05 Ton. Height of lift is 40' <u>GENERAL</u> <u>SPECIFICATION - MADE /Brand:</u> Elephant Japan Model: CH50-10. 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn). Maximum working load is 05 Ton. Height of lift is 40'	
61	DGT997 80	NO DATA AVAILABL E	041350000005 0 / BAR TUFNOL ROUND CARP BRAND DIA.2".		1 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
62	DGE985 73	NO DATA AVAILABL E	046250000002 2 / TAPE- BROWN- PAPER- GUMMED (DTLD. NSD/TD/19/286 .DT.090492		6 / ROLL	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Make/Model/Brand Transparent/Brown Carton Sealing Packing Tapes, Brand 7M,Pakistan. Detailed Specification/Technical Data 38-48 MICRON, 69-72 METER/YARD LENGTH, 46-48 MM WIDTH, WEBSITE:WWW.7mbrand. com Approx Price:Rs/-499 x 6 pieces, (www.daraz.com) <u>GENERAL</u> <u>SPECIFICATION -</u> Make/Model/Brand Transparent/Brown Carton Sealing Packing Tapes, Brand 7M,Pakistan.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Detailed Specification/Technical Data 38-48 MICRON, 69-72 METER/YARD LENGTH, 46-48 MM WIDTH, WEBSITE:WWW.7mbrand. com Approx Price:Rs/-499 x 6 pieces, (www.daraz.com)	
63	DGB975 31	NO DATA AVAILABL E	02685000004 6 / SALTER- CHECKWEIGH ER-MODLE 652-CAPACITY 30KG WITH HANGING PAN	30 KG X100G DIVISION DIAL 12" FITTED	2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
64	DGE970 93	NO DATA AVAILABL E	047450000030 7 / FENDER COIR ROUND		21 / EACH/N UMBER	600MM 24" ROUND COIR BOAT FENDER					<u>TECHNICAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.</u> <u>GENERAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.</u>	
65	DGE995 87	NO DATA AVAILABL E	792000543649 2 / PAPER TOWEL		30 / BOX						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
66	DGE99981	NO DATA AVAILAB E	0422500000027 / IMPROVED VERSION PVC TILES MAROON SIZE 300X300X3MM		50 / EACH/ UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB GENERAL SPECIFICATION - NO DATA AVAILAB E	
67	DGE97250	NO DATA AVAILAB E	0422500000003 / CARPET WOOLEN.		400 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm GENERAL SPECIFICATION - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm	
68	DGE99058	NO DATA AVAILAB E	0451500000093 / CLOTH VALVET COLOUR RED WIDTH 40 INCH		40 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB GENERAL SPECIFICATION - NO DATA AVAILAB E	
69	DGE99984	NO DATA AVAILAB E	0432500000024 / HELMET PROTECTIVE WITH VISER COLOUR WHITE (HALF HEAD)		2 / EACH/ UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Make: UK Brand / Company Name: JSP Safety GENERAL SPECIFICATION - Make: UK Brand / Company Name: JSP Safety	
70	DGE99589	NO DATA AVAILAB E	0461500000024 / PAPER ABRASIVE 9" X11" WATERPROOF MATERIAL EMERY GRADE P-120D		42 / SHEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB GENERAL SPECIFICATION - NO DATA AVAILAB E	
71	DGE98363	NO DATA AVAILAB E	0461500000086 / GOGGLE CHIPPING		60 / EACH/ UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>fine particles. Liquid droplet protection. Protection against large dust particles at &gt;5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.</p> <p><u>GENERAL SPECIFICATION -</u> Concurrency to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at &gt;5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.</p>	
72	DGE99986	NO DATA AVAILABLE	04325000002 8 / HELMET PROTECTIVE WITH VISER COLOUR WHITE (FULL HEAD)		8 / EACH/NUMBER	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
73	DGE100161		813570506488 2 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	70 / ROLL						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
74	DGE100	R	834570504262	ITEM	15 /						<p><u>TECHNICAL SPECIFICATION -</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	236		9 / Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter)	REQUIRED FOR MAKING OF GIFT BOXES	METER						Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes <b>GENERAL SPECIFICATION -</b> Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes	
75	DGE99667	NO DATA AVAILABLE	834050503926 1 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		4 / EACH/NUMBER						<b>TECHNICAL SPECIFICATION - 1.</b> Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material; Kahoo/Sissoo or Teak wood of 2.5 feet length. 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos <b>GENERAL SPECIFICATION - 1.</b> Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos	
76	DGE98503	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	2 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAGE					<p><u>TECHNICAL SPECIFICATION - 1.</u>  100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH &amp; LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM &amp; 8-14 UM (MICROMETER) BANDS.</p> <p><u>GENERAL SPECIFICATION - 1.</u>  100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
77	DGE986 27	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATIO N	2 / EACH/N UMBER	OPTICAL INFRARE D CAMOUF LAGE NET, ANTI RADAR CAMOUF LAG					TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM &amp; 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS. 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH &amp; LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM &amp; 8-14 UM (MICROMETER) BANDS.</p> <p><u>TECHNICAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING</p>	
78	DGE98703	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	2 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET.						

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
						ANTI RADAR CAMOUF LAG					<p>DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH &amp; LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM &amp; 8-14 UM (MICROMETER) BANDS.</p> <p><u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH &amp; LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (c). HAMMER= 01 IN</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT. QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
79	DGE98576	MIL-C-20079	831500267163 3 / INSULATION TAPE THERMAL		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. WIDTH 3 INCH 2. THICKNESS (0.007) inch 3. LENGTH 50 YARD 4. OEM / country of Origin / Manufacture USA GENERAL SPECIFICATION - 1. WIDTH 3 INCH 2. THICKNESS (0.007) inch 3. LENGTH 50 YARD 4. OEM / country of Origin / Manufacture USA	
80	DGT97660	NO DATA AVAILABLE	010050000001 1 / Ply Wood GD-I, 13 ply (core and inner plies of Poplar Size:L = 8"W = 4?Th = 25 MM		64 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION:(1)BS-6566 OF 1985. PART 1-8. TYPE-INT. WOOD PRESERVATION AS PER BS-6566, Part-7.appendex.GENERAL SPECIFICATION - SPECIFICATION: (1)BS-6566 OF 1985. PART 1-8. TYPE-INT. WOOD PRESERVATION AS PER BS-6566,Part-7.appendex.	
81	DGH97887	NO DATA AVAILABLE	022270000090 5 / SWIVEL PIECE MOORING		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DGE100239	NOT KNOWN	792070518127 1 / BROOM SCRUBBING DECK (FOR DECONTAMINATION)	NIL	10 / EACH/NUMBER		NIL	LOCAL MARKET	NIL		TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21 GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21	
83	DGE985 84	NIL	351070518127 8 / TRAY BLEECH	NIL	1 / EACH/N UMBER	NIL		LOCAL MARKET	NOT KNOWN		TECHNICAL SPECIFICATION - GENERAL ITEM GENERAL SPECIFICATION - GENERAL ITEM	
84	DGH990 81		614599531023 0 / CABLE POWER ELECTRICAL 3CORE 440V 102A	CABLES	180 / METER	Def Stan 02-526 issue 2 Table B. 10	NA	MINISTRY OF DEFENCE (NAVY) SHIPS SUPPORT AGENCY DME ME253, ROOM 19, BLOCK B FOXHILL, BATH, UK TEL: 01225 883293 FAX: 01225 883548	DG SHIPS 212 UK		TECHNICAL SPECIFICATION - DEF STAN 02-526 ISSUE 2/ IEC-60332 DESIGN: IEC-60092-353 INSULATION: IEC-60092-360 CONDUCTOR: IEC:-60228 FLAME RETARDANR: IEC-60332 DEF STAN 02-526 ISSUE2 TABLE B.10 AS PER NMCRL AND DG SHIPS 212 Item will be accepted upon inspection of stores OEM cOC will be provided (required) GENERAL SPECIFICATION - DEF STAN 02- 526 ISSUE 2/ IEC-60332 DESIGN: IEC-60092-353 INSULATION: IEC- 60092-360 CONDUCTOR: IEC: -60228 FLAME RETARDANR: IEC- 60332 DEF STAN 02-526 ISSUE2 TABLE B.10 AS PER NMCRL AND DG SHIPS 212 Item will be accepted upon inspection of stores OEM cOC will be provided (required)	
85	DGE986 72	90-ISP- 91X-056	422071512976 2 / ORAL TUBE NON RETURN VALVE BLACK	LIFE JACKET ATLJ	3 / EACH/N UMBER			US	USA		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DGE972 68	100-65F	792099300899 7 / CLEANING LINT FREE CLOTH (GUC ITEM)	CLEANING CLOTH	66 / EACH/N UMBER	NO DATA AVAILAB LE		UK	MEMO HCG/MS D/03/336 DT 2/7/08		TECHNICAL SPECIFICATION - Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern; Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											sealed edges (+/- 3mm accuracy). <u>GENERAL SPECIFICATION -</u> Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy).	
87	DGB99980	TF-GFB400	4520705147079 / AUTOMATED GAS FIRED BURNER	FURNACES	1 / EACH/NUMBER	NO DATA AVAILABLE		PK		ADDRESS: M/S TECHNO FIELD FABRICATION 95-C, MEZZANINE FLOOR, 11TH STREET, JAMI COMMERCIAL, PHASE-7 DHA KARACHI	<u>TECHNICAL SPECIFICATION -</u> ADDRESS/SOURCE :M/S TECHNOFIELD FABRICATION 95-C,MEZZANINE FLOOR, 11th STREET, JAMI COMMERCIAL, PHASE-7 DHA KARACHI <u>GENERAL SPECIFICATION -</u> ADDRESS/SOURCE :M/S TECHNOFIELD FABRICATION 95-C,MEZZANINE FLOOR, 11th STREET, JAMI COMMERCIAL, PHASE-7 DHA KARACHI	
88	DGE98122	CCC-C-46TY2/02678	7920007823779 / Cloth cleaning Disposable oil treated heavy duty	NIL	20 / KILOGRAMME	NA	NA	NAVAL SEA SYSTEMS COMMAND, WASHINGTON, USA		NAVAL SEA SYSTEMS COMMAND, USA	<u>TECHNICAL SPECIFICATION -</u> PMS Item <u>GENERAL SPECIFICATION -</u> PMS Item	
89	DGE99987	7920-00-148-9666	7920001489666 / Rag wiping Cotton & cotton synthetic 50 lbs	NIL	250 / SET	NA	NA	ALFA LAVAL TUMBA AB, HANS STAHL VAG 7 TUMBA SWEDEN		ALFA LAVAL TUMBA AB, SWEDEN	<u>TECHNICAL SPECIFICATION -</u> PMS Item <u>GENERAL SPECIFICATION -</u> PMS Item	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
90	DGH100241	CEF80/SA/3X4MM2	6145785134190 / 03 CORE CABLE DC POWER SUPPLY PANNEL	ND-14A(AFT)	80 / METER	NO DATA AVAILAB LE		CH	CHINA		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
91	DGH85540	CEF80/SA/2X6MM2	6145785134189 / 02 CORE CABLE (PER CORE SHEATHED)	ND-14A DC POWER SUPPLY	1566 / METER	NO DATA AVAILAB LE		CH	M/S CSTC CHINA		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
92	DGE98115	H R 550	8020005984080 / COVER PAINT ROLLER	PAINT ROLLER	15 / EACH/N UMBER	CAGE CODE ODRR8		FEDERAL SPECIFICATION USA CAGE CODE 81348ODRR8	FEDERAL SPECIFIC ATION S USA		TECHNICAL SPECIFICATION - MATERIAL FIBER , POLYESTER PILE HEIGHT 0.625 INCHES NOMINAL , NOMINAL LENGTH 7.000 INCHES GENERAL SPECIFICATION - MATERIAL FIBER , POLYESTER PILE HEIGHT 0.625 INCHES NOMINAL , NOMINAL LENGTH 7.000 INCHES	
93	DGH97882		9515FP5153199 / STEEL PLATE 6000X1500X6.0MM (F-22P)	L907A GRADE STEEL PLATE	10 / EACH/N UMBER			OEM & SOURCE OF AVAILABILITY:M/S CSTC / ANGANG STEEL COMPANY NO.42 TUANIIE STREET TIEDONG DISTRICT 114002 ANSHAN P.R.CHINA TEL: 0086-8008900858 FAX: 0086-04126728486	CHINA		TECHNICAL SPECIFICATION - Material Grade: I907a 6000X1500X6.0MM GENERAL SPECIFICATION - Material Grade: I907a 6000X1500X6.0MM	
94	DGB97504		0283705711165 / SHEET-ALUMINIUM-LH-144-WIDTH-48-TH0.080"		25 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
95	DGE97177	NO DATA AVAILAB LE	0350599233575 / FENDER MARINE ROUND SISAL WT.32 LBS. OVERALL DIA 2',INTERNAL DIA 8" FOR HARBOUR LAUNCHES		8 / EACH/N UMBER						TECHNICAL SPECIFICATION - ∅ MEDIUM SIZE: ∅ 1000 MM LENGHT ∅ 500 MM DIAMETER ∅ 1550 MM CIRCUMFERENCE ∅ MATERIAL EVA FOAM AND NATURAL RUBBER ∅ tYPE: FLANGE TYPE AND ROPE TYPE ∅ ISO 9001 COMPLIANCE ∅ ENERGY ABSORPTION 08 K NM ∅ FORCE RECTION 71 KN GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - 1. MEDIUM SIZE: 1. 1000 MM LENGTH 2. 500 MM DIAMETER 3. 1550 MM CIRCUMFERENCE 4. MATERIAL EVA FOAM AND NATURAL RUBBER 5. TYPE: FLANGE TYPE AND ROPE TYPE 6. ISO 9001 COMPLIANCE 7. ENERGY ABSORPTION 08 K NM 8. FORCE RECTION 71 KN	
96	DGE98505	NO DATA AVAILABE	0350599233576 / FENDER MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6 INTERNAL DIA 10"	MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6	50 / EACH/NUMBER						TECHNICAL SPECIFICATION - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10" GENERAL SPECIFICATION - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10"	
97	DGE99890	NO DATA AVAILABE	0350599233577 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE: DIAMETER= 80-CM, LENGTH: 205-CM, EYE DIAM: 32-MM 2. GROSS BOYANCY: 720-KG, 3. WEIGHT APPROX: 28-KG, 4. PACKING: 1 PCS/POLY BAG, 5. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 6. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 7. MATERIAL: PVC 8. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 9. PICT/BROCHURE IS ATTACHED. GENERAL SPECIFICATION - 1. SIZE: DIAMETER= 80-CM, LENGTH: 205-CM, EYE DIAM: 32-MM 2. GROSS BOYANCY: 720-KG, 3. WEIGHT APPROX: 28-KG, 4. PACKING: 1 PCS/POLY BAG, 5. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 6. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 7. MATERIAL: PVC 8. UV PROTECTION FOR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TEMPERATURES BETWEEN -30 TO +60 DEGR CET 9. PICT/BROCHURE IS ATTACHED.	
98	DGE98101	0413/8568	041359924350 3 / FIBER SHEET, VULCANISED, LG,54"WD.42" THICKNESS 0.031"	FOR AIR COMPRESSOR	50 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
99	DGE97053	0413/8568	041359924350 3 / FIBER SHEET, VULCANISED, LG,54"WD.42" THICKNESS 0.031"	FOR AIR COMPRESSOR	100 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
100	DGE97484	0413-8532 & 0413 923 8899, BS1154	041359923889 9 / RUBBER SHEET,SOLID, NATURAL RUBBER, LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI		300 / KILOGRAMME						TECHNICAL SPECIFICATION - RUBBER SHEET,SOLID, NATURAL RUBBER, LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 GENERAL SPECIFICATION - RUBBER SHEET,SOLID, NATURAL RUBBER, LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21	
101	DGE100168	319-SIVLER-DE	047659000003 1 / BRUSH STEEL WIRE SURFACE CLEANING		12 / EACH/NUMBER	319-SILVER-DE					TECHNICAL SPECIFICATION - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SMALL								<p>FINE 5. ADDITIONAL INFO: ASIN BO7RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm. Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle, Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement <b>GENERAL SPECIFICATION</b> - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN BO7RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm. Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle, Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement</p>	
102	DGE100 164	NO DATA AVAILABL E	055979020048 5 / INSULATION- TAPE- POLYETHYLE NE TERAPHALAT E(TERYLENE) W/0.75		20 / ROLL						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
103	DGE972 64	U1901 AND P35M	041459923069 9 / PACKING ASSY MICA SZ.1.5/32,OD. 3/4,I/D 13/64 2 PERSET SQ. C/S		22 / SET						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
104	DGE100 165	NO DATA AVAILABL E	055979002055 2 / INSULATION TAPE ELECTRICAL SHRINKABLE	GENERAL ELECTRIC USE	56 / ROLL						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WD 2IN RUBBER									
105	DGE976 67	NO DATA AVAILABLE	0559790020552 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	52 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DGE971 41		0413599238752 / WASHER RUBBER 0.500X0.875IN		12 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DGE100 189	NO DATA AVAILABLE	0559794444690 / RUBBER-TAP-INSULATION		35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
108	DGE976 53		0414599230997 / WASHER ASBESTOS COPPER 1.000X0.250X1.000X0.500IN		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
109	DGE999 30		0461590000976 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE NO.0		40 / SHEET	local					TECHNICAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0 GENERAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0	
110	DGE100 271		0461590000976 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE NO.0		10 / SHEET	local					TECHNICAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0 GENERAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0	
111	DGE972 67	NO DATA AVAILABLE	0461590000980 / CLOTH ABRASIVE 9		57 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
112	DGE978 46	047694305 57, BS2992TA BLE8ITEM 8/5	047659943055 7 / BRUSH VARNISH TYNEX FIBER FLAT SQUIRE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	6 / EACH/N UMBER						TECHNICAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitableGENERAL SPECIFICATION -2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
113	DGE985 87	047694305 57, BS2992TA BLE8ITEM 8/5	047659943055 7 / BRUSH VARNISH TYNEX FIBER FLAT SQUIRE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	10 / EACH/N UMBER						TECHNICAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitableGENERAL SPECIFICATION -2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
114	DGE998 93	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		10 / EACH/N UMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
115	DGE984 55	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED		10 / EACH/N UMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH 3 INCH.								SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
116	DGE985 88	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
117	DGE984 48	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
118	DGE990 54	NIL	055979444489 7 / SLEEVE INSULATION ELECT CERAMIC, VARNISH GLASS FIBer, I/D 2MM		10 / METER						TECHNICAL SPECIFICATION - SPECS= BS 2848 OEM: UK TYPE OF SLEEVE W.R.T CONSTRUCTION: HEAT PROOF SLEEVE. COLOUR: WHITEGENERAL SPECIFICATION - SPECS= BS 2848 OEM: UK TYPE OF SLEEVE W.R.T CONSTRUCTION: HEAT PROOF SLEEVE. COLOUR: WHITE	
119	DGE100 166	NIL	055979444489 8 / INSULATION SLEEV ELEC INT DIA 3MM THICK0.500 MATER CERAMIC	GENERAL ELECTRIC USE	8 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
120	DGE99052	NIL	0559794444898 / INSULATION SLEEV ELEC INT DIA 3MM THICK0.500 MATER CERAMIC	GENERAL ELECTRIC USE	10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
121	DGE97405	NO DATA AVAILAB LE	0350595713132 / ROPE NYLON, 3-STRAND, CIRC: 4-INCH, DIA: 32MM		120 / FATHO M	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM, 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI	
122	DGE97140	NO DATA AVAILABLE	0413546004794 / EAR DEFENDER LARGE SIZE		25 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
123	DGB97045		0283502831521 / CADMIUM ANODE ROLLED LG 12 INCH WTH 8 INCH TH 3/8 INCH		7.25 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH GENERAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH	
124	DGB98651		0283595711455 / ROD NAVAL BRASS DIA 2 INCH (WT PER FT 11.72 LB)		5.6 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R. Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance. GENERAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.	
125	DGB81959	FA14774/EC2002M	0276709105270 / SOLDERING IRON NON ELECT.ST. TYPE.WT.12		3 / EACH/NUMBER	T0053298399					TECHNICAL SPECIFICATION - Make: Germany Brand: WELLER WE1010 GENERAL SPECIFICATION - Make: Germany Brand: WELLER WE1010	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OZ.BIT SZ. 3/4SQIN.D.T									
126	DGE981 00	BS 1154	041359923892 1 / RUBBER SHEET SOLID NATURAL LG. 72 WD 48 INCH THICKNESS 01 INCH		25 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
127	DGE975 21	0414-5162	041459923093 5 / ASBESTOS SHEET COMPRESSE D.	GENE RL PERPOSE	20 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - a. Standard/ Grade: BS 2815, Grade A b. Length = 60 Inch c. Width = 60-80 INCH d. Thickness= 3-MM e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS-2815</u> <u>GENERAL SPECIFICATION - a. Standard/ Grade: BS 2815, Grade A b. Length = 60 Inch c. Width = 60-80 INCH d. Thickness= 3-MM e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS-2815</u>	
128	DGE995 83	NIL	041359923892 3 / RUBBER SHEET SOLID NATURAL (CLOTH INSERT)		50 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCR: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.</u> <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCR: 1. STRENGTHENING</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.</p> <p>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCR: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.</p> <p>GENERAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCR: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND</p>	
129	DGE972 63	NIL	041359923892 3 / RUBBER SHEET SOLID NATURAL (CLOTH INSERT)		148 / KILOGR AMME							

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.	
130	DGE98577	0413-8553	0413599238926 / RUBBER SHEET SOLID NATURAL. LENGTH= 72", WIDTH= 43"		8 / KILOGRAMME						TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"	
131	DGE99588		0413599243505 / FIBER SHEET, VULCANISED, LG.56" WD.42" THICKNESS 0.125"		5 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
132	DGE98654	D5762 (4220-99-923-9594)	0434599239594 / MASK, SWIMMER, CRESSI PINOCCHIO. BLACK REF NO.AEDU DP 3259		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
133	DGE98925	NO DATA AVAILABLE	0350595713210 / ROPE SISAL HAWSERLAID, 3- STRAnD, CIR: 0.625",		480 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			DIA 0.1875" (5-MM)								ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5. OEM COC REQUIRED. 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM. 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK), 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5. OEM COC REQUIRED. 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM. 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK), 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI	
134	DGE976 52		041459924180 8 / PAPER GASKET OIL		72 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PROOF JOINTING, 100 YARD ROLLS, WIDTH: 42", THICKNESS= 1/64 INCH.								AVAILABLE	
135	DGB940 94		026759521328 0 / PIPING STEEL GALVANIZED SEAMLESS (EXT DIA 1.906		110 / METER						TECHNICAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P-265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0.128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr GENERAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P-265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0.128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr	
136	DGT975 42	NIL	010050100011 7 / PLY WOOD MARINE SHESHAM GRADE-I		64 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: 1. PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I (CORE INNER & OUTER PLYS OF SHESHAM WOOD) 5 PLY. TYPE OF BOND WBP CLASS-II BS EN 314-2 TREATED WITH PRESERVATIVE AS PER SPECS. 2. BS 1088 PART 1 & 2. 3. DENSITY OF TEMBER (SHEESHAM) AS PER INTERNATIONAL STANDARD. 4. SIZES: LENGTH: 8 FEET, WIDTH: 4 FEET, THICKNESS: 3/8 INCH, THICKNESS OF VEENER (FACE&BACK): 06MM (MIN). GENERAL SPECIFICATION - SPECIFICATION: 1. PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I (CORE INNER & OUTER PLYS OF SHESHAM WOOD) 5 PLY. TYPE OF BOND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											WBP CLASS-II BS EN 314-2 TREATED WITH PRESERVATIVE AS PER SPECS. 2. BS 1088 PART 1 & 2. 3. DENSITY OF TEMBER (SHEESHAM) AS PER INTERNATIONAL STANDARD. 4. SIZES: LENGTH: 8 FEET, WIDTH: 4 FEET, THICKNESS: 3/8 INCH, THICKNESS OF VEENER (FACE&BACK): 06MM (MIN).	
137	DGB977 19		026759571170 5 / PIPING STEEL GALV 6.00X6.500X0. 176IN		14 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
138	DGB968 17	BS 1421	027570910547 4 / PICK HEAD DIGGING TYPE CHISEL AND POINT 07LBS EYE 3" X3"		40 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
139	DGH978 89		022150221088 1 / CHAIN CABLE IRON FOR SEA 1.250INX12FM		5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
140	DGB943 66		021859571185 2 / PIPING STEEL SEAMLESS DIA 5.998" (152.150 MM) TH 0.249"		10 / METER						<u>TECHNICAL SPECIFICATION - STANDARD/SPECIFICATION-ISO-9329-1 OF 1989 MATERIAL GRADE-TS-430</u> <u>GENERAL SPECIFICATION - STANDARD/SPECIFICATION-ISO-9329-1 OF 1989 MATERIAL GRADE-TS-430</u>	
141	DGB746 40		027370910447 6 / DIVIDERS SPRING LG OF LEG 06IN		20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
142	DGB995 81		021459013141 4 / BOLT MACHINE, THREAD SERIES: BSF, MEDIUM		3000 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - HEAD: HEXAGON, THREAD SIZE: 7/8 INCH, NOMINAL LENGTH: 3 1/2 INCH, LENGTH OF THREAD: 1 3/4 INCH. SPECIFICATION: DEF STAN 02-862 Part 2, Issue 3 Class III,</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CLASS, HEXAGON, SIZE (0.875X3.500X1.750 INCH)								MATERIAL GRADE: BS EN 10269 42CrMo5-6 (OR) BS EN 10269 40CrMoV4-6 <u>GENERAL SPECIFICATION - HEAD:</u> HEXAGON, THREAD SIZE: 7/8 INCH, NOMINAL LENGTH: 3 1/2 INCH, LENGTH OF THREAD: 1 3/4 INCH. SPECIFICATION: DEF STAN 02-862 Part 2, Issue 3 Class III. MATERIAL GRADE: BS EN 10269 42CrMo5-6 (OR) BS EN 10269 40CrMoV4-6	
143	DGE989 81	C1560	033059571325 0 / TWINE HEMP WHITING LINE 40YDS STRENDS 3 MIN BREAKING 48 LBS, C1559	ALSO KNOWN AS FISHING LINE TO BS 2019	9 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - a.</u> Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019 <u>GENERAL SPECIFICATION - a.</u> Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019	
144	DGE986 60		033059571325 9 / TWINE NYLON MARLINE 3 STRD POLISHED MIN BKG STRENGTH 280 LBS		10 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - BKG STRENGTH 280 LBS TWINE NYLON MARLINE 3 STRD POLISHED (Dia 1.10 mm) PAKING:</u> Standard available <u>GENERAL SPECIFICATION - BKG STRENGTH 280 LBS TWINE NYLON MARLINE 3 STRD POLISHED (Dia 1.10 mm) PAKING:</u> Standard available	
145	DGE988 11	NIL	035059923712 6 / ROPE NYLON ,CIRC 2". DIA: 16-MM, HAWSERLAID, 3-sSTRAND, Z-LAY, 120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	60 / FATHOM						<u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.</u></p>	
146	DGT983 92	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	10 / CUBIC FOOT	NIL	NIL	LOCAL MARKET			<p><u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%<u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
147	DGT992 65	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	20 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		ONLY) moisture contents: 06 % to 18%  <u>TECHNICAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
148	DGE859 35	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	10 / EACH/N UMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4	GERMAN Y		<u>TECHNICAL SPECIFICATION</u> - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION</u> - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
149	DGE869 37	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	10 / EACH/N UMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4	GERMAN Y		<u>TECHNICAL SPECIFICATION</u> - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω GENERAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
150	DGT993 48		934070514992 4 / MEDIUM DENSITY FIBER BOARD (LASANI) WHITE COLOUR LAMINATION ONE SIDE DENSITY 750 KG cUB METER SIZE L:8' W: 4' TH: 3MM MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	5 / SHEET	NO DATA AVAILAB LE		PK		SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.	TECHNICAL SPECIFICATION - SIZE: Length: 8 feet Width: 4 feet Thickness: 3 MM colour: white SOURCE:M/S MEHRAN ART WOOD SHOP NO 9,PANJETANI HOUSE,SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI. TEL/ FAX: +92-21-32776064.MOBILE 0322- 2578654. PRICE:RS1350 APPOX PER SHEET.SIZE 8FEETX4FEETX1/8 INCHES. GENERAL SPECIFICATION - SIZE: Length: 8 feet Width: 4 feet Thickness: 3 MM colour: white SOURCE:M/S MEHRAN ART WOOD SHOP NO 9,PANJETANI HOUSE,SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI. TEL/ FAX: +92-21-32776064.MOBILE 0322- 2578654. PRICE:RS1350 APPOX PER SHEET.SIZE 8FEETX4FEETX1/8 INCHES.	
151	DGE872 68	3M 9332	4240TY520254 0 / 3M DISPOSABLE RESPIRATOR COMFORT SERIES (3M 9332)	SAFETY 8833	150 / EACH/NUMBER	8833		3M	3M		TECHNICAL SPECIFICATION - EN 149.2001+A1.2009 FFP2 NRD DUST MIST USAGE UP TO 50XTLVGENERAL SPECIFICATION -_EN 149.2001+A1.2009 FFP2 NRD DUST MIST USAGE UP TO 50XTLV	
152	DGE808		047659000006		128 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
	06		2 / GLOVES LEATHER LEFT HAND.		EACH/NUMBER						Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable <u>GENERAL SPECIFICATION</u> _Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable	
153	DGE99274		0350595713130 / ROPE NYLON, HAWSERLAID, 3-STRAND, CIRC: 3-1/2 INCH, NOM DIA: 24MM, TYPE-1,	TOWING & BERTHING ROPE	240 / METER						<u>TECHNICAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY. 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY. 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
154	DGB745 93		027179910198 1 / TAP THREAD CUTTING CS BSW B/S16. 0TPI0.375X1. 250X0.294X2. 937"		6 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION -</u> thread type; iso metric thread m type material grade: (single) SIGH SPEED STEEL(HSS-M2 GRADE) THREAD LENGTH: 18 MM SHANK LENGTH: 50 MM THREAD ANGLE: 600 MAJOR DIAMETER: 10 MM+0.1 MM PITCH DIAMETER: AS PER DEFIND ISO STANDARD THREAD PITCH: 1.5 MM+ 0.05 MM MATERIAL IS TO BE HEAT TREATED TO ACHIEVE HARDNESS LEVEL OF 62-64 HRC.</p> <p><u>GENERAL SPECIFICATION -</u> thread type; iso metric thread m type material grade: (single) SIGH SPEED STEEL(HSS-M2 GRADE) THREAD LENGTH: 18 MM SHANK LENGTH: 50 MM THREAD ANGLE: 600 MAJOR DIAMETER: 10 MM+0.1 MM PITCH DIAMETER: AS PER DEFIND ISO STANDARD THREAD PITCH: 1.5 MM+ 0.05 MM MATERIAL IS TO BE HEAT TREATED TO ACHIEVE HARDNESS LEVEL OF 62-64 HRC.</p>	
155	DGE634 58	NO DATA AVAILABL E	041354600480 3 / PVC PIPE DIA 1.50"		150 / METER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - a)</u> Material: Poly Vinyl Chloride b) Diameter 1.5 inch c) Environmental friendly material. d) Heat resistant. e) Fire resistant. f) Reputable company.</p> <p><u>GENERAL SPECIFICATION - a)</u> Material: Poly Vinyl Chloride b)</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Diameter 1.5 inch c) Environmental friendly material. d) Heat resistant. e) Fire resistant. f) Reputable company.	
156	DGB949 37		021450214065 0 / BOLT AND NUT M S HEX HD SZ 1 X 2.50IN		400 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
157	DGD900 30		003250003200 4 / 1. DISHES SIDE WITH COVER FOR CNS 2. DISH SIDE WITH COVER AND HANDLE (GOLDEN CREST) SIZE: MOUTH WIDTH- 23CM BOTTOM WIDTH- 12CM HIGHT- 8CM		30 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - dish side with cover gold crested (cera-e-noor ) (local) width 9" height 3" capacity 1 liter</u> <u>GENERAL SPECIFICATION - dish side with cover gold crested (cera-e-noor ) (local) width 9" height 3" capacity 1 liter</u>	
158	DGB819 57	NO DATA AVAILABL E	512073100058 2 / SOCKET SPANNER STANDARD 10-32MM 26PCSSET		3 / SET						<u>TECHNICAL SPECIFICATION - a. Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21,22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16) Sliding bar (10 inches) Flip drive ratchet c. Drive type: 1/2" square drive d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chrome</u> <u>GENERAL SPECIFICATION - a. Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21,22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Sliding bar (10 inches) Flip drive ratchet c. Drive type: ½" square drive d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chrome	
159	DGE769 28	SIZE 61/21MM	594070508995 7 / HEAT SHARINK TUBE RAYCHAM FOR 11KV SUPPLY HIGH VOLTAGE SIZE	FOR H_T CABLE	100 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
160	DGE721 98	E- AE10000	047650000006 8 / LEATHER CHROME BLACK 24X24X1/16 INCH		56 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE:24X24X1/16 INCH NATO Code: F3013 GENERAL SPECIFICATION - SIZE:24X24X1/16 INCH NATO Code: F3013	
161	DGD926 84	NO DATA AVAILABL E	003550000031 8 / Aluminium covers for utensil cooking (Large) O/D 25.50" TH 10 SWG.		53 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers. GENERAL SPECIFICATION - Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.	
162	DGT101 532	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 TO 14 INCH THICKNESS: 6 TO 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 TO 14 INCH THICKNESS: 6 TO 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
163	DGB101 161	DBS-01	731070527066 3 / DOUBLE BOWL SINK		1 / EACH/N UMBER	DBS-01					TECHNICAL SPECIFICATION - DIMENSION: 72X28X34INCH, BOWL S/S 304 1.2MM, TP S/S 304 1.5MM. S/S S. PIPER 1 1/2"X1 1/2" X 1.5"MM, STAINLESS STEEL ADJUSTABLE LEGS GENERAL SPECIFICATION - DIMENSION: 72X28X34INCH, BOWL S/S 304 1.2 MM, TP S/S 304 1.5MM, S/S S. PIPER 1 1/2"X1 1/2" X 1.5"MM, STAINLESS STEEL ADJUSTABLE LEGS	
164	DGE101 673	614-053	402079515314 5 / ROPE NYLON 12MM WHITE MULTIPLAIT, 8 STRAND, (FLEXABLE AND HIGH	TAL SHIP SAILING RIG	220 / METER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT.		UK	TECHNICAL SPECIFICATION - OEM: M/S COTESI UK MUNUFACTURED TP STANDARDS EN ISO ISO: 1140:2004 ISO: 2307: 2005 ISO: 9554:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE SPECIAL INSTRUCTIONS ATTACHED FOR SPI ONLY GENERAL SPECIFICATION - OEM: M/S COTESI UK MUNUFACTURED TP STANDARDS EN ISO ISO: 1140: 2004 ISO: 2307:2005 ISO: 9554: 2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE SPECIAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											INSTRUCTIONS ATTACHED FOR SPI ONLY	
165	DGH101 262	GDHBMK4 092040	4010FT100791 8 / STEEL WIRE ROPE (20MM/40M/NON-ROTATING/GALVANIZED)	9M COMBINED BOAT CRANE	6.75 / EACH/NUMBER	GD.HBM. K.S-40/6-PG&40/9	N/A	GURDESAN GEMI MAK. SAN.TIC.A.S, DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM, KOCAELI, TURKEY TEL # 9.02627E+11 FAX # 9.02627E+11 INFO@GURDESAN.COM. TR		GURDESAN GEMI MAK. SAN.TIC. A.S	TECHNICAL SPECIFICATION - A. Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual GENERAL SPECIFICATION - A. Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual	
166	DGE101 372	828 653-H9020051	801079520819 8 / FABRIC 1300 GSM MILITARY GREY (HYPALONE)	RHIB BOAT	7 / METER		NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON, SOMERSET, BA9 9RX, TEL*01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk		HENSHAW INFLATABLES LTD	TECHNICAL SPECIFICATION - TDS IS ENCLOSED WITH RWIMSGENERAL SPECIFICATION - TDS IS ENCLOSED WITH RWIMS	
167	DGH101 269		712570513723 4 / UPRIGHT FRAME SIZE 4800MM X 900MM	RACKING MATERIAL	26 / EACH/NUMBER	NO DATA AVAILABLE		PK		HABIB	TECHNICAL SPECIFICATION - SPECIFICATION SIZE 4800MM X 900MM ---MADE OF C.R.C PROFILE SECTION SIZE 80MM X 70MM X 2.5MM WITH CROSS BRACING OF 25MM X 25MM X 1.2 MM AND BASE PLATES GENERAL SPECIFICATION - SPECIFICATION SIZE 4800MM X 900MM ---MADE OF C.R.C PROFILE SECTION SIZE 80MM X 70MM X 2.5MM WITH CROSS BRACING OF 25MM X 25MM X 1.2MM AND BASE PLATES	
168	DGE101 352	Nil	841570522801 7 / PARACHUTE CLOTH FOR WEAPONS	Cloth	200 / METER	NIL		AL MUSTAFA TRADERS F-41/F-42, Iqbal Center, M. A. Jinnah Road, Karachi-74200		AL MUSTAFA TRADERS	TECHNICAL SPECIFICATION - Type of cloth: Parachute Cloth Code: D-16-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof, with good	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			AND SENSORS								quality gauge to withstand humid and hot environment. <u>GENERAL SPECIFICATION</u> - Type of cloth: Parachute Cloth Code: D-16-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof. with good quality gauge to withstand humid and hot environment.	
169	DGE101 314	B2315512	471070517796 0 / FLEXIBLE PIPE 1 INCH DIA	CNA LAN NETWORK	500 / METER			ADAMJEE PAKISTAN		ADAMJEE PAKISTAN	<u>TECHNICAL SPECIFICATION</u> - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter <u>GENERAL SPECIFICATION</u> - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter	
170	DGE101 541	C1512	033050571327 0 / TWINE LINEN SEAMING MEDIUM 2STRD NATURAL MIN BKG STRGTH 36LB	MATERIAL FLEX SPEC. BS-6125 OF1981	20 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - Medium 2 STRD Size 180 Mtr length 2mm diameter Material Cotton Color White 1. Supply Denomination: 12X12X8cm 250 Gram Cops 2. Dimension/Size: 2mm, 180M packing 3. Detailed Specification: Twine Line Seaming Medium 2 STRD 4. OEM COC: L-E Latief Sons Thread Works Pindi Bhattian Pakistan <u>GENERAL SPECIFICATION</u> - Medium 2 STRD Size 180 Mtr length 2mm diameter Material Cotton Color White 1. Supply Denomination: 12X12X8cm 250 Gram Cops 2. Dimension/Size: 2mm, 180M packing 3. Detailed Specification: Twine Line Seaming Medium 2 STRD 4. OEM COC: L-E Latief Sons Thread Works	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Pindi Bhattian Pakistan	
171	DGB101 556		028370000160 6 / ELECTRODE MONO METAL 08 SWG		10 / METER						<p><u>TECHNICAL SPECIFICATION</u> - a. Size 3.25 x 350 mm b. Current 90-120 c. Polarity DC Electrode Negative (DCEN) d. Position Flat, Horizontal, Vertical, Overhead e. Type of Arc Medium, Moderate, Penetration f. Material Low Carbon Steels g. Technique Use short Arc length with electrode angle 30o + 15o , to the line of weld. h. (8SWG) Mild Steel (HYUNDAI)<u>GENERAL SPECIFICATION</u> - a. Size 3.25 x 350 mm b. Current 90-120 c. Polarity DC Electrode Negative (DCEN) d. Position Flat, Horizontal, Vertical, Overhead e. Type of Arc Medium, Moderate, Penetration f. Material Low Carbon Steels g. Technique Use short Arc length with electrode angle 30o + 15o , to the line of weld. h. (8SWG) Mild Steel (HYUNDAI)</p>	
172	DGB101 284	BS1476/N E 8-M	028370571122 6 / ALUMINIUM ALLOYANGLE EQUALSIDED RT ANGLE LG 1.50"X1.50" X1/8"		60 / METER						<p><u>TECHNICAL SPECIFICATION</u> - Item Specification: BSEN-573-3 OF 1995 (CHEMICAL COMPOSITION) BSEN-485-2 OF 1995 (MECHANICAL PROPERTIES) GRADE ENAW 5083 <u>GENERAL SPECIFICATION</u> - Item Specification: BSEN-573-3 OF 1995 (CHEMICAL COMPOSITION) BSEN-485-2 OF 1995 (MECHANICAL PROPERTIES) GRADE ENAW 5083</p>	
173	DGE101 699		035059571323 5 / ROPE SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH (ROUNDED IN 9-MM)		440 / FATHO M						<p><u>TECHNICAL SPECIFICATION</u> - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB. 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LABELLED AND MARKING AS PER ISO 2307 AND 9554. GENERAL SPECIFICATION - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB. 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELLED AND MARKING AS PER ISO 2307 AND 9554.	
174	DGE101 538	NO DATA AVAILABL E	035059571324 4 / SPUN YARN SISAL "S" TWIST ROT PROOFED, 3/20 YARN, LENGTH PER COIL 811+-5% (FM)		120 / KILOGR AMME						TECHNICAL SPECIFICATION - BS-2052/65 TABLE 27 GENERAL SPECIFICATION - BS-2052/65 TABLE 27	
175	DGE101 308	NO DATA AVAILABL E	047659000006 3 / GLOVES- LEATHER RIGHT HAND		82 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10 GENERAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10	
176	DGE101 354	0413-8522	041359923891 3 / RUBBER SHEET SOLID NATURAL (48 inch X 72 inch x 1/4 inch )	CONT OIL TANKS	70 / KILOGR AMME						TECHNICAL SPECIFICATION - ITEM SPECIFICATION: STANDARD BS 1154. GENERAL SPECIFICATION - ITEM SPECIFICATION: STANDARD BS 1154.	
177	DGH101 329		054070505734 6 / M S ANGLE SIZE 3 1/2X1 1/2X 1/4	GENERAL USE	20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEG GENERAL SPECIFICATION - NO DATA AVAILABLE	
178	DGB101 743	BS2874, CZ112M	028359571142 9 / ROD NAVAL BRASS HEX SIZE	SERVICE PUMP	6 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEG GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			ACROSS FLATS 0.71" WT PER FT1. 630 LB									
179	DGE101 687	611-055	402079515314 3 / ROPE NYLON 16MM WHITE MULTIPLAIT (FLEXABLE AND HIGH	TAL SHIP SAILING RIG	440 / METER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT.	UK		TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG	
180	DGB101 742		028359571146 7 / ROD NAVAL BRASS RD DIA 5.12 INCH WT PER FT 76.98 LB		4 / METER						TECHNICAL SPECIFICATION - BS EN-12163 OF 1998 DESIGNATION : CW-712R CONDITION: M GENERAL SPECIFICATION - BS EN-12163 OF 1998 DESIGNATION : CW-712R CONDITION: M	
181	DGE101 353		041459924180 8 / PAPER GASKET OIL PROOF JOINTING, 100 YARD ROLLS, WIDTH; 42", THICKNESS= 1/64 INCH.		12 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
182	DGT101 552	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD-		352 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			II (CORE INNER & OUTER PLYS OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE								MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM)GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
183	DGH101 689		023159571531 3 / WIRE ROPE GRIP STEEL DIA 0.398".		100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
184	DGH101 330		023159571524 3 / WIRE ROPE STEEL EXTRA SPECIAL GALVA LAY OF ROPE RH CIRC 3/8"		100 / METER						<u>TECHNICAL SPECIFICATION - Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39)</u> <u>GENERAL SPECIFICATION - Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39)</u>	
185	DGE101 543	NO DATA AVAILABLE	033059571326 0 / TWINE COTTON CHALK LINE G/PURPOSE MIN BKG STRG25 LB20YDS LG; DIA 1.5mm	GENERAL PURPOSE BS 2019	151 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - BS 6125 of 1981</u> <u>GENERAL SPECIFICATION - BS 6125 of 1981</u>	
186	DGB101 286	BS2451 (5350-99-923-3461)	028370923346 1 / CHILLED-IRON-GRIT-TYPE-FINE-GD-24		400 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - STANDARD PARTIDE SIZE: G-24=0.6 TO 1.0 MM STANDARD: ISO 11124-2, METALLIC BLAST-CLEANING ABRASIVE. GRIT PARTICLE SHAPE. HARDNESS: ROCKWELL 61 TO 64 HRC, ± 3 HRC SHAPE: ANGULAR AND IRREGULAR. DENSITIES: 7g/ cm3 (APPARENT DENSITY) 3.8 g/ m3</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(BULK DENSITY) CHEMICAL COMPOSITION (APPROXIMATE VALUES) CARBON C: 3.00 % to 3.20 % MANGANESE Mn: 0.30 % to 1.00 % SILICON SI: 1.00 % to 1.50 % PHOSPHOROUS P: 0.10 % to 0.60 % SULFUR S: 0.07 % to 0.17 % <u>GENERAL SPECIFICATION - STANDARD PARTIDE SIZE: G-24=0.6 TO 1.0 MM STANDARD: ISO 11124-2. METALLIC BLAST-CLEANING ABRASIVE. GRIT PARTICLE SHAPE. HARDNESS: ROCKWELL 61 TO 64 HRC, ± 3 HRC SHAPE: ANGULAR AND IRREGULAR. DENSITIES: 7g/ cm3 (APPARENT DENSITY) 3.8 g/ m3 (BULK DENSITY) CHEMICAL COMPOSITION (APPROXIMATE VALUES) CARBON C: 3.00 % to 3.20 % MANGANESE Mn: 0.30 % to 1.00 % SILICON SI: 1.00 % to 1.50 % PHOSPHOROUS P: 0.10 % to 0.60 % SULFUR S: 0.07 % to 0.17 %</u>	
187	DGB101 554	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	10 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - a.</u> Dia: 3.2mm b. Length: 350 mm- 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface <u>GENERAL SPECIFICATION</u> -a. Dia: 3.2mm b. Length: 350 mm- 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
188	DGB101 399		021459941000 8 / BOLT MACHINE STEEL UNC HEX HD SZ 0.500X3. 500X1.250 IN	BR 320 D/70	20 / TEN						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
189	DGB101		025770128378		8 /						<u>TECHNICAL SPECIFICATION - NO</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	528		3 / BOLT MACHINE BRASS BSW HEX HD SZ 1.000X1.750X4.000 IN		DOZEN						DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
190	DGB101 615		026259001689 7 / CLIP IRON O/A LG 6" DIA 3/8"BOTH ANGLE 90 BOTH ARM 2" (LOCAL)	USE MARINE RAILWAY	1500 / EACH/NUMBER						TECHNICAL SPECIFICATION - MILD STEEL BS 970 EN 3A superceded by PD 970 (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local) GENERAL SPECIFICATION - MILD STEEL BS 970 EN 3A superceded by PD 970 (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local)	
191	DGB101 614	NO DATA AVAILABLE	026259419527 1 / SWIVEL-WITH-THIMBLE-LENGTH2.25"-DEP.50"		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
192	DGB101 527	(SIM)	025770941150 4 / NUT-PLAIN-HEXAGON (BRASS) THREAD UNF SZ .375"LH .350"		32 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
193	DGB101 176		451000273121 8 / BOWL WC		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
194	DGE101 672	NO DATA AVAILABLE	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH &amp; LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u>  SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
195	DGE101536	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						<p>ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH &amp; LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p>TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH &amp; LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS. FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH &amp; LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p>	
196	DGE101 686	BS 2052	402099942504 2 / ROPE SISAL HAWSERLAID CIR 12MM 3 STRAND	MIN BKG LOAD 955 KG	500 / FATHO M						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
197	DGH101 701	ITD	401070508999 4 / PVC	FOR GUARD RAIL PNS	300 / METER						<p><u>TECHNICAL SPECIFICATION - DIA: 10 mm plastic coating type of core:</u></p>	

S. No	LPR No-	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COATED FLEX STEEL WIRE ROPE DIA10MM STRAND 6/26 300FM	JALALAT							hc lay length: right hand regular lay lay direction: nil unit weight: kg/m 0.180 tencel strength: (kg/mm2): 180 breaking load: (kgs): 3100 total mlength: (mtr): 1525 unit length: (mtr) 1525 x 1 reel/coil nos. which this certificate GENERAL SPECIFICATION - DIA: 10 mm plastic coating type of core: hc lay length: right hand regular lay lay direction: nil unit weight: kg/m 0.180 tencel strength: (kg/mm2): 180 breaking load: (kgs): 3100 total mlength: (mtr): 1525 unit length: (mtr) 1525 x 1 reel/coil nos. which this certificate	
198	DGE101 345		533000618322 1 / PACKING MATERIAL SIZE 3/16"		20 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
199	DGE101 368	nil	533000038292 2 / PACKING-MATERIAL	FUEL OIL SERVICE PMP	38 / METER						TECHNICAL SPECIFICATION - SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C GENERAL SPECIFICATION - SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C	
200	DGE101 377	GRADE400	5350PK510407 1 / WATER PROOF SAND PAPER GRADE400	WOODEN & GRP BOATS,, AQUATIC CLUB D/YARD	100 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
201	DGE101 347	bs 1154-z60	533099923891 9 / RUBBER SHEET SOLID NATURAL RUBBER BLACK	FOR PACKING & JOINTING PURPOSE	74 / KILOGRAMME						TECHNICAL SPECIFICATION - size: length: 6 feet width: 48 inch thickness: 0.5 inch spec: bs 1154 compound designation: z60 GENERAL SPECIFICATION - size: length: 6 feet width: 48 inch thickness: 0.5 inch spec: bs 1154 compound designation: z60	
202	DGE101 350	P 51241/S	6150GR506607 5 / CABLE	MAN AUX MARINE	200 / EACH/N						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TIES200/5MM	DIESEL GENERATOR 300KW	UMBER						SPECIFICATION - NO DATA AVAILABLE	
203	DGE101349	NO DATA AVAILABLE	041350000133 / EAR DEFENDER		120 / PAIR	PELTOR H10A/OPTIME 105					<p><b>TECHNICAL SPECIFICATION -</b> acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB.</p> <p>a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar &amp; Industrial Safety Equip)</p> <p><b>GENERAL SPECIFICATION -</b> acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB.</p> <p>a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar &amp; Industrial Safety Equip)</p>	
204	DGB101617	NO DATA AVAILABLE	0263500001276 / TURN BUCKLE HOOK & EYE		30 / EACH/NUMBER	NO DATA AVAILABLE					<p><b>TECHNICAL SPECIFICATION -</b> Complete Dimensions: Length- 295 mm (11.61 Inches) Thread-12.7 mm (0.5 Inch) Material grade:forgad galvanized steel Testing/acceptance criteria: 1000lbs make, model, brand: Aashi Enterprises Suite # 48, 3rd, Floor Moosa Market / Shah rah Liaquat Karachi-74000. PH- +92-21-32427508 +92-21-32465654 Fax- +92-21-32432083 E-mail: ashenterprises.gsel@gmail.co ma shienterprises@hotmail.com</p> <p><b>GENERAL SPECIFICATION -</b> Complete Dimensions: Length- 295 mm (11.61 Inches) Thread-12.7 mm (0.5 Inch) Material grade:forgad galvanized steel Testing/acceptance criteria: 1000lbs make, model, brand:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Aashi Enterprises Suite # 48, 3rd, Floor Moosa Market / Shah rah Liaquat Karachi-74000. PH- +92-21-32427508 +92-21-32465654 Fax- +92-21-32432083 E-mail: ashienterprises.gsel@gmail.co ma shienterprises@hotmail.com	
205	DGE101 366	NO DATA AVAILABL E	047450000030 7 / FENDER COIR ROUND		5 / EACH/N UMBER	600MM 24" ROUND COIR BOAT FENDER					<p><u>TECHNICAL SPECIFICATION -</u> CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.<u>GENERAL SPECIFICATION -</u> CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.</p>	
206	DGE101 367	NO DATA AVAILABL E	043250000002 7 / HELMET PROTECTIVE DESPATCH RIDER WITH VISOR SIZE 6 3/4		5 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218) <u>GENERAL SPECIFICATION -</u> Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
207	DGE101671		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1/ EACH/ NUMBER						<p>Pakistan. OEM Authorization dot certified approved (FMUSS NO 218)</p> <p><b>TECHNICAL SPECIFICATION - 1.</b>  <b>SIZE/ DIMENSION</b> a. TENT SIZE (LENGTH &amp; WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. <b>OTHER SPECIFICATIONS</b> a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD &amp; INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31), d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET &amp; 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM &amp; THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER. MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO. MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS. WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p><u>GENERAL SPECIFICATION - 1.</u></p> <p>SIZE/ DIMENSION a. TENT SIZE (LENGTH &amp; WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD &amp; INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET &amp; 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM &amp; THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS. WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p>	
208	DGE101 535		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION</u> - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH &amp; WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD &amp; INNER FLY WITH DOUBLE FOLD), b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET &amp; 02 x STANDING POLES, LENGTH 12</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>FEET WITH JOINTED MALE/FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM &amp; THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p><u>GENERAL SPECIFICATION - 1.</u>  <u>SIZE/ DIMENSION</u>  a. TENT SIZE (LENGTH &amp; WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2.  <u>OTHER SPECIFICATIONS</u>  a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD &amp; INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET &amp; 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM &amp; THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA</p>	
209	DGE101 356		813570506488 2 / TAPE TRANSPAREN	GENERAL USE.	80 / ROLL							

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			T ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.								AVAILABLE	
210	DGE101 697		031050000000 4 / CANVAS COTTON GREY (WD: 24")		205 / METER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION</u> - a. Width 24' b. Weight 340-425 gsm c. Thickness 1-2mm d. Weave Tight weave for water resistance e. Material 100% Cotton with waterproof coating f. Thread Cotton 150-200-Thread per inch g. Waterproof Yes h. Water resistance 1000 mm WEIGHT 24 OZ PER SQ YD ROT PROOF &amp; WATER PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance</p> <p><u>GENERAL SPECIFICATION</u> - a. Width 24' b. Weight 340-425 gsm c. Thickness 1-2mm d. Weave Tight weave for water resistance e. Material 100% Cotton with waterproof coating f. Thread Cotton 150-200-Thread per inch g. Waterproof Yes h. Water resistance 1000 mm WEIGHT 24 OZ PER SQ YD ROT PROOF &amp; WATER PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance</p>	
211	DGE101 325	NO DATA AVAILAB LE	841570504570 5 / CLOTH PARASHUTE WHITE	CEREMONAL ACCOMODATI ON SCREEN	300 / METER						<p><u>TECHNICAL SPECIFICATION</u> - a. Nylon 1680D, PU Coating, Water Proof (Packing 50 yard per Roll, Width 5 Ft) b. <math>\pm 2\%</math> tolerance is acceptable</p> <p><u>GENERAL SPECIFICATION</u> - a. Nylon 1680D, PU Coating, Water Proof (Packing 50 yard per Roll, Width 5 Ft) b. <math>\pm 2\%</math> tolerance is acceptable</p>	
212	DGT101 533	NO DATA AVAILAB LE	010000000004 8 / TIMBER		10 / CUBIC	NO DATA AVAILAB					<u>TECHNICAL SPECIFICATION</u> - SIZE: LENGTH= 6-8 FEET WIDTH=	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		E	SHESHAM SLEEPER WELL SEASONED LOCAL		FOOT	LE					15-17 INCH BREATH= 12-14 INCH iM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL USE GENERAL SPECIFICATION - SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH iM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL USE	
213	DGT101530	NO DATA AVAILAB LE	010050000008 8 / Ply wood GD-I, 9 ply.	X 19.05 MM )	1472 / SQ FEET	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - 1.</u> Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' &amp; THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p><u>GENERAL SPECIFICATION -</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' &amp; THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop	
214	DGE101332	NO DATA AVAILABLE	8415PK506744 2 / CLOTH PARASHUTE GRAY		600 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
215	DGE101328	NO DATA AVAILABLE	8415PK506744 3 / CLOTH PARASHUTE GREEN		300 / METER						TECHNICAL SPECIFICATION - Nylon 1680D, PU Coating, Water Proof (Packing 50 yard per Roll, Width 5 Ft) GENERAL SPECIFICATION - Nylon 1680D, PU Coating, Water Proof (Packing 50 yard per Roll, Width 5 Ft)	
216	DGB101626	NO DATA AVAILABLE	026550000130 2 / HINGES-PYANO-STEEL- LG 6 FT 0.750-INCH WIDTH		125 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
217	DGT101563	NO DATA AVAILABLE	010050000003 9 / TIMBER FIR HIMALAYA/ SPRUCE SLEEPER, WELL SEASONED LOCAL/	(3.05MTR X254 MM X127 MM) SPECE/PSG 69	37 / CUBIC FOOT	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%. GENERAL SPECIFICATION - SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			IMPORTED, SIZE: L=8'-15', W=8"-14", h=4"-10"									
218	DGE101 364	NO DATA AVAILABLE	733070100228 9 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDU S/JOYD).		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - WITH FULLCOVER GENERAL SPECIFICATION - WITH FULLCOVER	
219	DGE101 370	0413-8522	041399923891 3 / RUBBER SHEET SOLID		30 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
220	DGT101 537	NO DATA AVAILABLE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		30 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
221	DGH101 522		793070533116 4 / TRIPLE MOP BUCKET		2 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
222	DGE101 318	HME-AB- CLAMP- PVC- 20MM-009	534070535124 3 / PIPE U CLAMP pvc type		45 / EACH/N UMBER	SS304 SURFAC E					TECHNICAL SPECIFICATION - PIPE U CLAMP PVC TYPE INNER 200mm outer dia 48mm height 38mm thickness 22mm GENERAL SPECIFICATION - PIPE U CLAMP PVC TYPE INNER 200mm outer dia 48mm height 38mm thickness 22mm	
223	DGE584 31		042159942563 7 / FILING CABINET SIZE, 4- DRAWERS W/LOCK combination AND COMPRESSO		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - GUAGE SWG:22 SIZE: Width:18 INCH, Dia:24 1/2 INCH. HEIGHT.52 INCH, MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			R PLATES GREY GUAGE SWG:22 SIZE; W18 INCH								GUAGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT.52 INCH. MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user	