

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 17-06-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGB99489	N /A	4710705232460 / SS PIPE 38Ø	AIS SPAT 1000A	120 / FOOT	N/A	N/A	SADDAR	PAKISTAN (LOCAL ITEM)		TECHNICAL SPECIFICATION - SS PIPE 38Ø, 03 FEET GENERAL SPECIFICATION - SS PIPE 38Ø, 03 FEET	
2	DGD99083	NO DATA AVAILAB L E	0031500000054 / DISH FLAT RICE 33cm GOLDEN CRESTED (AS PER STOCK SAMPLE)		10 / EACH/N UMBER	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - GOLDEN CRESTED ,MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) make/brand cera-e- noor material procelain size 12" (30cm) golden crested with pn logo (same standardised item is already issue to various pn unit ref haibat/03/7762412 GENERAL SPECIFICATION - GOLDEN CRESTED ,MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) make/brand cera-e- noor material procelain size 12" (30cm) golden crested with pn logo (same standardised item is already issue to various pn unit ref haibat/03/7762412	
3	DGE97245	ASTM D 6413	7210505155171 / FIRE RETARDANT SPRING MATTRESS (L6. 5"XW2'XH6)	MATRESSES FOR BED	10 / EACH/N UMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		TECHNICAL SPECIFICATION - MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500-1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA); GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL)</p> <p><u>GENERAL SPECIFICATION -</u> MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500-1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL)</p>	
4	DGE960 51	ASTM D 6413	721050515517 1 / FIRE RETARDANT SPRING MATRESS (L6. 5"XW2"XH6)	MATRESSES FOR BED	10 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		<p><u>TECHNICAL SPECIFICATION -</u> MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500-1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL)</p> <p><u>GENERAL SPECIFICATION -</u> MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500-1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL)	
5	DGE970 24	NIL	721050515517 2 / FIRE RETARDANT SPRING MATTRESS (L6' X W2' X H6")	MATRESSES FOR BED	30 / EACH/N UMBER			LOCAL ADDRESS:AL- KHAIR HOUSE-43-T,AL- KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL- KHAIR HOUSE- 43-T		TECHNICAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413GENERAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
6	DGE886 03	ALM7140A	841573513973 6 / DIVING GLOVES	DIVING	15 / PAIR	ISF PROLINE		OC		TIWAN	TECHNICAL SPECIFICATION - SOFT,THICK RUBBER, SIZE: NORMAL SIZEGENERAL SPECIFICATION - SOFT,THICK RUBBER, SIZE: NORMAL SIZE	
7	DGE101 026	SNR29 DB	6525TY520256 5 / 3M PRE MOULDED EARPLUGS ULTRA FIT WITH NATURAL COTTON CORD	BV	30 / EACH/N UMBER	NA		VHKMHMN		-	TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
8	DGE101 405		035059571324 7 / SPUN YARN SISAL S TWIST R. FROOFED 6/20 YARN WT PER COIL 56LB		250 / POUND						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DGE101 035	319- SIVLER- DE	047659000003 1 / BRUSH STEEL WIRE SURFACE CLEANING SMALL		27 / EACH/N UMBER	319- SILVER- DE					TECHNICAL SPECIFICATION - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN B07RP9X98J 6. ITEM WEIGHT: 4.9	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle, Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement <u>GENERAL SPECIFICATION - 1.</u> ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN BO7RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle, Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement</p>	
10	DGE101333		0474504740126 / SHAMIANA COMPLETE, SIZE: 15X30-FEET		4 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - 1. SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES (GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03 KGS WITH WOODEN HANDLE 1.5 FEET LENGTH)GENERAL SPECIFICATION - 1. SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03 KGS WITH WOODEN HANDLE 1.5 FEET LENGTH)	
11	DGE101 133	nil	035059571312 1 / Rope Nylon, Hawser laid, White, 3- Strand, Cir: 1- Inch, Diameter: 8-MM		120 / FATHO M						<p><u>TECHNICAL SPECIFICATION -</u> SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION -</u> SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
12	DGE99200	NIL	0350595713126 / ROPE NYLON, HAWSERLAID WHITE, 3-STRAND, CIRC: 02-INCH, DIA: 16MM (5/8"),		120 / FATHOM	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL. 3. OEM: COTESI UK GENERAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL. 3. OEM: COTESI UK	
13	DGB99480		0212595710215 / STRIP-STEEL-CARBON-HOT-ROLLED-1INCH TK 3/16" WT PER FT.64LB		60 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
14	DGB101032	NO DATA AVAILAB LE	0273780009426 / BLADE HACKSAW SIZE 12IN TP1-		6 / DOZEN	Eclipse Plus, Griffon,(or any other					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			32			brand)						
15	DGB100 806		021459013101 0 / BOLT MACHINE STEEL BSF MEDIUM CLASS	BR 320 D/78	400 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION</u> - Thread Size 5/8 Inch Nominal Length 2 1/2 Inch Length of Thread 1 1/4 Inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) METARIAL: STEEL 45 TON/SQ.IN.NTS TENSILE STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC REQUIRED</p> <p><u>GENERAL SPECIFICATION</u> - Thread Size 5/8 Inch Nominal Length 2 1/2 Inch Length of Thread 1 1/4 Inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) METARIAL: STEEL 45 TON/SQ.IN.NTS TENSILE STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC REQUIRED</p>	
16	DGB992 23		021470000062 4 / BOLT AND NUTS HEAT RESISTING SZ 4.000X0. 625 IN		50 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
17	DGB994 51	NO DATA AVAILABL E	021470941006 4 / SCREW MACHINE UNC STEEL BLACK HEX HD SZ 1.250X0.625IN	BR 320D/78	30 / EACH/N UMBER	BR 320 D/1978					<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
18	DGB994 50	NO DATA AVAILABL E	021470941006 5 / SCREW MACHINE UNC STEEL BLACK HEX HD SZ 1.500X0.625IN	BR 320D/78	6 / EACH/N UMBER	BR 320 D/1978					<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
19	DGB994 52	NO DATA AVAILABL E	021470941006 6 / SCREW MACHINE UNC	BR 320D/78	9 / EACH/N UMBER	BR 320 D/1978					<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			STEEL BLACK HEX HD SZ 1.500X0.750IN								AVAILABLE	
20	DGE992 75	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sTRAND, Z- LAY, 120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	240 / FATHO M						<p>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION -</u> SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
21	DGE101404	NO DATA AVAILAB LE	035059923713 0 / ROPE NYLON HAWSERLAID, DIA: 28-MM, 3- STRAND	MIN BRKG STRENGTH 15.500 TONS UNIT OF	120 / METER	NO DATA AVAILAB LE					<p>ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.</p> <p><u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.GENERAL</p> <p><u>SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
22	DGB99491		021470003356 6 / SCREW MACHINE BSW STEEL HEX HD SZ 1.000X0.750IN		20 / EACH/ NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DGB99225	NO DATA AVAILABLE	021470124029 2 / WASHER FLAT ROUND NOMINAL 0.50IN	SPEC. DGS/XCII/103/ 46	31 / EACH/ NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
24	DGH99161		028150281168 0 / DIVIDER		138 / EACH/ NUMBER						TECHNICAL SPECIFICATION - see attached file GENERAL SPECIFICATION - see attached file	
25	SGB91547		026659001603 2 / WASHER FLAT ROUND MILD STEEL 0.875X0. 937X1.875X0. 160*(LOCAL)	THK 0.160" APPROX WT PER 100 9 LB 6 OZ	350 / KILOGR AMME						TECHNICAL SPECIFICATION - Size: 0.875 x 0.937 x 1.875 x 0.16" δ Shape: Round δ Thickness: 3mm δ Usage: Used to distribute the load of a threaded fastener GENERAL SPECIFICATION - Size: 0.875 x 0.937 x 1.875 x 0.16" δ Shape: Round δ Thickness: 3mm δ Usage: Used to distribute the load of a threaded fastener	
26	DGB101310	MATERIAL GRADE EN 4140	021459941638 8 / BOLT MACHINE STEEL UNC HEX HD 0.75 X12X2 INCH TPI 10 (LOCAL)		384 / EACH/ NUMBER						TECHNICAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED GENERAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
27	DGB101376		0258502581203 / COPPER-WIRE-2-MM-DIA		10 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION -</u> Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER</p> <p><u>GENERAL SPECIFICATION -</u> Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER</p>	
28	DGD99099	NO DATA AVAILABLE	0031546000771 / DISH VEGETABLE (DONGA) GOLDEN CRESTED		4 / EACH/NUMBER	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION -</u> (Ceramic) with (lid) cover</p> <p><u>GENERAL SPECIFICATION -</u> (Ceramic) with (lid) cover</p>	
29	DGE99584	C-134	0851580000076 / DEFENCER EAR C-134 62TD		5 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE</p>	
30	DGE99283		4020999237137 / ROPE NYLON	NOR-SHIPS-USE-NASAR	120 / FATHOM						<p><u>TECHNICAL SPECIFICATION -</u> 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			HAWSERLAID, 3-STRND, Z-LAY, TYPE-1, NOM DIA: 64-MM, CIRC: 08-INCH,								<p>2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p> <p><u>GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021,</u></p> <p>2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
31	DGE101 305		402099923713 7 / ROPE NYLON HAWSERLAID, 3-STRND, Z- LAY, TYPE-1, NOM DIA: 64- MM, CIRC: 08- INCH,	NOR-SHIPS- USE-NASAR	120 / FATHO M						<p>WORKING/ BREAKING STRENGTH OF STORES.</p> <p><u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.<u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
32	DGH978 95		4030003731020 / SHAKLE2" OPENWD2.5" TO2.750" INSIDE-495" TO05.5" MATERIA DIA1.625	GENERAL USE	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
33	DGB992 21		5310591225295 / NUT,PLAIN, HEX ZINC PLATED 6X1MM PITCH, 10MM W A/F 5MM H O/A	30MM GUN EARTHING	46 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DGE992 64	MIL-P-15280	5640002374827 / INSULATION SLEEVING THERMAL		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
35	DGE992 62	MIL-P-15280	5640002374828 / INSULATION		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SLEEVING THERMAL								3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
36	DGE992 58	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		20 / EACH/ UMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature . Range: -40 to 90 °C Low Halogen: Yes	
37	DGD990 36	NO DATA AVAILABL E	773070504805 3 / PLATE DINNER 26CM GOLDEN CRESTED		24 / EACH/ UMBER						TECHNICAL SPECIFICATION - 26CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) plate dinner o/a dia 26 cm golden crested GENERAL SPECIFICATION - 26CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) plate dinner o/a dia 26 cm golden	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											crested	
38	DGD990 38		773070504805 4 / PLATE DESERT FLAT 19CM GOLDEN CRESTED WITH GOLDEN SHELL ON EDGE OF PLATE		24 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Material: porcelain Size: Width: 18CM, Height 2CMght <u>2CMGENERAL SPECIFICATION -</u> Material: porcelain Size: Width: 18CM, Height 2CMght 2CM	
39	DGD991 45		773070504805 5 / PLATE PUDDING FLAT 19CM GOLDEN CRESTED		24 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) <u>GENERAL SPECIFICATION -</u> FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
40	DGD970 26		773070504805 8 / PLATE SOUP 9INCH GOLDEN CRESTED		100 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) <u>GENERAL SPECIFICATION -</u> 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
41	DGD972 34		773070504805 8 / PLATE SOUP 9INCH GOLDEN CRESTED		100 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) <u>GENERAL SPECIFICATION -</u> 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
42	DGD990 39		773070504807 8 / CUP TEA BLUE CRESTED		24 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 <u>CMGENERAL SPECIFICATION -</u> Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
43	DGB98426	NO DATA AVAILABLE	0214580001168 / BOLT 228BSZ 14.00X55.00X35.00MM	S/M	25 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DGT90781	NO DATA AVAILABLE	0100000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	144 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DGT99331		9330992246090 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4.X0.60 to 0.70 MM	GENERAL USE	5 / SHEET						TECHNICAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 GENERAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
46	DGE101068	BS 419/156	0559546005362 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		55 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DGD99105	NO DATA AVAILABLE	0031500000096 / PLATE PUDDING 7" GOLDEN CRESTED		24 / EACH/NUMBER	Cera-e-noor					TECHNICAL SPECIFICATION - dia ; 7.48" material: porcelain golden crested with pn logo GENERAL SPECIFICATION - dia ; 7.48" material: porcelain golden crested with pn logo	
48	DGD93342		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
49	DGD92688		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		20 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
50	DGD78147		0035500000520 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		3 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER GENERAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
51	DGD99101		0034546000454 / Saucer Tea Blue Crested		24 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) As per existing Stock Make/Brand: CERA-E-NOOR with Blue Shell & PN Crest embossed on item GENERAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) As per existing Stock Make/Brand: CERA-E-NOOR with Blue Shell & PN Crest embossed on item	
52	DGD91433	NO DATA AVAILAB LE	0035500000454 / UTENSIL COOKING ALUMINIUM WITH COVER O/D 16-17".		15 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) GENERAL SPECIFICATION - Aluminium Grade	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESS 10 SWG								1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD)	
53	DGD99146		0034546000443 / PLATE DINNER PN BLUE CRESTED		24 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
54	DGE96714	ASTM D 6413	7210505155170 / FIRE RETARDANT SPRING MATTRESS (L6'XW2'XH4)	MATRESSES FOR BED	30 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.		AL-KHAIR HOUSE-43-T	TECHNICAL SPECIFICATION - FIRE RETARDANT SPRING MATTRESS (L6'XW2'XH4) GENERAL SPECIFICATION - FIRE RETARDANT SPRING MATTRESS (L6'XW2'XH4)	
55	DGE83202	N/A	9330705181279 / PLASTIC SHEET	GENERAL ITEM	3 / ROLL			LOCAL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
56	DGT101532	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
57	DGT103047	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	50 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
58	DGT992 65	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	20 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
59	DGT103 236	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	52 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
60	DGE101 687	611-055	402079515314 3 / ROPE NYLON 16MM WHITE MULTIPLAIT (FLEXABLE AND HIGH	TAL SHIP SAILING RIG	440 / METER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCCONNECT.		UK	TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG*	
61	DGE101 673	614-053	402079515314 5 / ROPE NYLON 12MM WHITE MULTIPLAIT, 8 STRAND, (FLEXABLE AND HIGH	TAL SHIP SAILING RIG	220 / METER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT.	UK		TECHNICAL SPECIFICATION - OEM: M/S COTESI UK MUNUFACTURED TP STANDARDS EN ISO ISO: 1140:2004 ISO: 2307: 2005 ISO: 9554:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE SPECIAL INSTRUCTIONS ATTACHED FOR SPI ONLY <u>GENERAL</u> SPECIFICATION - OEM: M/S COTESI UK MUNUFACTURED TP STANDARDS EN ISO ISO: 1140: 2004 ISO: 2307:2005 ISO: 9554: 2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE SPECIAL INSTRUCTIONS ATTACHED FOR SPI ONLY	
62	DGH990 81		614599531023 0 / CABLE POWER ELECTRICAL 3CORE 440V 102A	CABLES	180 / METER	Def Stan 02-526 issue 2 Table B. 10	NA	MINISTRY OF DEFENCE (NAVY) SHIPS SUPPORT AGENCY DME ME253, ROOM 19, BLOCK B FOXHILL, BATH, UK TEL: 01225 883293 FAX: 01225 883548	DG SHIPS 212 UK		TECHNICAL SPECIFICATION - DEF STAN 02-526 ISSUE 2/ IEC-60332 DESIGN: IEC-60092-353 INSULATION: IEC-60092-360 CONDUCTOR: IEC-60228 FLAME RETARDANR: IEC-60332 DEF STAN 02-526 ISSUE2 TABLE B.10 AS PER NMCRL AND DG SHIPS 212 Item will be accepted upon inspection of stores OEM cOC will be provided (required) <u>GENERAL</u> SPECIFICATION - DEF STAN 02- 526 ISSUE 2/ IEC-60332 DESIGN: IEC-60092-353 INSULATION: IEC- 60092-360 CONDUCTOR: IEC- -60228 FLAME RETARDANR: IEC- 60332 DEF STAN 02-526 ISSUE2 TABLE B.10 AS PER NMCRL AND DG SHIPS 212 Item will be accepted	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											upon inspection of stores OEM cOC will be provided (required)	
63	DGH101 262	GDHBMK4 092040	4010FT100791 8 / STEEL WIRE ROPE (20MM/40M/N ON- ROTATING/GA LVANIZED)	9M COMBINED BOAT CRANE	6.75 / EACH/N UMBER	GD.HBM. K.S-40/6- PG&40/9	N/A	GURDESAN GEMI MAK. SAN.TIC.A.S, DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM. KOCAELI, TURKEY TEL # 9.02627E+11 FAX # 9.02627E+11 INFO@GURDESAN.COM, TR	GURDES AN GEMI MAK. SAN.TIC. A.S		<p>TECHNICAL SPECIFICATION - A. Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual</p> <p>GENERAL SPECIFICATION - A. Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual</p>	
64	DGB999 80	TF-GFB 400	452070514707 9 / AUTOMATED GAS FIRED BURNER	FURNACES	1 / EACH/N UMBER	NO DATA AVAILAB LE		PK	ADDRES S:M/S TECHNO FIELD FABRICA TION 95- C. MEZZANI NE FLOOR, 11TH STREET, JAMI COMMER CIAL, PHASE-7 DHA KARACHI		<p>TECHNICAL SPECIFICATION - ADDRESS/SOURCE :M/S TECHNOFIELD FABRICATION 95- C.MEZZANINE FLOOR, 11th STREET, JAMI COMMERCIAL, PHASE-7 DHA KARACHIGENERAL SPECIFICATION - ADDRESS/SOURCE :M/S TECHNOFIELD FABRICATION 95- C.MEZZANINE FLOOR, 11th STREET, JAMI COMMERCIAL, PHASE-7 DHA KARACHI</p>	
65	DGE999 87	7920-00- 148-9666	792000148966 6 / Rag wiping Cotton & cotton synthetic 50 lbs	NIL	250 / SET	NA	NA	ALFA LAVAL TUMBA AB, HANS STAHL VAG 7 TUMBA SWEDEN	ALFA LAVAL TUMBA AB, SWEDEN		<p>TECHNICAL SPECIFICATION - PMS ItemGENERAL SPECIFICATION - PMS Item</p>	
66	DGH855 40	CEF80/SA 2X6MM2	614578513418	ND-14A DC POWER	1566 / METER	NO DATA AVAILAB		CH	M/S CSTC		TECHNICAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			9 / 02 CORE CABLE (PER CORE SHEATHED)	SUPPLY		LE			CHINA		<u>GENERAL SPECIFICATION - -</u>	
67	DGT103 048	NO DATA AVAILABL E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTABLISHMENT	24 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		<u>TECHNICAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM <u>GENERAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	
68	DGT103 238	NO DATA AVAILABL E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTABLISHMENT	17 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-		<u>TECHNICAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM <u>GENERAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									32776064 .MOBILE 0322-2578654.			
69	DGT993 48		934070514992 4 / MEDIUM DENSITY FIBER BOARD, (LASANI) WHITE COLOUR LAMINATION ONE SIDE DENSITY 750 KG cUB METER SIZE L:8' W: 4' TH: 3MM MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	5 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		TECHNICAL SPECIFICATION - SIZE: Length: 8 feet Width: 4 feet THickness: 3 MM colour: white SOURCE:M/S MEHRAN ART WOOD SHOP NO 9,PANJETANI HOUSE,SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI. TEL/ FAX: +92-21-32776064.MOBILE 0322- 2578654. PRICE:RS1350 APPOX PER SHEET,SIZE 8FEETX4FEETX1/8 INCHES. GENERAL SPECIFICATION - SIZE: Length: 8 feet Width: 4 feet THickness: 3 MM colour: white SOURCE:M/S MEHRAN ART WOOD SHOP NO 9,PANJETANI HOUSE,SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI. TEL/ FAX: +92-21-32776064.MOBILE 0322- 2578654. PRICE:RS1350 APPOX PER SHEET,SIZE 8FEETX4FEETX1/8 INCHES.	
70	DGE101 372	828 653-H9020051	801079520819 8 / FABRIC 1300 GSM MILITARY GREY (HYPALONE)	RHIB BOAT	7 / METER		NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX,TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHA W INFLATA BLES LTD		TECHNICAL SPECIFICATION - TDS IS ENCLOSED WITH RWIMSGENERAL SPECIFICATION - TDS IS ENCLOSED WITH RWIMS	
71	DGE101 699		035059571323 5 / ROPE SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH (ROUNDED IN 9-MM)		440 / FATHO M						TECHNICAL SPECIFICATION - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554. <u>GENERAL SPECIFICATION</u> - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554.</p>	
72	DGE100 168	319- SIVLER- DE	047659000003 1 / BRUSH STEEL WIRE SURFACE CLEANING SMALL		12 / EACH/N UMBER	319- SILVER- DE					<p><u>TECHNICAL SPECIFICATION</u> - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN BO7RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle, Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement <u>GENERAL SPECIFICATION</u> - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN BO7RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle, Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
73	DGE100164	NO DATA AVAILABLE	0559790200485 / INSULATION-TAPE-POLYETHYLENE TERAPHALATE(TERYLENE) W/0.75		20 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DGE100165	NO DATA AVAILABLE	0559790020552 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	56 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
75	DGE100189	NO DATA AVAILABLE	0559794444690 / RUBBER-TAP-INSULATION		35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
76	DGE100561		0414599230911 / PACKING MATERIAL HEMP FOR FURNACE FUEL, SIZE= 1/4" SQ		50 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DGE97270	NIL	0559794444898 / INSULATION SLEEV ELEC INT DIA 3MM THICK0.500 MATER CERAMIC	GENERAL ELECTRIC USE	145 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
78	DGB79518		0276795057080 / BOX SPANNER SET FROM 10MM TO 27MM(9 PIECES)+3 TOMMY BARS	FOR GENERAL USE	3 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DGE86473		0451594510094 / MATTRESS		20 / EACH/N						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FOAM RUBBER WITH COVER 82" X36"X4" (WARRANTY 10 YEARS)		UMBER						null	
80	DGB97045		028350283152 1 / CADMIUM ANODE ROLLED LG 12 INCH WTH 8 INCH TH 3/8 INCH		7.25 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH GENERAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH	
81	DGE101353		041459924180 8 / PAPER GASKET OIL PROOF JOINTING, 100 YARD ROLLS, WIDTH; 42", THICKNESS= 1/64 INCH.		12 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DGT101552	NO DATA AVAILABLE	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE		352 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT, THICKNESS =12MM (±1MM) GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT, THICKNESS =12MM(±1MM)	
83	DGH101689		023159571531 3 / WIRE ROPE GRIP STEEL DIA		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			0.398".									
84	DGB746 40		027370910447 6 / DIVIDERS SPRING LG OF LEG 06IN		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DGB995 81		021459013141 4 / BOLT MACHINE, THREAD SERIES: BSF, MEDIUM CLASS, HEXAGON, SIZE (0.875X3. 500X1.750 INCH)		3000 / EACH/N UMBER						TECHNICAL SPECIFICATION - HEAD: HEXAGON, THREAD SIZE: 7/8 INCH, NOMINAL LENGTH: 3 1/2 INCH, LENGTH OF THREAD: 1 3/4 INCH. SPECIFICATION: DEF STAN 02-862 Part 2, Issue 3 Class III, MATERIAL GRADE: BS EN 10269 42CrMo5-6 (OR) BS EN 10269 40CrMoV4-6 GENERAL SPECIFICATION - HEAD: HEXAGON, THREAD SIZE: 7/8 INCH, NOMINAL LENGTH: 3 1/2 INCH, LENGTH OF THREAD: 1 3/4 INCH. SPECIFICATION: DEF STAN 02-862 Part 2, Issue 3 Class III, MATERIAL GRADE: BS EN 10269 42CrMo5-6 (OR) BS EN 10269 40CrMoV4-6	
86	DGE995 85	NIL	035059942506 8 / ROPE SISAL, 03- STRANDS, CIRC 2.50 INCH, (DIA 20MM)		400 / FATHO M						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM: 1. TO BE COMPLY WITH SPECIFICATIONS OF ISO 1181-2004 OR LATEST VERSION, 2. ROOT PROOFING AS PER ISO 1181-2004 OR LATEST VERSION, 3. LENGTH PER COIL: 120 FATHOM. 4. OEM COC REQUIRED GENERAL SPECIFICATION - SPECIFICATION OF ITEM: 1. TO BE COMPLY WITH SPECIFICATIONS OF ISO 1181- 2004 OR LATEST VERSION, 2. ROOT PROOFING AS PER ISO 1181-2004 OR LATEST VERSION, 3. LENGTH PER COIL: 120 FATHOM. 4. OEM COC REQUIRED	
87	DGB101 554	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG	WELDING SYSTEMS (STAINLESS STEEL)	10 / KILOGR AMME						TECHNICAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			10								Current: 120-180 Amperes f. Application: To weld Mild Steel on surface <u>GENERAL SPECIFICATION</u> - a. Dia: 3.2mm b. Length: 350 mm-13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
88	DGB101399		021459941000 8 / BOLT MACHINE STEEL UNC HEX HD SZ 0.500X3. 500X1.250 IN	BR 320 D/70	20 / TEN						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
89	DGE99524	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/</u></u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
90	DGB101549		0214580001016 / BOLT WITH NUT STEEL 252TD SZ 15X14 AND 12X5MM	S/M	120 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
91	DGB78593		0273599104461 / CALIPER INSIDE 8IN		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DGB101615		0262590016897 / CLIP IRON O/A LG 6" DIA 3/8" BOTH ANGLE 90 BOTH ARM 2" (LOCAL)	USE MARINE RAILWAY	1500 / EACH/NUMBER						TECHNICAL SPECIFICATION - MILD STEEL BS 970 EN 3A superceeded by PD 970 (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local) GENERAL SPECIFICATION - MILD STEEL BS 970 EN 3A superceeded by PD 970 (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local)	
93	DGE78798	NO DATA AVAILABLE	0413546004797 / PVC PIPE-DIA-2"		500 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
94	DGB101614	NO DATA AVAILABLE	0262594195271 / SWIVEL-WITH-THIMBLE-LENGTH2.25"-DEP.50"		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DGB79214		0251594119648 / HINGE-BUTT-BRASS-SINGLE		116 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
96	DGE87671		2090505039233 / GROUND SHEET-CANVAS LG-2M 35CM WITH85CM THK 0.75MM		50 / EACH/NUMBER						TECHNICAL SPECIFICATION - Specifications: √ Material: Polyester-cotton canvas with PU/ PVC coating. √ Weight: 450-550 GSM √ Size: 5m x 8m (standard) √ Coating: Waterproof, anti-fungal, UV-resistant √ Color: Olive green/ khaki/ brown √ Edges: Reinforced with rust proof eyelets. √ Finish: Mildew resistant Technical Data: √ Waterproofing: 2000 mm hydrostatic head √ Tensile Strength: 350 N/ cm (warp), 300 N/ cm (weft). √ Tear Strength: 50N √ UV Resistance: 500 hrs exposure without degradation √ Abrasion: 30,000 rubs √ Shrinkage: 3% √ Temp Range: -100 C to + 550 √ Flame Retardant: NFPA 701/ BS 5852 compliant Testing Criteria : √ Hydrostatic pressure (ISO 811) √ Tensile & tear strength (ISO 13934-1, ISO 13937-2) √ UV resistance √ Mildew test √ Abrasion (ISO Standard) √ Shrinkage (ISO Standard) √ Fire resistance Accepting Criteria: √ Waterproof 2000 mm √ Tensile 350/300 N/cm √ Tear Strength > 50N √ No mildew growth (7 days) √ UV degradation 15% √ Abrasion > 30,000 rubs √ Shrinkage 3% √ Must pass flame test dimension: Width = 4 feet Height = 3 feet GENERAL SPECIFICATION - Specifications: √ Material: Polyester-cotton canvas with PU/ PVC coating. √ Weight: 450-550 GSM √ Size: 5m x	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>8m (standard) ∩ Coating: Waterproof, anti-fungal, UV-resistant ∩ Color: Olive green/ khaki/ brown ∩ Edges: Reinforced with rust proof eyelets. ∩ Finish: Mildew resistant Technical Data: ∩ Waterproofing: 2000 mm hydrostatic head ∩ Tensile Strength: 350 N/ cm (warp), 300 N/ cm (weft). ∩ Tear Strength: 50N ∩ UV Resistance: 500 hrs exposure without degradation ∩ Abrasion: 30,000 rubs ∩ Shrinkage: 3% ∩ Temp Range: -100 C to + 550 ∩ Flame Retardant: NFPA 701/ BS 5852 compliant Testing Criteria : ∩ Hydrostatic pressure (ISO 811) ∩ Tensile & tear strength (ISO 13934-1, ISO 13937-2) ∩ UV resistance ∩ Mildew test ∩ Abrasion (ISO Standard) ∩ Shrinkage (ISO Standard) ∩ Fire resistance Accepting Criteria: ∩ Waterproof 2000 mm ∩ Tensile 350/300 N/cm ∩ Tear Strength > 50N ∩ No mildew growth (7 days) ∩ UV degradation 15% ∩ Abrasion > 30,000 rubs ∩ Shrinkage 3% ∩ Must pass flame test dimension: Width = 4 feet Height = 3 feet</p>	
97	DGE100 238	205R 14C	132579272003 1 / TYRE- WITH-FLAPS		16 / EACH/N UMBER	UK					<p>TECHNICAL SPECIFICATION - DETAIL SPECIFICATION Size : 195 R14C Pattern : Rib Load index : 106/104 Ply Rating : 8 MAX INFLATED DIMENSION Overall Diameter (mm): 665 Over all Width (mm) : 200 RIM Size/ Code : 5.5" J x 14..0" LOAD AND INFLATION SINGLE Max load (KG) : 950 Max Pressure (PSI) : Follow vehicle manufacturer's Recommendation DUAL Max load (KG) : 900 Max Pressure (PSI) : Follow vehicle manufacturer's Recommendation NO DATA AVAILABLE GENERAL SPECIFICATION - DETAIL SPECIFICATION Size : 195 R14C</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											Pattern : Rib Load index : 106/104 Ply Rating : 8 MAX INFLATED DIMENSION Overall Diameter (mm): 665 Over all Width (mm) : 200 RIM Size/ Code : 5.5" J x 14..0" LOAD AND INFLATION SINGLE Max load (KG) : 950 Max Pressure (PSI) : Follow vehicle manufacturer's Recommendation DUAL Max load (KG) : 900 Max Pressure (PSI) : Follow vehicle manufacturer's RecommendationNO DATA AVAILABLE	
98	DGB101 176		451000273121 8 / BOWL WC		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
99	DGE101 536	NO DATA AVAILABL E	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p>GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p>TECHNICAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm</p>	
100	DGE740 05	621100/30 68.184	422079522956 2 / FINS SWIM RUBBER	FOR DIVING	11 / PAIR							

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BLACK								Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES, COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95Lbs(2.25Kg,MADE USA. GENERAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES, COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95Lbs(2.25Kg,MADE USA.	
101	DGE101 686	BS 2052	402099942504 2 / ROPE SISAL HAWSERLAID CIR 12MM 3 STRAND	MIN BKG LOAD 955 KG	500 / FATHO M						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
102	DGE101 064	nil	533000038292 2 / PACKING- MATERIAL	FUEL OIL SERVICE PMP	40 / METER						TECHNICAL SPECIFICATION - SPECIFICATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C GENERAL SPECIFICATION - SPECIFICATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C	
103	DGE999 23	MIL-P- 15280	564000237482 8 / INSULATION SLEEVEING THERMAL		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
104	DGE101349	NO DATA AVAILAB LE	041350000013 3 / EAR DEFENDER		120 / PAIR	PELTOR H10A/ OPTIME 105					<p><u>TECHNICAL SPECIFICATION</u> - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip) <u>GENERAL SPECIFICATION</u> - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip)</p>	
105	DGE98362	NO DATA AVAILAB LE	041350000013 3 / EAR DEFENDER		55 / PAIR	PELTOR H10A/ OPTIME 105					<p><u>TECHNICAL SPECIFICATION</u> - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip) <u>GENERAL SPECIFICATION</u> - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip)	
106	DGE970 50	NO DATA AVAILABL E	041350000013 3 / EAR DEFENDER		53 / PAIR	PELTOR H10A/ OPTIME 105					TECHNICAL SPECIFICATION - accaptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip) GENERAL SPECIFICATION - accaptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip)	
107	DGE101 366	NO DATA AVAILABL E	047450000030 7 / FENDER COIR ROUND		5 / EACH/N UMBER	600MM 24" ROUND COIR BOAT FENDER					TECHNICAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER-NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.	
108	DGD970 20		773070504805 5 / PLATE PUDDING FLAT 19CM GOLDEN CRESTED		100 / EACH/N UMBER						TECHNICAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
109	DGE999 84	NO DATA AVAILABL E	043250000002 4 / HELMET PROTECTIVE WITH VISER COLOUR WHITE (HALF HEAD)		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Make: UK Brand / Company Name: JSP SafetyGENERAL SPECIFICATION - Make: UK Brand / Company Name: JSP Safety	
110	DGE101 367	NO DATA AVAILABL E	043250000002 7 / HELMET PROTECTIVE DESPATCH RIDER WITH VISOR SIZE 6 3/4		5 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218) GENERAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218)	
111	DGE994 81		813570504263 2 / STRETCH FILM WRAPPER	PACKING MATERIAL L&E BRANCH NSSD	20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE 20"X30" IN									
112	DGE99986	NO DATA AVAILABLE	043250000028 / HELMET PROTECTIVE WITH VISER COLOUR WHITE (FULL HEAD)		8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
113	DGE100161		8135705064882 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	70 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
114	DGE100236	R	8345705042629 / Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter)	ITEM REQUIRED FOR MAKING OF GIFT BOXES	15 / METER						TECHNICAL SPECIFICATION - Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes GENERAL SPECIFICATION - Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes	
115	DGE102760	R	8345705042629 / Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter)	ITEM REQUIRED FOR MAKING OF GIFT BOXES	100 / METER						TECHNICAL SPECIFICATION - Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes GENERAL SPECIFICATION - Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes	
116	DGT101533	NO DATA AVAILABLE	0100000000048 / TIMBER SHESHAM SLEEPER WELL SEASONED		10 / CUBIC FOOT	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH iM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LOCAL								CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL USE GENERAL SPECIFICATION - SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH iM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL USE	
117	DGT103 218	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	704 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop GENERAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
118	DGT103046	NO DATA AVAILAB LE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	1120 / SQ FEET	NO DATA AVAILAB LE					<p>Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p>TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p>GENERAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop	
119	DGE972 36	ITD	841570508793 1 / CLOTH CURTAIN MATERIAL FIRE RETARDANT		45 / METER						<p><u>TECHNICAL SPECIFICATION -</u> Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150 Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire Retardancy test as Type-B of BS-5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1)</p> <p><u>GENERAL SPECIFICATION -</u> Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150 Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Retardancy test as Type-B of BS-5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1)	
120	DGT96504	NO DATA AVAILAB LE	010050000001 4 / PLYWOOD GRAD-1, (WBP) 5-PLY, SIZE: 6X4FT X 1/4-INCH (1.83 MTR X 1.22 MTR X 6.35 MM)		30 / SHEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> BS6566OF 1985 1 TO 8 <u>GENERAL</u> <u>SPECIFICATION - BS6566OF 1985</u> 1 TO 8	
121	DGE97431	NO DATA AVAILAB LE	045150000002 1 / CLOTH TICKEN BLUE STRIPS WIDTH 58 INCHES		1621 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - a.</u> WIDTH:58 INCH(1,473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT;40 d.COUNT OF YARN WARP;2/206 WEFT2/206 e. SHRINKAGE- WARP; 2%(MAX) WEFT;2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS) <u>GENERAL SPECIFICATION - a.</u> WIDTH:58 INCH(1,473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT;40 d.COUNT OF YARN WARP;2/206 WEFT2/206 e. SHRINKAGE- WARP; 2%(MAX) WEFT;2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS)	
122	DGE72198	E- AE10000	047650000006 8 / LEATHER CHROAME BLACK 24X24X1/16 INCH		56 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE:24X24X1/16 INCH NATO Code: F3013 <u>GENERAL</u> <u>SPECIFICATION - SIZE:24X24X1/16</u> INCH NATO Code: F3013	
123	DGT101563	NO DATA AVAILAB LE	010050000003 9 / TIMBER FIR HIMALAYA/ SPRUCE SLEEPER, WELL SEASONED LOCAL/	(3.05MTR X254 MM X127 MM) SPECE/PSG 69	37 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%, <u>GENERAL SPECIFICATION -</u> SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			IMPORTED, SIZE: L=8'-15', W=8"-14", h=4"-10"									
124	DGT945 28	BELFONT TRUWOOD DTEAK	933099224609 7 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM,SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		27 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
125	DGT103 219	BELFONT TRUWOOD DTEAK	933099224609 7 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM,SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		77 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
126	DGE101 370	0413-8522	041399923891 3 / RUBBER SHEET SOLID		30 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DGD956 67		734070510187 6 / MICROWAVE OVEN,18 LTR	MESS UTENSILS, OFFICER WARD PNS SHIFA	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - bran: WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCEGENERAL SPECIFICATION - bran: WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE	
128	DGE985 92		041354600365 0 / PVC PIPE DIA 1.50"		3500 / METER						TECHNICAL SPECIFICATION - Size: DIA 1.50"GENERAL SPECIFICATION - Size: DIA 1.50"	
129	DGD704 48		003550000045 7 / UTENSIL COOKING ALUMINUM		12 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG								GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
130	DGB75230	NO DATA AVAILAB LE	5120731000593 / WRENCH PIPE CHAIN CAPICTY 6INCH		6 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
131	DGT103220	NO DATA AVAILAB LE	0100500000043 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		30 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
132	DGE101318	HME-AB-CLAMP-PVC-20MM-009	5340705351243 / PIPE U CLAMP pvc type		45 / EACH/NUMBER	SS304 SURFACE					TECHNICAL SPECIFICATION - PIPE U CLAMP PVC TYPE INNER 200mm outer dia 48mm height 38mm thickness 22mm GENERAL SPECIFICATION - PIPE U CLAMP PVC TYPE INNER 200mm outer dia 48mm height 38mm thickness 22mm	
133	DGB102584	nl-fr-02	5340505301803 / solar frames		8 / EACH/NUMBER	00					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
134	DGE103445	N/A	9330705181279 / PLASTIC SHEET	GENERAL ITEM	20 / ROLL			LOCAL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
135	DGH103503	HO7RN-F	6145270106347 / SINGLE		300 / METER	ho7m-f					TECHNICAL SPECIFICATION - 185MM SINGLE CORE COPPER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			CORE FLEXIBLE CABLE 185MM E14 TYPE RUBBER (EPR) COMPUND 450/750V 341 AMPS								CONDUCTOR FLEXIBLE CABLE RUBBER INSULATED (EPR COMPUND), 450/750V MOBILE 341 AMPS, FIXED 475 AMPS GENERAL SPECIFICATION - 185MM SINGLE CORE COPPER CONDUCTOR FLEXIBLE CABLE RUBBER INSULATED (EPR COMPUND), 450/750V MOBILE 341 AMPS, FIXED 475 AMPS	
136	DGE95100	2040	5330705131806 / RUBBER STRIP	DOOR&HATC HES SEAL	370 / METER	NO DATA AVAILAB LE		PK		ABBASI TRADER S RUBBER STORE PH#2416 152	TECHNICAL SPECIFICATION - 1GENERAL SPECIFICATION - 1	
137	DGE101063	A-A-50162	7920006342408 / Towel, machinery wiping	0	1 / PACKE T	0	0	1333 ISAAC HULL AVE S E, WASHINGTON NAVY YARD, DC		NAVAL SEA SYSTEM S COMMAN D	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
138	DGT103450	NO DATA AVAILAB LE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR, LAMINATION ONE SIDE, DENSITY 750 KG/CUB to 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTAB LISHMENT	14 / SHEET	NO DATA AVAILAB LE		PK		SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.	TECHNICAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB GENERAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
139	SGB65953	DEVS7866	473099525334 8 / FLANGE		8 / EACH/NUMBER	NO DATA AVAILABLE		UK	MOD (NAVY) SHIP SUPPORT AGENCY DME MC253 ROOM 19 BLOCK B FRAHILL BATH UK		TECHNICAL SPECIFICATION - BS 1400 Inner dia: 1 1/2 inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: 1/2 inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing GENERAL SPECIFICATION -BS 1400 Inner dia: 1 1/2 inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: 1/2 inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing	
140	DGE87341	NO DATA AVAILABLE	047659000006 3 / GLOVES-LEATHER RIGHT HAND		680 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10 GENERAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10	
141	DGE99274		035059571313 0 / ROPE NYLON, HAWSERLAID, 3-STRAND, CIRC: 3-1/2 INCH, NOM DIA: 24MM, TYPE-1,	TOWING & BERTHING ROPE	240 / METER						TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY. 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	--------------	----------------	------------------	-----------

SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY. 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.

142	DGE97150	0414-5160	041459923093 4 / SHEET, ASBESTOS, COMPRESSE D TH 1/16", WD 54"X63" IN WT PER SHEET 22LBS		124 / KILOGR AMME						TECHNICAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)GENERAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)	
143	DGE99588		041359924350 5 / FIBER SHEET, VULCANISED, LG.56" WD.42" THICKNESS 0.125"		5 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
144	DGE103424		045159129298 9 / CLOTH COATED PVC FOR FURNITURE	FOR SPECS SEE CMD 8	300 / METER						TECHNICAL SPECIFICATION - ISO7617-2 OF 1994 colour blue wd . 50 INCHGENERAL SPECIFICATION - ISO7617-2 OF 1994 colour blue wd .50 INCH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			UPHOLSTERY COLOUR BLUE WD,50 INCH									
145	DGT103 449	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIV E		320 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM)GENERAL SPECIFICATION _SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
146	DGT103 315	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIV E		416 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM)GENERAL SPECIFICATION _SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
147	DGB963 85		021259923280 2 / BAR STEEL CORROSION RESISTING H/R RD 1.25" WT PER FT 4.209LBS		4 / METER						TECHNICAL SPECIFICATION - minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D) GENERAL SPECIFICATION - minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D)	
148	DGE986 60		033059571325 9 / TWINE NYLON		10 / KILOGR AMME						TECHNICAL SPECIFICATION - BKG STRENGTH 280 LBS TWINE NYLON MARLINE 3 STRD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MARLINE 3 STRD POLISHED MIN BKG STRENGTH 280 LBS								POLISHED (Dia 1.10 mm) PAKING: Standard available <u>GENERAL SPECIFICATION - BKG STRENGTH</u> 280 LBS TWINE NYLON MARLINE 3 STRD POLISHED (Dia 1.10 mm) PAKING: Standard available	
149	DGB101 286	BS2451 (5350-99- 923-3461)	028370923346 1 / CHILLED- IRON-GRIT- TYPE-FINE- GD-24		400 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> STANDARD PARTIDE SIZE: G- 24=0.6 TO 1.0 MM STANDARD: ISO 11124-2, METALLIC BLAST- CLEANING ABRASIVE. GRIT PARTICLE SHAPE. HARDNESS: ROCKWELL 61 TO 64 HRC, ± 3 HRC SHAPE: ANGULAR AND IRREGULAR. DENSITIES: 7g/ cm3 (APPARENT DENSITY) 3.8 g/ m3 (BULK DENSITY) CHEMICAL COMPOSITION (APPROXIMATE VALUES) CARBON C: 3.00 % to 3.20 % MANGANESE Mn: 0.30 % to 1.00 % SILICON SI: 1.00 % to 1.50 % PHOSPHOROUS P: 0.10 % to 0.60 % SULFUR S: 0.07 % to 0.17 % <u>GENERAL SPECIFICATION -</u> STANDARD PARTIDE SIZE: G- 24=0.6 TO 1.0 MM STANDARD: ISO 11124-2, METALLIC BLAST- CLEANING ABRASIVE. GRIT PARTICLE SHAPE. HARDNESS: ROCKWELL 61 TO 64 HRC, ± 3 HRC SHAPE: ANGULAR AND IRREGULAR. DENSITIES: 7g/ cm3 (APPARENT DENSITY) 3.8 g/ m3 (BULK DENSITY) CHEMICAL COMPOSITION (APPROXIMATE VALUES) CARBON C: 3.00 % to 3.20 % MANGANESE Mn: 0.30 % to 1.00 % SILICON SI: 1.00 % to 1.50 % PHOSPHOROUS P: 0.10 % to 0.60 % SULFUR S: 0.07 % to 0.17 %	
150	DGB973 62		021450214079 2 / NUT MILD STEEL FOR BOLT HEX .SZ 1.250 IN		220 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
151	DGT103489	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	15 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
152	DGB97386	(SIM)	0257709411504 / NUT-PLAIN-HEXAGON (BRASS) THREAD UNF SZ .375"LH .350"		32 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
153	DGB98424		0214502140620 / BOLT AND NUTS STEEL HEX HD THD LG 1.25" TPI12SZ6.000X0.750 IN		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
154	DGE101377	GRADE400	5350PK5104071 / WATER PROOF SAND PAPER GRADE400	WOODEN & GRP BOATS,, AQUATIC CLUB D/YARD	100 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
155	DGE99981	NO DATA AVAILABLE	0422500000027 / IMPROVED VERSION PVC TILES MAROON SIZE 300X300X3MM		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
156	DGE103349	NO DATA AVAILABLE	0432500000006 / DUST RESPIRATOR		60 / EACH/NUMBER	M 511-N95					TECHNICAL SPECIFICATION - packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size: Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											China (GB 2626-2006) Filtering Rate: = 95% <u>GENERAL SPECIFICATION</u> - packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size: Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95 China (GB 2626-2006) Filtering Rate: = 95%	
157	DGT103 447	NO DATA AVAILABL E	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	1408 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 <u>GENERAL SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
158	DGT103 501	NO DATA AVAILABL E	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	480 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											323 : 1993 <u>GENERAL SPECIFICATION</u> - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
159	DGT103 312	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	576 / SQ FEET	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION</u> - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p><u>GENERAL SPECIFICATION</u> - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop	
160	DGT103 448	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply.	X 19.05 MM)	320 / SQ FEET	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p>GENERAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop	
161	DGT103 505	NO DATA AVAILAB LE	010050000001 5 / PLY WOOD GRADE-1, 5 PLY		672 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 GENERAL SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993	
162	DGT103 050	NO DATA AVAILAB LE	010050000002 8 / PLY WOOD MARINE ALL SHESHAM DURABILITY	2.440X1. 220MTRX6. 35MM) SPECE/BS-1088	640 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLYS OF SHESHAM WOOD) 5-PLY								WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, <u>GENERAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,</u>	
163	DGE101364	NO DATA AVAILABLE	7330701002289 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDUS/JOYO).		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - WITH FULLCOVER</u> <u>GENERAL SPECIFICATION - WITH FULLCOVER</u>	
164	DGT103316		9330992246090 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4. X0.60 to 0.70 MM	GENERAL USE	17 / SHEET						<u>TECHNICAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794</u> <u>GENERAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794</u>	
165	DGT103313	BELFONT TRUWOOD TEAK	9330992246097 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK		14 / SHEET						<u>TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1</u> <u>GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WOOD) (GRADE DESIGNATION .STAN)									
166	DGE100 167	BS 419/156	055954600536 2 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		40 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
167	DGE100 163	NO DATA AVAILABL E	055978000018 5 / SLEEVE PLASTIC		5 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
168	DGT103 488	NO DATA AVAILABL E	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		13 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
169	DGT101 537	NO DATA AVAILABL E	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		30 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
170	DGT103 314	NO DATA AVAILABL E	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		28 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
171	DGE100268	LOCALLY DEVELOPED	4220546013157 / REPAIR KIT (FOR LIFE RAFT) CONTENTS OF 07 ITEMS, SHELF LIFE 05.		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
172	DGB98387		0214700000840 / WASHER MILD STEEL 0.50IN		17 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	