

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 23-06-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DRG96285	8814157000	6680ZO6529519 / TANK PRESSURE GENERATOR.		3 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - MATERIAL STRONG PLASTIC . CAPACITY 4.5 - 5.5 LTRS. PRESSURE 03 BAR WITH PRESSURE GAUGE, FILTER ETC. MODEL:229TS,MAKE GLORIA GERMANY/ANY COMPITABLE WITH BOOKLET a. OEM TURBOMECA (FRANCE)GENERAL SPECIFICATION - MATERIAL STRONG PLASTIC .CAPACITY 4.5 - 5.5 LTRS. PRESSURE 03 BAR WITH PRESSURE GAUGE, FILTER ETC. MODEL:229TS,MAKE GLORIA GERMANY/ANY COMPITABLE WITH BOOKLET a. OEM TURBOMECA (FRANCE)	
2	DRG100281	ZO6547932	2915ZO6547932 / REGULATOR HIGH PRESSURE		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - S2500 GP SINGLE STAGE REG FOR OXY/INERT GAS SVCE EAX INLET PRESS:300BAR/4350PSI, OUTLET PRESS:172BAROR 2500 PSI GENERAL SPECIFICATION - S2500 GP SINGLE STAGE REG FOR OXY/INERT GAS SVCE EAX INLET PRESS:300BAR/4350PSI, OUTLET PRESS:172BAROR 2500 PSI	
3	DPC103479	NO DATA AVAILAB LE	0473500005372 / SILICA GEL		15 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILAB LE	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
4	DPC103 485	NO DATA AVAILABE	047350224769 5 / REFINED SODIUM BICARBONATE (OEM = ICI PAKISTAN) Packing = 25kg Bag		30 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
5	DPC103 470	CC 2748M (5 liters packing) CC2750M (20 liters packing)	681071522985 7 / ES Complete EG premix coolant	MAIN ENGINE	1675 / LITER		22376716	CUMMINS FILTRATION FLEETGUARD DISTRIBUTERS	CUMMINS / FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
6	DPC103 643	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	176 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGINAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
7	DPC102 174	-	047350473004 9 / SILICA GEL (Packing = 5 KG Bag)		295 / KILOGRAMME						TECHNICAL SPECIFICATION - A. SILICA GEL (DESICCANT) IN GRAIN FORM FOR TRANSFORMERS HUMIDITY CONTROL. B. GRAIN SIZE 2.0 – 3.0 MM. C. CAPABLE TO ABSORB MOISTURE AT ROOM TEMPERATURE AND RELEASE MOISTURE WHEN HEATED UP. D. SMALL POROUS, WHITE STANDARD. GENERAL SPECIFICATION - A. SILICA GEL (DESICCANT) IN GRAIN FORM FOR TRANSFORMERS HUMIDITY CONTROL. B. GRAIN SIZE 2.0 – 3.0 MM. C. CAPABLE TO ABSORB MOISTURE AT ROOM TEMPERATURE AND RELEASE MOISTURE WHEN HEATED UP. D. SMALL POROUS, WHITE STANDARD.	
8	DPC103	NA	650870523178	SELF	30 /	NIL	NIL	PAKISTAN	PAKISTA		TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	663		5 / HAND SANITIZER		LITER				N		HAND SANITIZER GENERAL SPECIFICATION - HAND SANITIZER	
9	DPC103 423		044250942937 4 / VARNISH MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	USE ONWOOD UNDER CONDITIONS OF MARINE EX	440 / LITER						TECHNICAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED GENERAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED	
10	DPC103 414		044250442009 2 / VARNISH ELEC INSULATING AIR DRYING H/I THINNER UPTO 15% (Packing 20 Ltrs)		76 / LITER						TECHNICAL SPECIFICATION - IEC-60464-1, 2&3 GENERAL SPECIFICATION - IEC-60464-1, 2&3	
11	DPC103 420		044250442009 4 / VARNISH FINISHING ARR DRY (packing 4liter tin)		12 / LITER						TECHNICAL SPECIFICATION - S. NO INFORMATION REMARKS 01 NAME= SYNTHETIC CLEAR VARNISH (ELECTRIC VARNISH) 02 SPECIFIC GRAVITY= 0.87-0.91 03 COLOR= CLEAR HOMOGENEOUS DRAK BROWN 04 FLASH POINT= >30 °C 05 SURFACE DRY TIME= 5-6 HOURS 06 HARD DRY TIME= 24 HOURS 07 PACKAGING= 04 LITER (TIN PACKAGE) <u>GENERAL SPECIFICATION - S.NO</u> INFORMATION REMARKS 01 NAME= SYNTHETIC CLEAR VARNISH (ELECTRIC VARNISH) 02 SPECIFIC GRAVITY= 0.87-0.91 03 COLOR= CLEAR HOMOGENEOUS DRAK BROWN 04 FLASH POINT= >30 °C 05 SURFACE DRY TIME= 5-6 HOURS 06 HARD DRY TIME= 24 HOURS 07 PACKAGING= 04 LITER (TIN PACKAGE)	
12	DNM103 415	0149-2832/ FS1280	291070524597 6 / filter,fuel		1 / EACH/N	na					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION -	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
					UMBER						null	
13	DNM103 418	0121-0258	281571526753 6 / FEED PUMP (BOSCH PART No. 9 440 030 030)		1 / EACH/N UMBER	C22 D5					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
14	DNM103 405	0509-0494	533179523744 1 / SEAL OIL		1 / EACH/N UMBER	C110D5					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
15	DNM102 027	3019158/6 602766	533001080177 3 / GASKIT RADIATOR CUMMINS D/G NT-855-G4	CUMMINS ENGINE D/G	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
16	DNQ103 690	1-3-150 DEVELOP ED BY DTD	473099254274 7 / CLAMP PIPE REPAIR- 38-42MM LG 75MM	DAMAGE CONTROL &FIRE FIGHTING EQUIOMENT	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
17	DNM103 691	N4067	482072504238 0 / VALVE- INTAKE-24-R- STEEL- 28X34MM	R C CHAMBER PNS IOBAL	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - 24- R-STEEL-28X34MMGENERAL SPECIFICATION - 24-R-STEEL- 28X34MM	
18	DNH103 551	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/N UMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
19	DNH101 713	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		3 / EACH/N UMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
20	DNM103 413	FS100/L FS 100	294073521568 7 / FILTER 1 MICRON	MEDICAL OXYGEN GENERATOR O-500 ECO	4 / EACH/N UMBER	LF S 100	2011118	OXYMATE A/S, FASANVEJ 18-20, DK- 3200, HELSINGE DENMARK. TEL: +45 48797811 FAX: +45 48797813	OXYMAT A/S		TECHNICAL SPECIFICATION - 1. FILTER 1 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE. GENERAL SPECIFICATION - 1.	

Jo	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								E MAIL: service@oxymat.dk www.oxymat.dt			FILTER 1 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE.	
21	DNM103 407	162236948 0	481073521568 3 / BLOW-OFF VALVE	MEDICAL OXYGEN GENERATOR O-500 ECO	4 / EACH/NUMBER	GA45+	2011118	ATLAS COPCO AIR POWER N.V, B-2610 WILRIJK ? BELGIUM. TEL: +32-3-87021 11 FAX: +32-3-8702730 WWW.atlascopco.be	ATLAS COPCO		TECHNICAL SPECIFICATION - MAKE: ATLAS COPCO , BLOW OFF VALVE FITTED WITH UNLOADER ASSEMBLY FOR AUTO WORK oem: SWEEDEN supplier : Plot-8C, Phase -2 Commercial Area Defense Housing Authority Karachi. Contact: 021-345500451 GENERAL SPECIFICATION - MAKE: ATLAS COPCO , BLOW OFF VALVE FITTED WITH UNLOADER ASSEMBLY FOR AUTO WORK oem: SWEEDEN supplier : Plot-8C, Phase -2 Commercial Area Defense Housing Authority Karachi. Contact: 021-345500451	
22	DNQ103 698	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	1 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D		TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCR L GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCR L	
23	DPC103 658	G-1200	047550220561 3 / RTV		41 / TUBE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SILICON SEALANT (PACKING 310 ML TUBE)								SPECIFICATION - NO DATA AVAILABLE	
24	DPK101569	99000-22B55	915076522310 6 / ECSTAR OUT BOARD MOTOR GEAR OIL SUZUKI SAE-90 GL-5	SUZUKI OBM ENGINE	150 / MILLILITER	NIL		SHOWA SHELL SEKIYU K. K. 3-2 DAIBA-2-CHOME, MINATO-KU, TOKYO, 135-8074, JAPAN		OBM SUZUKI	TECHNICAL SPECIFICATION - ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE AUTOMOTIVE GEAR OIL GENERAL SPECIFICATION - ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE AUTOMOTIVE GEAR OIL	
25	DRG99464	180/R13 6PLY	2610ZO652447 7 / TYRE TUBELESS SYZE ST. 180/R13 6PLY		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DSA101160	CH 25601	666512145416 4 / MANOXYDE-CARBONE-SC-CH25601		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
27	DSA103345	D-18465	513076515711 6 / GRINDING DISC 5 INCH		87 / EACH/NUMBER	200213/ EN-12413					TECHNICAL SPECIFICATION - OEM: RHODIUS GERMANY Technical details: Series : RS2 Diameter: 125mm Thickness: 7.0mm Center hole: 22.23mm with steel core in & out side Model No: 200213/ EN-12413 PRO LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWEKZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROHI/ GERMANY SHELF LIFE EXPIERY DATE AT LEAST 03 YEARS AGAINST MANUFACTURING DATE GENERAL SPECIFICATION - OEM: RHODIUS GERMANY Technical details: Series : RS2 Diameter: 125mm Thickness:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											7.0mm Center hole: 22.23mm with steel core in & out side Model No: 200213/ EN-12413 PRO LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWEKZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROH/ GERMANY SHELF LIFE EXPIERY DATE AT LEAST 03 YEARS AGAINST MANUFACTURING DATE	
28	DGP103 967	32D2900	582073520849 6 / 32 INCH LED DISPLAY WITH HDMI & VGA I/P	CCTV System	1 / EACH/N UMBER	32D2900		TCL Electronics Australia Pty Ltd, Address: 797 Springvale Rd, Mulgrave, VIC 3170	M/s TCL Australia		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DPC102 805	NO DATA AVAILABL E	047450000702 8 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		2 / BAG						TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0	
30	DPK1029 60	HA5440	915073516428 5 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	100 / GALLO N	F350A	6AW- 1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	TELEFLE X MARINE CANADA		TECHNICAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270- 7172 WWW.seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604- 248-3858 GENERAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
31	DPC83761	GLDO1	6810705279752 / ADVANCE COAT POLYETHYLENE COATING POWDER GOLDEN SHADE		20 / KILOGRAMME	POLYETHYLENE					TECHNICAL SPECIFICATION - POLYETHYLENE COATING POWDER GOLDEN SHADE GENERAL SPECIFICATION - POLYETHYLENE COATING POWDER GOLDEN SHADE	
32	DPC102949	HRC-407C (HFC-407C) GENETRON R-407C	6830705118136 / GAS FOR (A/C) R-407C (packing = 11.3 kg) (Purity level 99% Min)	A/C SPLIT (02TONS)	102.15 / KILOGRAMME						TECHNICAL SPECIFICATION - OEM: HONEYWELL (USA) GENERAL SPECIFICATION - OEM: HONEYWELL (USA)	
33	DPC102107		0473504730004 / FLUXITE SOLDERING PASTE (ZINC CHLORIDE)		5 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DPC102100		0473502247701 / GUM ACACIA TECHNICAL		20 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
35	DNM102643	135326206 / 934-694	2940994713392 / main air filter		5 / EACH/NUMBER	135326206					TECHNICAL SPECIFICATION - External Diameter: 146.3mm Internal Diameter: 77mm Length: 322mm WIDTH: 356 MM HEIGHT: 152 MM DEPTH: 152 MM WEIGHT: 0.86 KG GENERAL SPECIFICATION - External Diameter: 146.3mm Internal Diameter: 77mm Length: 322mm WIDTH: 356 MM HEIGHT: 152 MM DEPTH: 152 MM WEIGHT: 0.86 KG	
36	DNM96754	2417090	5305735244810 / M8x25 8.8 zn DIN 912 hexagon socket head screw		8 / EACH/NUMBER	CLASSIC V					TECHNICAL SPECIFICATION - M8X25 8.8ZN DIN 912 HEXAGON SOCKET HEAD SCREW GENERAL SPECIFICATION - M8X25 8.8ZN DIN 912 HEXAGON SOCKET HEAD SCREW	
37	DNM100401	167-4407	5331715270249 / SEAL O RING FOR F/W LINE		1 / EACH/NUMBER	DE-660EO CATERPILLAR GENERATOR C18					TECHNICAL SPECIFICATION - SEAL O RING FOR F/W LINE cross section 3.53mm id: 69.44mm 70a shore GENERAL SPECIFICATION - SEAL O RING FOR F/W LINE cross section 3.53mm id: 69.44mm 70a	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
						600 KVA /480KW					shore	
38	DNQ100 606	RADTARG E-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		2 / EACH/NUMBER	RADTAR GE-H					<p><u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumolative dose graph data log and export user device, management tresh hold time settig</p> <p><u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumolative dose graph data log and export user device, management tresh hold time settig</p>	
39	DNH102 790	NO DATA AVAILAB LE	130850053012 5 / REFRIG 12CUFT DOUBLE DR 220V(DLT. NSSD/HM/PAT T/467 DT. 121093)	12 CUF	1 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
40	DNQ102 612	NO DATA AVAILAB LE	046150000028 0 / SAFETY GOGGLES WITH SUN GLASSES		76 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - MAKE/ BRAND/ EQUIVALENT: CHINA Color: Black Lenses Material: Polycarbonate Frame Material: PVC/PC Scratch Resistance: Yes Fog Resistant: Yes Weight: 40-50 gm (approx) Built in side shields to provide An ever greater level of impact protection. Petersafe/any well reputed firm having import/export license.</p> <p><u>GENERAL SPECIFICATION</u> - MAKE/ BRAND/ EQUIVALENT: CHINA Color: Black Lenses Material: Polycarbonate Frame Material: PVC/PC Scratch Resistance: Yes Fog Resistant: Yes Weight: 40-50 gm (approx) Built in side shields to provide An ever greater level of impact protection. Petersafe/any well reputed firm having import/export</p>	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											license.	
41	DPC102732	NO DATA AVAILABLE	801070509845 3 / SPRAY PAINT TIN (BOSNY no 39 black + BOSNY no 40 White) (300 GM bottle each)	PRESSURE GAUGES FOR REPAIR/CALIBRATION	60 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DNM100467	70HFR20	596175506777 7 / METAL STUD DIODE 70HFR20 METAL DO-5 PACKAGE	DORMAN D/G 500KVA (UK)	3 / EACH/NUMBER	70HFR20					TECHNICAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE GENERAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE	
43	DNQ100858	RANGE 120 TO 140MM (P/N 2201/0017)	473099533297 3 / CLAMP HOSE WORM DRIVE STEEL ZINC PLTD WD 13MM THK 1MM 70/226	E16 MACHINERY SPACE DAMAGE CONTROL TOOLB	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DNQ100681	11655778/SL60CP12	512099910596 6 / SPANNER OPENJAW ADJ 12IN 1-1/4 A/F TYPE (CRESCENT) 31.75 MM		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DNQ100808	H6880	512099136559 5 / SCREW DRIVER FLAT TIP LENGTH: 505 MM. BLADE LENGTH: 300 MM. TIP WIDTH: 16 MM. MATERIAL HANDLE: WOOD.	FOR FIRE FIGHTING	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 2559 PART 1. GENERAL SPECIFICATION - BS 2559 PART 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MATERIAL BLADE: STEEL.									
46	DNQ100 964	H6880	512099136559 5 / SCREW DRIVER FLAT TIP LENGTH: 505 MM. BLADE LENGTH: 300 MM. TIP WIDTH: 16 MM. MATERIAL HANDLE: WOOD. MATERIAL BLADE: STEEL.	FOR FIRE FIGHTING	7 / EACH/N UMBER						TECHNICAL SPECIFICATION - BS 2559 PART 1.GENERAL SPECIFICATION - BS 2559 PART 1.	
47	DNH101 566	NIL	411070506958 8 / DEEP FREEZER 17- CUFT 190- 230V 50HZ SINGEL PHASE	WAVES DEEP FREEZER 17- CUFT	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DNH102 217	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/N UMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DNH101 311	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH/N UMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
50	DNH102 421	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V		2 / EACH/N UMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			AC 50 HZ PEL, WAVES AND DAWLANCE									
51	DNH102082	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
52	DNQ102613		4210795101353 / EDBA LOCKERS (EXTENSION LOCKER)	EDBA	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Required Materia - Stainless Steel Grade-316 (non-magnetic). b. Body Gauge - 12 gauge (Thickness = 2.656mm). c. Paint Coating - Painting not required. d. Lock Type - Keyless Spring Latch. SIZE/ DIMENSION IN INCHES: H 35 w 18.5 b 10 material: aluminum paint scheme: fluorescent red GENERAL SPECIFICATION - a. Required Materia - Stainless Steel Grade-316 (non-magnetic). b. Body Gauge - 12 gauge (Thickness = 2.656mm). c. Paint Coating - Painting not required. d. Lock Type - Keyless Spring Latch. SIZE/ DIMENSION IN INCHES: H 35 w 18.5 b 10 material: aluminum paint scheme: fluorescent red	
53	DNQ100825	5114/15	4210994232704 / BRANCH PIPE FIRE HOSE FOAM TYPE-FB5(X) INSTANTANEOUS	FIRE FIGHTING	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
54	DNQ100906	0264-264034 LOCALLY DEVELOPED	2090994633937 / SPLINTER BOX 350X350X125 MM		1 / EACH/NUMBER	LOCALLY DEVELOPED					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DPC102634	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GAS (EMPTY) CAPACITY 45.40KG								CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doorn dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque. <u>GENERAL SPECIFICATION</u> - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120-150 Torque,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
56	DNM102639	127-2176	5331014771961 / SEAL-INTEGRAL	CATTER PILLER GENSET 3512B USA	12 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N. E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
57	DNQ100683	23/90538	4210997485226 / DISCHARGE HEAD ASSY	FIRE FIGHTING EQUIPMENT	50 / EACH/NUMBER	NO DATA AVAILABLE		UK	UK ENGLAND		<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
58	DNM101807	10000-05878 / 131017592	2910795215436 / FUEL INJECTION PUMP	15 KVA DG	2 / EACH/NUMBER	SDG15PS	15403027	PERKINS ENGINES LTD! CENTRAL PARTS OPERATION UNITED KINGDOM	PERKINS ENGINE		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
59	DNM100384	274-4491	5305015645267 / SCREW	MAIN ENGINE	12 / EACH/NUMBER	C-18 ACERT T2P1UP	T2P01436	3701 TATE ROAD 20 BAST TOWN ALFA VETTEIN POST CODE 47905 USA	CATTERPILLER		<u>TECHNICAL SPECIFICATION - FITTED IN ROCKER ARM ASSEMBLEGENERAL SPECIFICATION - FITTED IN ROCKER ARM ASSEMBLE</u>	
60	DNM100384	274-4491	5305015645267 / SCREW	MAIN ENGINE	12 / EACH/NUMBER	C-18 ACERT T2P1UP	T2P01436	3701 TATE ROAD 20 BAST TOWN ALFA VETTEIN POST CODE 47905 USA	CATTERPILLER		<u>TECHNICAL SPECIFICATION - FITTED IN ROCKER ARM ASSEMBLEGENERAL SPECIFICATION - FITTED IN ROCKER ARM ASSEMBLE</u>	
61	DNM102536	FF5488/3959612	4330015300044 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD	2 / EACH/NUMBER	QSB6.7-305MD	74126404	CUMMINS ENGINE COMPANY , INC PO BOX 3005 COLUMBUS IN 47202-9982	CUMMINS ENGINE COMPANY		<u>TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA</u>	
62	DNM102536	FF5488/3959612	4330015300044 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD	2 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s Cummins Inc		<u>TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA</u>	
63	DNQ103185	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	1 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND		<u>TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER</u>	

Jo	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
64	DNQ102526	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	1 / ROLL	NO DATA AVAILAB LE		UK		UK ENGLAN D	TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john- holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john- holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
65	DPC102797	A020EEV2	801070533282 5 / HIGHLY PERFUMED BACTERICIDA L WASHROOM CLEANER.		600 / LITER	HIGHLY PERFUM ED					TECHNICAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			THINNER 850-761-04 (04 Liter Packing)								SPECIFICATION - NO DATA AVAILABLE	
69	DPC102 869	COMP A = 430-101-04	8010PK5064838 / PERMOBEL EPOXY FINISH (COMPONENT A-SILVER-GREY-430-101-04) (04 Liter Packing)		5 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DPC102 574	BS 2451, DEFSTAN: 80-73/1 OF 1977	8010701004136 / PAINT NON SLIPING PREMIXED (LIGHT GREY) BS2451, DEFSTAN 80-73/1	FINISHING NON SLIP	457 / LITER						TECHNICAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0mm Thickness Level = 2.0mm to 3.0 mm GENERAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0 mm Thickness Level = 2.0mm to 3.0 mm	
71	DPC102 539	NO DATA AVAILABLE	6840705057111 / INSECTICIDE K-OTHRINE ec 15 (01 LITER PACKING) (OEM M/S Bayer Environmental Sciences)	TO CONTROL INSECT PASTS COCKROACHES BUGS	20 / LITER						TECHNICAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label. GENERAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.	
72	DPC101 890	NO DATA AVAILABLE	0442502202381 / PAINT PRIMING GRAPHITE BASIS (RED LEAD)	BUXLY/ICI/BERGER/KOSAR GRP-E VIDE NHQ LT	300 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DPK1030 97	0x-8	0475702202348 / HYDRAULIC FLUID		459 / LITER						TECHNICAL SPECIFICATION - SAE J1704. DEFSTAN 01-005 ISSUE 20. GENERAL SPECIFICATION - SAE J1704. DEFSTAN 01-005 ISSUE 20.	
74	DPK1029 04	OMALA 68	9150270001857 / SHELL OMALA OIL S2 GX 68 (PACKING 209 LTR DRUM)	MTP 750DD HUB OIL	110 / LITER	NO DATA AVAILABLE		OC		TURKEY	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
75	DPC102 838	CC 2748M (5 liters packing) CC2750M (20 liters packing)	681071522985 7 / ES Complete EG premix coolant	MAIN ENGINE	150 / LITER		22376716	CUMMINS FILTRATION FLEETGUARD DISTRIBUTERS	CUMMINS / FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
76	DPC102 767	CON-EDDC-1PP1-P30	801070520466 0 / EZIKLEAN DE-GREASER, CARBON AND SURFACE CLEANER CO	KACRHER MACHINE	75 / LITER	1PP1	RM-110	HEAD OFFICE: NURISTAA @ BUILDING NO 85, BLOCK DD CCA, PHASE 4, DHA LAHORE PH:+92 322-388-888-2 www.nuristaa.com E-mail: sales@nuristaa.com	PAKISTAN		TECHNICAL SPECIFICATION - ITEM REQUIRED FOR all metal surfaces (ferrous and no ferrous) stainless steel surface brass and chrome surface, glass surface, marble ceramic, procelain, plastic and wooden floor, kitchen equipment, plastic, rubber and leather surface GENERAL SPECIFICATION - ITEM REQUIRED FOR all metal surfaces (ferrous and no ferrous) stainless steel surface brass and chrome surface, glass surface, marble ceramic, procelain, plastic and wooden floor, kitchen equipment, plastic, rubber and leather surface	
77	DPC102 546	N/A	793070518128 0 / DETERGENT WATER SOLUBLE	GENERAL ITEM	90 / LITER			LOCKEL MARKET	GENERAL ITEM		TECHNICAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE GENERAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE	
78	DPK1015 59	FCW NMMA CERTIFIED	915076517954 6 / YAMALUBE/A DDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	123 / LITER	JAPAN		JAPAN	SHELL		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	