LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 18-11-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)

2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.

3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.

4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL:	clp@paknavy.gov.pk, localpurchasedivision@gmail.com
PHONE:	021-48508524, 48508828,
WHATSAPP NO.	92-322-0188121 (Message Only)

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGD109823		7730705048068 / POT MILK 6 OZ GOLDEN CRESTED		8 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - 6 OZ GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - 6 OZ GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
2	DPK112229	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/ADDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	400 / LITER	JAPAN		JAPAN	SHELL	.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
3	DPK107874	CORENA S2 P150	9150705196699 / SHELL CORENA S2 P150 (PACKING = 20 LITERS)	HPAC PNFT	60 / LITER	NA	NA	M/S SHELL	M/S SHELL	.	TECHNICAL SPECIFICATION - SHELL CORENA S2 P150GENERAL SPECIFICATION - SHELL CORENA S2 P150	
4	DNF114053	DGS-008D/E/ DF3709B1001785	5930715181162 / D-LINK 8 PORT NETWORK SWITCH	VIRDI AC-4000	1 / EACH/NUMBER	DGS 1008 D/E	NA	USA/CANADA	USA/CANADA	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - 8 PORT DESKTOP SWITCH SPORTING.803.3 ETHERNET, 80230FAST ETHERNET OR 8023ab GB ETHERNET CATS ETHERNT CABLEGENERAL SPECIFICATION - 8 PORT DESKTOP SWITCH SPORTING.803.3 ETHERNET, 80230FAST ETHERNET OR 8023ab GB ETHERNET CATS ETHERNT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CABLE	
5	DPK110962		9150705129215 / LUB-OIL-SAE 20W-50 API SL (Packing 04 liters & 20 LTRS))	MT-VEHICALES FOR PETROL ENGINE	500 / LITER			PK	CALTEX PAKISTAN		TECHNICAL SPECIFICATION - DEFSTAN 01-005 ISSUE 20. VISCOSITY TOLERANCE LIMIT ATTACHED IN WIMS PROFILE. GENERAL SPECIFICATION - DEFSTAN 01-005 ISSUE 20. VISCOSITY TOLERANCE LIMIT ATTACHED IN WIMS PROFILE.	
6	DNF113945	RP200-12	9999735179016 / BATTERY 12V 200A/H (MAINTENCE FREE)	Diesel Generator cummince	8 / EACH/NUMBER	RP200-12		ROCKT PREMIUM BATTERY.KOREA.WWW.gbattery.com	ROCKT PREMIUM BATTERY .KOREA	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
7	DNF108823	HDMI 1 x 4	5840705208583 / HDMI SPLITTER 4 PORT WITH POWER SUPPLY	CCTV System	1 / EACH/NUMBER	HDMI 1 x 4	NIL	M/s Network Solution, khizra arcade , Sarmad road Saddar , Karachi 74400 Tel : +9221-35621923-4, Fax : +9221-35621925, Email : info@ns.com.pk, URL : ww.ns.com.pk Ph no 03003003200	HDMI PAK	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Input: 01 x HDMI Output: 04 x HDMI Input supply: 5V DC No. of Ports: 4 One HDMI input signal split to two HDMI devices Supports 4Kx2K resolutions 2D HDMI 1.4 compliant Supports deep color 30/36bit. Supports up to 1080p/60HZ Supports xv-YCC. HDMI 1.4 support and 4000x2000. Digital audio formats: DTS-HD, Dolby-True-HD. LPCM7.1, AC3, DTS and DSD. GENERAL SPECIFICATION - Input: 01 x HDMI Output: 04 x HDMI Input supply: 5V DC No. of Ports: 4 One HDMI input signal split to two HDMI devices Supports 4Kx2K resolutions 2D HDMI 1.4 compliant Supports deep color 30/36bit. Supports up to 1080p/60HZ Supports xv-YCC. HDMI 1.4 support and 4000x2000. Digital audio formats: DTS-HD, Dolby-True-HD. LPCM7.1, AC3, DTS and DSD.	
8	DPC108611	ZIIE-15	6850705199638 / PROTECTIVE COATING ELECTRIC ,	PCB PROTECTOR SPRAY ESTONIA	15 / BOTTLE	150 ML	NA	NANO PROTECH OU, Uus Sadama 21, Tallinn 10120, Estonia Phone +3726683242	NANO PROTECH		TECHNICAL SPECIFICATION - Form: Liquid Colour: Green Ignition Point: 250 Degree C GENERAL SPECIFICATION - Form: Liquid Colour: Green Ignition Point: 250	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OEM NANO PROTECH, Packing = 150 ML bottle								Degree C	
9	DPK82131	3809441	9150735169761 / SYNTHETIC TRANSMISSION OIL SAE75W-90 (Packing 20 LITRE)	VOLVO PENTA ENGINES	70 / LITER	SAE75W-90		AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	VOLVO PENTA		TECHNICAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669 AB VOLVO PENTA PAKISTAN VPL PLOT 6 SECT 24 KORANGI INDUSTRIAL AREA KARACHI 2811+4669GENERAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669 AB VOLVO PENTA PAKISTAN VPL PLOT 6 SECT 24 KORANGI INDUSTRIAL AREA KARACHI 2811+4669	
10	DPC109139	Comp A= EPA001, Comp B = EPA740	8010997404333 / PAINT INTERGARD 400 DARK GREY (Comp A = 17 Ltrs + Comp B = 03 Ltrs)	HULL PRESERVATION OF F-22P FRIGATES	260 / LITER	NO DATA AVAILABLE		UK	INTERNATIONAL PAINTSLTD.P.O. BOX: 20980, ORIEL HOUSE 16 CANNAUGHT PLACE, LONDON, W22 2ZB, UNITED KINGDOM.		TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY:M/S SEA TRADE COMPANY, KARACHIGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY:M/S SEA TRADE COMPANY,KARACHI	
11	DNQ111555	464748 ABN.	4730014355106 / REPAIR KIT,PIPE, EMERGENCY	EMERGENCY CONTROL , PIPE REPAIR KIT.	4 / KIT			OEM: c IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST	INDUMAR PRODUCTS INC DBA	TDS/BROUCHER OR PIC MUST BE	TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DAMAGE CONTROL					STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	STOP ..	ENCLOSED WITH QUOTATION	STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM GENERAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	
12	DNM112064	21113522	5331145655130 / GASKET	MAIN ENGINE D6-370D-E SWEDEN	2 / EACH/NUMBER	D6-370D-E	NA	AB VOLVO PENTA SE 40508 GOTHENBERGE SWEDEN	VOLVO PENTA	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OEM & MAKE: VOLVO PENTAGENERAL SPECIFICATION - OEM & MAKE: VOLVO PENTA	
13	DNF113931	s310-24P4X / S4600-28P-SI /J9776A	7025145837789 / SWITCH UNIT 24 PORT WITH 4SFP & Accessories	Local Area Network (LAN) (Intranet)	2 / EACH/NUMBER	S4600-28P-SI /CSS326-24G-2SRM	0	1 AV DU CANADA LES ULIS LES ULIS	HEWLET T-PACKARD CENTRE COMPETENCE FRANCE	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - Switch unit 24 port with 4SFP & Accessories DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFPGENERAL SPECIFICATION - Switch unit 24 port with 4SFP & Accessories DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFP	
14	DPK111783	7101001002	9150735232473 / REFRIGERATION LUB OIL DHB-002 (19 Liters Packing)	HARD FORD AC COMPRESSOR	91 / LITER	DHB-002	17FA000G5737A	DUNHAM-BUSH INDUSTRIES SND.BHD. LOT 5755-6,KIDMAL INDUSTRIAL PARK,BUKIT ANGKAT,43000 KAJANG. SELANGOR PH:+603-89249000 FAX:+603-89395020	DUNHAM-BUSH INDUSTRIES		TECHNICAL SPECIFICATION - FLASH POINT (ASTM D-92,COC) 190C,MELTING POINT :(ASTM D-92,COC)-30 CGENERAL SPECIFICATION - FLASH POINT (ASTM D-92,COC)190C,MELTING POINT :(ASTM D-92,COC)-30 C	
15	DNF114063	DLS/RS-120	6135755194390 / DRY BATTERY SOLITE MARINE AND CARAVAN 12V 90AH	350 HP OBM ENGINE YAMAHA	2 / EACH/NUMBER	drs-120/DLS 120		SUNGWOO AUTOMOTIVE CO LTD KOREA	SUNGWOO AUTOMOTIVE CO LTD KOREA	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
16	DNF113939	DLS/RS-120	6135755194390 / DRY BATTERY SOLITE MARINE AND CARAVAN 12V 90AH	350 HP OBM ENGINE YAMAHA	2 / EACH/NUMBER	drs-120/DLS 120		SUNGWOO AUTOMOTIVE CO LTD KOREA	SUNGWOO AUTOMOTIVE CO LTD KOREA	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
17	DPK109302	828250	9150735175624 / GREASE	IPS 500	4 / EACH/NUMBER	IPS 500	IPS-F3940012979	VOLVO PENTA	VPL SWEDEN VOLVO PENTA		TECHNICAL SPECIFICATION - VOLVO PENTAGENERAL SPECIFICATION - VOLVO PENTA	
18	DNF108463	OTMU30134SL/ OMU25134SL-PX	6150795195722 / MASTERPLUG 25M ,4 SOCKET ELECTRICAL CABLE REEL.	DATA NODES	7 / EACH/NUMBER			masterplug-4.salewow.co.uk	masterplug-4.salewow.co.uk	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - 4x13 amp rated sockets with safety shutters. The cable reel itself has a also a safety thermal cut out to prevent overheating. 13 amps, 240 voltsGENERAL SPECIFICATION - 4x13 amp rated sockets with safety shutters. The cable reel itself has a also a safety thermal cut out to prevent overheating. 13 amps, 240 volts	
19	DPC111050	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
20	DPC108705	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
21	DPC106780	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	56.75 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
22	DPC111423	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	136 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
23	DPC108186	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
24	DNF112145	BOOM	1560705171053 / BOOM BARRIER	N/A	1 / EACH/NUMBER	NECOP		PAKISTAN	SHENZHEN ELECTRONICS	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - BOOM LENGTH 2500MM.DUTY CYCLE 1200 OPERATION/HOUR POWER SOURCE EITHER PNEUMATIC OPERATED OR ELECTRIC MOTOR OPERATED HOUSING SIZE 1000 MM X 300 MM X 300 MM STRUCTUAL STEEL POST POWDER COATED ALUMINNUM BOOM 8 FEET IN LENGTHGENERAL SPECIFICATION - BOOM LENGTH 2500MM.DUTY CYCLE 1200 OPERATION/HOUR POWER SOURCE EITHER PNEUMATIC OPERATED OR ELECTRIC MOTOR OPERATED HOUSING SIZE 1000 MM X 300 MM X 300 MM STRUCTUAL STEEL POST POWDER COATED ALUMINNUM BOOM 8 FEET IN LENGTH	
25	DNF113972		6070705229821 / 24 JOINT BOX	PSS SYSTEM	4 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL,PAKISTAN	LTE	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal typeGENERAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
26	DNF111643	TL-SG1024	7025290001813 / NETWORK SWITCH TP LINK (PROCESSOR, GATEWAY)	SCADA	1 / SET	TL-SG1024	NOT KNOWN	145 SOUTH STATE COLLEGE BLUD SOUT 400, BREA CA 92821 TP LINK RESEARCH AMERICA CROPORATION.	USA	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - 100 V TO 220 V AC MAX POWER 13.6 WM, OPERATING TEMPERATURE 0 TO 40 C,STORAGE TEMP. 40 TO 70 C. MAC ADDRESS TABLE 8K SWITCHING CAPABILITY 48 GBPS. ACKED FORWARDING RATE 35.7 MBPS GENERAL SPECIFICATION - 100 V TO 220 V AC MAX POWER 13.6 WM, OPERATING TEMPERATURE 0 TO 40 C, STORAGE TEMP. 40 TO 70 C. MAC ADDRESS TABLE 8K SWITCHING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CAPABILITY 48 GBPS. ACKED FORWARDING RATE 35.7 MBPS	
27	DNQ112149	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	23 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
28	DNJ106829	12915-93J60	4810765222489 / VALVE, EXHAUST	SUZUKI DF300AP 300 HP OBM	48 / EACH/NUMBER	Suzuki 300 HP 4 Stroke Engine/DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - No of valves per cylinder: 02 Material : Stainless Steel Dimensions /sizes: Exhaust valve diameter: 31.4 mm Valve guide to stem clearance (service limits): 0.09 mmGENERAL SPECIFICATION - No of valves per cylinder: 02 Material : Stainless Steel Dimensions /sizes: Exhaust valve diameter: 31.4 mm Valve guide to stem clearance (service limits): 0.09 mm	
29	DNJ108296	38890-98J00/38890-98J12	2815765221422 / ACTUATOR, SHIFT	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	300 HP Suzuki OBMs 4 stroke (DF300AP) /DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - System Integration: It is a Component of Suzuki Precision Control (SPC) system. It is operated when throttle is moved head/ astern and an electrical signal passes via SPC and electronic signal is processed through shift actuator and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											converted in to mechanical signal. Electrical Compliance: Operating voltage is a standard marine 12V DC system. Acceptance Criteria: Digital diagnostic communication check via the Suzuki Diagnostic system (SDS) tool without throwing shift actuator related fault codes. Shift engagements must be smooth and immediate across forward, Neutral and reverse position during functional water or tank testing. Dimensions: Approximately 9x6x5 inches (packaged size) Weight: Approximately 1.8 KgGENERAL SPECIFICATION - System Integration: It is a Component of Suzuki Precision Control (SPC) system. It is operated when throttle is moved head/ astern and an electrical signal passes via SPC and electronic signal is processed through shift actuator and converted in to mechanical signal. Electrical Compliance: Operating voltage is a standard marine 12V DC system. Acceptance Criteria: Digital diagnostic communication check via the Suzuki Diagnostic system (SDS) tool without throwing shift actuator related fault codes. Shift engagements must be smooth and immediate across forward, Neutral and reverse position during functional water or tank testing. Dimensions: Approximately 9x6x5 inches (packaged size) Weight: Approximately 1.8 Kg	
30	DNF108462	58000-600MAR	6350015887654 / SMOKE DETECTOR DISCOVERY MARINE OPTICAL	APOLLO FIRE ALARM SYSTEMS BM02-1/2 UK	6 / EACH/NUMBER	C		36 BROOKSIDE ROAD, CITY HAVANTCONTACT NO 023 9249 2412FAX NO 023 9249 2755SALES@APOLLO-FIRE.CO.UKFAX NO 023 9249 2755SALES@APOLLO-	APOLLO FIRE DETECTORS LTD, UK	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - SMOKE DETECTOR 58000-600MAR, FIRE DETECTION ALARM EQUIPMENTGENERAL SPECIFICATION - SMOKE DETECTOR 58000-600MAR, FIRE DETECTION ALARM EQUIPMENT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								FIRE.CO.UK3				
31	DNF108201	EQ 72K	6625725160636 / LPAC AMPERE METER 0 - 30A	HPAC AMPERE METER	1 / EACH/NUMBER			HPAC HATLAPA GERMANY	HATLAPA	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - Ampere meter range 0-30A Outer Square shape size 2.25" x 2.5" dimensions/ Inner round shape 2" dia (Picture sizes enclosed) HPAC HATLAPA GERMANYGENERAL SPECIFICATION - Ampere meter range 0-30A Outer Square shape size 2.25" x 2.5" dimensions/ Inner round shape 2" dia (Picture sizes enclosed) HPAC HATLAPA GERMANY	
32	DPC108518	COSMADEC-10 EPOXY PRIMER	5610705197497 / COSMADEC-10 EPOXY PRIMER (COMP A + COMP B) (Packing = KIT) (Color = Clear Transparent)	CHEMICAL	32 / KIT	-	-	M/S LABCO FINE CHEMICALS KARACHI TEL: 021-32562622 EMAIL: labcod200@yahoo.com	M/S LABCO FINE CHEMICALS	.	TECHNICAL SPECIFICATION - COSMADEC-10 EPOXY PRIMER COMPONENT A: BASE COMPONENT COMPONENT B: CURING AGENT GENERAL SPECIFICATION - COSMADEC-10 EPOXY PRIMER COMPONENT A: BASE COMPONENT COMPONENT B: CURING AGENT	
33	DNM111569	3970911	6685015301220 / TRANSMITTER, TEMPERATURE /SENSOR WATER	MARINE ENGINE CUMMINS(UTBOAT)	12 / EACH/NUMBER	QSB5.9-225BHP		23, BRENTFORD ROAD, KINGSHEATH, BIRMINGHAM B14 4DQ, ENGLAND	M/S MECHANICAL & ELECTRICAL (UK) LTD	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
34	DNF114055	N1537	6110705155260 / ENERGY SAVER 220V-240V ,11W. (screw type)	SELF,FOR DISTRIBUTION SYS.	16 / EACH/NUMBER			SOURCE OF AVALIBILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI.	PHILIPS CO LTD.	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - SOURCE OF AVALIBILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/1,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi 'GENERAL SPECIFICATION - SOURCE OF AVALIBILITY: PHILIPS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/I,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi '	
35	DNJ95382	NIL	4720705142506 / RUBBER LINE(D SHAPE) OUTER DIA 250MM INER DIA 50MM -	HULL	200 / FOOT	NO DATA AVAILABLE	-	PK	TAJ AUTO MOBILES ,30 JAMILA STREET, OPP SAEED MANZIL, OFF M A JINNAH ROAD, KARACHI . PH#2720920, 2724072	tds brocher or pics of item must be enclosed with quot -	TECHNICAL SPECIFICATION - OEM ADD/SOURCE OF AVAILIBILITY: TAJ AUTOMOBILES, 30 JAMILA STREET,OPP SAEED MANZIL,OFF M.A.JINNAH ROAD, KARACHI.PH#2720920, 2724072GENERAL SPECIFICATION - OEM ADD/SOURCE OF AVAILIBILITY: TAJ AUTOMOBILES,30 JAMILA STREET,OPP SAEED MANZIL,OFF M.A.JINNAH ROAD,KARACHI. PH#2720920,2724072	-
36	DPK104369	GREATWALL HM 100	9150SV5231607 / LUBRICATING OIL GREATWALL HM 100	STERN TUBE	2000 / LITER	GREATWALL HM 100		SINOPEC CO,CHINA	CHEVRON MARINE	.	TECHNICAL SPECIFICATION - LUBRICATING OIL GREATWALL HM 100 technical spec atteched as documentGENERAL SPECIFICATION - LUBRICATING OIL GREATWALL HM 100 technical spec atteched as document	
37	DPC112376	-	0474500001889 / CLEANING POWDER, 1 CWT.DRUM (BR 320 D CLASS GROUP 0474 PG 2	BR320D REVISED 1965 CLASS GROUP 0474 PG2	1158.8 / KILOGRAMME					.	TECHNICAL SPECIFICATION - a. Type Cleaning Powder b. Age Group Any Age c. Brand Cesco Solutions d. Item weight 5 pounds or dependent upon market availability e. Packing material Woven Bag carton GENERAL SPECIFICATION - a. Type Cleaning Powder b. Age Group Any Age c. Brand Cesco Solutions d. Item weight 5 pounds or dependent upon market availability e. Packing	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO		Availability	Tender Remarks	TECH / GEN SPECS	Dimension
												material Woven Bag carton	
38	DPC112380	NO DATA AVAILABLE	0474500007028 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		216.5 / BAG							TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0	
39	DPK111600	0474-7021 (0475-99-224-2137)	0474502242137 / TALLOW WHITE (GREASE) (200 KG DRUM)		200 / KILOGRAMME							TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
40	DPC110486		0473502247624 / LIQUID AMMONIA (33% AMMONIA 67% WATER)		9 / BOTTLE							TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DPC110473	NO. NS/C01/GEN/566 DT 210902	044250942912 0 / PAINT OIL FINISHING G. O.S.B. (GREEN)	FINISHING	513 / KILOGRAMME							TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DPC109515	106 OF BS381-C OF 1996	044250442006 1 / PAINT VEHICLE CELLULOSE (ROYAL NAVY BLUE)	VEHICLES, DECORATIVE FINISHING	40 / LITER							TECHNICAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996. GENERAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.	
43	DPC111272		044250442006 4 / PAINT WEATHER WORK (LIGHT GREY)NHQ	WEATHER WORK	40 / KILOGRAMME							TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LTR NS/G/1303/C DT 270199									
44	DPC107 087		044250442006 4 / PAINT WEATHER WORK (LIGHT GREY)NHQ LTR NS/G/1303/C DT 270199	WEATHER WORK	841 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DPC109 524		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		132 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
46	SPC1094 64		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		416 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DPC111 243		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DPC112 246		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		388 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DPC109 514		044250442004 1 / PAINT ENAMEL (WHITE), Brushing, Flash Point 32C(Min),	3 INCH ROCK LAUNCH	823 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-59/1 OF 1976 Stage inspection prescribed 04 ltr tin Flash point: 32 C Type: ALKYEDGENERAL SPECIFICATION - DEFSTAN 80-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ALKYED Type (04 LTR TIN)								59/1 OF 1976 Stage inspection prescribed 04 ltr tin Flash point: 32 C Type: ALKYED	
50	DPC109 504	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		20 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL.n, n- diethyi-meta -toluamide (deet) GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL.n, n- diethyi-meta -toluamide (deet)	
51	DNQ112 152	FRP/E3S0 4	035099571316 9 / ROPE FIBROUS.	DIVING PANNEL	26 / COIL					TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
52	DNQ112 151	NO DATA AVAILABL E	034059923624 3 / BAG CANVAS TOOL SATCHEL W/WOODEN		12 / EACH/N UMBER					TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5							QUOTATION		
53	DPC113877	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		817.2 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
54	DPC113314	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		908 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUFACTURER	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
55	DPC113204	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		908 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
56	DPC109505	SUPERSEDED BY DGS 1035	0442502202020 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	13 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribedGENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
57	DNM111513	NO DATA AVAILABLE	1325723250003 / WIDIA DIAMOND CUTTING TIP TOOL C-25MM		5 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSE	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			AT DIN 4966							D WITH QUOTATION		
58	DNM109315		1325794390033 / BIT TOOL STANDARD SIZE 5/8"X 8" (SQUARE) HSS		15 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DPC111306		1365997456895 / LIQUID FOR FOGGING		2 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DPC110548		0474500740012 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)		20 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DPC100489		0474502242463 / SOAP SCRUBBING		80 / KILOGRAMME					.	TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose.	
62	DPC110487	NO DATA AVAILABLE	0473500730033 / DISTILLED WATER (10 ltr packing)		50 / GALLON					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
63	DNF109948	MA3000C-48/BL820E	4440795061524 / DEHUMIDIFIER PORTABLE	(YSD) GENERAL USE	20 / EACH/NUMBER	PREM-I-AIR ELITE EH1418 XTREEM				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - IP Rating: IP 21 or above Voltage RATING: 110/220 V 50/60 Hz Power Rating: 470 Watts Over-current PROTECTION: Should be installed with circuit breaker/ fuse protection against over-current and short-circuit Grounding/ Earthing: Must comply with Unit's earthing system Cable/ Plug Design: Special electrical cable with fol properties: ¿ Extra flexible ¿ Tough outer covering Flame retardant with 3 Pin Plug Material Body: Special Plastic/ Composite with Fire Retardant Additives Refrigerant: R-22 Water Tank	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Capacity: 6 Liters Weight: 21 Kg Size: 455 mm x 350 mm x 603mm Dehumidifying Capacity: 28-35 Ltrs per day D/fying capc(Ltrs):28-35 per day Power input (Watt): 510 D/fying: 4.8 Refrigrent: R22 W/tank cap (Ltr): 06 Rated power:470W Rated current: 4.1A Opertaing Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600WGENERAL SPECIFICATION - IP Rating: IP 21 or above Voltage RATING: 110/220 V 50/60 Hz Power Rating: 470 Watts Over-current PROTECTION: Should be installed with circuit breaker/ fuse protection against over-current and short-circuit Grounding/ Earthing: Must comply with Unit's earthing system Cable/ Plug Design: Special electrical cable with fol properties: ¿ Extra flexible ¿ Tough outer covering Flame retardant with 3 Pin Plug Material Body: Special Plastic/ Composite with Fire Retardant Additives Refrigerant: R-22 Water Tank Capacity: 6 Liters Weight: 21 Kg Size: 455 mm x 350 mm x 603mm Dehumidifying Capacity: 28-35 Ltrs per day D/fying capc(Ltrs):28-35 per day Power input (Watt): 510 D/fying: 4.8 Refrigrent: R22 W/tank cap (Ltr): 06 Rated power:470W Rated current: 4.1A Opertaing Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600W	
64	DNQ112914	PN SPECS:	4210701003277 / FIRE EXT	FIRE FIGHTING	4 / EACH/N					TDS/BROUCHER OR	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		11-006	STORED PRESSURE(D.C.P)02 KGS S/STEEL D/DRAWN BODY	EQUIPMENT	UMBER					PIC MUST BE ENCLOSED WITH QUOTATION	SPECIFICATION - NO DATA AVAILABLE	
65	DNQ112168	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	8 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
66	DNQ112004	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	12 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
67	DNF109380	A-2060/P2240/VP-1240A	5835765013357 / Amplifier 30W/ 60W/ 120W/ 240W TOA JAPAN	P.A SYSTEM.	1 / EACH/NUMBER	A-2060/P2240				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - General Spec: RATED OUTPUT: 30W/ 60W/ 120W/ 240W, BASE AND TREBLE CONTROL POWER CONSUMPTION: 72W/150W/4A, MIC INPUT: 3 ELECTRONICALLY BALANCED AUX INPUT: 2 OUTPUT: PHANTOM POWER FOR MIC 1 AC & DC OPERATIONGENERAL SPECIFICATION - General Spec: RATED OUTPUT: 30W/ 60W/ 120W/ 240W, BASE AND TREBLE CONTROL POWER CONSUMPTION: 72W/150W/4A, MIC INPUT: 3 ELECTRONICALLY BALANCED AUX INPUT: 2 OUTPUT: PHANTOM POWER FOR MIC 1 AC & DC OPERATION	
68	DPK111664	S-758/MIL-PRF-63460E/NYCOLUBE 127	9150010536688 / CLEANER, LUBRICANT AND	USE FOR DIESEL ENGINE/12.7 MM GUN, MPAC,MRTPS	4 / GALLON						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PRESERVATIVE WEAPON OIL									
69	DPK87569	RIMULA R3+30	9150705052441 / SHELL RIMULA R3+30 HIGH PERFORMANCE DIESEL OIL	DIESEL ENGINES (TRANSPORT)	209 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DPK111782	90790-BS455	9150218770478 / OIL SAE 10W40 API SJ for YAMALUBE 4 STROKE MOTOR (01 Liter Packing)	RADAR-DA08	160 / LITER						TECHNICAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g: 6.9 D4739,mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attachedGENERAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g:6.9 D4739, mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached	
71	DPK111759	90790-BS455	9150218770478 / OIL SAE 10W40 API SJ for YAMALUBE 4 STROKE MOTOR (01 Liter Packing)	RADAR-DA08	179 / LITER						TECHNICAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g: 6.9 D4739,mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attachedGENERAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g:6.9 D4739, mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached	
72	DPK108328	90790-BS802	9150705102424 / GEAR OIL (750CC X 1) FOR OBM ENGINE (GL4 OUTBOARD GEAR OIL SAE 90) OEM = YAMALUBE	OBM ENGINE, GEAR,MOBILE ASHARI PVTLTD.KAR	480 / TUBE						TECHNICAL SPECIFICATION - 750 ml Tube PackingGENERAL SPECIFICATION - 750 ml Tube Packing	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
73	DPK111075	1N70015/ NUTO H 32	9150795102743 / OIL NUTO H 32 Elevators skirt shift (MOBIL NUTO tm H 32) 20 liter Drum)	HOVERCRAFT ,GRIFFON HOVERCRAFT LTD,UK	125 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DPC111363	B71003, B71046 OR ACCELRATOR G (POLYACC P-A)	6810731001000 / COBALT BASED ACCELERATOR/ CRYSTIC ACCELRATOR G/ POLYACC P-A/ LLOYD APPROVED EQUIVALENT PRODUCT		18 / KILOGRAMME						TECHNICAL SPECIFICATION - Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 "C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 "C 12 Months (Min) E. pACKING: 15 OR 25 KG GENERAL SPECIFICATION - Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 "C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 "C 12 Months (Min) E. pACKING: 15 OR 25 KG	
75	DNF113930	ep-1000t/blazer vista 1000	7035705059927 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	1 / EACH/NUMBER	BLAZER VISTA 1000/Aurora				TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V ACGENERAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V AC	
76	DNF114050	NC216A	5925745123915 / MINIATURE CIRCUIT BREAKER 220V 2POLE 16AMPS	A/C SYSTEM	4 / EACH/NUMBER					TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DNF1140	CLKB-	613577511875	MARINE	2 /	LONG,				TDS/BROC	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	57	131/MD6.200.100.B/LP-12-200	4 / MARINE BATTERIES 12 V 200AH	STARTER	EACH/NUMBER	LEOCH, MUTLU				HER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	S&A, DEFENCE TRADERS TOOBA APARTMENT ,KARACHI CEL:.0300-2811770 OEM,MUTLU TURKEY, GENERAL SPECIFICATION - S&A, DEFENCE TRADERS TOOBA APARTMENT ,KARACHI CEL:.0300-2811770 OEM,MUTLU TURKEY,	
78	DPK110108	DCSEA220AGRADE 80W90T20L	9150144025416 / LUBRICATION OF CRANE & WINCH 80W-90 (TRANS AXLE 7 80W-90) 20 Liters Packing OEM = M/s TOTAL		60 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DPC109133	KUA752/ KUA759	8010785265948 / intergard 7500 aluminium		300 / LITER	INTERGARD7500 ALUMINIUM					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
80	DNF113952		7025705249038 / LED TV 50 INCH		3 / EACH/NUMBER					TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
81	DNO108473	ASTM D-120-87	8415011589452 / GLOVES, ELECTRICAL WORKERS'		2 / EACH/NUMBER	ASTM D-120-87				TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - ¿ Class: 0 ¿ Thickness: 0.75MM – 1.52 MM ¿ Testing: Half yearly Dimension: 280MM - 360MM Size: 7-12 ¿ Standard: ASTM D120GENERAL SPECIFICATION - ¿ Class: 0 ¿ Thickness: 0.75MM – 1.52MM ¿ Testing: Half yearly Dimension: 280MM - 360MM Size: 7-12 ¿ Standard: ASTM D120	
82	DNF114065	WP7-12 / GP-1272-F2	6135016089403 / SEALED LEAD BATTERY 12V 7.2AH (Mainyenance		39 / EACH/NUMBER	CSB GP-1272-FF 7.2 AH				TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSE	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Free)							D WITH QUOT		
83	DNF113933	DGS-1510-28X	5930705246333 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT)		8 / EACH/NUMBER	dgs-1510-28x,DEM-310GT,				TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT) cpu speed 400mhz system d ram 256mb flASH MEMORY 32MB SWITCHING CAPACITY 128GBPS JAMBOO FRAME SIZEGENERAL SPECIFICATION - D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT) cpu speed 400mhz system d ram 256mb flASH MEMORY 32MB SWITCHING CAPACITY 128GBPS JAMBOO FRAME SIZE	
84	DNQ112917		1290705293027 / FIRE STAND for fire BUCKET AND FIRE EXTINGUISHERs (LOCAL MADE)		2 / EACH/NUMBER	nil				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - fire stand fixed buckets and fire extinguishersGENERAL SPECIFICATION - fire stand fixed buckets and fire extinguishers	
85	DPK107881	H 100	9150705237689 / MOBIL NUTO H 100		100 / LITER	MOBIL H SERIES					TECHNICAL SPECIFICATION - MOBIL NUTO H 100 HYDRAULIC OIL FOR STERN TUBE 208 Ltr DrumGENERAL SPECIFICATION - MOBIL NUTO H 100 HYDRAULIC OIL FOR STERN TUBE 208 Ltr Drum	
86	DNF110024	ha-10si	5999705246088 / ir beam (RECEIVER AND TRANSMITTER)		2 / PAIR	HA-10SI				TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - NO. OF BEAMS: 2 Beams Detection Mode: 2 beam blocked simultaneous Optical Source: Infrared digital pulse beam Respond speed: 50-700 m sec Power Supply: DC 10.5 24 V Optical axis adjustment (H): 180 Deg (+-90 Deg) Optical axis adjustment (V): 20 Deg (+- 10 Deg) Material: ABS Resin	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Operational Humidity & Temperature : -25 C to -55 C Dimensions /sizes: Length: 171 mm Width: 77 mmGENERAL SPECIFICATION - NO. OF BEAMS: 2 Beams Detection Mode: 2 beam blocked simultaneous Optical Source: Infrared digital pulse beam Respond speed: 50-700 m sec Power Supply: DC 10.5 24 V Optical axis adjustment (H): 180 Deg (+-90 Deg) Optical axis adjustment (V): 20 Deg (+- 10 Deg) Material: ABS Resin Operational Humidity & Temperature : -25 C to -55 C Dimensions /sizes: Length: 171 mm Width: 77 mm	
87	DNF114058	OSAKA XPRESS SERIES 100W	6230765280845 / OSAKA FLOOD LIGHT 100W		4 / EACH/NUMBER	OSAKA 100W				TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - OSAKA FLOODLIGHTGENERAL SPECIFICATION - OSAKA FLOODLIGHT	
88	DNF113932	ds2de4425iwde	6710785235876 / 4inch 4mp 25x powered by dark fighter ir network speed dome camera hikvision		10 / EACH/NUMBER	ds-2de4425iw-de				TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOT	TECHNICAL SPECIFICATION - 4inch 4mp 25x powered by dark fighter ir network speed dome camera hikvision ds-2de4425iw-deGENERAL SPECIFICATION - 4inch 4mp 25x powered by dark fighter ir network speed dome camera hikvision ds-2de4425iw-de	
89	DNM113955	1622369480	4810735215683 / BLOW-OFF VALVE	MEDICAL OXYGEN GENERATOR O-500 ECO	4 / EACH/NUMBER	GA45+	2011118	ATLAS COPCO AIR POWER N.V, B-2610 WILRIJK ? BELGIUM. TEL: +32-3-87021 11 FAX: +32-3-8702730 WWW.atlascopco.be	ATLAS COPCO	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MAKE: ATLAS COPCO , BLOW OFF VALVE FITTED WITH UNLOADER ASSEMBLY FOR AUTO WORK oem: SWEEDEN supplier : Plot-8C, Phase -2 Commercial Area Defense Housing Authority Karachi. Contact: 021-345500451GENERAL SPECIFICATION - MAKE: ATLAS COPCO , BLOW OFF VALVE FITTED WITH UNLOADER ASSEMBLY FOR AUTO WORK oem: SWEEDEN supplier : Plot-8C, Phase -2 Commercial Area Defense	

S. No	LPR No	PART NO	NSN / Descfiption	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Housing Authority Karachi. Contact: 021-345500451	
90	DNM113959	FS100/LFS 100	2940735215687 / FILTER 1 MICRON	MEDICAL OXYGEN GENERATOR O-500 ECO	3 / EACH/NUMBER	LF S 100	2011118	OXYMATE A/S, FASANVEJ 18-20, DK-3200, HELSINGE DENMARK. TEL: +45 48797811 FAX: +45 48797813 E MAIL: service@oxymat.dk www.oxymat.dt	OXYMAT A/S	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. FILTER 1 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE. GENERAL SPECIFICATION - 1. FILTER 1 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE.	
91	DNH113958	FX100/LFX 100	2940735215688 / FILTER 0.01 MICRON	MEDICAL OXYGEN GENERATOR	3 / EACH/NUMBER	LF X 100	2011118	OXYMATE A/S, FASANVEJ 18-20, DK-3200, HELSINGE DENMARK. TEL: +45 48797811 FAX: +45 48797813 E MAIL: service@oxymat.dk www.oxymat.dt	OXYMAT A/S	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. FILTER 0.01 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE. GENERAL SPECIFICATION - 1. FILTER 0.01 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE.	
92	DNM113956	Etanorm g 50-250 & 50-160	4320705349831 / condenstae pump with Motor of lg 60 ton plant etanorm Etn 050-032-160		2 / EACH/NUMBER	etanorm g 50-250				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CONDENSATE PUMP INSTALLED AT MIN OT AC PLANT OF PNS SHIFA. SINGLE STAGE PUMP , HORIZANTAL VOLUTE CASING PUMP 3 PHASE ELECTRIC MOTOR DRIVEN TYPE ETANORM TYPE SERIESGENERAL SPECIFICATION - CONDENSATE PUMP INSTALLED AT MIN OT AC PLANT OF PNS SHIFA. SINGLE STAGE PUMP , HORIZANTAL VOLUTE CASING PUMP 3 PHASE ELECTRIC MOTOR DRIVEN TYPE ETANORM TYPE SERIES	
93	DNM109138	21985	4130731002014 / CHARGING LINE PORTABLE A/C PLANTS USA	PORTABLE AIR CONDITIONER PLANT (USA)	3 / EACH/NUMBER	YELLOW JACKET PLUS II				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Internal dia 0.250" inch, length 36" inches both ends fitted with manually operateable flair nuts. Said item is used for gas charging of Air conditioning plants. Said charging line is made up of flexible rubber pipes both ends fitted with flair nuts.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Picture of the item is enclosed. a. Refrigerant charging hose for R-22 and R-410, b. Nylon Hose length 6" /150 cm, 800 psi/ 55 Bar max.,Flare size ¼GENERAL SPECIFICATION - Internal dia 0.250" inch, length 36" inches both ends fitted with manually operateable flair nuts. Said item is used for gas charging of Air conditioning plants. Said charging line is made up of flexible rubber pipes both ends fitted with flair nuts. Picture of the item is enclosed. a. Refrigerant charging hose for R-22 and R-410, b. Nylon Hose length 6" /150 cm, 800 psi/ 55 Bar max.,Flare size ¼	
94	DNM112226	920-007925	7025735347601 / SET, KEYBOARD, MOUSE		1 / EACH/NUMBER	NA				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
95	DNH114040		2340705059829 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SOHRAB/SHAHEEN/SUMAC DELUXE		5 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - SIZE: 22 INCHESGENERAL SPECIFICATION - SIZE: 22 INCHES	