

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 10-11-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNS111981	FIG.100-PN10 DN25	4820FT100477 1 / Globe Valve (Shut-Off Straight Type) PN10 DN25	Phalanx Cooling System	18 / EACH/N UMBER	PNFT- 52400- 172503	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
2	DNF110541	HJSZ3	594570526968 9 / ELECTRONIC TIME RELAY		3 / EACH/N UMBER	NA				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
3	DNN98404	STR-HS-10KRH	590550531271 2 / 10 KV A Double Conversion Online UPS		1 / EACH/N UMBER	N/A				dimension required height:9cm width:48cm depth: 40cm TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE	<u>TECHNICAL SPECIFICATION - 10</u> <u>KV A</u> <u>GENERAL SPECIFICATION -</u> 10 KV A	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION		
4	DNF109625	SC-630M	5965765101887 / HORN SPEAKER, 30WATT WITH MATCHING TRANSFORMER & VOL. CONTRPL	SRE SYSTEM, PNS NASR	10 / EACH/NUMBER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
5	DNF112052	SD700/RH520B/RH520A	6630705179660 / HUMIDITY & TEMPERATURE CHART RECORDER WITH UNIVERSAL ADAPTER	Test Equip	1 / EACH/NUMBER	SD700/RH520		M/s MAKKEYS, B-26 Block 15 Gulshan -e-Iqbal Karachi, e-mail Karachi@makkeys.com	www.extech.com	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Complete with built in stand detachable probe with 3 ft (1m) cable, RS 232 cable, RS-232 to USB adapter, Lab view -based PC software, 100-240VAC 50/60 Hz adapter and 3AA Batteries GENERAL SPECIFICATION - Complete with built in stand detachable probe with 3 ft (1m) cable, RS 232 cable, RS-232 to USB adapter, Lab view -based PC software, 100-240VAC 50/60 Hz adapter and 3AA Batteries	
6	DNO106532	LS1526S	5331775266023 / O-Ring		16 / EACH/NUMBER	3516E				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - O-Ring GENERAL SPECIFICATION - O-Ring	
7	DNF111642	DH-IPC-B1E49-A-IL / DH-IPC-HFW1431SP-S4 / DH-IPC-HFW5431EP-Z5E	6710785224610 / 4MP WDR IR BULLET NETWORK CAMERA	PTZ CAMERA ECO SAVVY 3.0 SERIES CHINA	26 / EACH/NUMBER	3.0 SERIES/ dh-ipc-hfw1431s p-s4		NO 1189 BINAN ROAD BINJIANG DIST. HANGZHOU CHINA 310053	DAHUA TECHNOLOGIES	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - IMAGE SENSOR 1/3 INCHES 4MP CMOS FOV-H 106 DEGREEE ~ 31 DEGREE MAX. IR DISTANCE 50METER VIDEO COMPRESSION H.265+/H.265/H.264+/H.264 Make: dahua GENERAL SPECIFICATION - IMAGE SENSOR 1/3 INCHES 4MP CMOS FOV-H 106 DEGREEE ~ 31	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										N	DEGREE MAX. IR DISTANCE 50METER VIDEO COMPRESSION H.265+/H.265/H.264+/H.264 Make: dahua	
8	DNF111725	ML-1102S-A & B(2 RJ-45 PORTS)/ 4V1D	6030705215937 / FIBER OPTIC MEDIA CONVERTER FOR IP CAMERAS	CCTV SYSTEM 4V1D PAKISTAN	48 / PAIR	ml-1102s-a & ml-1102s-b		Al-Sa'ee business Solutions Suit 30, 3rd Floor, Crown Centre Plot SB-1, Opp Balt-ul-Mukarram Masjid, Gulshan-e-Iqbal Karachi Tel & Fax (9221)3483-7233	Al-Sa'ee/Pro Secure	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission. <u>GENERAL SPECIFICATION - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission.</u>	
9	DNF111592	6-FMX-100B/cmbt -g-12-150/ DLS-120	6140785221249 / MAINTENANCE FREE BATTERIES 12 VOLT 90-100 AH	Microwave	13 / EACH/NUMBER	Crown Micro		WAREHOUSE NO.CA02, Near R/A08, Jebel Ali Freezone, Dubai, UAE Phone(INTERNATIONAL) +971-4-883-9373 AX +971-4-883 9756	CROWN MICRO AGM CHINA	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MAINTENANCE FREE BATTERIES 12 VOLT 90-100 AH <u>GENERAL SPECIFICATION - MAINTENANCE FREE BATTERIES 12 VOLT 90-100 AH</u>	
10	DNF108174	GPTS 20 KVA/ VANGUARD-30 KVA	6110795222843 / 3 PHASE SERVO STABILIZER 20 KVA/30 KVA	TRANSFORMER	1 / EACH/NUMBER	GSPT-20 KVA/30 KVA, MADE IN ENGLAND	GSPT -20000 VA, MADE IN ENGLAND	GREEN POWER SYSTEM UK LTD	BPL ENTERPRISES	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - INPUT 150-250 VAC PHASE VOLTAGE, 277-430 VAC, WIRE VOLTAGE 220V/ 380 V FREQUENCY 50 HZ/ 60 HZ PHASE 3 PHASE <u>GENERAL SPECIFICATION - INPUT 150-250 VAC PHASE VOLTAGE, 277-430 VAC, WIRE VOLTAGE 220V/ 380 V FREQUENCY 50 HZ/ 60 HZ PHASE 3 PHASE</u>	
11	DNS111530	27 513 001 GROHE/27 51200F/M RN-102-051/ CODE257, CODE 269	4510FT1008599 / Muslim Shower	MRN Shower Wet Unit (with Wall Model Vacuum Toilet)	5 / EACH/NUMBER	MERCAN, MRN Shower Wet Unit	0	DERI ORGANIZE SANAYI BOLGESI 7. YOL F 7 PARSEL TUZLA	MERCAN GEMICILIK SAN. VE TIC. A.S.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED	TECHNICAL SPECIFICATION - null <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
12	DNS110678	27 513 001 GROHE/27 51200F/M RN-102- 051/ CODE257, CODE 269	4510FT100859 9 / Muslim Shower	MRN Shower Wet Unit (with Wall Model Vacuum Toilet)	7 / EACH/N UMBER	MERCAN, MRN Shower Wet Unit	0	DERI ORGANIZE SANAYI BO'LGESI 7. YOL F 7 PARSEL TUZLA	MERCAN GEMICILI K SAN. VE TIC. A.S.	D WITH QUOTATIO N TDS/BROC HURE OR PHOTOGR APH OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
13	DNF111584	DLS/RS -120	613575519439 0 / DRY BATTERY SOLITE MARINE AND CARAVAN 12V 90AH	350 HP OBM ENGINE YAMAHA	2 / EACH/N UMBER	drs- 120/DLS 120		SUNGWOO AUTOMOTIVE CO LTD KOREA	SUNGWOO AUTOMOTIVE CO LTD KOREA	TDS/BROC HURE OR PHOTOGR APH OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
14	DNF111955	SUA 10001 APC	613072514039 3 / APC UPS 1KVA 230VAC WITH 2X BATTERIES 12V 12AH	BERQ PROJECT	4 / EACH/N UMBER	APC BRAND		GE	ROHDE & SCHWARZ INTL GMBH GERMANY	TDS/BROC HURE OR PHOTOGR APH OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - ONE PC average voltage consumption in 250 Watts Battery backup time of said UPS is: Backup Time = $AH * 12V * N * \text{Efficiency of Battery} / \text{Load in watts}$ Where: AH= Ampere hour Capacity of battery (12AH) N= Number of 12 batteries attached (2) Efficiency of Battery = $0.8 \text{ } 12AH * 12V * 2 * 0.8 / 250 = 0.9216$ hours Approx. : 30 minutes 230VAC WITH@X BATTERIED 12V 12AH GENERAL SPECIFICATION - ONE PC average voltage consumption in 250 Watts Battery backup time of said UPS is: Backup Time = $AH * 12V * N * \text{Efficiency of Battery} / \text{Load in watts}$ Where: AH= Ampere hour Capacity of battery (12AH) N= Number of 12 batteries attached (2) Efficiency of Battery = $0.8 \text{ } 12AH * 12V * 2 * 0.8 / 250 = 0.9216$ hours Approx. : 30 minutes 230VAC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WITH@X BATTERIED 12V 12AHM	
15	DNF112049	SUA 10001 APC	613072514039 3 / APC UPS 1KVA 230VAC WITH 2X BATTERIES 12V 12AH	BERQ PROJECT	5 / EACH/N UMBER	APC BRAND		GE		ROHDE & SCHWARZ INTL GMBH GERMAN Y	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ONE PC average voltage consumption in 250 Watts Battery backup time of said UPS is: Backup Time = AH *12V*N*Efficiency of Battery / Load in watts Where: AH= Ampere hour Capacity of battery (12AH) N= Number of 12 batteries attached (2) Efficiency of Battery = 0.8 12AH*12v*2*0.8/250 = 0.9216 hours Approx. : 30 minutes 230VAC WITH@X BATTERIED 12V 12AHM GENERAL SPECIFICATION _ONE PC average voltage consumption in 250 Watts Battery backup time of said UPS is: Backup Time = AH *12V*N*Efficiency of Battery / Load in watts Where: AH= Ampere hour Capacity of battery (12AH) N= Number of 12 batteries attached (2) Efficiency of Battery = 0.8 12AH*12v*2*0.8/250 = 0.9216 hours Approx. : 30 minutes 230VAC WITH@X BATTERIED 12V 12AHM
16	DNF111844	ST4000NM0053/ST4000VX000	702578520784 9 / 4TB SURVEILLANCE HARD DISK-SATA FOR NVR	CCTV System ST4000VX000 CHINA	5 / EACH/N UMBER	ST4000VX000	NA	Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888		CHINA	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32 GENERAL SPECIFICATION - Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32
17	DNF111729	DH-SD6CE445GB-HNR/DH-SD6CE445XA-HNR/DH-SD5A445XA-HNR/DH-	582078520788 6 / NETWORK PTZ CAMERA 4MP WITH ACCESSORIES	CCTV System DH-SD6AL240-HNI CHINA	4 / EACH/N UMBER	DH-SD6AL240-HNI	NA	No. 1199 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86-571-87688883		M/s Dahua	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Image Sensor 1/2.8" CMOS Effective Pixels 1920(H) x 1080(V), 2 Megapixels RAM/ROM 512M/32M Scanning System Progressive Electronic Shutter Speed 1/1s~1/30, 000s S/N Ratio More than 56dB IR Distance Distance up to 500m (1640ft) IR On/Off Control Auto/Manual IR LEDs Laser module

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		SD6AL240-HNI									GENERAL SPECIFICATION - mage Sensor 1/2.8" CMOS Effective Pixels 1920(H) x 1080(V), 2 Megapixels RAM/ROM 512M/32M Scanning System Progressive Electronic Shutter Speed 1/1s-1/30,000s S/N Ratio More than 56dB IR Distance Distance up to 500m (1640ft) IR On/Off Control Auto/Manual IR LEDs Laser module	
18	DNJ107963	8M0057936/ 8M0204728	2920016505202 / SPARK PLUG	OEM ENGINE 150 XL 4S USA	14 / EACH/NUMBER	150 XL 4S	1B983809	MURCERY MARINE W6230 PIONEER ROAD FOND DU LAC WISCONSIN USA	MERCURY USA	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - store i.e dimensions/ sizes. Threaded Diameter: 14mm Thread Pitch: 1.25 mm Thread Reach: 19mm Hex Size: 16mm GENERAL SPECIFICATION - store i.e dimensions/ sizes. Threaded Diameter: 14mm Thread Pitch: 1.25 mm Thread Reach: 19mm Hex Size: 16mm	
19	DNF111538	2080/G	5963755207325 / SMART LOOP MODULE 2080/G	FIRE ALARM 2080/G ITALY	1 / EACH/NUMBER	2080/G	NA	INIM ELECTRONICS ITALY TEL +39 0735705007 FAX +390735704910	INIM ELECTRONICS	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OPERATING VOLTAGE: 230V AC -15% +10% 50/60 HZ MAX INTERNAL POWER CURRENT: 4A BATTERY SPECIFICATIONS: 12V @7AH OR 12V @17AH OPERATING TEMPERATURE: DA -5 A +40C DIMENSION: 48CM X 47CM X 13.5 CM WEIGHT: 8 KG MAKE: ITALY GENERAL SPECIFICATION - OPERATING VOLTAGE: 230V AC -15% +10% 50/60 HZ MAX INTERNAL POWER CURRENT: 4A BATTERY SPECIFICATIONS: 12V @7AH OR 12V @17AH OPERATING TEMPERATURE: DA -5 A +40C DIMENSION: 48CM X 47CM X 13.5 CM WEIGHT: 8 KG MAKE: ITALY	
20	DNF111727	LAN1-24AE-PGTL-B	5998705229830 / ODF 24-PORT SWITCH (FOR CCTV) RACKMOUNT	PSS SYSTEM	1 / EACH/NUMBER	LAN1	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION		
21	DNF111742	ZA3000E	635070522032 3 / SMART WALK THROUGH GATE	SWTG	3 / EACH/NUMBER			DEFENCE SCIENCE AND TECHNOLOGY ORGANIZATION CHAKIALA CANTT RAWALPINDI	DESTO	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DIMENSIONS H: 2210MM W: 810MM D: 605MM OPERATING VOLTAGE AC 200-230V/DC 12V POWER CONSUMPTION 35 WATT WORK ENVIRONMENT -5c-50c NO OF ZONES 06 DISPLAY TYPE LCD GENERAL SPECIFICATION - DIMENSIONS H: 2210MM W: 810MM D: 605MM OPERATING VOLTAGE AC 200-230V/DC 12V POWER CONSUMPTION 35 WATT WORK ENVIRONMENT -5c-50c NO OF ZONES 06 DISPLAY TYPE LCD	
22	DNS111549	11994	533014569854 5 / GASKET	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	2 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60	AB Volvo Penta Sweden	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT) GENERAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)	
23	DNC107796	02232077/ DANFOS/ WBCL002 301/023z1 471	413074513314 9 / BI-FLOW FILTER/DRYER 1/2 FOR CHILLER-42 T060 MONO	A/C SYSTEM PNS KARRAR	3 / EACH/NUMBER	NO DATA AVAILABLE		FR	WEBASTO MARINE COMFORT FRANCE	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - .com: Danfoss source of availability: YONK-ONUJVG GENERAL SPECIFICATION - .com: Danfoss source of availability: YONK-ONUJVG	
24	DNF111597	CMS-118	599870521930 4 / POWER EXTENSION BOARD CAMELLION MODEL CMS-118	SM RACK	18 / EACH/NUMBER	CMS-118 (CAMELLION)	NA	Commercially Of The Shelf (COTS)/Local Market	COTS	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan GENERAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
QUOTATION												
25	DNJ103806	65770-93J02 / 65770-93J04 / 65770-93J13	294076522220 2 / PUMP, SQUEEZE	SUZUKI DF300AP 300 HP OBM	6 / EACH/NUMBER	300 HP Suzuki OBMs 4 stroke (DF300AP)	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - a. Specification / Technical data /Testing /Acceptance criteria: Nitrile rubber squeeze bulb with reinforced multilayered PVC fuel hose with brass one-way check valves. UV and fuel resistant outer coating B. Technical parameters of store i.e Dimensions /sizes and etc: Designed explicitly for Suzuki four stroke marine outboard engines including the 300 HP DF300AP and DF250AP models. Manufacture: Suzuki Motor Corporation Japan OEM: SUZUKI country of origin: JAPANGENERAL SPECIFICATION - a. Specification / Technical data /Testing /Acceptance criteria: Nitrile rubber squeeze bulb with reinforced multilayered PVC fuel hose with brass one-way check valves. UV and fuel resistant outer coating B. Technical parameters of store i.e Dimensions /sizes and etc: Designed explicitly for Suzuki four stroke marine outboard engines including the 300 HP DF300AP and DF250AP models. Manufacture: Suzuki Motor Corporation Japan OEM: SUZUKI country of origin: JAPAN	
26	DNJ107862	15643-93J00	294076522180 2 / FILTER, FUEL (L)	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
27	DNF111952	S-100-12/ YH-100-12 / P-0145000-A	613078516724 9 / POWER SUPPLY 12V6A 119-	FIXED PTZ IP CAMERA	4 / EACH/NUMBER	YH-100-12		M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District,	M/S CETC INTERNATIONAL	TDS/BROCHURE OR PHOTOGRAPH OF	TECHNICAL SPECIFICATION - M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			239V					Beijing, China 100120	CO CETC CHINA	ITEM MUST BE ENCLOSED WITH QUOTATION	China 100120 oem hi- tech security products nargis block ilama iqbal town lahore 03081517664 <u>GENERAL SPECIFICATION</u> - M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120 oem hi- tech security products nargis block ilama iqbal town lahore 03081517664	
28	DNF112075	CAT-6	7830705193850 / d link 24 AWG 4 pair CAT-6 s/ftp CABLE ROLL (305M / 1000ft)	DAWN NETWORK	13 / ROLL	D-LINK		M/S MICROTECH INC 184, CO-OPERATIVE MARKET SADDAR KARACHI	M/S MICROTECH INC	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - Cable Name: D-Link 24 AWG Cat 6 s/FTP Cable Roll (pic enclosed) Brand: D-Link (4 pair Foildd Twisted Pair (s/FTP) Cable) material: solid bare copper with 24 awg brand: d link (4 pair folded twisted pair (s/ftp) cable. shield: aluminum polyester foil jacket material: pvc ul 94v-0 <u>GENERAL SPECIFICATION</u> - Cable Name: D-Link 24 AWG Cat 6 s/FTP Cable Roll (pic enclosed) Brand: D-Link (4 pair Foildd Twisted Pair (s/FTP) Cable) material: solid bare copper with 24 awg brand: d link (4 pair folded twisted pair (s/ftp) cable. shield: aluminum polyester foil jacket material: pvc ul 94v-0	
29	DNC107803	21159044	9611735212776 / TRANSMISSION CABLE HARNESS IPS 350-600, 3 FEET 0.9 METERS	VOLVO PENTA ENGINE 370 HP	2 / EACH/NUMBER	D-6-370	A195788 (FPSVV-3526)	AB VOLVO PENTA. SE-40508. GOTE BORG SWEDEN	VOLVO PENTA SWEDEN	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - TRANSMISSION CABLE HARNESS IPS 350-600, 3 FEET 0.9 METERS <u>GENERAL SPECIFICATION</u> - TRANSMISSION CABLE HARNESS IPS 350-600, 3 FEET 0.9 METERS	
30	DNF109309		0584799965452 / LAMP FILAMENT CAP TYPE BC 115V 40W 60X105MM G. RED A SHAPE		25 / EACH/NUMBER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
31	DNF109307	AP9899, DEE10500	0584799952403 / LAMP FILAMENT CAP TYPE SBC 22V 30W 38X56MM CLEAR P SHAPE TCC		75 / EACH/NUMBER					QUOTATION TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
32	DNF111508	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIER, 300W, 220/240V SIZE: 350X452X275 MM	DEHUMIDIFIER RS	30 / EACH/NUMBER	MD231 (CROWN) /EH1504/ EH1418				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG GENERAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG	
33	DNF111442	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIER, 300W, 220/240V SIZE: 350X452X275 MM	DEHUMIDIFIER RS	25 / EACH/NUMBER	MD231 (CROWN) /EH1504/ EH1418				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG GENERAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											10.5 KG	
34	DNF112002	MD231 (CROWN) /EH1504 /EH1418	444079510254 4 / PREMI-AIR DEHUMIDIFIERS, 300W, 220/240V SIZE: 350X452X275 MM	DEHUMIDIFIERS	7 / EACH/NUMBER	MD231 (CROWN) /EH1504/ EH1418				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<p><u>TECHNICAL SPECIFICATION -</u> Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG</p> <p><u>GENERAL SPECIFICATION -</u> Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG</p>	
35	DNG110677	WD001114	513000226538 4 / DRILL MACHINE (BLACK & DECKER)		2 / EACH/NUMBER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<p><u>TECHNICAL SPECIFICATION -</u> OEM: FEDERAL SPECIFICATION PROMULGATED GENERAL SERVICES USA. MAKE MODEL IS USA.</p> <p><u>GENERAL SPECIFICATION -</u> OEM: FEDERAL SPECIFICATION PROMULGATED GENERAL SERVICES USA. MAKE MODEL IS USA.</p>	
36	DNF104062	FC-20	611076506327 5 / CONTACTOR MAGNETIC 440V 50HZ 3PH COILVOL220V 22A 68X64X82MM	A/C PLANT MOTOR NATIONAL (JAPAN)	1 / EACH/NUMBER	HIMC12				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<p><u>TECHNICAL SPECIFICATION - AC1 (Lth) Ampers 20 Rated Insulation Voltage V 750 Rated Operational Voltage V 690 Dimension W x D x H mm 66 x 86 x 90</u> Stage-1: Upon receiving the store item verify that any physical damage, brand, manufacturer, part/ model no, specification is exactly correct/ match against LPO. Stage-2: magnetic contactor can't be tested without system upon receipt, user will receive/ issue the item on DPL-15 and mount it onto the live system to verify operational performance.</p> <p><u>GENERAL SPECIFICATION - AC1 (Lth) Ampers 20 Rated Insulation</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Voltage V 750 Rated Operational Voltage V 690 Dimension W x D x H mm 86 x 86 x 90 Stage-1: Upon receiving the store item verify that any physical damage, brand, manufacturer, part/ model no, specification is exactly correct/ match against LPO. Stage-2: magnetic contactor can't be tested without system upon receipt, user will receive/ issue the item on DPL-15 and mount it onto the live system to verify operational performance.	
37	DNF111990	CW-770	5995715118130 / POWER CABLE 3 CORE FOR CCTV SYSTEM		550 / METER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DNF111589	CP12240E-X / NP24-12B	6140705052213 / BATTERY 12V 24/AH RECHARGABLE M/FREE NP24-12B 17.5 X16.5X12.5CM	MM211,BEWT, SIMULATOR, EW TRAINER	10 / EACH/NUMBER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
39	DNF111558	PM-120-(TOA JAPAN)	5965765116036 / PUSH TO TALK MIC 600 OHMS	COMMUNICATION FACILITY SYS	6 / EACH/NUMBER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
40	DNC105096	ELEC-2650 / IN 63047/	6230795110272 / SEARCH LIGHT HAND	GRIFFON HOVER CRAFT LTD	10 / EACH/NUMBER	GEEPAS®				TDS/BROCHURE OR PHOTOGRAPH	TECHNICAL SPECIFICATION - 1. Make/ Brand; GEEPAS ® 2. Model: GSL5706 - 30Watt GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Avallability	Tender Remarks	TECH / GEN SPECS	Dimension
		2850	HELD (24V DC&230 WATT)	UK						APH OF ITEM MUST BE ENCLOSED WITH QUOTATION	SPECIFICATION - 1. Make/ Brand: GEEPAS @ 2. Model: GSL5708 - 30Watt	
41	DNF112051	SURT10000XLI	5963715112878 / APC SMART-UPS RT 1000VA 230V (I/P=230V, O/P=230V)	UPS	6 / EACH/NUMBER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DNF111594	99-743-0489	6145998920042 / ELECTRICAL CABLE 2 CORE CABLE 2.5MM2	MS830MM GUN	1050 / METER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
43	DNF105582	CX-405 SONY	6710765085708 / VIDEO CAMERA RECORDER 8 HANDY CAM VIDEO 8		1 / EACH/NUMBER	CCDTR410E/TR420E/TR440E				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - a. 4K video capturing feature. b. Alongwith motion stabilizer equipment. c. Alongwith standard size stand for placing the video camera. d. At least 1 TB memory space. e. Alongwith long range lenses. f. Alongwith additional batteries and chargers. g. Night video capturing feature. h. Go Pro Mode feature (optional). GENERAL SPECIFICATION - a. 4K video capturing feature. b. Alongwith motion stabilizer equipment. c. Alongwith standard size stand for placing the video camera. d. At least 1 TB memory space. e. Alongwith long range lenses. f. Alongwith additional batteries and chargers. g.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Night video capturing feature. h. Go Pro Mode feature (optional).	
44	DNF111989	SMT3000I C/SURTD3000XLI/3000VA APC	6130715063823 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/NUMBER	MODEL ESP-808 (E) /SYSTEK PVT.				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
45	DNF111723	SRV10KL / ONL-10000 STAB/APC SURT10000XLIM/ EH-10000	4470705120759 / UPS 10KVA 220V,50HZ,1 PHASE) BACKUP TIME: 20-25 MINS LOAD: 10 KVA	SELF	1 / EACH/NUMBER	SRV10KL				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BACKUP TIME: 20-25 MINS LOAD: 10 KVA 110 - 300V AC 40 - 70 Hz/ 200 - 240 V AC 50 - 60 Hz (Adjustable) GENERAL SPECIFICATION - BACKUP TIME: 20-25 MINS LOAD: 10 KVA 110 - 300V AC 40 - 70 Hz/ 200 - 240 V AC 50 - 60 Hz (Adjustable)	
46	DNN109818	CYQJ2317-1B25E 20W	6240FP0990036 / Fluorescent ceiling lights (white) 20 WATT model Y220RR32	GENERAL USE LIGHT	700 / EACH/NUMBER	NO DATA AVAILABLE				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - zul Itr 11963303 dt 03-01-22 for specs is relevant, model: Y220RR32 GENERAL SPECIFICATION - zul Itr 11963303 dt 03-01-22 for specs is relevant, model: Y220RR32	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
47	DNF111587	DJW12-0	6130735310046 / BATTERY 12V 9AH		2 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
48	DNF111563		7025705249038 / LED TV 50 INCH		2 / EACH/NUMBER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
49	DNJ106486	17562-87L00	3110765310131 / BUSH, WATER TUBE UPPER		1 / EACH/NUMBER	N/A				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
50	DNZ111540	22894	4730705243378 / UNION DIA 1/2 INCH STAINLESS STEEL		30 / EACH/NUMBER	UNION				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - a. Standard: ASME A213 b. Material: SS 316 c. Specification: Straight Union 1/2 Inch d. Dimension Compatible with Tube Outer Dia 12.7 mm e. Working Pressure: 3000 Psi f. Fitting Type Ferrule Fitting/ Compression fitting GENERAL SPECIFICATION - a. Standard: ASME A213 b. Material: SS 316 c. Specification: Straight Union 1/2 Inch d. Dimension Compatible with Tube Outer Dia 12.7 mm e. Working Pressure: 3000 Psi f. Fitting Type Ferrule Fitting/ Compression fitting	
51	DNF111596	ds-1ln6-uu	5995131182007 / hikvision utp cable		3030 / METER	ds-1ln6-uu				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
52	DNF112007	PE-LAP-SS (10 PAIRS)	5995705248823 / SELF SUPPORTING ARIEL TELEPHONE CABLE SIZE 10 PAIRS 0.5 MM		100 / METER	10/0.5 MM SSAU				QUOTATION TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OEM, PTCL CABLES PAKISTAN TELEPHONE CABLES LIMITED KARACHI GENERAL SPECIFICATION - OEM, PTCL CABLES PAKISTAN TELEPHONE CABLES LIMITED KARACHI	
53	DN0111593	7.5-GZT-XDC/VR12-100	6140FP1000016 / BATTERY (12V, 100 AH)		2 / EACH/NUMBER	7.5M				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NAGENERAL SPECIFICATION - NA	
54	DNF111578	ha-10si	5999705246088 / Ir beam (RECEIVER AND TRANSMITTER)		10 / PAIR	HA-10SI				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO. OF BEAMS: 2 Beams Detection Mode: 2 beam blocked simultaneous Optical Source: Infrared digital pulse beam Respond speed: 50-700 m sec Power Supply: DC 10.5 24 V Optical axis adjustment (H): 180 Deg (+90 Deg) Optical axis adjustment (V): 20 Deg (+- 10 Deg) Material: ABS Resin Operational Humidity & Temperature : -25 C to -55 C Dimensions /sizes: Length: 171 mm Width: 77 mm GENERAL SPECIFICATION - NO. OF BEAMS: 2 Beams Detection Mode: 2 beam blocked simultaneous Optical Source: Infrared digital pulse beam Respond speed: 50-700 m sec Power Supply: DC 10.5 24 V Optical axis adjustment (H): 180 Deg (+90 Deg) Optical axis adjustment (V): 20 Deg (+- 10 Deg) Material: ABS Resin Operational Humidity & Temperature : -25 C to -55 C Dimensions /sizes: Length: 171 mm Width: 77 mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
55	DNF111743	OSAKA XPRESS SERIES 100W	623076528084 5 / OSAKA FLOOD LIGHT 100W		71 / EACH/NUMBER	OSAKA 100W				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OSAKA FLOODLIGHT GENERAL SPECIFICATION - OSAKA FLOODLIGHT	
56	DNT106845	A 8112000	597773530882 1 / ZINC ANODE		6 / EACH/NUMBER	NA				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
57	DNF106371	EP104UC	592550534414 3 / BREAKERS MCB 04 POLE 10 AMPS		4 / EACH/NUMBER	N/A				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - amperas 10a pole 4 pole minature circuit breaker B10 GENERAL SPECIFICATION - amperas 10a pole 4 pole minature circuit breaker B10	
58	DN0107902	H/LWSAP-CJJQ-TJ /CJJQ-TJ 0103	2990FP115000 3 / Mesh pad stage (INTAKE FILTER)		8 / EACH/NUMBER	CJJQ-TJ 0103				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - The mesh pad stage uses the condensation principle to capture and coalesce the tiny salt spray aerosol particles in the air intake into large droplets, most of which fall into the drain tank along the mesh by gravity dimension / size: 1800×1300×300 (mm) GENERAL SPECIFICATION - The mesh pad stage uses the condensation principle to capture and coalesce the tiny salt spray aerosol particles in the air intake into large droplets, most of which fall into the drain tank along the mesh by gravity dimension / size: 1800×1300×300	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(mm)	
59	DNT106846	A 8112167	597773530830 / ZINC ANODE		1 / EACH/NUMBER	NA				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
60	DNF105391	MSH-20D	663571524129 / MAGNETIC STIRRER WITH HOT PLATE-DIGITAL		2 / EACH/NUMBER	MSH-20D				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Instrument compliance to attached brochure and specification at Annex A. Final acceptance after successful completion of installation/ commissioning/training. 190 x 320 x130 GENERAL SPECIFICATION - Instrument compliance to attached brochure and specification at Annex A. Final acceptance after successful completion of installation/ commissioning/training. 190 x 320 x130	
61	DNF108140	J9776A	703571524883 2 / HP ARUBA 2530 24G network switch		1 / EACH/NUMBER	ARUBA 2530 24G (J9776A)				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH GENERAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH	
62	DNF112070	ub500 / ZA3000E	635078524635 9 / WALK THROUGH GATE WITH MONITOR & FACE CAPTURE CAMERA		2 / EACH/NUMBER	ub500 /ZA3000E				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
63	DNF111590	CT 2.3-12	614078514081 4 / FIRE ALARM BATTERY 12V 2.3AH	FIRE ALARM SYSTEM	2 / EACH/NUMBER	NO DATA AVAILABLE		CH	LEOCH, CHINA	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: J.S. ELECTRONICS, SHOP#166, CO-OPERATIVE MARKET, SADDAR, KARACHI. PH#021-7695262. E-MAIL: sohaib-jamalgr81@hotmail.com GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: J.S. ELECTRONICS, SHOP#166, CO-OPERATIVE MARKET, SADDAR, KARACHI. PH#021-7695262. E-MAIL: sohaib-jamalgr81@hotmail.com	
64	DNF111462	XE005319605	701070511899 6 / STP CAT 5E/CAT6E NETWORK CABLE (4 PAIR) AMP/AVAYA (1000 FFFFT)	FAWMIS NETWORKING CABLE	10 / ROLL					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DNS109616	FIG.4820-PN10 DN450 S2.2	4820FT101822 4 / Double Flanged Buterfly Valve	Main Propulsion Sea Water Cooling System	1 / EACH/NUMBER	25000HI.0002	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
66	DNF112371	NIKON 850 DSLR	635076522555 5 / NIKON 850 DSLR CAMERA ALONG WITH LENS 24-120 MM	STILL CAMERA	1 / EACH/NUMBER	NIKON 850 DSLR	NA	NIKON JAPAN	NIKON	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - HARD COPY IS ATTACHED GENERAL SPECIFICATION - HARD COPY IS ATTACHED	
67	DNF112175	LITHIUM 123 (ENERGIZER)CR-	613576523167 5 / DRY LITHIUM BATTERY	NIGHT VISION GOGGLES	200 / EACH/NUMBER	CR-123A		MATSUSHITA ELECTRONIC INDUSTRIAL CO LTD OSAKA 5708511 JAPAN.	PANASONIC	TDS/BROCHURE OR PHOTOGRAPH OF	TECHNICAL SPECIFICATION - IDEAL FOR NVG, D BALL, AND TACTICAL FLASH LIHTS ITS A LIGHT WEIGHT AND DURABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		123A/123	CELL 3 VOLT							ITEM MUST BE ENCLOSED WITH QUOTATION	POWER SOURCE. IT POSSESE GREAT PEFOMANCE IN EXTREME TEMPERATURES. country of origin Japan <u>GENERAL SPECIFICATION - IDEAL FOR NVG ,D BALL, AND TACTICAL FLASH LIHTS ITS A LIGHT WEIGHT AND DURABLE POWER SOURCE. IT POSSESE GREAT PEFOMANCE IN EXTREME TEMPERATURES. country of origin Japan</u>	
68	DNJ113033	701-48320-70	5820765170579 / CABLE REMOTE CONTROL 20 FEET	OBM 90 HP YAMAHA	4 / EACH/NUMBER			JAPAN	JAPAN	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - STANDARD SPECIFICATION</u> <u>GENERAL SPECIFICATION - STANDARD SPECIFICATION</u>	
69	DNF112956	CMDT 391 K-SL / CMAS100-SL/ 32150500-EN	5905715141324 / SKF MACHINE CONDITION ADVISOR	SKF MACHINE CONDITION ADVISOR	1 / EACH/NUMBER	CMAS100-SL		US	M/S SKF RELIABILITY SYSTEM S,5271 VIEW BRIDGE COURT, SAN DIEGO CALIFORNIA,USA. TEL#+1 8584963400, FAX#+1 8584963531	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - OEM ADD:M/S RELIABILITY SYSTEMS,5271 VIEW BRIDGE COURT,SAN DIEGO CALIFORNIA, USA.TEL#+1 8584963400,FAX#+1 8584963531</u> <u>GENERAL SPECIFICATION - OEM ADD:M/S RELIABILITY SYSTEMS,5271 VIEW BRIDGE COURT,SAN DIEGO CALIFORNIA,USA.TEL#+1 8584963400,FAX#+1 8584963531</u>	
70	DNF113018	CMAC112 K / CMAC 105	6615715141325 / ACCELEROMETER WITH INTEGRAL CABLE FOR	SKF MACHINE CONDITION ADVISOR	1 / EACH/NUMBER	NO DATA AVAILABLE		US	M/S SKF RELIABILITY SYSTEM S,5271 VIEW BRIDGE	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSE	<u>TECHNICAL SPECIFICATION - OEM ADD:M/S RELIABILITY SYSTEMS,5271 VIEW BRIDGE COURT,SAN DIEGO CALIFORNIA, USA.TEL#+1 8584963400,FAX#+1 8584963531</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SKF MACHINE CONDITION ADVISOR						COURT, SAN DIEGO CALIFORNIA,USA. TEL#+1 8584963400, FAX#+1 8584963531	D WITH QUOTATION	SPECIFICATION - OEM ADD:M/S RELIABILITY SYSTEMS,5271 VIEW BRIDGE COURT,SAN DIEGO CALIFORNIA,USA.TEL#+1 8584963400,FAX#+1 8584963531	
71	DNS113027	4996707	2920014074857 / Starter Motor 24 volt	Starting Motor	1 / EACH/NUMBER	OPTION ST9491	0	500 JACKSON ST COLUMBUS	CUMMINS INC.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
72	DNF112147	TURNSTILE	6350705171056 / FULL HEIGHT TURNSTILE	NA	1 / EACH/NUMBER	NA		PAKISTAN	NECOP	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DIMENSION 7 FT HEIGHT, 6 FT WIDE PASSAGE WIDTH 30 INCH THROUGH RUN RATE 25-30 PERSON/MIN POWER SUPPLY 12 VDC BIOMETRIC AND RFID ACCESS CONTROL SYSTEM (F-18) GENERAL SPECIFICATION - DIMENSION 7 FT HEIGHT, 6 FT WIDE PASSAGE WIDTH 30 INCH THROUGH RUN RATE 25-30 PERSON/MIN POWER SUPPLY 12 VDC BIOMETRIC AND RFID ACCESS CONTROL SYSTEM (F-18)	
73	DNF112140	ROAD BLOCKER	6310705171057 / AUTOMATIC ROAD BLOCKER	NA	2 / EACH/NUMBER	NA		PAKISTAN	NECOP	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - FAST OPERATION 4-6 SEC, 60 OPERATION/HOUR DIMENSION 12 X 3 FEET, ERECTED 30 INCH LOAD BEARING CAPACITY 15 TON GENERAL SPECIFICATION - FAST OPERATION 4-6 SEC, 60 OPERATION/HOUR DIMENSION 12 X 3 FEET, ERECTED 30 INCH LOAD BEARING CAPACITY 15 TON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
74	DNF109521	HR1221W	6135735178805 / CSB BATTERY - 12V 21W 2.1A	APC UPS	32 / EACH/NUMBER	HR1221W		CSB TAIWAN	CSB	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CellsPerUnit 6 VoltagePerUnit 12 Capacity 21W@15min-rateto1.67Vpercell @25 (77) Weight Approx. 1.80 kg(3.97 lbs) MaximumDischargeCurrent 60A/90A (5sec) InternalResistance Approx. 25 m OperatingTemperatureRange Discharge: -15 ~50 (5 ~122) Charge: -15 ~40 (5 ~104) Storage:-15 ~40 (5 ~104) OEM, CSB BATTERY CO., LTD. (TAIWAN)GENERAL SPECIFICATION - CellsPerUnit 6 VoltagePerUnit 12 Capacity 21W@15min-rateto1.67Vpercell @25 (77) Weight Approx. 1.80 kg(3.97 lbs) MaximumDischargeCurrent 60A/90A (5sec) InternalResistance Approx. 25 m OperatingTemperatureRange Discharge: -15 ~50 (5 ~122) Charge: -15 ~40 (5 ~104) Storage:-15 ~40 (5 ~104) OEM, CSB BATTERY CO., LTD. (TAIWAN)	
75	DNF112308		6070705229821 / 24 JOINT BOX	PSS SYSTEM	6 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal typeGENERAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
76	DNF113012	N150/ N140,125, EXIDE	0562799004653 / BATTERY 12V 115-125 AH SEC ACID TYPE	GENERAL USE	1 / EACH/NUMBER	N140, N125 EXIDE				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - oem exide karachi pakistanGENERAL SPECIFICATION - oem exide karachi pakistan	
77	DNF112243	MA3000C-48/BL820E	4440795061524 /	(YSD) GENERAL USE	1 / EACH/NUMBER	PREM-I-AIR ELITE				TDS/BROCHURE OR PHOTOGRAPH	TECHNICAL SPECIFICATION - IP Rating: IP 21 or above Voltage	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DEHUMIDIFIER PORTABLE			EH1418 XTREEM				APH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<p>RATING: 110/220 V 50/60 Hz Power Rating: 470 Watts Over-current PROTECTION: Should be installed with circuit breaker/ fuse protection against over-current and short-circuit Grounding/ Earthing: Must comply with Unit's earthing system Cable/ Plug Design: Special electrical cable with fol properties: 2 Extra flexible 2 Tough outer covering Flame retardant with 3 Pin Plug Material Body: Special Plastic/ Composite with Fire Retardant Additives Refrigerant: R-22 Water Tank Capacity: 6 Liters Weight: 21 Kg Size: 455 mm x 350 mm x 603mm Dehumidifying Capacity: 28-35 Ltrs per day Drying cap(Ltrs):28-35 per day Power input (Watt): 510 Drying: 4.8 Refrigerant: R22 W/tank cap (Ltr): 06 Rated power:470W Rated current: 4.1A Operating Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600W</p> <p><u>GENERAL SPECIFICATION</u> - IP Rating: IP 21 or above Voltage RATING: 110/220 V 50/60 Hz Power Rating: 470 Watts Over-current PROTECTION: Should be installed with circuit breaker/ fuse protection against over-current and short-circuit Grounding/ Earthing: Must comply with Unit's earthing system Cable/ Plug Design: Special electrical cable with fol properties: 2 Extra flexible 2 Tough outer covering Flame retardant with 3 Pin Plug Material Body: Special Plastic/ Composite with Fire Retardant Additives Refrigerant: R-22 Water Tank Capacity: 6 Liters Weight: 21 Kg Size: 455 mm x 350 mm x 603mm</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											Dehumidifying Capacity: 28-35 Ltrs per day D/fying capc(Ltrs):28-35 per day Power input (Watt): 510 D/fying: 4.8 Refrigerant: R22 W/tank cap (Ltr): 06 Rated power:470W Rated current: 4.1A Operatng Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600W	
78	DNH112303	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
79	DNF112883	PP3 , 6F22, (6135-00-900-2139)	6135701004118 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25.75X017MM	AVO METER	10 / EACH/NUMBER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
80	DNF111641	HI-PE MULTI-ZONE / PD6500	6350715095514 / WALK THROUGH GATE METAL DETECTOR C/W ACCESORIOES	SECURITY DETECTION (OEM CEIA ITALY)	1 / EACH/NUMBER					TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
81	DNF113016	HA/623-3-1	961175065002	SWITCH BOARD	1 / EACH/NUMBER	5433				TDS/BROCHURE OR	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		TERASAKI	3 / CIRCUIT BREAKER 100AMPS 220/500V		UMBER					PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	ITEM IS TO-100BA,AC 550V, DC250V,100 AMP,3 POLE(SHT-TRIP) TERASAKI AND 5433 RESPECTIVELY..GENERAL SPECIFICATION - ITEM IS TO-100BA,AC 550V,DC250V,100 AMP,3 POLE(SHT-TRIP) TERASAKI AND 5433 RESPECTIVELY..	
82	DNF113011	ep-1000t/blazer vista 1000	7035705059927 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	2 / EACH/NUMBER	BLAZER VISTA 1000/Aurora				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V AC GENERAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V AC	
83	DCW111191		8430500900367 / SHOES BLACK LEATHER OXFORD STYLE SIZE 10		165 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 10 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 10 FOR SAILOR	ITEM ON REQUIRE AS PER SPECIFICATION
84	DCW111187		8430500900364 / SHOES BLACK LEATHER OXFORD STYLE SIZE 07		165 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 07 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 07 FOR SAILOR	ITEM ON REQUIRE AS PER SPECIFICATION
85	DCW111203		8430500001480 / Shoes White		100 / PAIR					Participated firms must	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION -	ITEM ON REQUIRE

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Leather Size 8							be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	null	AS PER SPECIFICATION
86	DCW927 08		843050090036 5 / SHOES BLACK LEATHER OXFORD STYLE SIZE 08		180 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date.	<u>TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 08 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 08 FOR SAILOR</u>	
87	DCW111 188		843050090036 5 / SHOES BLACK LEATHER OXFORD STYLE SIZE 08		165 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	<u>TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 08 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 08 FOR SAILOR</u>	ITEM ON REQUIRE AS PER SPECIFICATION
88	DCW927 13		843050090036 9 / SHOES BLACK LEATHER OXFORD STYLE SIZE 12		180 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date.	<u>TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 12 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 12 FOR SAILOR</u>	
89	DCW111 193		843050090036 9 / SHOES		165 / PAIR					Participated firms must	<u>TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD</u>	ITEM ON REQUIRE

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BLACK LEATHER OXFORD STYLE SIZE 12							be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	STYLE (WITH TOE) 20 EYELETS SIZE 12 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 12 FOR SAILOR	AS PER SPECIFICATION
90	DCW111 183		843550018004 8 / SHOES BLACK LEATHER OXFORD STYLE SIZE 5 FOR FMA		185 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 5 FOR FMA GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 5 FOR FMA	ITEM ON REQUIRED AS PER SPECIFICATION
91	DCW111 208		843050080018 0 / SHOES WHITE LEATHER SIZE 13		100 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - SHOES WHITE LEATHER IN OXFORD STYLE WITH IMS BROWN SOLE AND 16 EYELETS SIZE 13 GENERAL SPECIFICATION - SHOES WHITE LEATHER IN OXFORD STYLE WITH IMS BROWN SOLE AND 16 EYELETS SIZE 13	ITEM ON REQUIRED AS PER SPECIFICATION
92	DCW111 206		843050000148 3 / Shoes White Leather Size 11		100 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	ITEM ON REQUIRED AS PER SPECIFICATION

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
93	DCW111 207		843050000148 4 / Shoes White Leather Size 12		100 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	ITEM ON REQUIRED AS PER SPECIFICATION
94	DCW111 189		843050090036 6 / SHOES BLACK LEATHER OXFORD STYLE SIZE 09		165 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 09 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 09 FOR SAILOR	ITEM ON REQUIRED AS PER SPECIFICATION
95	DCW927 14		843070090762 6 / SHOES BLACK LEATHER OXFORD STYLE SIZE 13		180 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date.	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 13 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 13 FOR SAILOR	
96	DCW111 194		843070090762 6 / SHOES BLACK LEATHER OXFORD STYLE SIZE 13		165 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 13 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 13 FOR SAILOR	ITEM ON REQUIRED AS PER SPECIFICATION

S. No	LPR No	PART,NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										opening date otherwise quotes not accepted.		
97	DCW111205		8430500001482 / Shoes White Leather Size 10		100 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	ITEM ON REQUIRED AS PER SPECIFICATION
98	DCW111182		8435500180047 / SHOES BLACK LEATHER OXFORD STYLE SIZE 4 FOR FMA		165 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYLETSSIZE 4 FOR FMA GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYLETSSIZE 4 FOR FMA	item on required as per specificatio
99	DCW92703		8435500180047 / SHOES BLACK LEATHER OXFORD STYLE SIZE 4 FOR FMA		180 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date.	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYLETSSIZE 4 FOR FMA GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYLETSSIZE 4 FOR FMA	
100	DCC113511		8440503202176 / NECK TIE BLACK		1000 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	the item is procured a per specificati

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
101	DCW92715		8430500900124 / SHOES BLACK LEATHER OXFORD STYLE SIZE 14		180 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date.	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 14 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 14 FOR SAILOR	
102	DCW111195		8430500900124 / SHOES BLACK LEATHER OXFORD STYLE SIZE 14		165 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 14 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 14 FOR SAILOR	ITEM ON REQUIRE AS PER SPECIFICATION
103	DCW111209		8430500800181 / SHOES WHITE LEATHER SIZE 14		100 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - SHOES WHITE LEATHER IN OXFORD STYLE WITH IMS BROWN SOLE AND 16 EYELETS SIZE 14 GENERAL SPECIFICATION - SHOES WHITE LEATHER IN OXFORD STYLE WITH IMS BROWN SOLE AND 16 EYELETS SIZE 14	ITEM ON REQUIRE AS PER SPECIFICATION
104	DCW111192		8430500900388 / SHOES BLACK LEATHER OXFORD STYle SIZE 11		165 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date	TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 11 FOR SAILOR GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 11 FOR SAILOR	ITEM ON REQUIRE AS PER SPECIFICATION

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										otherwise quotes not accepted.		
105	DCW111200		843050000187 2 / shoes white leather size 5		100 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	ITEM ON REQUIRED AS PER SPECIFICATION
106	DCW111201		843050000147 8 / Shoes White Leather Size 6		100 / PAIR	TEST				Participated firms must be ensuring sample provided as per requirement on tender opening date.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	ITEM ON REQUIRED AS PER SPECIFICATION
107	DCW111204		843050000148 1 / Shoes White Leather Size 9		100 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	ITEM ON REQUIRED AS PER SPECIFICATION
108	DNF112307	PFS4207-4GT-DP/DH-HS4208-4GT-90	702570524048 5 / 4 channel POE switch with complete accessories		16 / EACH/NUMBER	PFS4207-4GT-DP				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSE	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION		
109	DCW111199		843050000187 1 / shoes white leather size 4		100 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	ITEM ON REQUIRED AS PER SPECIFICATION
110	DCW111202	8430500001479	843050000147 9 / SHOES WHITE LEATHER SIZE-7		100 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	ITEM ON REQUIRED AS PER SPECIFICATION
111	DNZ112810	ST786Pea ufeoec124	671058530089 9 / color camera		1 / EACH/NUMBER	ST786PE AUFEOECC124				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ipc attached GENERAL SPECIFICATION - ipc attached	
112	DCD113509		844050000217 5 / BUTTON GOLDEN (22.86MM) FORE AND AFT RIG dress no 1&2 AND 7&7A		1200 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
113	DNF108548	12-Fiber SMF G.	704570524962 0 / Optical fiber		2000 / METER	12-Fiber SMF G.				TDS/BROCHURE OR	TECHNICAL SPECIFICATION - Complete details regarding OFC 12-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		652.D	cables CLT			652.D				PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	Fiber are available on page 18 of the provided Brochure named "PTCL Product Catalogue" NOTE: SM G. 652.D is the common standard for all type of OFC just the number of fibers varies i.e. 2 Fiber, 4 Fiber, 8 Fiber, 24 Fiber etc <u>GENERAL SPECIFICATION</u> - Complete details regarding OFC 12- Fiber are available on page 18 of the provided Brochure named "PTCL Product Catalogue" NOTE: SM G.652.D is the common standard for all type of OFC just the number of fibers varies i.e. 2 Fiber, 4 Fiber, 8 Fiber, 24 Fiber etc	
114	DNF112176	AA2500mah	6140715281910 / battery pack rechargeable NIMH (pack of 4) DURACELL AA 2500MAH		40 / PACKET	AA2500MAH				TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
115	DCW111185		8430500900363 / SHOES BLACK LEATHER OXFORD STYLE 06		165 / PAIR					Participated firms must be ensuring sample provided as per requirement on tender opening date otherwise quotes not accepted.	<u>TECHNICAL SPECIFICATION</u> - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 06 FOR SAILOR <u>GENERAL SPECIFICATION</u> - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 06 FOR SAILOR	ITEM ON REQUIRED AS PER SPECIFICATION
116	DCW92706		8430500900363 / SHOES BLACK LEATHER OXFORD STYLE 06		180 / PAIR					Participated firms must be ensuring sample provided as per requirement	<u>TECHNICAL SPECIFICATION</u> - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 06 FOR SAILOR <u>GENERAL SPECIFICATION</u> - SHOES BLACK LEATHER OXFORD STYLE (WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										on tender opening date.	TOE) 20 EYELETS SIZE 06 FOR SAILOR	
117	DNF109122	MCTX-CAT6	5915705248710 / CAT 6 networkig cable		1500 / METER	MCTX-CAT6				1) D-LINK CAT-6 23 AWG UTP CABLE 305M (99.9% bARE COPPER & MUST PROVIDE BROACHE R AND TDS (OTHERWISE QUOTE WILL BE REJECTED)	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
118	DGP109882	CORE I5	7025705246091 / PERSONAL COMPUTER CORE I5 12th GENERATION or above		4 / SET	CORE I5					<u>TECHNICAL SPECIFICATION - 1.</u> CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>GENERAL SPECIFICATION - 1.</u> CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.</p>	
119	DPC112 651	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENLOSER WIRH QUOTATION	<p>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA</p>	
120	DPC113 946	NO DATA AVAILABE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		817.2 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENLOSER WIRH QUOTATION	<p>TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - . psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
121	DPC113 877	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		817.2 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENLOSER WITH QUOTATION	<p><u>TECHNICAL SPECIFICATION - CHARACTERISTICS:</u> SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.</p> <p><u>GENERAL SPECIFICATION - CHARACTERISTICS:</u> SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 95% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.</p>	
122	DPC112 322	NO DATA AVAILABLE	044350443000 5 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENLOSER WITH QUOTATION	<p><u>TECHNICAL SPECIFICATION - 1.</u> grade-1 l. a. w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1184mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1, FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 – 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=JIS G 311287 grade SR 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA</p> <p>Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120-150 Torque, GENERAL SPECIFICATION - 1. grade-1 i. a. w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA. Product=LPG Cylinder, type=commercial 45.4 kg capacity.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doorn dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 - 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120-150 Torque,</p>	
123	DNQ113376	0472-5580	047259425974 7 / LIFE JACKET GENERAL SERVICE ORALLY INFLATED WITH LAMP WITH SERVICE		230 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - 1. FACE SHIELD/HOOD IS ADDED MATERIAL/COMPONENTS:\ a. RUBBRISED FABRIC b. LIFTING BECKET c. ORAL INFLATION VALVE d. STORAGE POUCH e. WAIST BELT f. METAL COMPONENTS (BUCKLESS & BUTTONS) g. RETRO-REFLECTIVE COVER h. WHISTLE i. FACE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MANUAL								SHIELD k. SEA WATER OPERATED BATTERY l. REFLECTIVE PANELS SPECIFICATIONS: ITEM TO BE PROVIDED AS PER PN SPEC NO. 11-008/06 ISSUE 03 OF 22 FEB 07 (PY ENCLOSED) RUBBER LIFEJACKET MUST BE WELL PACKED & PRES <u>GENERAL SPECIFICATION</u> - 1. FACE SHIELD/HOOD IS ADDED MATERIAL/COMPONENTS:\ a. RUBBERISED FABRIC b. LIFTING BECKET c. ORAL INFLATION VALVE d. STORAGE POUCH e. WAIST BELT f. METAL COMPONENTS (BUCKLESS & BUTTONS) g. RETRO-REFLECTIVE COVER h. WHISTLE j. FACE SHIELD k. SEA WATER OPERATED BATTERY l. REFLECTIVE PANELS SPECIFICATIONS: ITEM TO BE PROVIDED AS PER PN SPEC NO. 11-008/06 ISSUE 03 OF 22 FEB 07 (PY ENCLOSED) RUBBER LIFEJACKET MUST BE WELL PACKED & PRES	
124	DPC112 216	NO DATA AVAILABLE	044350443000 5 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 – 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120–150 Torque, GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doorn</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1184mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,</p>	
125	DGP113 839	4003DN	743570513863 2 / PRINTER HP LASER JET	COMPUTER	1 / EACH/N UMBER	NO DATA AVAILAB LE		PK		PAKISTA N	<p><u>TECHNICAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Avallabill ty	Tender Remarks	TECH / GEN SPECS	Dimension
126	DGP113 518	4003DN	743570513863 2 / PRINTER HP LASER JET	COMPUTER	2 / EACH/N UMBER	NO DATA AVAILAB LE		PK		PAKISTA N	<p><u>TECHNICAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both</p> <p><u>GENERAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both</p>	
127	DGP113 735		773070517439 1 / LED TV 55 INCH / 46/49/50 INCH	LED TV	1 / EACH/N UMBER			SAMSUNG		SAMSUN G	<p><u>TECHNICAL SPECIFICATION -</u> SAMSUNG/CHANGHONG RUBA/TCL LED TV 46/49/50 INCH origin: china</p> <p><u>GENERAL SPECIFICATION -</u> SAMSUNG/CHANGHONG RUBA/TCL LED TV 46/49/50 INCH origin: china</p>	
128	DGP113 515	E- STUDIO35 S/E- STUDIO35 7/ E- STUDIO35 28A (35CPM), E-STUDIO E-3508A	361070514044 9 / PLAIN PAPER COPIER TOSHIBA E- STUDIO 355 /357 HEAVY DUTY/CANNO N 2535	PLAIN PAPER COPIER	1 / EACH/N UMBER	E- STUDIO3 55/E- STUDIO3 57/ e- studio352 8a (35cpm)		PK		PAKISTA N	<p><u>TECHNICAL SPECIFICATION -</u> AUTOMATIC DUPLEX (RADF) MR3022 SRDF, PAPER SIZE A3 A5R,CONTOLER TYPE TOSHIBA E BRIDGE, INTERFACE 10/100 BASET, DUPLES SCANNING AND PRINTING FACILITY OF A4, A3 ETC</p> <p><u>PAPER GENERAL SPECIFICATION -</u> AUTOMATIC DUPLEX (RADF) MR3022 SRDF, PAPER SIZE A3 A5R,CONTOLER TYPE TOSHIBA E BRIDGE, INTERFACE 10/100 BASET, DUPLES SCANNING AND PRINTING FACILITY OF A4, A3 ETC PAPER</p>	
129	DGP113 568	E2725HM/ E2722HM 27FW	743570521488 5 / LCD MONITOR 27 Inch	Instructor Console	2 / EACH/N UMBER	E2725HM /E2417H (24") /e2722hV 22P MCR Simulator	NOT KNOWN	PLOT NO C-4/A, S.I.T.E., Karachi, Pakistan. Tel: +929213257111-2 Fax: +92(21)32553111		DELL	<p><u>TECHNICAL SPECIFICATION -</u> VX 2781 MH WITH: A) IPS PANEL AND THIN PROFILE. B) FRAMELESS BEZEL WITH UNIQUE TRIANGULAR STAND. C) 75 HZ REFRESH RATE. D) VGA AND HDMI INPUTS. RESOLUTION-</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											1920X1080@60 HZ (FHD) DISPLAY SIZE -27 INCH (DIAGONAL) DISPLAY TYPE -IPS WITH LED LACK LIGHT ANTI-GLARE INPU27 T -1 VGA &2 HDMI WEIGHT -3.68 KGS (UNPACKED)GENERAL SPECIFICATION - VX 2781 MH WITH: A) IPS PANEL AND THIN PROFILE. B) FRAMELESS BEZEL WITH UNIQUE TRIANGULAR STAND. C) 75 HZ REFRESH RATE. D) VGA AND HDMI INPUTS. RESOLUTION-1920X1080@60 HZ (FHD) DISPLAY SIZE -27 INCH (DIAGONAL) DISPLAY TYPE -IPS WITH LED LACK LIGHT ANTI-GLARE INPU27 T -1 VGA &2 HDMI WEIGHT -3.68 KGS (UNPACKED)	
130	DGP113 369	NO DATA AVAILABL E	005150000140 3 / Binder Medium F(NS) -101 SIZE 9X12 INCH, Board Texture, Hard & Plyable Thickness 03 mm		124 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size: 9 x 12 inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing PressGENERAL SPECIFICATION - Size: 9 x 12 inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing Press	
131	DGP113	NO DATA	005150000140		124 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	502	AVAILABLE	3 / Binder Medium F(NS) -101 SIZE 9X12 INCH, Board Texture, Hard & Plyable Thickness 03 mm		EACH/NUMBER						Size: 9 x 12 inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing Press <u>GENERAL SPECIFICATION</u> - Size: 9 x 12 inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing Press	
132	DGP113519	NO DATA AVAILABLE	773070508858 3 / LED TV 32 INCH	TELEVISION	2 / EACH/NUMBER	tdf					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
133	DGP85857	NIL	764070511028 1 / PERSONEL FOLDER FOR RECORD KEEPING OF CPOS/SAILORS	NIL(AUTH;ST-S/3922 24 DEC 04	550 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - 1. Size of Folder a. Length: 365 mm ± 1 mm b. Width: 260 MM ± 1 MM c. Width of Folding Portion: 35 MM ± 1 MM 2. Material: a. Outer and inner cover: Textured Raxin Best quality (not commercial quality) thick 1 mm b. Pockets: Transparent Polythene thick 0.1 mm c. Inner lining of back side of cover: Card board hard thick 4.5 mm ± 0.2 mm d. Inner lining of front side of cover: Card board hard thick 4.5 mm± 0.2 mm e. File fastner cover with lining: Textured Rexin thick 1 mm f. File fastner inner lining: Card board thick 2.5 mm ± 0.1 mm g.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Eyelets: Black Aluminium h. Tag Cotton: Length 260 mm along with iron tip with black enamel 3. No of Pockets: a. Front side 02 pocket: LENGTH WIDTH i. For Name Talley: 40 MM 65 mm i. For Photograph: 70 mm 65 mm b. Inner Pocket left hand side: 215 mm 260 mm c. Inner Pocket right hand side: 130 mm 260 mm d. Back side pocket: 340 mm 260 mm e. Side pocket on folding portion: 65 mm 35 mm 4. Stitches by : By Heat Machine 5. Printing i. Printing by: By foil printing ii. Printing colour, word title and Logo : As per approval by Drafting Authority 6. Colour of Rexin : Navy blue</p> <p><u>GENERAL SPECIFICATION - 1.</u></p> <p>Size of Folder a. Length: 365 mm $\pm$ 1 mm b. Width: 260 MM $\pm$ 1 MM c. Width of Folding Portion: 35 MM $\pm$ 1 MM 2. Material: a. Outer and inner cover: Textured Raxin Best quality (not commercial quality) thick 1 mm b. Pockets: Transparent Polythene thick 0.1 mm c. Inner lining of back side of cover: Card board hard thick 4.5 mm $\pm$ 0.2 mm d. Inner lining of front side of cover: Card board hard thick 4.5 mm $\pm$ 0.2 mm e. File fastner cover with lining: Textured Rexin thick 1 mm f. File fastner inner lining: Card board thick 2.5 mm $\pm$ 0.1 mm g. Eyelets: Black Aluminium h. Tag Cotton: Length 260 mm along with iron tip with black enamel 3. No of Pockets: a. Front side 02 pocket: LENGTH WIDTH i. For Name Talley: 40 MM 65 mm i. For Photograph: 70 mm 65 mm b. Inner Pocket left hand side: 215 mm 260 mm c. Inner Pocket right hand side: 130 mm 260 mm d. Back side pocket: 340 mm 260 mm e. Side pocket on folding portion: 65 mm 35 mm 4. Stitches by</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											: By Heat Machine 5, Printing i. Printing by: By foil printing ii. Printing colour, word title and Logo : As per approval by Drafting Authority 6, Colour of Rexin : Navy blue	
134	DGP113 834		702570505746 1 / TONNER FOR LASER JET III		4 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - 1.</u> HP 147A Black Original Laser Jet Toner Cartridge (P/N W1470A) for HP Laser Jet Enterprise M611 Printer 2. Average cartridge yield 10,500 pages 3. Dimensions (l x w x d) 380 x 180 x 270 mm 4. Weight 2.1 KG 5. UPC Code 194441304671</p> <p><u>GENERAL SPECIFICATION - 1.</u> HP 147A Black Original Laser Jet Toner Cartridge (P/N W1470A) for HP Laser Jet Enterprise M611 Printer 2. Average cartridge yield 10,500 pages 3. Dimensions (l x w x d) 380 x 180 x 270 mm 4. Weight 2.1 KG 5. UPC Code 194441304671</p>	
135	DGP113 391	NO DATA AVAILABLE	005050000022 3 / PAPER DUPLICATING COLOUR WHITE		470 / REAM	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION -</u> LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON</p> <p><u>GENERAL SPECIFICATION -</u> LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON</p>	
136	DGP111 580	B12B8084 11	702514583518 2 / SCANNER EPSON DS- 6000		1 / SET	DS-6000					<p><u>TECHNICAL SPECIFICATION -</u> SCANNER EPSON DS-60000 FLAT BED COLOR IMAGE SCANNER 600DPI COLOR CCD 4 LINE SENCER (RGB & BLACK FLAT BED 11.7" X 17" <u>GENERAL SPECIFICATION -</u> SCANNER EPSON DS-60000 FLAT BED COLOR IMAGE SCANNER 600DPI COLOR CCD 4 LINE SENCER (RGB & BLACK FLAT BED 11.7" X 17"</p>	
137	DGP113	T-3028P	704570534422		2 /	T-3028P					<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	192		1 / TONER CARTRIDGE original BLACK TOSHIBA		EACH/NUMBER						TONER CARTRIDGE BLACK TOSHIBA YIELDS 43000 PAGES CLOUR BLACK WEIGHT 700GRAMS PARENT EQUIPMENT E-STUDIO355/E-STUDIO357/ E-STUDIO3528A(35CPM),E-STUDIO, E-3508A NSN 3610705140449GENERAL SPECIFICATION - TONER CARTRIDGE BLACK TOSHIBA YIELDS 43000 PAGES CLOUR BLACK WEIGHT 700GRAMS PARENT EQUIPMENT E-STUDIO355/E-STUDIO357/ E-STUDIO3528A(35CPM),E-STUDIO, E-3508A NSN 3610705140449	
138	DGP113 570		702570527485 2 / LED TV 65 INCH		1 / PCS						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
139	DGP113 831	074229/84 051	676076526406 9 / FARGO HDP Retransfer film for fargo hdp5000 card printer		1 / EACH/NUMBER	HDP5000					TECHNICAL SPECIFICATION - HP 728, (F9J65A) YELLOW ORIGINAL INK CARTRIDGES INK DROP 6PL PRINT HEAD NOZZLES 9632 CARTRIDGE COLLOR YELLOW COLOR (S) OF PRINTING SUPPLIES YELLOW GENERAL SPECIFICATION - HP 728, (F9J65A) YELLOW ORIGINAL INK CARTRIDGES INK DROP 6PL PRINT HEAD NOZZLES 9632 CARTRIDGE COLLOR YELLOW COLOR (S) OF PRINTING SUPPLIES YELLOW	
140	DGP113 629	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		2 / SET	CORE I5					TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. GENERAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 8 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.</p> <p>TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 8 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING</p>	
141	DGP113 678	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		2 / SET	CORE I5						

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. GENERAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM. 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.</p> <p>TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM. 9. OPERATING SYSTEM= MS - DOS ONLY</p>	
142	DGP113 564	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		2 / SET	CORE I5						

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF FR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>GENERAL SPECIFICATION</u> - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.	
143	DGP110 877	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		1 / SET	CORE i5					<u>TECHNICAL SPECIFICATION</u> - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>GENERAL SPECIFICATION</u> - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.</p>	
144	DGP112 367	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		2 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION</u> - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>GENERAL SPECIFICATION</u> - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.</p>	
145	DGP113 589	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE I5 12th GENERATION or above		2 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION</u> - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>GENERAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.</u>	
146	DGP113 830	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		2 / SET	CORE I5					<u>TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>GENERAL SPECIFICATION</u> - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.</p> <p><u>TECHNICAL SPECIFICATION</u> - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of</p>	
147	DGP113 495	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE I5 12th GENERATION or above		5 / SET	CORE I5						

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											genuineness. d. Online PC verification. e. PC without modification/ upgradation. GENERAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 8 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.	
148	DGP113 837	NIL	593073527733 0 / LAPTOP CORE i7 11th Generation		1 / EACH/NUMBER	NIL					TECHNICAL SPECIFICATION - 1. CPU Technology= Intel @ Core i7 (10th Generation or Above) (Minimum 2.8 GHZ upto 4.7 GHZ) 2. System Memory= 8 GB RAM DDR4 3. Hard Disk= 1 TB SATA 4. Optical Disk Drive= DVD RW 5. LED= MINIMUM 15.6" FHD 6. LAN= BUILT IN 7. Warranty= 01 Year OEM COC 8. Operating System= Windows 10 Or Above (Licensed) 9. Graphics= Intel FHD Graphics Built-In 10. Carrying Bag= Yes 11. Web Cam= Yes GENERAL SPECIFICATION - 1. CPU Technology= Intel @ Core i7 (10th Generation or Above) (Minimum 2.8 GHZ upto 4.7 GHZ) 2. System Memory= 8 GB RAM DDR4 3. Hard Disk= 1 TB SATA 4. Optical Disk Drive= DVD RW 5. LED=	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MINIMUM 15.6" FHD 6. LAN= BUILT IN 7. Warranty= 01 Year OEM COC 8. Operating System= Windows 10 Or Above (Licensed) 9. Graphics= Intel FHD Graphics Built-In 10. Carrying Bag= Yes 11. Web Cam= Yes	
149	DGP113 833	074230/84 053	676076526407 0 / FARGO hdp color RIBBON emhfc rbn h2 ymck 1500 images for emhfc HDP 5000		1 / EACH/NUMBER	FARGO HDP COLOR RIBBON EMHFC RBN H2 YMCK 1500 IMAGES					TECHNICAL SPECIFICATION - fargo hdp color ribbon compatible with fargo emhfc hdp 5000 color card printer GENERAL SPECIFICATION - fargo hdp color ribbon compatible with fargo emhfc hdp 5000 color card printer	
150	DGP113 810	4003DN	743570513863 2 / PRINTER HP LASER JET	COMPUTER	2 / EACH/NUMBER	NO DATA AVAILAB LE		PK		PAKISTA N	TECHNICAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both GENERAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
151	DGP113 733	NIL	743570514000 6 / MULTIMEDIA PROJECTOR (4000 LUMENS)	MULTIMEDIA PROJECTOR	1 / EACH/NUMBER	PANASONIC PT-VW360 (4000 LUMENS PROJECTOR) OR ABOVE		PK		PAKISTA N	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
152	DGP113 679	HP Scanner 20G05A/L2 747A	749070521848 3 / HP SCANNER PRO 2500 F1/2600 F1 FLATBED	HP SERVER Pro 2500 F1	3 / EACH/NUMBER	HP Scanner 20G05A/L2 ro 2500 F1/PRO 2600 F1	NIL	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II,	HP		TECHNICAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441			BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 <u>GENERAL SPECIFICATION</u> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297	
153	DGP113 836	HP Scanner 20G05A/L2 747A	749070521848 3 / HP SCANNER PRO 2500 F1/2600 F1 FLATBED	HP SERVER Pro 2500 F1	1 / EACH/NUMBER	HP Scanner 20G05A/Pro 2500 F1/PRO 2600 F1	NIL	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441	HP		<u>TECHNICAL SPECIFICATION</u> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 <u>GENERAL SPECIFICATION</u> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297	
154	DGP113 516	HP Scanner 20G05A/L2 747A	749070521848 3 / HP SCANNER PRO 2500 F1/2600 F1 FLATBED	HP SERVER Pro 2500 F1	2 / EACH/NUMBER	HP Scanner 20G05A/Pro 2500 F1/PRO 2600 F1	NIL	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441	HP		<u>TECHNICAL SPECIFICATION</u> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 <u>GENERAL SPECIFICATION</u> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297	
155	DGP113 515	E-STUDIO355/E-STUDIO357/ E-STUDIO3528A (35CPM), E-STUDIO E-3508A	361070514044 9 / PLAIN PAPER COPIER TOSHIBA E-STUDIO 355 /357 HEAVY DUTY/CANNO N 2535	PLAIN PAPER COPIER	1 / EACH/N UMBER	E-STUDIO355/E-STUDIO357/ e-studio3528a (35cpm)		TOSHIBA SINGAPUR PTE LTD		TOSHIBA JAPAN	TECHNICAL SPECIFICATION - AUTOMATIC DUPLEX (RADF) MR3022 SRDF, PAPER SIZE A3 A5R,CONTOLER TYPE TOSHIBA E BRIDGE, INTERFACE 10/100 BASET, DUPLES SCANNING AND PRINTING FACILITY OF A4, A3 ETC PAPERGENERAL SPECIFICATION -AUTOMATIC DUPLEX (RADF) MR3022 SRDF, PAPER SIZE A3 A5R,CONTOLER TYPE TOSHIBA E BRIDGE, INTERFACE 10/100 BASET, DUPLES SCANNING AND PRINTING FACILITY OF A4, A3 ETC PAPER	
156	DGP912 72	folder L12" W10" CONFIEN TIAL	753070525884 8 / personal folder confdiential (officer dossier) for hq scni(s)		200 / EACH/N UMBER	nil					TECHNICAL SPECIFICATION - 1. SIZE OF FOLDER L12" W10" 2. POCKET (OUTER,INNER,& SIDE) A.UPPER TRANSPARENT POCKET (L1.5" &W 2.5") B.UPPER PHOTOGRAPH POCKET(PASPORT SIZE) C.LOWER POCKET (L1.5" & W 2.5") D.SIDE POCKET (L3" & W 1.5") 3.BINDING STRIPS AS SAMPLE 4.PRINTING QUALITY & COLOUR SHADE A. CONFIDENTIONAL (FOIL PRINTING GOLDEN) B. MONOGRAM (FOIL PRINTING GOLDEN) C.SECT HQ NI (S) (FOIL PRINTING GOLDEN) D.OFFICER (FOIL PRINTING RED) E. PERSONAL DOSSIER (FOIL PRINTING GOLDEN) 5.CARD BOARD THICKNESS 3MM 6. REXINE THICKNESS & COLOUR SHADE THICKNESS:(AS SAMPLE) COLOUR (NAVY BLUE) 7.TEXTURE COLOUR SHADE NAVY BLUE 8. STITCHING OF FOLDER BY HEAT PRESS 9.WALL HIGHT 1.5	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SIZE OF FOLDER L12" W10" 2. POCKET (OUTER, INNER, & SIDE) A. UPPER TRANSPARENT POCKET (L1.5" & W 2.5") B. UPPER PHOTOGRAPH POCKET (PASPORT SIZE) C. LOWER POCKET (L1.5" & W 2.5") D. SIDE POCKET (L3" & W 1.5") 3. BINDING STRIPS AS SAMPLE 4. PRINTING QUALITY & COLOUR SHADE A. CONFIDENTIAL (FOIL PRINTING GOLDEN) B. MONOGRAM (FOIL PRINTING GOLDEN) C. SECT HQ NI (S) (FOIL PRINTING GOLDEN) D. OFFICER (FOIL PRINTING RED) E. PERSONAL DOSSIER (FOIL PRINTING GOLDEN) 5. CARD BOARD THICKNESS 3MM 6. REXINE THICKNESS & COLOUR SHADE THICKNESS: (AS SAMPLE) COLOUR (NAVY BLUE) 7. TEXTURE COLOUR SHADE NAVY BLUE 8. STITCHING OF FOLDER BY HEAT PRESS 9. WALL HEIGHT 1.5	
157	DGP113 460	LE1901W/ HP	702578514128 5 / LCD MONITOR 18.5"/19" (AS PER APPROVAL)	COMPUTER	1 / EACH/NUMBER	NO DATA AVAILAB LE		US	HAWLET PACKAR D, 11445 COMPAQ CENTRE DRIVE WEST, HOUSTON TAXAS 77070, USA		TECHNICAL SPECIFICATION - OEM ADD: HAWLET PACKARD, 11445 COMPAQ CENTRE DRIVE WEST, HOUSTON TAXAS 77070, USA. GENERAL SPECIFICATION - OEM ADD: HAWLET PACKARD, 11445 COMPAQ CENTRE DRIVE WEST, HOUSTON TAXAS 77070, USA.	
158	DGP113 734		753570613302 1 / LAPTOP COMPUTER	COMPUTER	1 / EACH/NUMBER	Dell inspire 1520		PK	VIDE NHQ LETTER ST- S/3200/81 98 DT 23/07/08		TECHNICAL SPECIFICATION - HP/DELL/LENOVO LAPTOP. S NO COMPONENTS SPECIFICATION 1. CPU TECHNOLOGY: INTEL® CORE I5 (13TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ). 2. SYSTEM MEMORY: 8 GB DDR3/DDR4 or above 3. DISPLAY: 15.6" LED. 4. HARD DISK: 512 gb ssd. 5 OPTICAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DISK DRIVE: DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL @ HD/HD GRAPHICS 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS 11 (LICENSED VERSION). GENERAL SPECIFICATION- HP/DELL/LENOVO LAPTOP. S NO COMPONENTS SPECIFICATION 1. CPU TECHNOLOGY: INTEL@ CORE I5 (13TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ). 2. SYSTEM MEMORY: 8 GB DDR3/DDR4 or above 3. DISPLAY: 15.6" LED. 4. HARD DISK: 512 gb ssd. 5 OPTICAL DISK DRIVE: DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL @ HD/HD GRAPHICS 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS 11 (LICENSED VERSION).	