

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 11-08-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR' NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPC105018	DOWCAL 100 / 132253896301	6850992161665 / HEAT TRANSFER FLUID		30 / LITER	3d radar				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> DOWCAL™ 100 IS AN ETHYLENE GLYCOL-BASED HEAT TRANSFER FLUID FOR USE IN A WIDE RANGE OF INDUSTRIAL, CONSTRUCTION AND INFRASTRUCTURE APPLICATIONS. IT IS HIGHLY RECOMMENDED FOR HEATING APPLICATIONS. recommended operating temperature of this fluid ranges from -50°C TO 175°C. <u>GENERAL SPECIFICATION -</u> DOWCAL™ 100 IS AN ETHYLENE GLYCOL-BASED HEAT TRANSFER FLUID FOR USE IN A WIDE RANGE OF INDUSTRIAL, CONSTRUCTION AND INFRASTRUCTURE APPLICATIONS. IT IS HIGHLY RECOMMENDED FOR HEATING APPLICATIONS. recommended operating temperature of this fluid ranges from -50°C TO 175°C.	
2	DNM101089	8199620020	6685725353070 / air pressure gauge (0-16bar) 2-1/2"		2 / EACH/NUMBER	na				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 2-1/2" AIR PRESSURE GAUGE (0-16BAR)</u> <u>GENERAL SPECIFICATION - 2-1/2" AIR PRESSURE GAUGE (0-16BAR)</u>	
3	DNQ105019	FXWC2, FXWC3 &	421079526887		15 / LITER	fxwc2/fxwc3/fxwc6				TDS\BROCHER OR	<u>TECHNICAL SPECIFICATION - xtr</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		FXWC6	9 / WET CHEMICAL							PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	wet chemical / fat seal fire extinguisher agentGENERAL SPECIFICATION - xtr wet chemical / fat seal fire extinguisher agent	
4	DNQ103 487	FXWC2, FXWC3 & FXWC6	421079526887 9 / WET CHEMICAL		36 / LITER	fxwc2/fxwc3/fxwc6				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - xtr wet chemical / fat seal fire extinguisher agentGENERAL SPECIFICATION - xtr wet chemical / fat seal fire extinguisher agent	
5	DNQ100 961	00-54007-98954-7	424071526961 2 / 3m gloves general use		40 / EACH/N UMBER	nil				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
6	DRG984 08	I-6000T CC-6000 OR I-633MMTB	291570515008 8 / COALESCER ELEMENT ASSY		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
7	DNM106 454	T400727/T 402521	281579530099 3 / FUEL INJECTION PUMP		1 / EACH/N UMBER	N/A				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N. PERKINS EQUIPMEN T	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
8	DNM104 500	N-961-BO1920/F WHP-2S-20	432073513766 3 / FRESH WATER HYDROPHOR	FRESH WATER HYDROPHOR E PUMP	1 / EACH/N UMBER	BO-19/20		OC	BOMBAS AZCU S/A FACTOR Y AND	TDS\BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			E SET PUMP						OFFICE ARRONA GUIPUZC OA SPAIN PO BOX 3420750 ZUMAIA TELE. 94314704 7 FAX. 94314744 0	BE ENCLOSE D WITH QUOTATIO N		
9	DNH106 250	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	1 / EACH/NUMBER	OWR- 528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> white colour only NASGAS WATER DISPENSER <u>GENERAL</u> <u>SPECIFICATION -</u> white colour only NASGAS WATER DISPENSER	
10	DNH106 026	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	3 / EACH/NUMBER	OWR- 528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> white colour only NASGAS WATER DISPENSER <u>GENERAL</u> <u>SPECIFICATION -</u> white colour only NASGAS WATER DISPENSER	
11	DNM103 407	1622369480	481073521568 3 / BLOW-OFF VALVE	MEDICAL OXYGEN GENERATOR O-500 ECO	4 / EACH/NUMBER	GA45+	2011118	ATLAS COPCO AIR POWER N.V, B-2610 WILRIJK ? BELGIUM. TEL: +32-3-87021 11 FAX: +32-3-8702730 WWW.atlascopco.be	ATLAS COPCO	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> MAKE: ATLAS COPCO , BLOW OFF VALVE FITTED WITH UNLOADER ASSEMBLY FOR AUTO WORK oem: SWEEDEN supplier : Plot-8C, Phase -2 Commercial Area Defense Housing Authority Karachi. Contact: 021-345500451 <u>GENERAL</u> <u>SPECIFICATION -</u> MAKE: ATLAS COPCO , BLOW OFF VALVE FITTED WITH UNLOADER ASSEMBLY FOR AUTO WORK oem: SWEEDEN supplier : Plot-8C, Phase -2 Commercial Area Defense Housing Authority Karachi. Contact:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											021-345500451	
12	DNM103413	FS100/LFS 100	2940735215687 / FILTER 1 MICRON	MEDICAL OXYGEN GENERATOR O-500 ECO	4 / EACH/NUMBER	LF S 100	2011118	OXYMATE A/S, FASANVEJ 18-20, DK-3200, HELSINGE DENMARK. TEL: +45 48797811 FAX: +45 48797813 E MAIL: service@oxymat.dk www.oxymat.dt	OXYMAT A/S	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. FILTER 1 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE. GENERAL SPECIFICATION - 1. FILTER 1 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE.	
13	DNH103412	FX100/LFX 100	2940735215688 / FILTER 0.01 MICRON	MEDICAL OXYGEN GENERATOR	4 / EACH/NUMBER	LF X 100	2011118	OXYMATE A/S, FASANVEJ 18-20, DK-3200, HELSINGE DENMARK. TEL: +45 48797811 FAX: +45 48797813 E MAIL: service@oxymat.dk www.oxymat.dt	OXYMAT A/S	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. FILTER 0.01 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE. GENERAL SPECIFICATION - 1. FILTER 0.01 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE.	
14	DNM104355	3393041/4334439	5330715177061 / RING, WEAR	MAIN ENGINE KTA50M2	1 / EACH/NUMBER			CUMMINS Ins SOUTH CAROLINA USA	CUMMINS USA	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - RING, WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL. GENERAL SPECIFICATION - RING, WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL.	
15	DPC104439	H-300 HUX	8040735140710 / HARDNER (SET OF 2X1KG BOTTLE)	AC COMPRESSOR KALMAT GWADER	1 / SET	NO DATA AVAILABLE		00		TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - A.V 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown , Flash point, 200f> GENERAL SPECIFICATION - A.V 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown , Flash point, 200f>	
16	DNQ106160	CEN1000063A	5510FT1019830 / Wooden Plug, 200 x 30 x 8 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD.	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									STI.	D WITH QUOTATION		
17	DNQ106159	CEN1000063D	5510FT1019833 / Wooden Plug 250 x 100 x 40 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
18	DNQ106158	CEN1000063E	5510FT1019834 / Wooden Plug 300 x 120 x 50 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
19	DPC104430	BOSTIK M501	8010795208200 / BOSTIK THINNERS / CLEANER M501	RHIB BOAT	105 / LITER	BOSTIK M501	NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX,TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHAW INFLATABLES LTD	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - M501 IS USED TO CLEAN, DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 2402ADHESIVE.THINNING BOSTIK NE486,CLEANING GLUE BRUSHES.SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW TOP.HIGHLY FLAMMABLE PRODUCT AND MUST BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA.GENERAL SPECIFICATION - M501 IS USED TO CLEAN,DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 2402ADHESIVE.THINNING BOSTIK NE486,CLEANING GLUE BRUSHES.SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW TOP.HIGHLY FLAMMABLE PRODUCT AND MUST BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
20	DPC105 025	BOSTIK 2402	651079520819 7 / BOSTIK 2402 ADHESIVE + HARDENER	RHIB BOAT	35 / LITER	BOSTIK2 402		HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX,TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHA W INFLATA BLES LTD	TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - BOSTIK 2402 CREATES A STRONG BOND WHICH IS RESISTANT TO HEAT -40 DEG C -90 DEG C,UV, SALTWATER AND HUMIDITY COVERAGE IS APPROX 4 SQUARE METER PER LITRE(VARIES WITH SURFACE).SUPPLIED AS 1 L TIN OF ADHESIVE AND A 40 ML BOTTLE OF BOSTIKURE D HARDENER.STORE B/W 5 DEG AND 25 DEG IN A DRY FLAMPROOF AREA.GENERAL SPECIFICATION - BOSTIK 2402 CREATES A STRONG BOND WHICH IS RESISTANT TO HEAT -40 DEG C -90 DEG C,UV, SALTWATER AND HUMIDITY COVERAGE IS APPROX 4 SQUARE METER PER LITRE(VARIES WITH SURFACE).SUPPLIED AS 1 L TIN OF ADHESIVE AND A 40 ML BOTTLE OF BOSTIKURE D HARDENER.STORE B/W 5 DEG AND 25 DEG IN A DRY FLAMPROOF AREA.	
21	DPC104 462	PILOT-II	801079517183 9 / MAMMUT PRIMER WHITE	Tall ship	340 / LITER			Jotun Paints (Europe) Ltd. Stather Road Flixborough, Scunthorpe North Lincolnshire DN15 8RR England Tel: +44 17 24 40 00 00 Fax: +44 17 24 40 01 00 SDSJotun@jotun.com	JOTUN	TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - undercoat primer whiteGENERAL SPECIFICATION - undercoat primer white	
22	DNQ103 698	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	1 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D	TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
23	DNQ106030	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	24 / ROLL	NO DATA AVAILAB LE		UK		UK ENGLAN D	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
24	DNQ103474	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	5 / ROLL	NO DATA AVAILAB LE		UK		UK ENGLAN D	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www. JOHN-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
25	DNM102639	127-2176	5331014771961 / SEAL- INTEGRAL	CATTER PILLER GENSET 3512B USA	12 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
26	DNM104914	PROPELLER MICHIGAN GOLDLINE	2010715220349 / PROPELLER MICHIGAN GOLDLINE CLOCKWISE ROTATION FOR 60 MM SHAFT DIA	MARINE GEAR BOX	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED</u> <u>GENERAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED</u>	
27	DPC103485	NO DATA AVAILABLE	0473502247695 / REFINED SODIUM BICARBONATE (OEM = ICI		30 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PAKISTAN) Packing = 25kg Bag							ENCLOSED WITH QUOTATION		
28	DPC104 418	G-1200	047550220561 3 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		8 / TUBE					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DPC103 423		044250942937 4 / VARNISH MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	USE ONWOOD UNDER CONDITIONS OF MARINE EX	440 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED GENERAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED	
30	DPC103 348	DEF-1145/1956	044250442007 9 / THINNER (SPEC) DEF STAN 80-38/2 1985 (PACKING 20 LTRS DRUM)		92 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-38/2 of 1985 GENERAL SPECIFICATION - DEFSTAN 80-38/2 of 1985	
31	DPC103 420		044250442009 4 / VARNISH FINISHING ARR DRY (packing 4liter tin)		12 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - S. NO INFORMATION REMARKS 01 NAME= SYNTHETIC CLEAR VARNISH (ELECTRIC VARNISH) 02 SPECIFIC GRAVITY= 0.87-0.91 03 COLOR= CLEAR HOMOGENEOUS DRAK BROWN 04 FLASH POINT= >30 °C 05 SURFACE DRY TIME= 5-6 HOURS 06 HARD DRY TIME= 24 HOURS 07 PACKAGING= 04 LITER (TIN PACKAGE) GENERAL SPECIFICATION - S.NO INFORMATION REMARKS 01 NAME= SYNTHETIC CLEAR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											VARNISH (ELECTRIC VARNISH) 02 SPECIFIC GRAVITY= 0.87-0.91 03 COLOR= CLEAR HOMOGENEOUS DRAK BROWN 04 FLASH POINT= >30 °C 05 SURFACE DRY TIME= 5-6 HOURS 06 HARD DRY TIME= 24 HOURS 07 PACKAGING= 04 LITER (TIN PACKAGE)	
32	DNQ106020	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		14 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
33	DPC103366	NO DATA AVAILABLE	0442502202381 / PAINT PRIMING GRAPHITE BASIS (RED LEAD)	BUXLY/ICI/BERGER/KOSAR GRP-E VIDE NHQ LT	60 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DPC103580	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. grade-1 i. a. w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S. COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 – 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,	
35	DPC103528	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. grade-1 i. a. w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque. <u>GENERAL SPECIFICATION</u> - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,	
36	DPC103600	NO DATA AVAILABL E	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		450 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATIO	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N	Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Di Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
37	DPC103459		0442509429119 / PAINT OIL FINISHING FOR MEASURES (BLUE)	FINISGING	96 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
38	DNQ106155	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		14 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. <u>GENERAL SPECIFICATION</u> - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
39	DPC103582		0474504740012 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)		12 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
40	DNQ106087	PURIFIED LOCALLY DEVELOPED	4220795055188 / EMERGENCY PURIFIED DRINKING WATER CONTENT 500 ML (LIFE RAFT).	S/PACK USED IN 20MEN LIFE RAFT	246 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DNQ104876	54.107.00	4210995413550 / INLINE INDUCTOR, 2.5" BSPF COUPLING, 445MM LG, 160.5 MM DIA	FIRE AND REPAIR PARTY POST UPPER DECK FO	4 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG, 160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8 GENERAL SPECIFICATION - Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG, 160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8	
42	DNQ105016	BS EN-3	4210705036007 / CO2 CYLINDER TROLLY MOUNTED 50KG WITH VALVE &HP HOSE DIA 0.75"	FIRE FIGHTING EQUIPMENT	3 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DES:CO2 CYLINDER TRALLY MOUNTED 50KG GENERAL SPECIFICATION - DES:CO2 CYLINDER TRALLY MOUNTED 50KG	
43	DNH106085	EAC-70/WP-1302/ECM 6500	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	1 / EACH/NUMBER	EAC-70/WP-1302/ECM 6500				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE GENERAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
44	DNM103336	F48E-P/DEU48	4130715089740 / CONDENSING UNIT CRUISAIR TYPE SELF A/C UNIT 4TON	MAIN A/C CRISAIR USA TYP.F48E-P.	1 / EACH/NUMBER	DEU48				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DNH104924		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	1 / EACH/NUMBER	WA60000514				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W GENERAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W	
46	DNQ104929	1-3-150 DEVELOPED BY DTD	4730992542747 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	2 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DNQ106154	1-3-150 DEVELOPED BY DTD	4730992542747 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	4 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DNQ101882	1-3-150 DEVELOPED BY DTD	4730992542747 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	1 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION		
49	DNQ106157	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	6 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
50	DNM100467	70HFR20	596175506777 7 / METAL STUD DIODE 70HFR20 METAL DO-5 PACKAGE	DORMAN D/G 500KVA (UK)	3 / EACH/NUMBER	70HFR20				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE</u> <u>GENERAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE</u>	
51	DPC104025	BS 2451, DEFSTAN: 80-73/1 OF 1977	801070100413 6 / PAINT NON SLIPING PREMIXED (LIGHT GREY) BS2451, DEFSTAN 80-73/1	FINISHING NON SLIP	100 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0mm Thickness Level = 2.0mm to 3.0 mm</u> <u>GENERAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0 mm Thickness Level = 2.0mm to 3.0 mm</u>	
52	DPC103279	HRC-407C (HFC-407C) GENETRON R-407C	683070511813 6 / GAS FOR (A/CS) R-407C (packing = 11.3 kg) (Purity level 99% Min)	A/C SPLIT (02TONS)	102.15 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - OEM: HONEYWELL (USA)</u> <u>GENERAL SPECIFICATION - OEM: HONEYWELL (USA)</u>	
53	DPC103530	HRC-407C (HFC-407C) GENETRON R-407C	683070511813 6 / GAS FOR (A/CS) R-407C (packing = 11.3 kg) (Purity level 99% Min)	A/C SPLIT (02TONS)	102.15 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED	<u>TECHNICAL SPECIFICATION - OEM: HONEYWELL (USA)</u> <u>GENERAL SPECIFICATION - OEM: HONEYWELL (USA)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
54	DPC103705	NIL-SHELF LIFE 3 MONTH	6810705039263 / DECK COMPOUND FLASH POINT 89C SP-GR-1009 (ANTI SKID)	LOCAL PURCHASE	50 / KILOGRAMME					D WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DPC105024	NO DATA AVAILABLE	6810731000999 / MARINE GRADE POLYESTER RESIN/ CRYSTIC 406E/ POLYPOL-1009/ LLOYD APPROVED EQUIVALENT PRODUCT	FOR GRP BOAT	75 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - General purpose unsaturated, polyester resin unpromoted thixotropic, laminating type orthophthalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 °C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25°C - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time, 30°C with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30°C accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25°C without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max) GENERAL SPECIFICATION - General purpose unsaturated, polyester resin unpromoted thixotropic, laminating type orthophthalic, suitable for hand and spray lay up of marine vessels in	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 "C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time,30oC with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max)	
56	DPC104 801	NO DATA AVAILAB L E	681073100099 9 / MARINE GRADE POLYESTER RESIN/ CRYSTIC 406E/ POLYPOL-1009/ LLOYD APPROVED EQUIVALENT PRODUCT	FOR GRP BOAT	880 / KILOGR AMME					TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - General purpose unsaturated, polyester resin un promoted thixotropic, laminating type orthophatalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 "C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											175 (Min) k. Typical gel time,30oC with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max)<u>GENERAL SPECIFICATION</u> - General purpose unsaturated, polyester resin unpromoted thixotropic, laminating type orthophatalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 °C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time,30oC with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max)	
57	DNH103052	NO DATA AVAILABLE	1308750530106 / REFRIGERATOR 10.CU FT-220V AC (NO FROST)		1 / EACH/NUMBER	NO DATA AVAILABLE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
58	DNH104051	UNE-36011	953070528393		2 / METER	NA				TDS\BROCHER OR	<u>TECHNICAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6 / HIGH CARBON STEEL ROD (C35K) DIA -80 MM							PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	Dimension Dia: 80mm Length: 2750mm Composition C=0.3200-0.3900 Cr=0.2000-0.4000 Mn=0.5000-0.8000 Ni=0.3900 P=0.025 (Max) S=0.025(Max) <u>GENERAL SPECIFICATION</u> - Dimension Dia: 80mm Length: 2750mm Composition C=0.3200-0.3900 Cr=0.2000-0.4000 Mn=0.5000-0.8000 Ni=0.3900 P=0.025 (Max) S=0.025(Max)	
59	DNQ102 808	RADTARG E-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		2 / EACH/NUMBER	RADTAR GE-H				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting <u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting	
60	DNQ103 471	RADTARG E-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		3 / EACH/NUMBER	RADTAR GE-H				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting <u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting	
61	DNQ102 317	RADTARG E-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		5 / EACH/NUMBER	RADTAR GE-H				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION	cumulative dose graph data log and export user device, management fresh hold time setting <u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting	
62	DNQ104864	RADTARGE-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		10 / EACH/NUMBER	RADTARGE-H				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting <u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting	
63	DNQ104329	RADTARGE-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		3 / EACH/NUMBER	RADTARGE-H				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting <u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting	
64	DNM100023	3681P046	533079523819 3 / GASKET TIMING CASE COVER		1 / EACH/NUMBER	1103A-230				TDS/BROCHER OR PIC OF ITEM MUST BE	<u>TECHNICAL SPECIFICATION</u> - GASKET TIMING CASE COVER I: 21.26 inches (540mm) w: 12.6 inches h: 0.59 inch free shape type inner cut-out /bolt pattern <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION	SPECIFICATION - GASKET TIMING CASE COVER I: 21.26 inches (540mm) w: 12.6 inches h: 0.59 inch free shape type inner cut-out /bolt pattern	
65	DNM103419	0541-1564	293501574275 1 / PUMP KIT		1 / EACH/NUMBER	C1 10 D5				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> Refer to Parts List for APL 66P843597 206416 - Support Gasket (QTY: 01) 206455 - Water Pump Gasket (QTY: 01) 206457 - O-Ring Seal (QTY: 01) 3179035 - Water Transfer Connection Gasket (QTY: 01) 3252438 - Tube Connector (QTY: 01) 3975774 - O-Ring Seal (QTY: 02) 4006795 - Connection Gasket (QTY: 01) 3050944 - Flange Gasket (QTY: 01) 3635395 - Water Transfer Connection Gasket (QTY: 02) <u>GENERAL SPECIFICATION -</u> Refer to Parts List for APL 66P843597 206416 - Support Gasket (QTY: 01) 206455 - Water Pump Gasket (QTY: 01) 206457 - O-Ring Seal (QTY: 01) 3179035 - Water Transfer Connection Gasket (QTY: 01) 3252438 - Tube Connector (QTY: 01) 3975774 - O-Ring Seal (QTY: 02) 4006795 - Connection Gasket (QTY: 01) 3050944 - Flange Gasket (QTY: 01) 3635395 - Water Transfer Connection Gasket (QTY: 02)	
66	DPC105013	INDUSTRIAL SEALANT 800	803000080217 1 / INDUSTRIAL SEALANT (SEALING COMPOUND) (Each Tube contains 147.9 ml)		1 / EACH/NUMBER	EC800				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> 3M Scotch-Seal Industrial Sealant 800 is a reddish brown, brushable sealant that air dries to a flexible seal that resists water, oils and fuel and adheres to many metallic surfaces. useful temperature range: -65° to 200°F (-54 to 93°C). <u>GENERAL SPECIFICATION -</u> 3M Scotch-Seal Industrial Sealant 800 is a reddish brown, brushable sealant that air dries to a flexible seal that resists water, oils and fuel and adheres to many metallic surfaces. useful	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											temperature range: -65° to 200°F (-54 to 93°C).	
67	DNM101087	8199620001	4820725350812 / drain valve		2 / EACH/NUMBER	NK200				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> DRAIN VALVE DN-50 Motorized Valve get the signal from level sensor from EVAC collecting tank and DN-50 motorized valve is operated for Auto Drain Valve of EVAC system. <u>GENERAL SPECIFICATION -</u> DRAIN VALVE DN-50 Motorized Valve get the signal from level sensor from EVAC collecting tank and DN-50 motorized valve is operated for Auto Drain Valve of EVAC system.	
68	DPC105021	ASTM D1193	6810003564936 / Distilled-deionized water		60 / LITER	N/A				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> N/A <u>GENERAL SPECIFICATION -</u> N/A	
69	DNQ106270	15199001	4220795289489 / SOLAS SOFTPACK RFD (FIRST AID KIT) FOR LIFE RAFT - LIFE BOAT		12 / EACH/NUMBER	life raft				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
70	DNM104707	Etanorm g 50-250 & 50-160	4320705349831 / condensate pump with Motor of lg 60 ton plant etanorm Etn 050-032-160		2 / EACH/NUMBER	etanorm g 50-250				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> CONDENSATE PUMP INSTALLED AT MIN OT AC PLANT OF PNS SHIFA. SINGLE STAGE PUMP , HORIZONTAL VOLUTE CASING PUMP 3 PHASE ELECTRIC MOTOR DRIVEN TYPE ETANORM TYPE SERIES <u>GENERAL SPECIFICATION -</u> -CONDENSATE PUMP INSTALLED AT MIN OT AC PLANT OF PNS SHIFA. SINGLE STAGE PUMP , HORIZONTAL VOLUTE CASING PUMP 3 PHASE ELECTRIC MOTOR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DRIVEN TYPE ETANORM TYPE SERIES	
71	DNQ104884	0841-3009	804073530063 7 / REPAIR ADHESIVE 70 ML TUBE		12 / EACH/N UMBER	n/a				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
72	DPK106060	FCW NMMA CERTIFIED	915076517954 6 / YAMALUBE/A DDINOL API SJ SAE 10W- 30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	500 / LITER	JAPAN		JAPAN	SHELL	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
73	DPK104327	CORENA S2 P150	915070519669 9 / SHELL CORENA S2 P150 (PACKING = 20 LITERS)	HPAC PNFT	80 / LITER	NA	NA	M/S SHELL	M/S SHELL		TECHNICAL SPECIFICATION - SHELL CORENA S2 P150 GENERAL SPECIFICATION - SHELL CORENA S2 P150	
74	DPK104366	MOBILUBE GX 80W- 90	9150SV120000 4 / LUBE OIL MOBILUBE GX 80W-90	RO PLANTS	10 / LITER	MOBILUBE GX 80W-90	RO 00752/RO 00753	EXXON MOBIL FUELS AND LUBRICANTS CO CHINA	EXXON MOBIL	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - LUBE OIL MOBIL GEAR 600 XP 100 GENERAL SPECIFICATION - LUBE OIL MOBIL GEAR 600 XP 100	
75	DNM105145	itd/SES/AF /0089	299070520319 3 / PORT MAIN ENGINE EXHAUST FLAP	M ENGINE MTU16V396TE 94 GERMANY	1 / EACH/N UMBER	MTU16V3 96TE94	5591986	FAST ENGINEERING & SERVICES A-49 MEZZANINE FLOOR SALMAN TOWER NATIONAL HIGHWAY MALIR KARACHI	M/S SYSCO	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Hard copy for Technical specs will pe be provided shortly. <u>GENERAL SPECIFICATION</u> - Hard copy for Technical specs will pe be provided shortly.	
76	DNM103335	0781- 5134/0781-	343871523105	METAL SPRAY GUN (ZINC)	1 / EACH/N	ESS4-15- 993 /		THERMADYNE® INDUSTRIES, INC. 2800	THERMA DYNE®	TDS\BROCHER OR	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		3604	9 / HIGH CAPACITY ACETYLENE REGULATOR (VICTOR USA)	WITH PANEL 16 E USA	UMBER	ess42-15-993		AIRPORT ROAD ,DENTON TX-76208 (940) 566-2000 WWW.VICTOREQUIP.COM US. CUSTOMER CARE: 1-800-426-1888 FAX: 1-800-535-0557	INDUSTR IES, INC.	PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	HIGH CAPACITY ACETYLENE REGULATOR (VICTOR USA) <u>GENERAL SPECIFICATION - HIGH CAPACITY ACETYLENE REGULATOR (VICTOR USA)</u>	
77	DPC106 175	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGR AMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTI C MARINE	TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL <u>SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
78	DNM962 99	PP97301/3 931019/55 29516	281501523007 8 / Cylinder Head GASKET	CUMMINS 200 KVA DG	1 / EACH/N UMBER	6CTA8.3	78515443	Cummins Americas Inc, 3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Tell (1-954) 431-5511 Fax (1-954)433-5797	USA	TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - CYLINDER HEAD GASKET D/G CUMMINS USAGENERAL SPECIFICATION - CYLINDER HEAD GASKET D/G CUMMINS USA</u>	
79	DPC104 423	ODD099X 05	251079514764 2 / HARDTOP AS BLACK A (3.94 LTRS PACKING), PAINTS.	PAINTS SCHEM FOR TALL SHIP	20 / LITER	NO DATA AVAILAB LE		UK	OEM: JOTUN PAINTS EUROPE LTD STATHER ROAD, FLIXBOR OUGH, DN15 8PR,TEL: +44 1724 400000, FAX:+44 1724 400100.	TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - OEM:JOTUN PAINTS EUROPE LTD Stather road,FLIXBOROUGH, DN15 8PR,TEL:+44 1724 400000,FAX:+44 1724 400100. OEM:MS SUE HOEY CUSTOMER SERVICE ADVISOR JOTUN PAINTS (EUROPE)LTD FLIXBOROUGH(UK)DDI +441724 400185,FAX:+441724 400130 ,E-mail :sue.hoeey@jotun.co.uk,http: //www.jotun.co.uk</u> <u>GENERAL SPECIFICATION - OEM:JOTUN PAINTS EUROPE LTD Stather road, FLIXBOROUGH, DN15 8PR,TEL:+44 1724 400000,FAX:+44 1724 400100.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									POINT OF CONTRACT:MS SUE HOEY CUSTOMER SERVICES ADVISOR ,JOTUN PAINTS (EUROPE) LTD, FLIXBOROUGH (UK),D		OEM:MS SUE HOEY CUSTOMER SERVICE ADVISOR JOTUN PAINTS (EUROPE)LTD FLIXBOROUGH(UK) DDI +441724 400185,FAX:+441724 400130 ,E-mail :sue.hoeey@jotun.co.uk,http://www.jotun.co.uk	
80	DNM99183	3901793/3934048	2815012113886 / PIN PISTON	CUMMINS STANDBY EMERGENCY GENERATOR 4BT3-9D UK	6 / EACH/NUMBER	4BT3-9D	MAD 46950895 RSD 46954407	CUMMINS LTD T/A CUMMINS UK RUTHERFORD DRIVE, PARK FARM INDUSTRIAL ESTATE, WELLINGBOROUGH, NORTHAMPTONSHIRE, UK Tel : 01933 672 200 Fax : 01933 403 200 Email/URL : www.cummins.com	CUMMINS LTD UK	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
81	DPK104369	GREATWALL HM 100	9150SV5231607 / LUBRICATING OIL GREATWALL HM 100	STERN TUBE	2000 / LITER	GREATWALL HM 100		SINOPEC CO,CHINA	CHEVRON MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - LUBRICATING OIL GREATWALL HM 100 technical spec attached as document GENERAL SPECIFICATION - LUBRICATING OIL GREATWALL HM 100 technical spec attached as document	
82	DPC106098	SAME AS S NO 9 EXECPT SHADE.	0442502201637 / PAINT FINISHING (GREEN)	USES FOR STEEL ALUMINUM OR WOOD ON GLASS	314 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Avallability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
83	DPC106064	2	0442500004314 / ACETONE TECHNICAL	CATHODIC PROTECTION SYSTEM	25 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Appearance: Liquid, Colour: Colourless Odour, Characteristics: Explosion Limit value 1,8-11,5% Vapor, Pressure Value: 12,6 Kpa Test Temperature: 20c GENERAL SPECIFICATION - Appearance: Liquid, Colour: Colourless Odour, Characteristics: Explosion Limit value 1,8-11,5% Vapor, Pressure Value: 12,6 Kpa Test Temperature: 20c	
84	DPC106084	WHO/SIF/13.R5	0442502201201 / Lambda Cyhalothrin 2.5 or 25% EC. 01LTR PLASTIC PACKING WITH REGISTERED LABEL.	KEROCANE OIL.	120 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label. GENERAL SPECIFICATION - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label.	
85	DPC106091	MAINLY SPECIFIED AS A PRE-WELD	0442502201209 / PAINT ALUMINEUM DUCO (NSSD/C01/0442/GEN/173DT 060393)		35 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DPC106103		0442504420051 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal	FINISHING INTERIOR	678 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTION PRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101 OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg GENERAL SPECIFICATION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing								- 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
87	DPC106 182		044250943448 1 / PAINT ACID AND ALKALY RESISTANT A/R (BLACK) 05 LTR TIN Flash Point: 32 Degree C (min) Packing: standard oem 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	113 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED 3. DEFSTAN 80-72/3 OF 2006GENERAL SPECIFICATION - 1. NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED 3. DEFSTAN 80-72/3 OF 2006	
88	DPC106 188		044250943448 3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	141 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C OF 1996GENERAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C OF 1996	
89	DPC106 113	106 OF BS381-C OF 1996	044250442006 1 / PAINT VEHICLE CELLULOSE (ROYAL NAVY	VEHICLES, DECORATIVE FINISHING	737 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - DEFSTAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996. GENERAL SPECIFICATION - DEFSTAN 80-37/2 COLOR SHADE NO,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BLUE)							ENCLOSED WITH QUOTATION	106 OF BS 381 C OF 1996.	
90	DPC106 120		0442504420069 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		344 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
91	DPC106 141		0442504420075 / THINNER		311 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DPC106 179		0442509423538 / PAINT MARKING BRUSH STENCILLING (BLACK) type: alky6ed, Flash Point: 32 Degreee C (Min) moethod of application brushing, Packing: 04 ltr tin gauge of drum 26 to 28 swg	N B C D MARKING ETC.	113 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed GENERAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed	
93	DPC106 194		0442799423542 / Paint Marking, Stencilng (Signal Red) flash point: 32 degree C (Min) method of		66.5 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. DEFSTAN 80-68/4 2. NS/P/012 OF 2013 (REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996 GENERAL SPECIFICATION - 1. DEFSTAN 80-68/4 2. NS/P/012 OF 2013	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			application: brushing & stenciling type: Alkyed Packing: 04 liter tin gauge of tin 26 to 28 SWG							N	(REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996	
94	DPC106 040		044250942937 4 / VARNISH MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	USE ONWOOD UNDER CONDITIONS OF MARINE EX	293 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED GENERAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED	
95	DPC106 036		044250442004 3 / PAINT FINISHING MID BROWN GLOSS FLASH POINT 32C (04 LTR Packing)	MULTI COAT FINISH PRIMED SEEL ALUMINUM	358 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996 GENERAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996	
96	DPC106 142		044250442009 7 / VARNISH OIL EXTERIOR GARDE-II	AMPN	79 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DPC106 166	WHO/SIF/ 14 R-5 (6TH EDITION OF 85)	044250442013 6 / Insecticide Malathian 60		120 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Insecticide Malathion 57 to 60% EC, SPECIFICATION: Active Ingredience (A.1) Malathion 57 to 60% EC W/W PACKING: 01 Ltr Plastic Packing with registered label GENERAL SPECIFICATION - Insecticide Malathion 57 to 60% EC, SPECIFICATION: Active Ingredience	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(A.1) Malathion 57 to 60% EC W/W PACKING: 01 Ltr Plastic Packing with registered label	
98	DNQ105787	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		6 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
99	DPC106025	NO DATA AVAILABLE	0442502202381 / PAINT PRIMING GRAPHITE BASIS (RED LEAD)	BUXLY/ICI/BERGER/KOSAR GRP-E VIDE NHQ LT	210 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
100	DPC106174	NO DATA AVAILABLE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		90 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Date D. Water Capacity E. Cylinder Weight F. Design Gas	
101	DPC106172	SPEC,DEF 1052 COLOURS TO BS 381C	0442509107035 / PAINT FNSHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/566DT210902		566 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
102	DPC106063	NO DATA AVAILABLE	0276145055100 / CONTACT CLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS) Packing = 200ml	FOR GENERAL USE	115 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
103	DPC106041	NO DATA AVAILABLE	0473504730033 / DISTILLED WATER (10 ltr packing)		60 / GALLON					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
104	DNM104943	A/C 1-1/2 TON 03 YEAR GUARANTEED	4310731001978 / A/C COMP 50HZ 220-240V 18000BTU 1-PH COPLAND USA 52-68 LRA	A/C 1-1/2 TON	1 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DNH105790	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
106	DNH105789	9140	4110705041926 / REFRIGERATOR 8CUFT-283 LITERS DOUBLE DOOR 190/230 VOLTS SINGLE PHASE 50HZ WITH OVER LOAD CIRCUIT	REFRIGERATOR 8CUFT (283LITRES)	2 / EACH/NUMBER	9140				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
107	DPK104088	AEROSHELL GREASE 6	9150001806383 / AEROSHELL GREASE 6 (PACKING 03 KG)	SELF	6 / CAN					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
108	DPC103756	BELZONA 9111	8010705040915 / BELZONA 9111 CLEANER/DEGREASER (0.5 liter packing)	FOR DEGREAS SURFACE & CLEANS APPLI TOOLS	6 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
109	DPC106236	NO DATA AVAILABLE	0473500000111 / PASTE OIL RED OXIDE		34 / KILOGRAMME	NO DATA AVAILABLE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DPC104431	850-761-04	8010PK5064841 / EPOXY THINNER 850-761-04 (04 Liter Packing)		20 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION		
111	DPC106044	NO DATA AVAILABLE	6850785031104 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMENT FOR PNS NASR	340 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. <u>GENERAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
112	DPC103708	BUTANOX M-60	6810731000994 / METHAILETHYLE KETONE PEROXIDE		1 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> PACKING: 20,25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4 <u>GENERAL SPECIFICATION -</u> PACKING: 20,25 OR 30 LTRS: SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4	
113	DPC103224	B71003, B71046 OR ACCELRA	6810731001000 / COBALT BASED		30 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST	<u>TECHNICAL SPECIFICATION -</u> Accelerator Cobalt based, Preferably USA West Europe, Japan make	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		TOR G (POLYACC P-A)	ACCELERATOR / CRYSTIC ACCELERATOR G/ POLYACC P-A/ LLOYD APPROVED EQUIVALENT PRODUCT							BE ENCLOSED WITH QUOTATION	mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25 KG <u>GENERAL SPECIFICATION</u> - Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25 KG	
114	DPC105022	B71003, B71046 OR ACCELERATOR G (POLYACC P-A)	6810731001000 / COBALT BASED ACCELERATOR / CRYSTIC ACCELERATOR G/ POLYACC P-A/ LLOYD APPROVED EQUIVALENT PRODUCT		40 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25 KG <u>GENERAL SPECIFICATION</u> - Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25 KG	
115	DPC104427	33940-1288	6810002817453 / MERCURY ACS		700 / GRAM					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION		
116	DNM103418	0121-0258	2815715267536 / FEED PUMP (BOSCH PART No. 9440 030 030)		1 / EACH/NUMBER	C22 D5				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
117	DPC104057	Q3-1566	8040015990596 / ADHESIVE (SEALANT SILICON) (310 ML CARTRIDGE) DOWSIL BRAND		1 / CARTRIDGE	NA				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
118	DPC102355	555623	6810251617210 / NITRITE NO 1 TABLETS (POTASSIUM NITRITE, ANALYZED REAGENT)		22 / BOTTLE	NITRITE NO 1 TABLETS				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Manufacturer Address Wilhelmsen Ships Services AS P.O Box 33 NO-1324 LYSAKER, NORWAY Tel: +4767584550 General Specifications Bottle contains 100 tablets Used for measuring Nitrite contents in NALFLEET-2000 General Specification Item is part of SPECTRAPACK 309 Cooling Water Test Kit (Part No 739466, NSN 6630735232429) GENERAL SPECIFICATION - Manufacturer Address Wilhelmsen Ships Services AS P.O Box 33 NO-1324 LYSAKER, NORWAY Tel: +4767584550 General Specifications Bottle contains 100 tablets Used for measuring Nitrite contents in NALFLEET-2000 General Specification Item is part of SPECTRAPACK 309 Cooling Water Test Kit (Part No 739466, NSN 6630735232429)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
119	DPK105823	GB495-65	9150705139823 / CALCIUM BASE GREASE GREY (KUNLUN) 15KG	BOATBEARING OF ELECTRIC WINCH	15 / KILOGRAMME	NO DATA AVAILABLE		UK	UK	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
120	DPC106331	1141674/22567233/22567259 (20 ltr)	6150735141424 / COOLANT READY MIX (volvopenta)	VOLVOPANTA ENGINE	130 / LITER	NO DATA AVAILABLE	00		M/S AB VOLVOPANTA 40508 GOTEBO RG SWEEDN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - PACKING: 05 LITER CAN /20 Liter can GENERAL SPECIFICATION - PACKING: 05 LITER CAN /20 Liter can	
121	DPC106324		0473546004703 / SODA CAUSTIC (PACKING 25 KG)		300 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Soda Caustic (chemical nomenclature SODIUM HYDROOXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments GENERAL SPECIFICATION - Soda Caustic (chemical nomenclature SODIUM HYDROOXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments	
122	DPC106354		6840705057109 / Insecticide-K-Othrine 25 WP (Wetable Powder)	TO CONATROL INSECTS COCKROACHES ANTS ETC	100 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - Permethrin 0.5% D Insecticide active Ingredient (A.1) Permethrin 0.5% Dust W/W PACKING: 1 Kg Polyethylene Packing with registered label GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATION	Permethrin 0.5% D Insecticide aCTIVE Ingredience (A.1) Permethrin 0.5% Dust W/W PACKING: 1 Kg Polyethylene Packing with registered label	
123	DNQ106315	NO DATA AVAILABLE	0262500001365 / LADDER-ALUMINIUM-EXTENDING-28FEET CAPABLE OF WITH STANDING		1 / EACH/NUMBER	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. Closed height: 5 Meter 2. Extended height: 9 Meter 3. Approximately weight: 26 KG 4. Loading capacity: 150 KG 5. Warranty: Life time GENERAL SPECIFICATION - 1. Closed height: 5 Meter 2. Extended height: 9 Meter 3. Approximately weight: 26 KG 4. Loading capacity: 150 KG 5. Warranty: Life time	
124	DPC106335	BS 3591 of 1985	6810992201733 / METHYLATED SPIRIT INDUSTRIAL GEN/PURPOSE (Packing = 20 LTR), highly flammable	FOR GENERAL USE	123 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
125	DNH106314	NO DATA AVAILABLE	4110500530125 / REFRIGE 12CU/FT DOUBLE DOOR 220V 50 HZ PHILCO/DAWLANCE/WAVES/PEL	DAWLANCE, WAVES, PHILICO (PAKISTAN), PEL (PAK)	2 / EACH/NUMBER	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
126	DPC106374	NO DATA AVAILABLE	8010705098453 / SPRAY PAINT TIN (BOSNY no 39 black + BOSNY no 40 White) (300 GM bottle each)	PRESSURE GAUGES FOR REPAIR/CALIBRATION	60 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DPC106356	MIL-C-43616	6850010457929 / CLEANING COMPOUND,	CIWS	3 / EACH/NUMBER					TDS/BROCHER OR PIC OF	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			AIRCRAFT SURFACE							ITEM MUST BE ENCLOSED WITH QUOTATION	AVAILABLE	
128	DPC106373	BS 2451, DEFSTAN: 80-73/1 OF 1977	8010701004136 / PAINT NON SLIPING PREMIXED (LIGHT GREY) BS2451, DEFSTAN 80-73/1	FINISHING NON SLIP	195 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0mm Thickness Level = 2.0mm to 3.0 mm GENERAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0 mm Thickness Level = 2.0mm to 3.0 mm	
129	DNM104942	B57121X513F075xx/P7800B3X/P425S-2373D-512-7.5T (340970)	4140715092410 / A/C SEA/CHILL WATER PUMP WITH MOTOR	A/C UNIT OEM:M/S TAYLOR MADE ENVIRONMEN T	1 / EACH/N UMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OEM: DOMETIC ENVIROMENTAL CORPORATION P.O BOX 15299 RICHMOND USA VA 23227-0699 GENERAL SPECIFICATION - OEM: DOMETIC ENVIROMENTAL CORPORATION P.O BOX 15299 RICHMOND USA VA 23227-0699	
130	DNM105090	751-40551	2815795093701 / INLET VALVE	LISTER PETTER D/G LPWT 4 OEM: UK	1 / EACH/N UMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
131	DNQ106312	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/N UMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
132	DPC106325	DEFSTAN 68-30/1 OF 1974	0474502204834 / CHLORINATED LIME, TECHNICAL 30% MIN available CHLORINE (25 KG Packing)		4415.64 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 68-30/1 OF 1974 OEM COC DATE OF MANUFACTURING & EXPIRY OEM TEST CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE <u>GENERAL SPECIFICATION - DEFSTAN 68-30/1 OF 1974 OEM COC DATE OF MANUFACTURING & EXPIRY OEM TEST CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE</u>	
133	DNM104696	200931012006	5305123853365 / BOLT AH HEX	MTU MAIN PROP DIESEL ENGINE 16V4000M90 GERMANY	42 / EACH/NUMBER	MTU 16V4000M90	AZMAT 527108133-36 & DEHSHT 527108596-99	MTU FRIEDRICHSHAFEN GMBH ST MAYBACHPLATZ 1 GERMANY	MTU GERMAN Y	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AVAILABLE IN ILS <u>GENERAL SPECIFICATION - AVAILABLE IN ILS</u>	
134	DPK105838	SHELL OMELAVISCOSITY-68	2590735165521 / HUB OIL	MJP	10 / LITER	MJP 750 SERIES		MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	MJP OSTERBY	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN <u>GENERAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN</u>	
135	DPK105804	SAE 90 (80W90)	9150251145135 / ENGINE GEAR OIL SAE 90 (80W90) (03 Ltr to 18 Ltr PACKING)	YAMAHA OUTBOARD ENGINE	36 / LITER	NO DATA AVAILABLE		US	SOCIETY OF AUTOMOTIVE ENGINEERS INC, COMMONWEALTH DRIVE, WARREN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - SAE 90 (80W90) <u>GENERAL SPECIFICATION - SAE 90 (80W90)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
									DALE, USA., PSC: 15096, TEL#724-776-4841			
136	DNM105222	4907485/WF2126	2940715154573 / RESISTER CORRSION	CUMMINS ENGINE 550KVA FILTER	1 / EACH/NUMBER	QS X 15 CUMMINS	79308093	M/S CUMMINS INC.500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 TEL:812-377-3920 FAX:812-377-1715 DUNS 006415160 STEVE.A.HEWITT@CUMMINS.COM	CUMMINS INC. USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OEM:M/S CUMMINS INC.500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX:812-377-1715 DUNS 006415160 STEVE.A.HEWITT@CUMMINS.COM GENERAL SPECIFICATION - OEM: M/S CUMMINS INC.500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 TEL:812-377-3920 FAX: 812-377-1715 DUNS 006415160 STEVE.A.HEWITT@CUMMINS.COM	
137	DPK105784	TEXAMAT C 1888 SAE DEXRON-III	9150014878530 / STEERING LUB OIL (PETROL/DIESEL ENGINE MT VEHICLES) (01 ltrs packing)	MT VEHICLE	70 / BOTTLE			GENERAL MOTORS CORP 3044 W GRAND BLVD DETROIT MI UNITED STATES PSC: 48202-3091 TEL: 248-857-2576	GENERAL MOTORS CORP	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
138	DPC106361	SALT-X	6850013851430 / Corrosion removing compound		6 / BOX			3609 SCOTT FUTRELL DR., CHARLOTTE, NC	INNOVATIVE CHEMICALS INC DBA INNO-CHEM	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AS PER TP GENERAL SPECIFICATION -AS PER TP	
139	DNM104918	imp/gp/str/pk-01	2010715221036 / P BRACKET FOR CLOCKWISE ROTATION SHAFT 50 MM DIA	SHAFTING ARRANGEMENT	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - P-BRACKET FOR CLOCK WISE ROTATION SHAFT , SINGLE ARM MAIN STRUT, CAST MnBr, FOR 50MM DIA SHAFT TYPE: OMM VTR 50 BRONZE QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										N	SPECIFICATION - P-BRACKET FOR CLOCK WISE ROTATION SHAFT , SINGLE ARM MAIN STRUT, CAST MnBr, FOR 50MM DIA SHAFT TYPE: OMM VTR 50 BRONZE QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED	
140	DPC106 289	NO DATA AVAILABL E	047350942924 4 / PIGMENT POWDER (LEAD CHROME) BS-282		30 / KILOGR AMME					TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - Yellow oxide (fine powder) Plastic packing 0.5 Kg Brand Name: Blue Bird GENERAL SPECIFICATION - Yellow oxide (fine powder) Plastic packing 0.5 Kg Brand Name: Blue Bird	
141	DPC106 287	NO DATA AVAILABL E	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		270 / KILOGR AMME					TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
142	DPC106 317	NO DATA AVAILABL E	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity		45 / KILOGR AMME					TDS\BROC HER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			99.5%) wight 01 to 45 kg with protection cap							ENCLOSED WITH QUOTATION	Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Dioxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
143	DPC106080	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA <u>GENERAL SPECIFICATION</u> - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
144	DPC106286	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA <u>GENERAL SPECIFICATION</u> - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
145	DPC106318	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	FORAN USA <u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA <u>GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
146	DRG100520	TRI CYCLE	2340ZO6569529 / TRI CYCLE		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - 1.</u> Overall dimensions of tricycle to be as per drawing. 2. Steel frame of welded tubing. 3. Wooden frame mounted on rear axle behind seat for loading of items. 4. Rear axle to be supported on shock absorbers (coil or leaf springs). 5. Internal side of Wooden frame to be lined with 1 inch soft rubber padding. 6. Chain length of approximately 9 ft 2 inches 7. Tricycle to be delivered in yellow paint scheme (minimum 2 coats). 8. Rear tires to be heavy duty used on motorcycles (CG125) Part No 42701-KCS- 65K or equivalent. 9. Tricycle to be provided with following set of standard spares: a. 1 x seat b. 1 x chain c. 1 x set of Brake pads d. 2 x brake wires e. 1 x set of pedals f. 3 x air charging nozzles PHOTO COPY OF DRAWING HELD WITH TECH LIB MADE IN PAKISTAN <u>GENERAL SPECIFICATION - 1.</u> Overall dimensions of tricycle to be as per drawing. 2. Steel frame of welded tubing. 3. Wooden frame mounted on rear axle behind seat for loading of items. 4. Rear axle to be supported on shock absorbers (coil or leaf	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											springs). 5. Internal side of Wooden frame to be lined with 1 inch soft rubber padding. 6. Chain length of approximately 9 ft 2 inches 7. Tricycle to be delivered in yellow paint scheme (minimum 2 coats). 8. Rear tires to be heavy duty used on motorcycles (CG125) Part No 42701-KCS- 65K or equivalent. 9. Tricycle to be provided with following set of standard spares: a. 1 x seat b. 1 x chain c. 1 x set of Brake pads d. 2 x brake wires e. 1 x set of pedals f. 3 x air charging nozzles PHOTO COPY OF DRAWING HELD WITH TECH LIB MADE IN PAKISTAN	
147	DSA103090	536-415-17DET6	5985705233298 / SANDOW		10 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Reference physical properties of Al. Alloy AA6061 Property Unit VALUE 1. Density Kg/m ³ 2700 2. Elastic Modulus (TENSION/COMPRESSION) GPA 68.9 3. Coefficient of Linear Thermal EXPANSION (A)(20°C to 100°C) PPM/°C 23.6 4. Thermal Conductivity (at 20°C) W/mK 167 5. Specific Heat J/g°C 0.896 CHEMICAL COMPOSITION (AL. ALLOY AA6061) element (% by weight) 1. copper (cu) 0.15-0.4 2. magnesium (mg) 0.8-1.2 3. silicon (si) 0.4-0.8 4. iron (fe) 0.7 (max) 5. manganese (mn) 0.15 (MAX) 6. zinc (zn) 0.25 (MAX) 7. titanium (ti) 0.15 (MAX) 8. chromium (cr) 0.04-0.35 9. other each 0.05 (MAX) 10. other total 0.15 (MAX) 11.mg si ratio 1.6-1.8 12-aluminium (al) balance GENERAL SPECIFICATION - Reference physical properties of Al. Alloy AA6061 Property Unit VALUE 1. Density Kg/m ³ 2700 2. Elastic Modulus (TENSION/COMPRESSION) GPA 68.9 3. Coefficient of Linear Thermal	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											EXPANSION (A)(20°C to 100°C) PPM/°C 23.6 4. Thermal Conductivity (at 20°C) W/mK 167 5. Specific Heat J/g°C 0.896 CHEMICAL COMPOSITION (AL. ALLOY AA6061) element (% by weight) 1. copper (cu) 0.15-0.4 2. magnesium (mg) 0.8-1.2 3. silicon (si) 0.4-0.8 4. iron (fe) 0.7 (max) 5. manganese (mn) 0.15 (MAX) 6. zinc (zn) 0.25 (MAX) 7. titanium (ti) 0.15 (MAX) 8. chromium (cr) 0.04-0.35 9. other each 0.05 (MAX) 10. other total 0.15 (MAX) 11.mg si ratio 1.6-1.8 12- aluminium (al) balance	
148	DSB96222	SIPMAA9000400	472014521619 8 / HOSE ASSEMBLY METALIC DN16 250X250		2 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> 2.1.10.1-HOSES XJ20012 (18FH000K0106) manufacturer . indret part no . SIPMAA9000400 dimenation. L=500MM MAXIMUM OPERATING PRESSURE . 10 BAR MAXIMUM OPERATING TEMPURATURE . 50 C <u>GENERAL SPECIFICATION -</u> 2.1.10.1-HOSES XJ20012(18FH000K0106) manufacturer . indret part no . SIPMAA9000400 dimenation. L=500MM MAXIMUM OPERATING PRESSURE . 10 BAR MAXIMUM OPERATING TEMPURATURE . 50 C	
149	DSB106231	LOCAL ITEM	000000050000 1 / GARBAGE BAG		600 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<u>SPECIFICATION</u> - Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag	
150	DSA97938	GSM141-08F5MLEB ZCN17-03	5306143299374 / VIS-F90EV1-CARRE-B-ZISCN17-0 (SCREW)		1000 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
151	DSB97945	EMB4PS-D1-SEW	5935705174621 / EMBASE 4PIN MALE		5 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
152	DSB96224	SIPMAA9000300	4720145216197 / FLEXIBLE HOSE ASSEMBLY METALLIC 200X200 (XJ20013)		2 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - 2.1.10.1-HOSES XJ20013() (18FH000K0105) MANUFACTURER . INDRET PART NO . SIPMAA9000300 DIMENATION. L=400MM MAXIMUM OPERATING PRESSURE . 10 BAR MAXIMUM OPERATING TEMPURATURE . 50 C <u>GENERAL SPECIFICATION</u> - 2.1.10.1-HOSES XJ20013() (18FH000K0105) MANUFACTURER . INDRET PART NO . SIPMAA9000300 DIMENATION. L=400MM MAXIMUM OPERATING PRESSURE . 10 BAR MAXIMUM OPERATING TEMPURATURE . 50 C	
153	DSA102568	Q1-52-8-10X100	4730142910075 / RACCORD DROIT Q1-52-8-10X100		52 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(adapter straight tube to boss)									