LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 24-11-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)

2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.

3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.

4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL:	clp@paknavy.gov.pk, localpurchasedivision@gmail.com
PHONE:	021-48508524, 48508828,
WHATSAPP NO.	92-322-0188121 (Message Only)

TENDER BULLETIN

LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE110109	NOT KNOWN	7920705181271 / BROOM SCRUBBING DECK (FOR DECONTAIMINATION)	NIL	10 / EACH/NUMBER		NIL	LOCAL MARKET	NIL		TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21	
2	DGD110061	NO DATA AVAILABLE	0035500000379 / LADLE S/S HANDLE (L-13") WITH WOODEN GRIP,POT WD 3.5".		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
3	DGD110043	NO DATA AVAILABLE	0032500000155 / POTS TEA STAINLESS STEEL MEDIUM SIZE		3 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Stainless Steel grade (Food Grade) Material (Food Grade) Lead Free. GENERAL SPECIFICATION - Stainless Steel grade (Food Grade)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Material (Food Grade) Lead Free.	
4	DGD110060	NO DATA AVAILABLE	003550000045 4 / UTENSIL COOKING ALUMINIUM WITH COVER O/D 16-17", INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESSS 10 SWG		6 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) GENERAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD)	
5	DGE110107	NO DATA AVAILABLE	041478000021 0 / INSULATING RUBBER GLOVES	MSI	8 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - ELASTOMER= NATURAL RUBBER,, THICKNESS= 1.5MM, LINING= UNLINED CHLORINATED, FORMER= PLAIN SMOOTH, CUFF TYPE= STRAIGHT, EXERIOR= CHLORINATED, TENSILE STRENGTH= 16.0 MPA (MIN), TENSIION SET= 15% (MAX), ELONGATION AT BREAK= 600% (MIN), MAX USE VOLTAGE AC= 7500V, PROOF TEST VOLTAGE AC= 10000V,GENERAL SPECIFICATION - ELASTOMER= NATURAL RUBBER,, THICKNESS= 1.5MM, LINING= UNLINED CHLORINATED, FORMER= PLAIN SMOOTH, CUFF TYPE= STRAIGHT, EXERIOR= CHLORINATED, TENSILE STRENGTH= 16.0 MPA (MIN), TENSIION SET= 15% (MAX), ELONGATION AT BREAK= 600% (MIN), MAX USE VOLTAGE AC= 7500V, PROOF TEST VOLTAGE AC= 10000V,	
6	DGE106278	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		45 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Low Halogen: YesGENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
7	DGE111280	MIL-P-15280	5640002374827 / INSULATION SLEEVING THERMAL		60 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
8	DGE110402	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOFLAGE THE 14.5MM GUNS	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
9	DGE110186	13213E5456-12	4220002753156 / LIFE BOUY (RING BOUY LIFE SAVING) ROUND ORANGE OUTER (COMD8)		16 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
10	DGE106614		0472594259799 / WHALER 27FT DROP REEL		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
11	DGD110049		0032500032008 / KNIVES BUTTER FOR CNS		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL S/S 304 /316 FOOD GRADE NON MAGNETIC (LOCAL) PN CREST ENGRAVED ON KNIFE STAINLESS STEEL M/GRADE SS 304/316 (FOOD GRADE) LENGTH 21 TO 23 CMGENERAL SPECIFICATION - MATERIAL S/S 304 /316 FOOD GRADE NON MAGNETIC (LOCAL) PN CREST ENGRAVED ON KNIFE STAINLESS STEEL M/GRADE SS 304/316 (FOOD GRADE) LENGTH 21 TO 23 CM	
12	DGB109885	SPEC; BS1769	0266590016031 / WASHER FLAT ROUND MILD STEEL O/D1.625"I/D0.792"THICK0.128"		20 / KILOGRAMME						TECHNICAL SPECIFICATION - Spec: BS-970 EN 3AGENERAL SPECIFICATION - Spec: BS-970 EN 3A	
13	DGB111274		0276709106592 / VICE	JAW 3-1/4" PARALLEL,	2 / EACH/N						TECHNICAL SPECIFICATION - Jaw Opening: 5.5 Inch Depth of Jaw: 3	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ENGINEERS WIDTH OF JAW 4.5", NOM OPENING 5-1/2",	QUICK RELEASE	UMBER						Inch Weight with stationary base: 91.1 kg Make/ Model: England GENERAL SPECIFICATION - Jaw Opening: 5.5 Inch Depth of Jaw: 3 Inch Weight with stationary base: 91.1 kg Make/ Model: England	
14	DGE110886	NIL	5430705134177 / FLEXIBLE FUEL TANK 250 GALLONS	-	4 / EACH/NUMBER	NO DATA AVAILABLE		PK	M/S SAMAD RUBBER WORKS (PVT) LTD 409 FEROZEPUR ROAD LAHORE		TECHNICAL SPECIFICATION - LENGTHXWIDTHXHEIGHT 13'-6" X13-6"X2'-8"(APPROXIMATELY) GENERAL SPECIFICATION - LENGTHXWIDTHXHEIGHT 13'-6" X13-6"X2'-8"(APPROXIMATELY)	
15	DGB88582		0257704195039 / NUT-PLAIN-WING-TH-SZ-0.25"WG.HT0.718(BRASS) WING-SPRD 1.187"		48 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
16	DGE87137	FEC 1735511	6532705172593 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	10 / EACH/NUMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4	GERMANY		TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 ¿ to 108 ¿GENERAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 ¿ to 108 ¿	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
17	DGD107925	NO DATA AVAILABLE	7320705013216 / POTATOES PEELER MACHINE 15 to 20 kg CAPACITY s/steel		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local MarketGENERAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market	
18	DGD107924	T52254 / E-6228	7320705045236 / MINCING MACHINE NO 22 WITH 2HP MOTOR BASE FRAME RPM 1420		1 / EACH/NUMBER	pakistan					TECHNICAL SPECIFICATION - Frame of Machine Material: Mild Steel, MATERIAL OF Motor body and Mincing Machine: Cast Iron NOTE: ITEMS MADE IN PAKISTAN TECHNICALY ACCPEPTENCE BY END USERGENERAL SPECIFICATION - Frame of Machine Material: Mild Steel, MATERIAL OF Motor body and Mincing Machine: Cast Iron NOTE: ITEMS MADE IN PAKISTAN TECHNICALY ACCPEPTENCE BY END USER	
19	DGD110052		7340705101874 / Cruests Complete Small	MESS UTENSILS, OFFICER WARD PNS SHIFA	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - As per existing Stock, Make/Brand is Regal China with Blue Shell & PN Crest embossed on itemGENERAL SPECIFICATION - As per existing Stock, Make/Brand is Regal China with Blue Shell & PN Crest embossed on item	
20	DGE111309	0730003000000A/6220-02	4220715060127 / FINS STRAP RUBBER SIZE, LENGTH= 20-INCH (51-CM) , WD= 01-INCH (24 CM)	FOR FINS USE	10 / PAIR						TECHNICAL SPECIFICATION - 1. RUBBER PROFESSIONAL FINS COLOR= BLACK, 2. ADJUSTABLE STRAPS FOR A PERFRCT ADAPTATION TO THE DIVER'S FEET, 3. DESIGNED TO COMBINE COMFORT AND PERFORMANCE ROCKET ARE VERY POPULAR AMOUNG PROFESSIONAL AND MILITARY DIVERS, 4. METAL BUCKLES VERSIONGENERAL SPECIFICATION - 1. RUBBER PROFESSIONAL FINS COLOR= BLACK, 2. ADJUSTABLE STRAPS FOR A PERFRCT ADAPTATION TO THE DIVER'S FEET, 3. DESIGNED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TO COMBINE COMFORT AND PERFORMANCE ROCKET ARE VERY POPULAR AMOUNG PROFESSIONAL AND MILITARY DIVERS, 4. METAL BUCKLES VERSION	
21	DGD99094	NO DATA AVAILABLE	0035500000318 / Aluminium covers for utensil cooking (Large) O/D 25.50" TH 10 SWG.		8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.GENERAL SPECIFICATION - Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.	
22	DGE111064	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	5 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
23	DGB107600	NO DATA AVAILABLE	0268500000044 / SALTER-COUNTER-SCALE-MODLE250-CAP-15-KG		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
24	DGB111275	1A1155	0274709104966 / FILE ENGINEER THREE SQUARE D-CUT SMOOTH 4" LG,11 MM WIDTH		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - tRIANGLE FILE SIZE: 5 INCHGENERAL SPECIFICATION - tRIANGLE FILE SIZE: 5 INCH	
25	DGB111276	SPECIFICATION BS 887	0274599100077 / CALIPER VERNIER ENG&MM COMB IN&EXT W/CASE 0-TO9"(0-TO-225MM)	MEASURING TOOL	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION BS 887GENERAL SPECIFICATION - SPECIFICATION BS 887	
26	DGE78765	ITD	0413599238926 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		17 / KILOGRAMME						TECHNICAL SPECIFICATION - COMPLETE SPECIFICATION (PN/TECH SPECS/RSSN/03/2026) IS ATTACHED WITH LETTER (PN/DID/PROJECTS/6761360 DATED 17 AUG 2026).GENERAL SPECIFICATION - COMPLETE SPECIFICATION (PN/TECH SPECS/RSSN/03/2026) IS ATTACHED WITH LETTER (PN/DID/PROJECTS/6761360 DATED 17 AUG 2026).	
27	DGE101442	NO DATA AVAILABLE	0451594510013 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	55 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINSGENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
28	DGB106752		0283595711474 / SHEET-NAVAL-BRASS-ANNEALED 48		1.75 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
29	DGB111273	H 2956	0276709106593 / VICE ENGINEER WIDTH OF JAW 6"NOM OPENING 7.250 D OF JAW 04IN	7-1/4", PARALLEL QUICK RELEASE	2 / EACH/NUMBER	63302					TECHNICAL SPECIFICATION - dimension: (l x w x h): 18 x 8.7 x 9.7 brand: wilton tools material: cast iron manufacture: jpw industries inc wilton ukGENERAL SPECIFICATION - dimension: (l x w x h): 18 x 8.7 x 9.7 brand: wilton tools material: cast iron manufacture: jpw industries inc wilton uk	
30	DGD105617		0035546000614 / POT ALU 15/7" WITH COVER		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 200 TO 250 LBSGENERAL SPECIFICATION - 200 TO 250 LBS	
31	DGE111269	14.02.0012	0350599233577 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED. GENERAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT),	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED.	
32	DGE111051	14.02.0012	0350599233577 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED. GENERAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED.	
33	DGD107863	NO DATA AVAILABLE	0035500000274 / BOARD KNIFE		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952	
34	DGE87587	RB10002 local	6150705264085 / INSULATION RUBBER MAT		25 / FOOT	NA					TECHNICAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm.GENERAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm.	
35	DGE101520	NO DATA AVAILABLE	0330546004484 / HEAVING LINE 06MM L50MM 466MS	MSI	1620 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - length :06MM L50MM 466MS material : nylonGENERAL SPECIFICATION - length :06MM L50MM 466MS material : nylon	
36	DGB74613	0140	4030795153887 / SPLIT THIMBLES (316 STAINLESS STEEL)10MM	TAL SHIP SAILING RIG	14 / EACH/NUMBER			BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST,HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE. MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE. CO.UK	UK		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY ; BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE. SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX;+44(0) 1489578835. GENERAL SPECIFICATION - SOURCE OF AVAILABILITY ;BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX;+44(0) 1489578835.	
37	DGE101638	FEC 1735511	6532705172593 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	58 / EACH/NUMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4	GERMANY		TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 ¿ to 108 ¿GENERAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 ¿ to 108 ¿	
38	DGE109689	23-53-21-17-01SA	0476705207319 / SHOOTER GLOVES	GLOVE	5 / EACH/NUMBER	X-PRO by Alif	NA	M SADIQ ALI & SONS, 217/15,SALEH MARKET, ADAMJEE ROAD, SADDAR, RAWALPINDI. 051-5527252 051-5513958	M SADIQ ALI & SONS		TECHNICAL SPECIFICATION - goatskin leather (abrasion resistant) reinforced palm and double stiching for heavy duty protection from abrasion reinforced digital leather layer with antislip feature and grip for tactical applications durable, lightweight, breathable and comfortable adjustable wrist design (X-PRO by Alif).GENERAL SPECIFICATION - goatskin leather (abrasion resistant) reinforced palm and double stiching for heavy duty protection from abrasion reinforced digital leather layer with antislip feature and grip for tactical applications durable, lightweight, breathable and comfortable adjustable wrist design (X-PRO by Alif).	
39	DGE111406	14.02.0012	0350599233577 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED. GENERAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED.	
40	DGE98101	0413/8568	0413599243503 / FIBER SHEET, VULCANISED, LG,54"WD.42" THICKNESS 0.031"	FOR AIR COMPRESSOR	50 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DGE97053	0413/8568	0413599243503 / FIBER SHEET, VULCANISED, LG,54"WD.42" THICKNESS 0.031"	FOR AIR COMPRESSOR	100 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DGE73719		0451594510094 / MATTRESS FOAM RUBBER WITH COVER 82" X36"X4" (WARRANTY 10 YEARS		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
43	DGB106453		0283595711451 / ROD		2 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2024, CW712R,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NAVAL BRASS RD DIA 1.50 INCH(38MM), L: 4 MTR, WT/FT: 6.05 LBS								MATERIAL CONDITION: R-400. GENERAL SPECIFICATION - BSEN 12163 OF 2024, CW712R, MATERIAL CONDITION: R-400.	
44	DGB74774		0283595711474 / SHEET-NAVAL-BRASS-ANNEALED 48		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
45	DGE101988	ITD	0413599238926 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		25 / KILOGRAMME						TECHNICAL SPECIFICATION - COMPLETE SPECIFICATION (PN/TECH SPECS/RSSN/03/2026) IS ATTACHED WITH LETTER (PN/DID/PROJECTS/6761360 DATED 17 AUG 2026).GENERAL SPECIFICATION - COMPLETE SPECIFICATION (PN/TECH SPECS/RSSN/03/2026) IS ATTACHED WITH LETTER (PN/DID/PROJECTS/6761360 DATED 17 AUG 2026).	
46	DGE97806		0415599231412 / SHEET PLASTIC METHYL METHACRYLATE PLAIN TRANSPARENT L X W X THIC 48"X48"X0.250"		60 / SHEET						TECHNICAL SPECIFICATION - Manfr/Tech.Sponcer Code reference: DTD 5592GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference:DTD 5592	
47	DGH99182	NO DATA AVAILABLE	0212590017878 / CHANNEL STEEL12"X3.5" X1/2"		12 / METER						TECHNICAL SPECIFICATION - CHANNEL STEEL12"X3.5" X 1/2". GENERAL SPECIFICATION - CHANNEL STEEL12"X3.5" X 1/2".	
48	DGB78423		0273599104463 / CALIPER INSIDE SPRING JOINT		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			06IN (LOCAL)									
49	DGB77812	BS1780 / EN 837-1 NS 100	024259942044 7 / GAUGE-PRESSURE INDICATING DIAL (0-100PSI)		5 / EACH/NUMBER	111.10					TECHNICAL SPECIFICATION - NOMINAL SIZE (NS): 100 MM (4 INCH) CONNECTION LOCATION: LOWER MOUNT (RADIAL) MATERIAL: STEEL BLACK MEASURING ELEMENT: BOURDON TUBE, C-TYPE OR HELICALGENERAL SPECIFICATION - NOMINAL SIZE (NS): 100 MM (4 INCH) CONNECTION LOCATION: LOWER MOUNT (RADIAL) MATERIAL: STEEL BLACK MEASURING ELEMENT: BOURDON TUBE, C-TYPE OR HELICAL	
50	DGB100963	SKF 6208Z	026959950011 4 / BEARING BALL JOURNAL SKF 6208Z 040X080X18MM	SUPPLY&EXHAUST FAN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
51	DGB102166	MILE22200-2QA	343900878215 4 / ELECTRODE WELDING AWS E308-16 DIA: 2.6MM (LENGTH PER UNIT/ELECTRODE: 300 MM)	WELDING (STEEL)	20 / KILOGRAMME						TECHNICAL SPECIFICATION - Ø: 2.6 mm Spec: AWS A5.4-81 E 308-16 Chemical Composition C 0. 02 Si 0.8 Mn 1.0 Ni 10.0 Cr 19.5 Tensile STRENGTH : 590 N/mm2 Current RANGE: 60-90 Amps Area reduction: 50.0% Elongation: 40.0% Packaging: 01 kg per bag. Final delivery with one batch/lot Classification SOCIETY: Approval of any international classification i.e. LR,BV,ABS,DNV. GL,C€,JIS,ISO-9001-2015 GENERAL SPECIFICATION - Ø: 2.6 mm Spec: AWS A5.4-81 E 308-16 Chemical Composition C 0. 02 Si 0.8 Mn 1.0 Ni 10.0 Cr 19.5 Tensile STRENGTH : 590 N/mm2 Current RANGE: 60-90 Amps Area reduction: 50.0% Elongation: 40.0% Packaging: 01 kg per bag. Final delivery with one batch/lot Classification SOCIETY: Approval of any international	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											classification i.e. LR,BV,ABS,DNV. GL,C€,JIS,ISO-9001-2015	
52	DGH103280	751F00	3439010560949 / CLEANER NOZZLE (CLEANER SET, WELDING)	GAS CUTTING AND WELDING NOZZLE	20 / SET						TECHNICAL SPECIFICATION - L TEC WELDING & CUTTING SYSTEMS EBENEZERGENERAL SPECIFICATION - L TEC WELDING & CUTTING SYSTEMS EBENEZER	
53	DGB103963	SKF-6207 ZZ	3110991199546 / BEARING BALL JOURNAL SKF-6207ZZ 035X072X17MM	GENERAL ITEM	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
54	DGB99552	0251-9681	4010994119681 / CHAIN WELDLESS BRASS B13304 429012BR	ELECTRO HYDROLIC STEEING GEAR BALL SHAH	2 / EACH/NUMBER	PUMP					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DGE97115		5350994616829 / STEEL WOOL 1 LB PER BALLS 50 BALLS PER CARTOON GRADE-3	FOR GENERAL USE	6 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DGE97257		5350994616829 / STEEL WOOL 1 LB PER BALLS 50 BALLS PER CARTOON GRADE-3	FOR GENERAL USE	16 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DGE101374	CM6538-000	5970705044352 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: YesGENERAL SPECIFICATION - Material System:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
58	DGE103344	-	8340705087916 / TENT MARQUEE UNIVERSAL G.S (SIZE 27X19.6FT) FOLD & FLY TWO (J/GREEN)	GENERAL PURPOSE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 27 X 19.6 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF, FIRE PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM b. IRON PEGS: QTY 24 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. WALL PIPE (LATHI): QTY 24 NOS OF MATERIAL: MS (MILD STEEL), LENGTH 06 FEET, THICKNESS 25 MM. d. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MANUFACTURER, MATERIAL: NYLON/ COTTON, DIA MINIMUM 16 MM. e. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. f. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. GROUND SHEET FIREPROOF 200 GSM. 4. VENTILATION FEATURE: WINDOW: 06 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. GENERAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 27 X 19.6 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF, FIRE PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM b. IRON PEGS: QTY 24 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. WALL PIPE (LATHI): QTY 24 NOS OF MATERIAL: MS (MILD STEEL), LENGTH 06 FEET, THICKNESS 25 MM. d. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/ COTTON, DIA MINIMUM 16 MM. e. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. f. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. GROUND SHEET FIREPROOF 200 GSM. 4. VENTILATION FEATURE: WINDOW: 06 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
59	DGE103368	-	8340705087916 / TENT MARQUEE UNIVERSAL G.S (SIZE 27X19.	GENERAL PURPOSE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 27 X 19.6 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimensio
			6FT) FOLD & FLY TWO (J/GREEN)								HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF, FIRE PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM b. IRON PEGS: QTY 24 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. WALL PIPE (LATHI): QTY 24 NOS OF MATERIAL: MS (MILD STEEL), LENGTH 06 FEET, THICKNESS 25 MM. d. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/ COTTON, DIA MINIMUM 16 MM. e. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. f. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. GROUND SHEET FIREPROOF 200 GSM. 4. VENTILATION FEATURE: WINDOW: 06 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimensior
											AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. GENERAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 27 X 19.6 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF, FIRE PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM b. IRON PEGS: QTY 24 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. WALL PIPE (LATHI): QTY 24 NOS OF MATERIAL: MS (MILD STEEL), LENGTH 06 FEET,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											THICKNESS 25 MM. d. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/ COTTON, DIA MINIMUM 16 MM. e. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. f. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. GROUND SHEET FIREPROOF 200 GSM. 4. VENTILATION FEATURE: WINDOW: 06 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
60	DGE98069		8305PK5124167 / FABRIC CURTAIN WITH FITTING (MOAWIN A&A)	SENIOR OFFICER CABIN	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DGE64951	CTLBS12202003	5340735267409 / BASE 4' (1220 X 200 X 3MM)		96 / FOOT RUN	BASE 4' CTLBS12 202003					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
62	DGT114052	NIL	7230705132910 / BAMBOOS	-	4000 / FOOT	NO DATA AVAILAB		PK	TAWAKAL BANS		TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OF 35 to 45 FEETS, diameter: 4"-6"			LE			STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment : required GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment :required	
63	DGD113857	JE-01	7320705269664 / STAINLESS STEEL JUICE EXTRACTOR		1 / EACH/NUMBER	UDZZ-A2000					TECHNICAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201 GENERAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201	
64	DGB113508		0283700001608 / INGOT-BRASS		200 / KILOGRAMME						TECHNICAL SPECIFICATION - Specification: BSEN 1982 OF 2024, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kgGENERAL SPECIFICATION - Specification: BSEN 1982 OF 2024, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg	
65	DGB113700		0283700001608 / INGOT-BRASS		280 / KILOGRAMME						TECHNICAL SPECIFICATION - Specification: BSEN 1982 OF 2024, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kgGENERAL SPECIFICATION - Specification: BSEN 1982 OF 2024, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
66	DGB113505		028370923350 4 / ZINC INGOT 99.995% PURITY LG 16",BREADTH 8",HT 1.75"		240 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005% GENERAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005%	
67	DGB113683		028359571144 7 / ROD NAVAL BRASS RD DIA 01 INCH	GENERAL USE	31 / METER						TECHNICAL SPECIFICATION - BS EN 12163 OF 2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98LBS, R-LENGTH-03 METERS (EACH)GENERAL SPECIFICATION - BS EN 12163 OF 2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98 LBS, R-LENGTH-03 METERS (EACH)	
68	DGB113506		028359571144 7 / ROD NAVAL BRASS RD DIA 01 INCH	GENERAL USE	22 / METER						TECHNICAL SPECIFICATION - BS EN 12163 OF 2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98LBS, R-LENGTH-03 METERS (EACH)GENERAL SPECIFICATION - BS EN 12163 OF 2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98 LBS, R-LENGTH-03 METERS (EACH)	
69	DGB113		028359571147		13.75 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	507		4 / SHEET-NAVAL-BRASS-ANNEALED 48		EACH/NUMBER						Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
70	DGB113701		0283705711462 / ROD NAVAL BRASS RD DIA 3.125" WT PER FOOT 28.65 (LB)		3 / METER						TECHNICAL SPECIFICATION - specs: BS EN 12163 of 2024 with material grade CW712 and material conditions M. RUNNING LENGTH : 01 METER GENERAL SPECIFICATION - specs: BS EN 12163 of 2024 with material grade CW712 and material conditions M. RUNNING LENGTH : 01 METER	
71	DGD113848	NO DATA AVAILABLE	0033546000911 / Tumbler Glass for Soda Water		256 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Material: Glass (Crystal clea) Capacity: 280/300ml Brand: Toya Nasic / Nova (LOCAL)GENERAL SPECIFICATION - Material: Glass (Crystal clea) Capacity: 280/300ml Brand: Toya Nasic / Nova (LOCAL)	
72	DGH114062		0561595218492 / CABLE, power, ELECT ELASTOMERIC LFH , 3 cores, cond276/0.40 440 v, 160 amp, 100 lg.		100 / METER						TECHNICAL SPECIFICATION - 3 CORES, COND276/0.40 440 V, 160 AMP, 100 LG. DEFSTAN 02-526 GENERAL SPECIFICATION - 3 CORES, COND276/0.40 440 V, 160 AMP, 100 LG. DEFSTAN 02-526	
73	DGT114034	NO DATA AVAILABLE	5530705042933 / PLY WOOD NATURAL TEAK FINISH ONE SIDE (NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W= 4' TH=03mm to 04mm	PRESENTATION BOXES FOR VVIPS	320 / SQ FEET						TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mmGENERAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Thickness of face and back veneer = 0.6mm	
74	DGD113860	MS-3443-A/DW-136G	7310705121904 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	1 / EACH/NUMBER	DW-136G					TECHNICAL SPECIFICATION - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHIGENERAL SPECIFICATION - brand name: (i.e. WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI	
75	DGD113654		7730705048078 / CUP TEA BLUE CRESTED		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CMGENERAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CM	
76	DGT113876	NO DATA AVAILABLE	0100500000030 / PLY WOOD NATURAL TEAK FINISH BOTH SIDE (NOT ARTIFICIAL) GRADE-1, 9-PLY,	2.44X1.22MTRX19.05MM) SPECE/BS6566 OF1985	64 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION OF THE ITEM: SIZE= LENGTH= 8-FEET, WIDTH= 4-FEET, THICKNESS= 16mm ±2, SPECS: 1. bs-1088 part-1&II, DENSITY OF TIMBER (TEAK) AS INTERNATIONAL STANDAR, 2. thickness of face back venEer should be 0.6 mm (min) 3. density of PLY WOOD TEAK= 500 TO 850 KG/M3, GENERAL SPECIFICATION - SPECIFICATION OF THE ITEM: SIZE= LENGTH= 8-FEET, WIDTH= 4-FEET, THICKNESS= 16mm ±2, SPECS: 1. bs-1088 part-1&II, DENSITY OF TIMBER (TEAK) AS INTERNATIONAL STANDAR, 2. thickness of face back venEer should be 0.6 mm (min) 3. density of PLY WOOD TEAK= 500 TO 850 KG/M3,	
77	DGT114	NO DATA	010050000002	2.440X1.	712 /	NO DATA					TECHNICAL SPECIFICATION - 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	042	AVAILABLE	8 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLIES OF SHESHAM WOOD) 5-PLY	220MTRX6. 35MM) SPECE/BS-1088	SQ FEET	AVAILABLE					SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, GENERAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,	
78	DGT113866	NO DATA AVAILABLE	0415500000009 / FORMICA ENGRAVING WHITE FACE BLACK CORE (1220MMX1220MMX1.57MM		3 / SHEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness.GENERAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness.	
79	DGT114033	NO DATA AVAILABLE	0415500000009 / FORMICA ENGRAVING WHITE FACE BLACK CORE (1220MMX1220MMX1.57MM		5 / SHEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness.GENERAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness.	
80	DGD113717		7340705060449 / TABLE SPOON		260 / EACH/NUMBER						TECHNICAL SPECIFICATION - Length = 190-200 mm Material = SS 304 food grade base s with golden color. Thickness = 2.5- 3.0 mm Weight = 45- 55 g Finish = Mirror	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											polish with handle design. Edge = Smooth rounded, No sharp edges Packing= VIP single poly/ velvet box Standard= Food grade, lead/nickel freeGENERAL SPECIFICATION - Length = 190-200 mm Material = SS 304 food grade base s with golden color. Thickness = 2.5- 3.0 mm Weight = 45- 55 g Finish = Mirror polish with handle design. Edge = Smooth rounded, No sharp edges Packing= VIP single poly/ velvet box Standard= Food grade, lead/nickel free	
81	DGD113719		7340705060453 / SERVICE RICE SPOON 8"		70 / EACH/NUMBER						TECHNICAL SPECIFICATION - 8", Grade 304 S/S FOOD GRADE NON Magnetic (LOCAL)GENERAL SPECIFICATION - 8", Grade 304 S/S FOOD GRADE NON Magnetic (LOCAL)	
82	DGD113699		7340705060454 / CHAFING SPOON 12"		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 12", Grade 304 S/S FOOD GRADE NON Magnetic (LOCAL)GENERAL SPECIFICATION - 12", Grade 304 S/S FOOD GRADE NON Magnetic (LOCAL)	
83	DGD113716	O/A WEIGHT-750 GM ± 10 GMS	7330705050023 / JUG S/STEEL 18/8 WITH FINSIHED THK OF BODY 21SWG/HANDLE SWG9		50 / EACH/NUMBER						TECHNICAL SPECIFICATION - 18/8 WITH FINSIHED THK OF BODY 21SWG/HANDLE SWG9GENERAL SPECIFICATION - 18/8 WITH FINSIHED THK OF BODY 21SWG/HANDLE SWG9	
84	DGD113698	NO DATA AVAILABLE	0035500000452 / UTENSILS COOKINGALUM O/D 10" TO 10.5" "H 4" TO 5.5" TH 12 SWH WITH COVER		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd) DIMENSION: O/D 10" to 10.5" "H 4" to 5.5" TH 12 SWg ALUMINIUM GRADE 3003, 1100, 2024 AND 5052 GENERAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd) DIMENSION: O/D 10" to 10.5" "H 4"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											to 5.5" TH 12 SWg ALUMINIUM GRADE 3003, 1100, 2024 AND 5052	
85	DGD113685		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		6 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWGGENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
86	DGD113682		0035500000520 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		6 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER GENERAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
87	DGD113692	NO DATA AVAILABLE	0035500000454 / UTENSIL COOKING ALUMINIUM WITH COVER O/D 16-17", INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESSS 10 SWG		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) GENERAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD)	
88	DGD113688	NO DATA	0035500000456 / UTENSIL COOKING ALUMINUM WITH COVER		6 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - ALUMINIUM ALLOY FOOD GRADE, 100% FREE FROM LEAD (PB) AND CADMIUM (CD). O/D:18.5", H:10", THICKNESS 10 SWG ALUMINIUM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimensior
			O/D:18.5", H: 10", THICKNESS 10 SWG, Cover Thickness: 10 SWG								GRADE 3003, 1100, 2024 AND 5052GENERAL SPECIFICATION - ALUMINIUM ALLOY FOOD GRADE, 100% FREE FROM LEAD (PB) AND CADMIUM (CD). O/D:18.5", H:10", THICKNESS 10 SWG ALUMINIUM GRADE 3003, 1100, 2024 AND 5052	
89	DGD113671	NO DATA AVAILABLE	0032500000171 / SPOON TABLE MEDIUM S/STEEL		260 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - pn crest is to be embosed. specs : stainless steel grade 316GENERAL SPECIFICATION - pn crest is to be embosed. specs : stainless steel grade 316	
90	DGD113863	NO DATA AVAILABLE	0033500000200 / JUGS WATER GLASS 1 QT		35 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Capacity = 946 ml Material = Borosilicate glass with gold crusted Glass Thickness = 3-5 mm Finish = Clear glass with gold crusted borer, hand decorated. Packing= VIP premium velvet/ gift box Standard= Food grade gold, lead/nickel freeGENERAL SPECIFICATION - Capacity = 946 ml Material = Borosilicate glass with gold crusted Glass Thickness = 3-5 mm Finish = Clear glass with gold crusted borer, hand decorated. Packing= VIP premium velvet/ gift box Standard= Food grade gold, lead/nickel free	
91	DGD113677	NO DATA AVAILABLE	0033500000200 / JUGS WATER GLASS 1 QT		24 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Capacity = 946 ml Material = Borosilicate glass with gold crusted Glass Thickness = 3-5 mm Finish = Clear glass with gold crusted borer, hand decorated. Packing= VIP premium velvet/ gift box Standard= Food grade gold, lead/nickel freeGENERAL SPECIFICATION - Capacity = 946 ml Material = Borosilicate glass with gold crusted Glass Thickness = 3-5 mm Finish = Clear glass with gold crusted borer, hand decorated. Packing= VIP premium velvet/ gift box Standard= Food grade gold, lead/nickel free	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
92	DGD113674	NO DATA AVAILABLE	0033500000206 / Tumbler Glass for Drinking Water		30 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Material: Glass (Crystal Clear) Capacity: 280/300 ml Brand: Toya Nasic / Nova (LOCAL)GENERAL SPECIFICATION - Material: Glass (Crystal Clear) Capacity: 280/300 ml Brand: Toya Nasic / Nova (LOCAL)	
93	DGT114043	NO DATA AVAILABLE	0100500000043 / TIMBER GURJAN GRADE-I SLEEPER SEASONED (SWAN)		15 / CUBIC FOOT	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH 2. MOISTURE CONTENT: 30% (±10%), 3. ENDS TO BE COATED WITH PRESERVATION AFTER INSPECTION, 4. COLOR= REDDISH BROWN, 5. QUALITY= AS PER TIMBER GURJAN GRADE-1 SPECS, 6. DEFECT= FREE FROM DEFECT, 7. KNOTS= FREE FROM KNOTSGENERAL SPECIFICATION - 1. SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH 2. MOISTURE CONTENT: 30% (±10%), 3. ENDS TO BE COATED WITH PRESERVATION AFTER INSPECTION, 4. COLOR= REDDISH BROWN, 5. QUALITY= AS PER TIMBER GURJAN GRADE-1 SPECS, 6. DEFECT= FREE FROM DEFECT, 7. KNOTS= FREE FROM KNOTS	
94	DGT113872	NO DATA AVAILABLE	0100500000043 / TIMBER GURJAN GRADE-I SLEEPER SEASONED (SWAN)		20 / CUBIC FOOT	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH 2. MOISTURE CONTENT: 30% (±10%), 3. ENDS TO BE COATED WITH PRESERVATION AFTER INSPECTION, 4. COLOR= REDDISH BROWN, 5. QUALITY= AS PER TIMBER GURJAN GRADE-1 SPECS, 6. DEFECT= FREE FROM DEFECT, 7. KNOTS= FREE FROM KNOTSGENERAL SPECIFICATION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											- 1. SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH 2. MOISTURE CONTENT: 30% (±10%), 3. ENDS TO BE COATED WITH PRESERVATION AFTER INSPECTION, 4. COLOR= REDDISH BROWN, 5. QUALITY= AS PER TIMBER GURJAN GRADE-1 SPECS, 6. DEFECT= FREE FROM DEFECT, 7. KNOTS= FREE FROM KNOTS	
95	DGT114035	NO DATA AVAILABLE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB to 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	27 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETANI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		TECHNICAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB GENERAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	
96	DGB113809	NO DATA AVAILABLE	5660705148476 / CONCErTINA WIRE BLADE SIZE: 22MML, 14MMW THIcKNESS: 0.5MM	FOR BOUNDARY PROTECTION	36 / ROLL			SOURCE OF AVALIBILTY: PAKISTAN WIRE SITE AREA KARACHI .Mr WASEEM CONTRACT NO 0333-2112465.	PAKISTAN WIRE		TECHNICAL SPECIFICATION - BLADE SIZE: 22MML,14MMW BLADE THIcKNESS: 0.5MM LINE WIRE: 2.6/3MM 10-12 GAUGE SIZE: 36INCH DIA MATERIAL: (MILD STEEL&GALVANIZEDWEIGHT / ROLL: 25 KG PER ROLL COUNTRY OF ORIGIN PAKISTAN GENERAL SPECIFICATION - BLADE SIZE: 22MML,14MMW BLADE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											THICKNESS: 0.5MM LINE WIRE: 2.6 /3MM 10-12 GAUGE SIZE: 36INCH DIA MATERIAL: (MILD STEEL&GALVANIZEDWEIGHT / ROLL: 25 KG PER ROLL COUNTRY OF ORIGIN PAKISTAN	
97	DGE111 281	large 94.2 ltrs 300 plus	811570525959 7 / coleman ice boxes or EQUIVALENT (LARGE) 94.2 LTRS 300 (PLUS)		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)GENERAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)	
98	DGB111 352		027679910662 0 / VICE WOOD WORKERS WIDTH OF JAW 9" NOM. OPENING 13" DEPTH JAW 4	JAW 4",QUICK RELEASE SCREW TYPE	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - JAW NOMINAL OPENING: 330.00 MM. SPECIAL FEATURES: W/ STEEL SLIDES;QUICK RELEASE; 230 MM W/JAW,100 MM THROAT DEPTH. MATERIAL: IRON. GENERAL SPECIFICATION - JAW NOMINAL OPENING: 330.00 MM. SPECIAL FEATURES: W/ STEEL SLIDES;QUICK RELEASE;230 MM W/JAW,100 MM THROAT DEPTH. MATERIAL: IRON.	
99	DGB113 707		028359571115 5 / SHEET ALUMINIUM ALLOY ANNEALED		13 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2+A1 OF 2018 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN:573-3 OF 2026 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251). DIMENSIONAL TOLERANCE: 2440±10MM X 1220±10MM X 1.6 MMGENERAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2+A1 OF 2018 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN:573-3 OF 2026 (CHEMICAL COMPOSITION),	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GRADE (EN-AW-5251). DIMENSIONAL TOLERANCE: 2440±10MM X 1220±10MM X 1.6MM	
100	DGT70242	NO DATA AVAILABLE	0100546002290 / BAMBOO SIZE 28FT-30FT LONG	DEISEL GENERATOR	30 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10-30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREEGENERAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10-30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREE	
101	DGH113984	SPEC:BS 1449/3A/HS22/C	0212595710917 / CHANNEL STEEL CARBON 2-1/2X1-1/4 IN W/FT 2.95 LB		168 / METER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIREDGENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED	
102	DGB113942		0212599232805 / BAR STEEL CORROSION RESISTING H/R RD 2.50" WT PER FT16.700LBS		6 / METER						TECHNICAL SPECIFICATION - BS-970, Stainless Steel Grade 316L, Running Length: 6 meter (OLD GRADE EN-58J)GENERAL SPECIFICATION - BS-970, Stainless Steel Grade 316L, Running Length: 6 meter (OLD GRADE EN-58J)	
103	DGB111351	NO DATA AVAILABLE	0246705231435 / HOIST-CHAIN-RATCHET-SWL1.5PROOF-LOAD2.25 TON.		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Load Capacity: 2.25 Ton b. Test Load (Kg): 3800 c. Standard Lift (m): 1.5 - 2 d. Mass (Net Weight) Approx KG: 10 -14GENERAL SPECIFICATION - a. Load Capacity: 2.25 Ton b. Test Load (Kg): 3800 c. Standard Lift (m): 1.5 - 2 d. Mass (Net Weight) Approx KG: 10 -14	
104	DGD113990		7730705048061 / SAUCER TEA GOLDEN CRESTED		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - MATERIAL PORCELAIN FOOD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GRADE CERA-E-NOOR (LOCAL)	
105	DGD113989		7730705048078 / CUP TEA BLUE CRESTED		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CMGENERAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CM	
106	DGE105046	NO DATA AVAILABLE	8340705014084 / TENT FOR CPOS/SAILORS, WT= 120 LBS, ALONGWITH COMPLETE ACCESSORIES		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. LENGTH: 10 FEET (± 2-INCH) b. WIDTH: 10 FEET (± 2-INCH) c. CENTRAL HEIGHT: 07 FEET (± 2-INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 05 NOS (02 x RIDGE POLES, LENGTH 05 FEET & 03 x STANDING POLES, LENGTH 07 FEET). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM, THICKNESS 02 MM ±0.50 MM. b. IRON PEGS: QTY 12 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 18 NOS, LENGTH: 06 INCHES. c. ROPE: QTY: 12 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 03 KGS WITH WOODEN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											HANDLE, LENGTH 1.5 FEET. f. FLAPPER FOR GROUND: MATERIAL: POLYPROPYLENE OF 180-200 GSM. 4. VENTILATION FEATURE: WINDOW 02 (SIZE: 1.5 x 1.5 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 02 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 01 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. GENERAL SPECIFICATION - 1. SIZE/DIMENSION a. LENGTH: 10 FEET (± 2-INCH) b. WIDTH: 10 FEET (± 2-INCH) c. CENTRAL HEIGHT: 07 FEET (± 2-INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 05 NOS (02 x RIDGE POLES, LENGTH 05 FEET & 03 x STANDING POLES, LENGTH 07 FEET). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM, THICKNESS 02 MM ±0.50 MM. b. IRON PEGS: QTY 12 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PIN QTY 18 NOS, LENGTH: 06 INCHES. c. ROPE: QTY: 12 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 03 KGS WITH WOODEN HANDLE, LENGTH 1.5 FEET. f. FLAPPER FOR GROUND: MATERIAL: POLYPROPYLENE OF 180-200 GSM. 4. VENTILATION FEATURE: WINDOW 02 (SIZE: 1.5 x 1.5 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 02 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 01 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
107	DGD113228	NO DATA AVAILABLE	0247500000019 / GAS BURNER WITH HANDLE VALVE FITTED IN A ROUND STEEL FRAME TH 6mm,H 8" WITH 20FT RUBBER TUBE		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - ROUND STEEL FRAME THickness: 6MM, Hieght: 8" WITH 20FT RUBBER TUBEGENERAL SPECIFICATION - ROUND STEEL FRAME THickness: 6MM, Hieght: 8" WITH 20FT RUBBER TUBE	
108	DGD114044	NO DATA AVAILABLE	0451546004455 / TUMBLER GLASSES		36 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material = Glass 280/300 ml Toya Nasic / Noya (LOCAL)GENERAL SPECIFICATION - Material = Glass 280/300 ml Toya Nasic / Noya (LOCAL)	
109	DGD110067	NO DATA AVAILABLE	0035500000273 / BOARD CHOPPING		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - make/brand ken wood size ; 12" x 6" x 1/2" material; fiber/nylon ref	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											haibat/03/7765652GENERAL SPECIFICATION - make/brand ken wood size ; 12" x 6" x 1/2" material; fiber/nylon ref haibat/03/7765652	
110	DGD110066	NO DATA AVAILABLE	0035500000274 / BOARD KNIFE		15 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952GENERAL SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952	
111	DGH113979	CTLBS12202003	5340735267409 / BASE 4' (1220 X 200 X 3MM)		192 / FOOT RUN	BASE 4' CTLBS12202003					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
112	DGH113980	CTLCB10008025	5340735267410 / CANTILEVER BRACKET 3' (1000 X 80 X 2.5MM)		144 / EACH/NUMBER	CANTILEVER BARACKET 3' CTLCB10008025					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONSGENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
113	DGE102350	d000-004	8440735270720 / cotton gloves (pack of 12 gloves)		5 / PAIR	na					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
114	DGH113981	CTLCS15011016	5340735267412 / CROSS (1500 X 1100 X 1.6MM)		80 / EACH/NUMBER	CROSS CTLCS15011016					TECHNICAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500 X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
115	DGT75244	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	40 / FOOT	NO DATA AVAILABLE		PK	TAWAKAL BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment : required GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment :required	
116	DGE72244		0476599430422 / BRUSH ARTIST MET FER/SQU HAIR ST SPECT LG 0.750" WD 0.500"		32 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
117	DGE76630	SPEC-HMSO TG27	0476599430452 / BRUSH ARTISTS QUILL FIRRULE RED SABLE HAIR WRITING CROW 3/4"		7 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: 33-37 mm Length: 185-224 mm Weight: 12gmGENERAL SPECIFICATION - Size: 33-37 mm Length: 185-224 mm Weight: 12gm	
118	DGE97095	NO DATA AVAILABLE	0476590000033 / BRUSH WRITEING GOOSE		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
119	DGE98125	NO DATA AVAILABLE	0476546005949 / BRUSH WRITING NO-6		15 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
120	DGB74679	SPEC-BS 2558 GRADE A	0277790002438 / SPANNER BOX DOUBLE ENDED BA 09X10 LG 04"		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DRILLED BOR DIA 1/8"									
121	DGE107421	NO DATA AVAILABLE	4931705129578 / FOLDING TABLE 3X2 (STEEL)	FOULDING TABLE	40 / EACH/NUMBER			PK	PAKISTAN		TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DGE113225	1-401-47845	8305991252223 / COTTON CLOTH		20 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - ¿ 100 % Cotton ¿ Color White ¿ Pieces 1 x 1 Feet ¿ Lint FreeGENERAL SPECIFICATION - ¿ 100 % Cotton ¿ Color White ¿ Pieces 1 x 1 Feet ¿ Lint Free	
123	DGE114152	NO DATA AVAILABLE	0350595713244 / SPUN YARN SISAL "S" TWIST ROT PROOFED, 3/20 YARN, LENGTH PER COIL 811+-5% (FM)		20 / KILOGRAMME						TECHNICAL SPECIFICATION - BS-2052/65 TABLE 27GENERAL SPECIFICATION - BS-2052/65 TABLE 27	
124	DGE113868		0350595713248 / SPUN YARN SISAL S TWIST R. FROOFED 2/40 YARN WT 56LBLG 2430FM	YARN 2 , LENGTH PER COIL 2430 FM, RUNNAGE	10 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
125	DGE113221	NO DATA AVAILABLE	0350599233576 / FENDER MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6 INTERNAL DIA 10"	MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10"GENERAL SPECIFICATION - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10"	
126	DGT114289	NO DATA AVAILABLE	0100546002290 / BAMBOO SIZE 28FT-30FT LONG	DEISEL GENERATOR	250 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10-30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREEGENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LENGTH: 30 FEET DIAMETER: 10-30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREE	
127	SGB114305		0212599232805 / BAR STEEL CORROSION RESISTING H/R RD 2.50" WT PER FT16.700LBS		4 / METER						TECHNICAL SPECIFICATION - BS-970, Stainless Steel Grade 316L, Running Length: 6 meter (OLD GRADE EN-58J)GENERAL SPECIFICATION - BS-970, Stainless Steel Grade 316L, Running Length: 6 meter (OLD GRADE EN-58J)	
128	DGE113565	C1560	0330595713250 / TWINE HEMP WHITING LINE 40YDS STRENDS 3 MIN BREAKING 48 LBS, C1559	ALSO KNOWN AS FISHING LINE TO BS 2019	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019GENERAL SPECIFICATION - a. Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019	
129	DGE113220	0330-1225	0350599233868 / FENDER MARINE LENGTH 9.0 INCHES WIDTH 5.0 INCHES		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT. GENERAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT.	
130	DGB114454		0276799105870 / SCREW DRIVER RATCH, DOUBLE SPIRAL,AUTO RETURN, 250MM LG,3 BITS		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in ChinaGENERAL SPECIFICATION - Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											215MM, 30 Accessories by HOLZER Made in China	
131	DGB114156	NO DATA AVAILABLE	026359923698 7 / THIMBLE, ROPE STEEL BS 970-EN 3A GALVANISED PEAR SHAPED OPEN TYPE WT 1.75LBS SIZE 1.25	SPEC NO DGS 5031NO.40	14 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material specification: BS 970/ EN 3A material grade : 070M20. Galvanized thickness: 1.25mm.GENERAL SPECIFICATION - Material specification: BS 970/ EN 3A material grade : 070M20. Galvanized thickness: 1.25mm.	
132	DGB114132		025850258120 3 / COPPER-WIRE-2-MM-DIA		20 / KILOGRAMME						TECHNICAL SPECIFICATION - Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm2 Resistivity Max: 0.01739 ¿ x332/m Conductivity Min: 57.5 m/ ¿ xmm2 Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETERGENERAL SPECIFICATION - Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm2 Resistivity Max: 0.01739 ¿ x332/m Conductivity Min: 57.5 m/ ¿ xmm2 Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER	
133	DGE114	NO DATA	033078000021		50 /	NO DATA					TECHNICAL SPECIFICATION - 6 x	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	179	AVAILABLE	4 / CLOTH CLEANING 6X6		EACH/NUMBER	AVAILABLE					6 as per atock sampleGENERAL SPECIFICATION - 6 x 6 as per atock sample	
134	DGE113224	NO DATA AVAILABLE	033078000021 4 / CLOTH CLEANING 6X6		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 6 x 6 as per atock sampleGENERAL SPECIFICATION - 6 x 6 as per atock sample	
135	SGE112926	NO DATA AVAILABLE	046150000008 6 / GOGGLE CHIPPING		615 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.GENERAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.	
136	DGE113025		8340PK5073827 / TENT 400 LBS DOUBLE		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PLY WITH COMPLETE ACCESSORIES								(± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. GENERAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
137	DGE113032		8340705087913 / TENT 40 POUND, ARMY PATT, FLY & FOLD DOUBLE, (JUNGLE GREEN)	GENERAL PERPOSE	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE= 6X7 FEET 2. Tent 40 Pounds Army Pattern A. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 3. On inner fly with curtains on sides and walls fitted with pockets 4. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 5. ACCESSORIES: A. STANDING POLE QTY= 02 NO, B. RICH POLE, QTY= 01 NO, C. IRON PEGS QTY= 12, STANDARD SIZE, C. Rope QTY= 12, STANDARD SIZE, E. Hammer QTY= 01NO (3 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET), F. PACKING BAG QTY= 02 NO. 6. Testing/Acceptance Criteria: CINS/END USER GENERAL SPECIFICATION - 1. SIZE= 6X7 FEET 2. Tent 40 Pounds Army Pattern A. Double fly tent having one outer fly with weather hood on both sides made of two folds	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											of cotton sheeting cloth. 3. On inner fly with curtains on sides and walls fitted with pockets 4. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 5. ACCESSORIES: A. STANDING POLE QTY= 02 NO, B. RICH POLE, QTY= 01 NO, C. IRON PEGS QTY= 12, STANDARD SIZE, C. Rope QTY= 12, STANDARD SIZE, E. Hammer QTY= 01NO (3 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET), F. PACKING BAG QTY= 02 NO. 6. Testing/Acceptance Criteria: CINS/END USER	
138	DGE113089		8340705087914 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIES)	OLIVE GREEN WATERPROOF INNER LINNING OF,	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 50 X 20 FEET (± 6 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 07 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 850 GSM OR ABOVE AND WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, (DOSUTI CLOTH; 100% COTTON) AND COLOR: ROYAL BLUE. e. CANVAS PROPERTIES INCLUDING BREAKING STRENGTH, SHRINKAGE, PLIABILITY FOR PROOFED CANVAS AND HYDROSTATIC PRESSURE RESISTANCE SHALL BE IN ACCORDANCE WITH PS-319. 3.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. (PAINT COATING THICKNESS: (45-50 MICRONS) OR GALVANIZATION (300 G/M² MINIMUM ZING COATING MASS) b. IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. (PAINT COATING THICKNESS: (45-50 MICRONS) OR GALVANIZATION (300 G/M² MINIMUM ZING COATING MASS) c. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: 100% HIGH TENACITY NYLON (POLYAMIDE) 3-STAND BRAIDED, DIA: MINIMUM 16-MM, WITH CONFORMING TO ISO 1140:2021. d. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											END USER PRIOR TO BULK PRODUCTION.GENERAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 50 X 20 FEET (± 6 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 07 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 850 GSM OR ABOVE AND WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, (DOSUTI CLOTH; 100% COTTON) AND COLOR: ROYAL BLUE. e. CANVAS PROPERTIES INCLUDING BREAKING STRENGTH, SHRINKAGE, PLIABILITY FOR PROOFED CANVAS AND HYDROSTATIC PRESSURE RESISTANCE SHALL BE IN ACCORDANCE WITH PS-319. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. (PAINT COATING THICKNESS: (45-50 MICRONS) OR GALVANIZATION (300 G/M² MINIMUM ZING COATING MASS) b. IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCHES. (PAINT COATING THICKNESS: (45-50 MICRONS) OR GALVANIZATION (300 G/M² MINIMUM ZING COATING MASS) c. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: 100% HIGH TENACITY NYLON (POLYAMIDE) 3-STAND BRAIDED, DIA: MINIMUM 16-MM, WITH CONFORMING TO ISO 1140:2021. d. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
139	DGE113914	TPT400-F1755	8305995275924 / GLASS CLOTH FIBER, PLAIN WEAVE, COLOUR NATURAL, FOR LAGGING PURPOSE	FOR LAGGING PURPOSE	18 / METER						TECHNICAL SPECIFICATION - testing criteria: DEFSTAN02-801, PART-2, WIDTH: 01 METER (39.4 INCH) FIBER MATERIAL: GLASS, CLOTH WEIGHT: 800 GRMS PER SQUARE METER, SPECIAL FEATURES: PLAIN WEAVE, MULTIFILAMENT WARP YARN, NATURAL COLOUR, 50 METERS PER ROLL GENERAL SPECIFICATION - testing criteria: DEFSTAN02-801, PART-2, WIDTH: 01 METER (39.4 INCH) FIBER MATERIAL: GLASS, CLOTH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WEIGHT: 800 GRMS PER SQUARE METER, SPECIAL FEATURES: PLAIN WEAVE, MULTIFILAMENT WARP YARN, NATURAL COLOUR, 50 METERS PER ROLL	
140	DGT105705	NO DATA AVAILABLE	010050000008 / Ply wood GD-I, 9 ply,	X 19.05 MM)	880 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.GENERAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
141	DGT114297	NO DATA AVAILABLE	010050000003 0 / PLY WOOD NATURAL	2.44X1. 22MTRX19. 05MM)	160 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION OF THE ITEM: SIZE= LENGTH= 8-FEET, WIDTH=	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TEAK FINISH BOTH SIDE (NOT ARTIFICIAL) GRADE-1, 9-PLY,	SPECE/BS6566 OF1985							4-FEET, THICKNESS= 16mm ±2, SPECS: 1. bs-1088 part-1&II, DENSITY OF TIMBER (TEAK) AS INTERNATIONAL STANDAR, 2. thickness of face back venEer should be 0.6 mm (min) 3. density of PLY WOOD TEAK= 500 TO 850 KG/M3, GENERAL SPECIFICATION - SPECIFICATION OF THE ITEM: SIZE= LENGTH= 8-FEET, WIDTH= 4-FEET, THICKNESS= 16mm ±2, SPECS: 1. bs-1088 part-1&II, DENSITY OF TIMBER (TEAK) AS INTERNATIONAL STANDAR, 2. thickness of face back venEer should be 0.6 mm (min) 3. density of PLY WOOD TEAK= 500 TO 850 KG/M3,	
142	DGD107550		7340705060449 / TABLE SPOON		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - Length = 190-200 mm Material = SS 304 food grade base s with golden color. Thickness = 2.5- 3.0 mm Weight = 45- 55 g Finish = Mirror polish with handle design. Edge = Smooth rounded, No sharp edges Packing= VIP single poly/ velvet box Standard= Food grade, lead/nickel freeGENERAL SPECIFICATION - Length = 190-200 mm Material = SS 304 food grade base s with golden color. Thickness = 2.5- 3.0 mm Weight = 45- 55 g Finish = Mirror polish with handle design. Edge = Smooth rounded, No sharp edges Packing= VIP single poly/ velvet box Standard= Food grade, lead/nickel free	
143	DGE113563	-	5610992004386 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	5 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCRETE UK LTD THE FLOORING TECHNOLOGIES CENTRE BOOTH		TECHNICAL SPECIFICATION - BAG SAND(LOCAL GOOD QUALITY ACCEPTABLE) 25 kg unfilledGENERAL SPECIFICATION - BAG SAND(LOCAL GOOD QUALITY ACCEPTABLE) 25 kg unfilled	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									LANE SANDBATCH CHESHIRE CW11 3QF UK PH:+44(0)1270 753000 & FAX :+44 (0)1270 753333			