

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 28-07-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPK105402	20W-50	9150PK5079480 / LUB OIL 20W50 PKG 4LTR (FOR PETROL VEHICLES)	PETROL VEHICLES	308 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
2	DSX100377	3AG255	5330755043790 / O-RING GASKET RUBBER DIA 288.8X300X7.0MM		30 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
3	DSX100376	3BG291	5330755058317 / O RING OR-O/D-6.50MM-LG-3900MM RUBBER		60 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
4	DSB101579	LW-PM-14-3KVTX/ LW-PM-14-VTX (LOCAL)	5310705251577 / lock washer dn14 (LOCAL)		204 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm GENERAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm	
5	DSB102914	LW-PM-14-3KVTX/ LW-PM-14-VTX (LOCAL)	5310705251577 / lock washer dn14 (LOCAL)		300 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm GENERAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											16mm	
6	DSA97352	2902879	596370523322 8 / REDUNDANT MODULE		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
7	DNQ103178	0121-924-0372	012199924037 2 / LUMBER SOFT WOOD DIM SZ 100X100MM (LENGTH=07 FEETS)	NBCD DAMAGE CONTROL & FIRE FIGHTING EQUIP	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
8	DNQ103812	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
9	DNH103913		411070505848 6 / DEEP FREEZER 30 CUFT 220V 50HZ SINGLE	USER MRO LAHORE	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
10	DNQ102214	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR- 38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	3 / EACH/NUMBER					TDS/BROCHER OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
11	DNQ103187	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR- 38-42MM LG	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			75MM									
12	DNQ102012	1-3-150 DEVELOPED BY DTD	4730992542747 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
13	DNQ101322	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER					TDS/BROCHER OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
14	DPK104328	Mobilux EP2	9611790170396 / Mobilux Grease EP2 (16 OR 18 Kg Packing)		5 / KILOGRAMME						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
15	DPC104058	HRC-407C (HFC-407C) GENETRON R-407C	6830705118136 / GAS FOR (A/C) R-407C (packing = 11.3 kg) (Purity level 99% Min)	A/C SPLIT (02TONS)	102.15 / KILOGRAMME						TECHNICAL SPECIFICATION - OEM: HONEYWELL (USA) GENERAL SPECIFICATION - OEM: HONEYWELL (USA)	
16	DNQ100846	159081	8465999244592 / FIREMAN'S BELTG, MODEL AUSTRIA WITH CARABINER	FIRE FIGHTING EQUIPMENT OEM: FIREKILINT	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - DSI, SIZE WAIST (75-110 CM) Weight: 1.5 kg Certified as to Austrian Standard ON F 4030:2008, EN 358, All polyester webbing, breaking load 2000kg. Dual thorn buckle. Comes with descender and steel snap hook, serving as a hand brake for self-rescue. Accepts leather hatcher hoder GENERAL SPECIFICATION - DSI, SIZE WAIST (75-110 CM) Weight: 1.5 kg Certified as to Austrian Standard ON F 4030:2008, EN 358, All polyester webbing, breaking load 2000kg. Dual thorn buckle. Comes with descender and steel snap hook, serving as a hand brake for self-rescue. Accepts leather	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											hatchet holder	
17	DPK104300	S-758/MIL-PRF-63460E/N YCOLUBE 127	9150010536688 / CLEANER, LUBRICANT AND PRESERVATIVE WEAPON OIL	USE FOR DIESEL ENGINE/12.7 MM GUN, MPAC,MRTPS	15 / GALLON						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
18	DNF103181	BG-424	5995755124607 / CABLE ELECTRICAL MINIATURE 04 CORE FOR MIC	SRE SYSTEM ITALY	1260 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
19	DPK87802	10250	5970143407636 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	20 / KILOGRAMME	NO DATA AVAILABLE				TDS/BROCHER OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
20	DGE101318	HME-AB-CLAMP-PVC-20MM-009	5340705351243 / PIPE U CLAMP pvc type		45 / EACH/NUMBER	SS304 SURFACE					TECHNICAL SPECIFICATION - PIPE U CLAMP PVC TYPE INNER 200mm outer dia 48mm height 38mm thickness 22mm GENERAL SPECIFICATION - PIPE U CLAMP PVC TYPE INNER 200mm outer dia 48mm height 38mm thickness 22mm	
21	DNQ103819	RADTARGE-H	6665785274041 / HIGH SENSITIVE PERSONAL DOSIMETER		11 / EACH/NUMBER	RADTARGE-H					TECHNICAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting GENERAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
22	DPK104540	GB11120-2011 ISO VG 32	9140FP0010021 / ISO VG 32 GB11120-2011 TURBINE OIL		1 / LITER	GB11120-2011					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
23	DN0102115	kiwi-dn50	4730705344196 / bulk head connector for dn-50		12 / EACH/NUMBER	dn-50					TECHNICAL SPECIFICATION - fitted on bulkhead used for connecting DN-50 between two compartments fire hoses/ water hoses GENERAL SPECIFICATION - fitted on bulkhead used for connecting DN-50 between two compartments fire hoses/ water hoses	
24	DNM102744	248-5513	5340715270350 / TEMPRATURE REGULATOR		4 / EACH/NUMBER	DE-660EO CATERPILLAR GENERATOR C18 600 KVA /480KW					TECHNICAL SPECIFICATION - TEMPRATURE REGULATOR GENERAL SPECIFICATION - TEMPRATURE REGULATOR	
25	DNQ103824	15199001	4220795289489 / SOLAS SOFTPACK RFD (FIRST AID KIT) FOR LIFE RAFT - LIFE BOAT		9 / EACH/NUMBER	life raft					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
26	DNF102167	HME-AB-SLV-220AC-005	5975705351270 / electrical CONNECTION BOX		12 / EACH/NUMBER	SS304 SURFACE box					TECHNICAL SPECIFICATION - ELECTRICAL CONNECTION BOX material pvc no of glands 04 width 12 inches length 10 INCHES height 6 INCHES GENERAL SPECIFICATION - ELECTRICAL CONNECTION BOX material pvc no of glands 04 width 12 inches length 10 INCHES height 6 INCHES	
27	DNF102168	HME-AB-LED-IND-20MM-GRNRD-006	6210705351274 / INDICATION LED LIGHT 230vac 20MM (GREEN & RED)		24 / EACH/NUMBER	led light					TECHNICAL SPECIFICATION - INDICATION LED LIGHT 230VAC 20MM (GREEN & RED) head dia 29-30mm overhaul length 50mm panEl thikness 6mm shape round GENERAL SPECIFICATION - INDICATION LED LIGHT 230VAC 20MM (GREEN & RED) head dia 29-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											30mm overhaul length 50mm panEl thickness 6mm shape round	
28	DNM98924	342-6510	5306715240108 / BOLT-TORX (M14X1.5X70-MM)		3 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - NOT KNOWN GENERAL SPECIFICATION - NOT KNOWN	
29	DNM101825	198586080 /T402621	3110785235515 / BIG END BEARING KIT		1 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - PERKINS,DIESEL GENERATOR 15 KVA PERKINS ENGINE COMPANY LIMITED FRANK PERKINS WAY CAMBERIGH SHIRE PE 15 FQ UNITED KINGDOM GENERAL SPECIFICATION - PERKINS, DIESEL GENERATOR 15 KVA PERKINS ENGINE COMPANY LIMITED FRANK PERKINS WAY CAMBERIGH SHIRE PE 15 FQ UNITED KINGDOM	
30	DNH103409	058825A	4440013106604 / DRYER CARTRIDGE/CARTRIDGE, DEHYDRATOR		2 / EACH/NUMBER	o 26-d dps					TECHNICAL SPECIFICATION - 0 26-D DPS MEDIUM AIR CHARGIN RATE 26.4 SCFM INLET PRESSURE ATMOSPHERIC OPERATING PRESSURE 5000 PSIG AMBIENT TEMPERATURE 40 TO 115 F WEIGHT 2000 IBS APPROX TECHNICAL SPEC ENCLOSED GENERAL SPECIFICATION - 0 26-D DPS MEDIUM AIR CHARGIN RATE 26.4 SCFM INLET PRESSURE ATMOSPHERIC OPERATING PRESSURE 5000 PSIG AMBIENT TEMPERATURE 40 TO 115 F WEIGHT 2000 IBS APPROX TECHNICAL SPEC ENCLOSED	
31	DPK104477	SPIRAX S2 G 140	9150795293050 / shell SPIRAX S2 G 140		2 / LITER	EMPERO EM.09.P					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
32	DPC104663	SPECIFICATION BS 479 SECTION 5	0442509429219 / NAPHTHA COALTAR (HEAVY) 90/190 (THINNER	THINNER FOR BOTTOM COMPOSITIO NS	20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FOR BOTTOM COMPOSITIO N									
33	DPC104 686		044250442005 1 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	260 / LITER						TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg GENERAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
34	DPK1044 44	0474-7021 (0475-99- 224-2137)	047450224213 7 / TALLOW WHITE (GREASE) (200 KG DRUM)		200 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
35	DPC102 100		047350224770 1 / GUM ACACIA TECHNICAL		20 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
36	DRG998 87	I-6000T CC-6000 OR I- 633MMTB	291570515008 8 / COALESCER ELEMENT ASSY		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DNQ101 312	464748 ABN.	473001435510 6 / REPAIR KIT,PIPE, EMERGENCY DAMAGE CONTROL	EMERGENCY CONTROL , PIPE REPAIR KIT.	5 / KIT			OEM: c IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES	INDUMAR PRODUC TS INC DBA STOP ..		TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM			//WWW.STOPIT.COM <u>GENERAL SPECIFICATION</u> - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	
38	DNM102777	352-9766	610571522588 7 / MOTOR GP ELECTRICAL	GEN SET	1 / EACH/NUMBER	3512B	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR, USA		<u>TECHNICAL SPECIFICATION</u> - ITEM IS USED FOR STARTING SYSTEM OF CATERPILLAR GEN SET 1. Rating: 1088 KW 2. Brand: CATERPILLAR DG 3. Model No: 3512B 4. ESN: BS500559 5. Unit: NMG (O), DG No 3 <u>GENERAL SPECIFICATION</u> - ITEM IS USED FOR STARTING SYSTEM OF CATERPILLAR GEN SET 1. Rating: 1088 KW 2. Brand: CATERPILLAR DG 3. Model No: 3512B 4. ESN: BS500559 5. Unit: NMG (O), DG No 3	
39	DNM105382	CWCU-230-27	413070521434 5 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 24	HVAC PLANT 02 CWAHU-24 PAKISTAN	8 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www. guardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20" <u>GENERAL SPECIFICATION</u> - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20"	
40	DNM105386	CWCU-230-27 (12)	413070521434 6 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	1 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www. guardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20" <u>GENERAL SPECIFICATION</u> - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"	
41	DNM105386	CWCU-230-27 (12)	413070521434 6 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	1 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www. guardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20" <u>GENERAL SPECIFICATION</u> - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
42	DNM105300	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	CAT00C715GTY00677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MAKE: CATERPILLAR GENERAL SPECIFICATION - MAKE: CATERPILLAR	
43	DNH105141	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
44	DNQ105149	HAMMAR H 20	4220735199199 / HAMMAR H 20 R HYDROSTATIC RELEASE FOR LIFERAFTS	HAMMAR H 20 R HYDROSTATIC RELEASE FOR LIFE RAFT	12 / EACH/NUMBER	G91154/0902	NA	CM Hammar AB, August Barks gata 15, SE-421 32 Västra Frölunda (Göteborg), Sweden Phone: +46 31 709 65 50 Fax: +46 31 49 70 23 Email: info@cmhammar.com www.cmhammar.com	CM Hammar Sweden	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - The Hammar H20 hydrostatic release unit is designed for liferafts from 6 up to 150 persons. The Hammar H20 release unit consists of a double looped white rope sling, a release mechanism and a Red Weak Link? (breaking strength 2,2 ± 0,4 kN) GENERAL SPECIFICATION - The Hammar H20 hydrostatic release unit is designed for liferafts from 6 up to 150 persons. The Hammar H20 release unit consists of a double looped white rope sling, a release mechanism and a Red Weak Link? (breaking strength 2,2 ± 0,4 kN)	
45	DNM105452	IQ/WC/011	4935705132911 / WATER COOLER(100 LTRS CAPACITY)	WATER COOLER	3 / EACH/NUMBER	NO DATA AVAILABLE		PK	SUNNY WATER COOLER COMPANY PAKISTAN	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
46	DNQ105227	06973009	6140FT1019336 / Torch (Long Life) c/w Spares	Emergency Pack - 1	14 / EACH/NUMBER	583210B.0006	0	KINGSWAY DUNMURRY BELFAST IRLAND	SURVITEC GROUP	TDS\BROCHER or pic OF ITEM MUST BE	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION		
47	DNM105433	TKTL30	6605725166349 / LASER TEMPERATURE GUN STAINLESS STEEL	ICE ENGINE	2 / EACH/NUMBER	SKF		OEM:WWW.MAPRO.SKFCOM.	GERMANY	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Make/ Model/ Brand: SKF TKTL 30 OEM:ELORA-WERKZEUGFABRIK GMBH AM BLAFFERTSBERG 33 REMSCHEID GERMANY 42899 12 02 62 PCC: REMSCHEID TEL: 02191/5627-0 FAX: 02191/562719 EMA: INFO@ELORA.DE WWW: WWW.ELORA.DE GENERAL SPECIFICATION - Make/ Model/ Brand: SKF TKTL 30 OEM:ELORA-WERKZEUGFABRIK GMBH AM BLAFFERTSBERG 33 REMSCHEID GERMANY 42899 12 02 62 PCC: REMSCHEID TEL: 02191/5627-0 FAX: 02191/562719 EMA: INFO@ELORA.DE WWW: WWW.ELORA.DE	
48	DPK102984	7101001002	9150735232473 / REFRIGERATION LUB OIL DHB-002 (19 Liters Packing)	HARD FORD AC COMPRESSOR	15 / LITER	DHB-002	17FA000G5737A	DUNHAM-BUSH INDUSTRIES SMD.BHD. LOT 5755-6,KIDMAL INDUSTRIAL PARK,BUKIT ANGKAT,43000 KAJANG. SELANGOR PH:+603-89249000 FAX:+603-89395020	DUNHAM-BUSH INDUSTRIES	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - FLASH POINT (ASTM D-92,COC) 190C,MELTING POINT :(ASTM D-92,COC)-30 CGENERAL SPECIFICATION - FLASH POINT (ASTM D-92,COC)190C,MELTING POINT :(ASTM D-92,COC)-30 C	
49	DNM79184	3588745/3588770	3426171227297 / ANODE KIT ZINC ANODE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBOG, SWEDEN	AB VOLVO PENTA		TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887	
50	DNM105306	A043Z558	2940715232077 / FILTER AIR	DG 138 KVA C150D5B	1 / EACH/NUMBER	C150D5B	78630284	M/S ORIENT ENERGY SYSTEM (PVT) LTD 52 WEST FIRST FLOOR WAHEED PLAZA BLUE AREA ISLAMABAD	CUMMINS/ORIENT ENERGY SYSTEM	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - FILTER AIR USED IN ENGINE(AIR) SYSTEM IN CUNMMINS 138 KVA DG AT RDS MIANWALI INSTALLEDGENERAL SPECIFICATION - FILTER AIR USED IN ENGINE(AIR) SYSTEM IN CUNMMINS 138 KVA DG AT RDS MIANWALI INSTALLED	
51	DNM105	CWCU-	413070521434	HVAC PLANT	8 /	CP-F6-95	NIL	COL POINT PLOT :	GUARD	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	382	230-27	5 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 24	02 CWAHU-24 PAKISTAN	EACH/NUMBER	3		SHARAZ AVENUE JATI UMER ROAD LAHORE COOL POINT PVT LMTD LAHORE PAKISTAN GUARD FILTERS PAKISTAN www.guardfilters.com	FILTERS PAKISTAN www.guardfilters.com	HER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20" GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20"	
52	DNM105386	CWCU-230-27 (12	413070521434 6 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	1 / EACH/NUMBER	CP-F6-95-3	NIL	COOL POINT PLOT : SHARAZ AVENUE JATI UMER ROAD LAHORE COOL POINT PVT LMTD LAHORE PAKISTAN GUARD FILTERS PAKISTAN www.guardfilters.com	GUARD FILTERS PAKISTAN www.guardfilters.com	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"	
53	DPC105447	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
54	DPC105513	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
55	DNM105452	IQ/WC/011	493570513291 1 / WATER	WATER COOLER	3 / EACH/NUMBER	NO DATA AVAILABLE		PK	SUNNY WATER COOLER	TDS\BROCHER or pic OF ITEM	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COOLER(100 LTRS CAPACITY)						COMPAN Y PAKISTAN	MUST BE ENCLOSED WITH QUOTATION		
56	DNQ103475	NIL	5120997876848 / HAMMER 910G (2LB) BALL PEIN	FIRE FIGHTING	14 / EACH/NUMBER	NO DATA AVAILAB LE		UK	UK	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
57	DNM105146	934-602/SE652 CJ	2815795170184 / TURBO CHARGER	PEKIN DIESEL GENERATOR 4006-23TAG3A	2 / EACH/NUMBER	4006-23TAG3A	1) DGF6116-U19638U 2) DGF6116-U19758U	PETER BOROUGH PE 15NA UNITED KINGDOM ENGLAND	PERKINS ENGINEERING COMPANY LIMITED	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> USED IN AIR INTAKE SYSTEM <u>GENERAL SPECIFICATION -</u> USED IN AIR INTAKE SYSTEM	
58	DPK101386	TEXAMAT C 1888 SAE DEXRON-III	9150014878530 / STEERING LUB OIL (PETROL/DIESEL ENGINE MT VEHICLES) (01 ltrs packing)	MT VEHICLE	80 / BOTTLE			GENERAL MOTORS CORP 3044 W GRAND BLVD DETROIT MI UNITED STATES PSC: 48202-3091 TEL: 248-857-2576	GENERAL MOTORS CORP	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
59	DNM103564	SE123B	6680998980409 / DIPSTICK ASSEMBLY	PEKIN DIESEL GENERATOR 4006-23TAG3A	1 / EACH/NUMBER	4006-23TAG3A	1) DGF6116-U19638U 2) DGF6116-U19758U	PETER BOROUGH PE 15NA UNITED KINGDOM ENGLAND	PERKINS ENGINEERING COMPANY LIMITED	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> USED IN SUMP SYSTEM <u>GENERAL SPECIFICATION -</u> USED IN SUMP SYSTEM	
60	DNM105300	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENS	TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> MAKE: CATERPILLAR <u>GENERAL SPECIFICATION -</u> MAKE: CATERPILLAR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									E PRODUCTS			
61	DPC105380		047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	180 / KILOGRAMME					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
62	DPC105384		047450220173 8 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY	SKF COUPLING	750 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	
63	DPC105481	DEFSTAN 68-30/1 OF 1974	047450220483 4 / CHLORINATED LIME, TECHNICAL 30% MIN available CHLORINE (25 KG Packing)		1500 / KILOGRAMME					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 68-30/1 OF 1974 OEM COC DATE OF MANUFACTURING & EXPIRY OEM TEST CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE GENERAL SPECIFICATION - DEFSTAN 68-30/1 OF 1974 OEM COC DATE OF MANUFACTURING & EXPIRY OEM TEST CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE	
64	DPC105461	SAME AS S NO 9 EXECPT SHADE.	044250220163 7 / PAINT FINISHING (GREEN)	USES FOR STEEL ALUMINUM OR WOOD ON GLASS	102 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DPC105292		044250442004	DECORATIVE/ FINISHING	40 / LITER					TDS\BROCHER or pic	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6 / PAINT GOLDEN (YELLOW)	FOR MOTOR VEHICLES						OF ITEM MUST BE ENCLOSED WITH QUOTATION	FLASH POINT 32C (min) COLOUR SHADE NO 356 OF BS 381-C OF 1996 defstan 80-72/3 of 2005 stage inspection prescribed PACKING 04 LTR gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION -</u> FLASH POINT 32C (min) COLOUR SHADE NO 356 OF BS 381-C OF 1996 defstan 80-72/3 of 2005 stage inspection prescribed PACKING 04 LTR gauge of tin 26 to 28 swg	
66	DPC105 508		044250442005 1 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	319 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
67	DPC105 612		044250943447 9 / PAINT PRIMING, LIGHT ADMIRALTY GREY FLASH POINT 23 DEGREE C	PRIMER FOR FINISHING ACID AND ALKALI	60 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> DEFSTAN 80-72/3 OF 2006 2. COLOUR SHADE NO 697 OF BS: 381 OF 1996 <u>GENERAL SPECIFICATION - 1.</u> DEFSTAN 80-72/3 OF 2006 2. COLOUR SHADE NO 697 OF BS:381 OF 1996	
68	DPC105 614		044250943448 1 / PAINT ACID AND ALKALY RESISTANT A/R (BLACK) 05 LTR TIN Flash Point: 32	FINISHING	4 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED 3. DEFSTAN 80-72/3 OF 2006 <u>GENERAL SPECIFICATION - 1.</u> NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Degree C (min) Packing: standard oem 04 ltr tin non corrosive gauge of tin 26 to 28 swg							N	3. DEFSTAN 80-72/3 OF 2006	
69	DPC105 373		044250943448 3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	72 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C OF 1996 <u>GENERAL SPECIFICATION -</u> DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C OF 1996	
70	DPC105 622		044250943448 3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	160 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C OF 1996 <u>GENERAL SPECIFICATION -</u> DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C OF 1996	
71	DPC105 511	106 OF BS381-C OF 1996	044250442006 1 / PAINT VEHICLE CELLULOSE (ROYAL NAVY BLUE)	VEHICLES, DECORATIVE FINISHING	67 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH	<u>TECHNICAL SPECIFICATION -</u> DEFSTAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996. <u>GENERAL SPECIFICATION -</u> DEFSTAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATION		
72	DPC105 221	S NO 120 SIMILAR	0442504420063 / PAINT WEATHER WORK(DARK GREY) (NSSD/C01/0442/GEN/173DT 060393)	WEATHER WORK	100 / KILOGRAMME					TDS/BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DPC105 512	S NO 120 SIMILAR	0442504420063 / PAINT WEATHER WORK(DARK GREY) (NSSD/C01/0442/GEN/173DT 060393)	WEATHER WORK	407 / KILOGRAMME					TDS/BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DPC105 564		0442509423538 / PAINT MARKING BRUSH STENCILLING (BLACK) type: alky6ed, Flash Point: 32 Degreee C (Min) moethod of application brushing, Packing: 04 ltr tin gauge of drum 26 to 28 swg	N B C D MARKING ETC.	235 / LITER					TDS/BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed GENERAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed	
75	DPC105 291		0442504420043 / PAINT FINISHING MID BROWN GLOSS FLASH POINT 32C (04 LTR Packing)	MULTI COAT FINISH PRIMED SEEL ALUMINUM	90 / LITER					TDS/BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996 GENERAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996	
76	DPC105		044250442009	AMPN	8 /					TDS/BROCH	TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	224		7 / VARNISH OIL EXTERIOR GARDE-II		LITER					HER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DPC105 229	DEFSTAN 80-37/2 OF 2006	044250442012 4 / Paint Cellulose White Finsihing for vehicles principal component Nitro Cellulose Base Flash Point 23		25 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
78	DNQ105 466	NO DATA AVAILABE	034059923624 3 / BAG CANVAS TOOL SATCHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		11 / EACH/NUMBER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
79	DPC105 506	NO DATA AVAILABE	044250220238 1 / PAINT PRIMING GRAPHITE BASIS (RED LEAD)	BUXLY/ICI/BERGER/KOSAR GRP-E VIDE NHQ LT	243 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
80	DPC105 489	SUPERSEDED BY DGS 1035	044250220202 0 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	264 / LITER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribedGENERAL SPECIFICATION - DEFSTAN 80-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
81	DPC105366	SPEC,DEF 1052 COLOURS TO BS 381C	0442509107035 / PAINT FNSHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/566DT210902		30 / KILOGRAMME					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DPC105533	SPEC,DEF 1052 COLOURS TO BS 381C	0442509107035 / PAINT FNSHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/566DT210902		285 / KILOGRAMME					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	DPC105462	NO DATA AVAILABLE	0276145055100 / CONTACT CLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS) Packing = 200ml	FOR GENERAL USE	45 / EACH/NUMBER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
84	DNQ105128	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/NUMBER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
85	DPC103548		0473504730053 / SALT		10 / KILOGRAMME					TDS\BROCHER or pic	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ZOZAX PASSIVTING		AMME					OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>SPECIFICATION - NO DATA AVAILABLE</u>	
86	DNM105091	NR-20550/96	2920725089587 / FOG GENERATOR TF-35 FOR CONTROL OF MOSQUITOES	FOR GENERATOR TF35FOR CONTROL (GERMANY)	1 / EACH/NUMBER	TF-35				TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - IGEBAGENERAL SPECIFICATION - IGEBAG</u>	
87	DNM105465	B57121X513F075xx/P7800B3X/P425S-2373D-512-7.5T (340970)	4140715092410 / A/C SEA/CHILL WATER PUMP WITH MOTOR	A/C UNIT OEM:M/S TAYLOR MADE ENVIRONMEN T	1 / EACH/NUMBER					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - OEM: DOMETIC ENVIROMENTAL CORPORATION P.O BOX 15299 RICHMOND USA VA 23227-0699GENERAL SPECIFICATION - OEM: DOMETIC ENVIROMENTAL CORPORATION P.O BOX 15299 RICHMOND USA VA 23227-0699</u>	
88	DNH105301	EAC-70/WP-1302/ECM 6500	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	1 / EACH/NUMBER	EAC-70/WP-1302/ECM 6500				TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZEGENERAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE</u>	
89	DNH98111		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	30 / EACH/NUMBER	WA60000514				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 WGENERAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W</u>	
90	DNM103689	525/50M	4730795066518 / CLIP (JUBLEE CLAMP)	DORMAN 6SETCW CONTINGENCY SPARES	12 / EACH/NUMBER					TDS\BROCHER or pic OF ITEM MUST BE	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			S/STEEL 60-80MM							ENCLOSE D WITH QUOTATIO N		
91	DNQ105 044	0413-2183	597099923966 3 / TAPE INSULATION ELECTRICAL	GENETAL USE	134 / EACH/N UMBER					TDS\BROC HER or pic OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION -</u> Brand: OSAKA, NEETO . Packing details: 10-12 in each packing <u>GENERAL SPECIFICATION -</u> Brand: OSAKA, NEETO . Packing details: 10-12 in each packing	
92	DNH982 40	NO DATA AVAILABL E	411075053010 5 / REFRIGERAT OR 6CUFT 220V 50HZ		30 / EACH/N UMBER	NO DATA AVAILAB LE				TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLEG <u>GENERAL SPECIFICATION -</u> NO DATA AVAILAB LE	
93	DPC105 517	NO DATA AVAILABL E	683070504133 8 / GAS ARGON N56 HIGH PURITY 99.9996%	FOR MISTRAL AIR DEFENCE SYSTEM	6.8 / CUBIC METER					TDS\BROC HER or pic OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION -</u> 1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes. <u>GENERAL SPECIFICATION -</u> 1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes.	
94	DNH105 126	NO DATA AVAILABL E	411076053012 4 / REFRIGERAT OR 20 CU/FT 220V 50 HZ		1 / EACH/N UMBER	NO DATA AVAILAB LE				TDS\BROC HER or pic OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLEG <u>GENERAL SPECIFICATION -</u> NO DATA AVAILAB LE	
95	DNM105 098	MURPHY LTD PDS 100-007	668571504852 7 / OIL PRESSURE GAUGE 0-TO-100 PSI& 0-7 BAR MURPHY	CUMMINS DIESEL ENGINE 34.5 KVA (USA/UK)	6 / EACH/N UMBER					TDS\BROC HER or pic OF ITEM MUST BE ENCLOSE D WITH	<u>TECHNICAL SPECIFICATION -</u> DIMENSION / SIZE: Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SWITCH GAUGE							QUOTATION	GaugeGENERAL SPECIFICATION - DIMENSION / SIZE: Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch Gauge	
96	DPC105304	NIL-SHELF LIFE 3 MONTH	6810705039263 / DECK COMPOUND FLASH POINT 89C SP-GR-1009 (ANTI SKID)	LOCAL PURCHASE	300 / KILOGRAMME					TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DPK105407	TCW3 NMMA	072150000013 / LUB OIL OMD-23 FOR TWO STROKE OUTBOARD GASOLINE ENGINE NMMA GRADE TCW3		200 / LITER	NO DATA AVAILABLE				TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLEGENERAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE	
98	DPC105456	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		1030 / LITER	PINAX-A				TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. GENERAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
99	DNQ105206	RADTARGE-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		10 / EACH/NUMBER	RADTARGE-H				TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting GENERAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting	
100	DRG98744	ZO6547932	2915ZO654793 2 / REGULATOR HIGH PRESSURE		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - S2500 GP SINGLE STAGE REG FOR OXY/INERT GAS SVCE EAX INLET PRESS:300BAR/4350PSI, OUTLET PRESS:172BAROR 2500 PSI GENERAL SPECIFICATION - S2500 GP SINGLE STAGE REG FOR OXY/INERT GAS SVCE EAX INLET PRESS:300BAR/4350PSI, OUTLET PRESS:172BAROR 2500 PSI	
101	DPC105460	ZEEPER114	801070533284 9 / ZEEPER 114 CLEANER		1520 / KILOGRAMME	ZEEPER. 114				TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years GENERAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
102	DSB74776	50TE000C0027	668574519428 3 / THERMOMETER BDT 25 & 26 0A 200 DIAM93 SUTTE OM		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
103	DSB87559	TAG-700 AIR ANGLE GRINDER/ NKS - NK2261G1	0099086072967 / PNEUMATIC ANGLE GRINDER KL/12 OR 700NA		3 / EACH/NUMBER	tag-700 qjl/NK2261G1					<u>TECHNICAL SPECIFICATION</u> - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2" <u>GENERAL SPECIFICATION</u> - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2"	
104	DSB86121	TAG-700 AIR ANGLE GRINDER/ NKS - NK2261G1	0099086072967 / PNEUMATIC ANGLE GRINDER KL/12 OR 700NA		3 / EACH/NUMBER	tag-700 qjl/NK2261G1					<u>TECHNICAL SPECIFICATION</u> - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2" <u>GENERAL SPECIFICATION</u> - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2"	
105	DRG100068	A5476VLP	2915ZO6527525 / REGULATOR LP AIR		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE), TANAKA JAPAN <u>GENERAL SPECIFICATION</u> - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE), TANAKA JAPAN	
106	DRG100280	A5476VLP	2915ZO6527525 / REGULATOR LP AIR		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE), TANAKA JAPAN <u>GENERAL SPECIFICATION</u> - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN	
107	DRG100349	A5476VLP	2915ZO6527525 / REGULATOR LP AIR		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN GENERAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN	
108	DRG79432	3916854	6110ZO6549107 / STARTER MOTOR(24V DC)		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - STARTER MOTOR WITH SOLONIDE SWITCH,24 V DC , MAKE: CUMMINS USA. GENERAL SPECIFICATION - STARTER MOTOR WITH SOLONIDE SWITCH, 24 V DC ,MAKE: CUMMINS USA.	
109	DPK105319	PYRATTEX EP2	9150145784933 / FIRE PROOF GREASE / GREASE, HEAT DISSIPATION COMPOUND		2 / KILOGRAMME	EP2				TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
110	DNM105147	EP6500 CXS	2895765289257 / HONDA GENERATOR (5 KVA, PETROL)		10 / EACH/NUMBER	EP 6500CXS				TDS\BROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
111	DRG100194	I-6000T CC-6000 OR I-633MMTB	2915705150088 / COALESCER ELEMENT ASSY		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
112	DPC103 659	236543	289571531213 2 / HAVOLINE XTENDED LIFE ANTIFREEZE/ COOLANT (Premixed 50/50)		40 / LITER	YANMAR, 6LPA-STP				TDSIBROCHER or pic OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
113	DSB93930	MAT820-0004F17	451014502208 3 / MIXING TAP ON PANTRY SINK		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
114	DSA101603	SC12SERIEWHA15-115V60HZ	411014324180 5 / FONTAINE REFT SC12		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
115	DNM102844	380-4843	530571520215 8 / SCREW-ADJUSTING (5/8-18X2.375-IN)	CATERPILLAR GENSET D3512B (YBB1) USA	12 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - 0 GENERAL SPECIFICATION - 0	
116	DPC103 658	G-1200	047550220561 3 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		41 / TUBE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
117	DPC103 518	NO DATA AVAILABLE	421070506993 6 / CYLINDER CO2 (72KG) CO2 FIXED FIRE FIGHTING SYSTEM BOAT WAIN (EMPTY)	PNS GAWADAR	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 01 Fire Extinguisher Cylinder CO2: 72 KG (Empty Weight) 02 Capacity :50 KG 03 Total Weight: 122 KG 04 Operation Method: Store Pressure 05 Extinguishing Agent: Carbon Dioxide 06 Operating Temperature: 30c to 60c 07 Discharge Time: 7 Sec per KG 08 Discharge Distance: 4 Meter 09 Height: 1440 mm 10 Width: 650 mm 11 Depth :1400 mm 12 Working Pressure: 60 Bar 13 Testing Pressure: 250 Bar 14 Material: Iron Steel GENERAL SPECIFICATION - 01 Fire Extinguisher Cylinder CO2: 72 KG (Empty Weight) 02 Capacity : 50 KG 03 Total Weight: 122 KG 04 Operation Method: Store Pressure 05	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Extinguishing Agent: Carbon Dioxide 06 Operating Temperature: 30c to 60c 07 Discharge Time: 7 Sec per KG 08 Discharge Distance: 4 Meter 09 Height: 1440 mm 10 Width: 650 mm 11 Depth :1400 mm 12 Working Pressure: 60 Bar 13 Testing Pressure: 250 Bar 14 Material: Iron Steel	
118	DPC103 800	RESIN 60 TO 70% (DRIER 01.5)	8010705061107 / PAINT WEATHER WORK FINISHING DLT LTR NS/G/1303/C DT 270199		60 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
119	DNM102 843	358-0768	5305715202157 / SCREW-ADJUSTING (1/2-20X2.42-IN)	CATERPILLAR GENSET D3512B (YBB1) USA	24 / EACH/N UMBER	NA	CAT3512 BEYBB00 583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - 0 GENERAL SPECIFICATION - 0	
120	DPC105 132	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
121	DNM103 943	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	1 / EACH/N UMBER	HD 8/18-4 M* KAR					TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control GENERAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	