

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 28-10-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE105345	611-055	402079515314 3 / ROPE NYLON 16MM WHITE MULTIPLAIT (FLEXABLE AND HIGH)	TAL SHIP SAILING RIG	440 / METER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT.	UK		TECHNICAL SPECIFICATION - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 220 METERS. 8. REQUIREMENT OF VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											RN/RELATED COUNTRY MOD. 10. VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. TALL SHIP SAILING RIG" GENERAL SPECIFICATION - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 220 METERS. 8. REQUIREMENT OF VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/ RN/RELATED COUNTRY MOD. 10. VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. TALL SHIP SAILING RIG"	
2	DGD109067	NO DATA AVAILABLE	0033500000206 / Tumbler Glass for Drinking Water		12 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Material: Glass (Crystal Clear) Capacity: 280/300 ml Brand: Toya Nasic / Nova (LOCAL)GENERAL SPECIFICATION - Material: Glass (Crystal Clear) Capacity: 280/300 ml Brand: Toya Nasic / Nova (LOCAL)	
3	DGE109664	20-53-21-17-01KEA	4240705207320 / ELBOW & KNEE PADS	KNEE PADS	100 / EACH/NUMBER	NIL	NIL	M SADIQ ALI & SONS, 217/15,SALEH MARKET, ADAMJEE ROAD, SADDAR, RAWALPINDI. 051-5527252 051-5513958		M SADIQ ALI & SONS	TECHNICAL SPECIFICATION - Specification: THE SUBJECT ITEM IS USED TO CARRY OUT AMMUNITIONS, WEAPONS AND SPARE MAGZINES. SUPPORTED BY A COMPREHENSIVE AND INTEGRATED SYSTEM OF MAGZINE POUCHES RADIO GRENADE AND MULTIPLE UTILITY USAGES. Technical Data: MADE WITH 100 D CORDURA / NYLON ALONGWITH WATEWR RESISTANT FINISH AT THE FRONT AND POLY URETHANE (PU) COATING AT THE BACK. PURPOSE BUILT SNIPER SHOULDER MADE WITH NON SLIP FABRIC AND OUTSIDE BUTTRETAINER FOR BETTER GRIP OF THE WEAPON IN FIRING POSITION. Testing/ Acceptance Criteria/ Applicable Standards: Testing, Acceptance and Standards by end user 1. MADE WITH 100 D CORDURA / NYLON ALONGWITH WATEWR RESISTANT FINISH AT THE FRONT AND POLY URETHANE (PU) COATING AT THE BACK. 2. PURPOSE BUILT SNIPER SHOULDER MADE WITH NON SLIP FABRIC AND OUTSIDE BUTTRETAINER FOR BETTER GRIP OF THE WEAPON IN FIRING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											POSITION. <u>GENERAL SPECIFICATION</u> - Specification: THE SUBJECT ITEM IS USED TO CARRY OUT AMMUNITIONS, WEAPONS AND SPARE MAGZINES. SUPPORTED BY A COMPREHENSIVE AND INTEGRATED SYSTEM OF MAGZINE POUCHES RADIO GRENADE AND MULTIPLE UTILITY USAGES. Technical Data: MADE WITH 100 D CORDURA / NYLON ALONGWITH WATEWR RESISTANT FINISH AT THE FRONT AND POLY URETHANE (PU) COATING AT THE BACK. PURPOSE BUILT SNIPER SHOULDER MADE WITH NON SLIP FABRIC AND OUTSIDE BUTTRETAINER FOR BETTER GRIP OF THE WEAPON IN FIRING POSITION. Testing/ Acceptance Criteria/ Applicable Standards: Testing, Acceptance and Standards by end user 1. MADE WITH 100 D CORDURA / NYLON ALONGWITH WATEWR RESISTANT FINISH AT THE FRONT AND POLY URETHANE (PU) COATING AT THE BACK. 2. PURPOSE BUILT SNIPER SHOULDER MADE WITH NON SLIP FABRIC AND OUTSIDE BUTTRETAINER FOR BETTER GRIP OF THE WEAPON IN FIRING POSITION.	
4	DGH107 120		614570520821 8 / 3X95 CU/PVC/PVC FLEXIBLE 600/1000 VOLT NONARMOUR ED 233amp cable	ELECTRIC CABLE FOR SHORE SUPPLY	25 / METER	3X95 CU/PVC/ PVC	NIL	ARIF HABIB CENTRE IST FLOOR 23 M T KHAN ROAD KARCHI UAN: 111-CABLES(222- 537) EMAIL: info@pakistancables.com	PAKISTA N CABLE		<u>TECHNICAL SPECIFICATION</u> - a. Cores 3 Core 95MM b. Material Copper c. Coatings PVC/PVC Flexible d. Voltage rating 600/1000 Volts e. Ampere rating 233 Amp f. Type Non Armored g. Conductor cross sectional area 95 mm h. Number of conductor 03 j. Approximate overall diameter 55 mm to 65 mm 3X95 3 CORE 95MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COPPER/PVC/PVC FLEXIBLE 600/1000VOLT 233AMP NONARMOURED CABLE. conductor crass sectional Area: 95 mm2 (Brief detail are available in upload brusher) Number of conductor: 03 Conductor Cross sectional area/ Diameter: 11.7 mm Approximate overall diameter 55mm to 65mm Thickness of over sheet and thickness of Insulation: 3.2 mm to 3.5mm and 4.5mm to 5.5mm Specification Standard (BS, Def-Stan etc) : BS5467 <u>GENERAL SPECIFICATION</u> - a. Cores 3 Core 95MM b. Material Copper c. Coatings PVC/PVC Flexible d. Voltage rating 600/1000 Volts e. Ampere rating 233 Amp f. Type Non Armored g. Conductor cross sectional area 95 mm h. Number of conductor 03 j. Approximate overall diameter 55 mm to 65 mm 3X95 3 CORE 95MM COPPER/PVC/PVC FLEXIBLE 600/1000VOLT 233AMP NONARMOURED CABLE. conductor crass sectional Area: 95 mm2 (Brief detail are available in upload brusher) Number of conductor: 03 Conductor Cross sectional area/ Diameter: 11.7 mm Approximate overall diameter 55mm to 65mm Thickness of over sheet and thickness of Insulation: 3.2 mm to 3.5mm and 4.5mm to 5.5mm Specification Standard (BS, Def-Stan etc) : BS5467	
5	DGH107059		6145705208218 / 3X95 CU/PVC/PVC FLEXIBLE 600/1000 VOLT NONARMOUR ED 233amp cable	ELECTRIC CABLE FOR SHORE SUPPLY	25 / METER	3X95 CU/PVC/ PVC	NIL	ARIF HABIB CENTRE IST FLOOR 23 M T KHAN ROAD KARCHI UAN: 111-CABLES(222-537) EMAIL: info@pakistancables.com		PAKISTAN CABLE	<u>TECHNICAL SPECIFICATION</u> - a. Cores 3 Core 95MM b. Material Copper c. Coatings PVC/PVC Flexible d. Voltage rating 600/1000 Volts e. Ampere rating 233 Amp f. Type Non Armored g. Conductor cross sectional area 95 mm h. Number of conductor 03 j. Approximate overall diameter 55 mm to 65 mm 3X95 3 CORE 95MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											COPPER/PVC/PVC FLEXIBLE 600/1000VOLT 233AMP NONARMoured CABLE. conductor crass sectional Area: 95 mm2 (Brief detail are available in upload brusher) Number of conductor: 03 Conductor Cross sectional area/ Diameter: 11.7 mm Approximate overall diameter 55mm to 65mm Thickness of over sheet and thickness of Insulation: 3.2 mm to 3.5mm and 4.5mm to 5.5mm Specification Standard (BS, Def-Stan etc) : BS5467 <u>GENERAL SPECIFICATION</u> - a. Cores 3 Core 95MM b. Material Copper c. Coatings PVC/PVC Flexible d. Voltage rating 600/1000 Volts e. Ampere rating 233 Amp f. Type Non Armored g. Conductor cross sectional area 95 mm h. Number of conductor 03 j. Approximate overall diameter 55 mm to 65 mm 3X95 3 CORE 95MM COPPER/PVC/PVC FLEXIBLE 600/1000VOLT 233AMP NONARMoured CABLE. conductor crass sectional Area: 95 mm2 (Brief detail are available in upload brusher) Number of conductor: 03 Conductor Cross sectional area/ Diameter: 11.7 mm Approximate overall diameter 55mm to 65mm Thickness of over sheet and thickness of Insulation: 3.2 mm to 3.5mm and 4.5mm to 5.5mm Specification Standard (BS, Def-Stan etc) : BS5467	
6	DGE105 683		035059571323 5 / ROPE SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH		120 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM/MANUFACTURED COC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(ROUNDED IN 9-MM)								REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM/MANUFACTURED COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
7	DGE104084		035059571323 5 / ROPE SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH (ROUNDED IN 9-MM)		120 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM/MANUFACTURED COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM/MANUFACTURED COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
8	DGE106282	0413/8520	041359923891 1 / SHEET RUBBER SOLID NATURAL, OFF WHITE SQ 1/2 LBS, SIZE; 1830MM X 1220MM X 16.0MM (39.29 KILOS PER SHEET)		10 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. BS-1154 OF 1992 COMPOUND CLASSIFICATION, Y-40 2. HARDNESS RATING: 38-40 DEGREES 3. TENSILE STRENGTH: 2500 PSI GENERAL SPECIFICATION - 1. BS-1154 OF 1992 COMPOUND CLASSIFICATION, Y-40 2. HARDNESS RATING: 38-40 DEGREES 3. TENSILE STRENGTH: 2500 PSI	
9	DGB99576	NO DATA AVAILABLE	028370000164 1 / SILVER SOLDER EASYFLO FOR STAINLESS STEEL IN ROD FORM		2700 / GRAM						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
10	DGB102092		026759521328 5 / Piping Steel Galv 3050x4. 0x0.250		40 / METER						TECHNICAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable. GENERAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable.	
11	DGE105234	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
12	DGE105 344	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
13	DGB109 652	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thickness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	120 / METER						<u>TECHNICAL SPECIFICATION -</u> BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR <u>GENERAL SPECIFICATION -</u> BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
14	DGE104 803	NIL	402099923713 3 / ROPE NYLON, HAWSERLAID, CIRC: 5-INCH, DIA: 40MM, Z- LAY, 3- STRAND,		220 / METER						<u>TECHNICAL SPECIFICATION - a.</u> 3 stand 40mm in Color white Nylon rope length 220 Mtr. b. Material quality top nylon fibers. c. Thickness and diameter 40mm or 5 inch. d. Length 220 Mtr commercial bulk coil. e. 3-strand or 3-ply twisted rope. f. Breaking strength 28,000 kg to 30,000 kg g. High temperature resistance then polypropylene -- working temperature up-to 100c (soften temperature 170c melting temperature 215c) h. A very strong and soft to touch synthetic fiber rope which has excellent shock absorption properties for use as a towing,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											mooring and as berthing hawser. j. High in strength and abrasion resistance, or elongation and absorbs moisture. 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 220 meter. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - a. 3 stand 40mm in Color white Nylon rope length 220 Mtr. b. Material quality top nylon fibers. c. Thickness and diameter 40mm or 5 inch. d. Length 220 Mtr commercial bulk coil. e. 3-strand or 3-ply twisted rope. f. Breaking strength 28,000 kg to 30,000 kg g. High temperature resistance then polypropylene – working temperature up-to 100c (soften temperature 170c melting temperature 215c) h. A very strong and soft to touch synthetic fiber rope which has excellent shock absorption properties for use as a towing, mooring and as berthing hawser. j. High in strength and abrasion resistance, or elongation	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											and absorbs moisture. 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 220 meter. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
15	DGE109 834	nil	533000038292 2 / PACKING-MATERIAL	FUEL OIL SERVICE PMP	50 / METER						<u>TECHNICAL SPECIFICATION -</u> SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C <u>GENERAL SPECIFICATION -</u> SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C	
16	DGE109 666	nil	533000038292 2 / PACKING-MATERIAL	FUEL OIL SERVICE PMP	75 / METER						<u>TECHNICAL SPECIFICATION -</u> SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C <u>GENERAL SPECIFICATION -</u> SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
17	DGH109527	TSGU-400	6145001106341 / CABLE ELECT 3-COND/0.742" SI & GLASS INSUL PVC JKT 1000V 400A		25 / METER						TECHNICAL SPECIFICATION - 04 ton Ac Compressor MIL-C-24643/16 GENERAL SPECIFICATION - 04 ton Ac Compressor MIL-C-24643/16	
18	DGE107343	RT876-1/4-0	5970UK5072933 / TUBING (HEAT SHRINK SLEEVE) FOR MARNESS EQUIPMENT		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
19	DGE96024	CM6538-000	5970705044352 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		13 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
20	DGE72407	NO DATA AVAILABLE	0433500000013 / FINS RUBBER FOR DIVERS.		14 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
21	DGT109699	NO DATA AVAILABLE	01000000000048 / TIMBER SHESHAM SLEEPER WELL SEASONED LOCAL		5 / CUBIC FOOT	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH 2. IM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector 3. PSG-847 4. MOISTURE CONTENT: 30% (±5%) 5. GRADE= A 6. SAP WOOD/WHITE PORTION= 30% OF LOG 7. DARK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											PORTION= 70% OF LOG 8. APPEARANCE= SWAN 9. KNOTS= FREE FROM KNOTS 10. CRACKS/SPLITS/DECAY/ROT= FREE FROM DEFECTSGENERAL SPECIFICATION - 1. SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH 2. iM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector 3. PSG-847 4. MOISTURE CONTENT: 30% (±5%) 5. GRADE= A 6. SAP WOOD/WHITE PORTION= 30% OF LOG 7. DARK PORTION= 70% OF LOG 8. APPEARANCE= SWAN 9. KNOTS= FREE FROM KNOTS 10. CRACKS/SPLITS/DECAY/ROT= FREE FROM DEFECTS	
22	DGT967 10	NO DATA AVAILABL E	010050000002 9 / Ply wood, Marine All Shesham, 13-Ply, GD-II, (WBP, Treated with Preservative) Size: L=8FT, W=4FT, TH=25MM, (Core inner plies & veneer) (Wood Should be all Shesham)		2 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER <u>GENERAL SPECIFICATION</u> -1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER	
23	DGT105 609	NO DATA AVAILABL E	010050000002 9 / Ply wood, Marine All Shesham, 13-Ply, GD-II, (WBP, Treated with Preservative) Size: L=8FT, W=4FT,		100 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER <u>GENERAL SPECIFICATION</u> -1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TH=25MM, (Core inner plies & veneer) (Wood Should be all Shesham)								PER CUBIC METER	
24	DGD99218		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		2 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG <u>GENERAL SPECIFICATION -</u> FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
25	DGD109090	NO DATA AVAILABLE	0035500000318 / Aluminium covers for utensil cooking (Large) O/D 25.50" TH 10 SWG.		6 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers. <u>GENERAL SPECIFICATION -</u> Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.	
26	DGE102301	NO DATA AVAILABLE	0559780000187 / SLEEVE PLASTIC DIA 0.5CM		5 / ROLL	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S,NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black GENERAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S, NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black	
27	DGD108304	NO DATA AVAILABLE	0033500000200 / JUGS WATER GLASS 1 QT		8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Capacity = 946 ml Material = Borosilicate glass with gold crusted Glass Thickness = 3-5 mm Finish = Clear glass with gold crusted borer, hand decorated. Packing= VIP premium velvet/ gift box Standard= Food grade gold, lead/nickel free GENERAL SPECIFICATION - Capacity = 946 ml Material = Borosilicate glass with gold crusted Glass Thickness = 3-5 mm Finish = Clear glass with gold crusted borer, hand decorated. Packing= VIP premium velvet/ gift box Standard= Food grade gold, lead/nickel free	
28	DGE107269	FEC 1735511	6532705172593 / LIGHTWEIGHT	PCB FABRICATION	50 / EACH/NUMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S	GERMAN Y		TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ESD COMPLAINT LAB COATS.					Block-6, Shara-e-Faisal Karachi Tele No.021-34302153-4			MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION</u> - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
29	DGT94531		010070514992 6 / LASANI PLY SHEET (SIZE 8'x' 4x16mm) SIMPLE.	WOOD WORK SHIPS/ESTAB LISHMENT.	32 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92- 21- 32776064 .MOBILE 0322- 2578654.		<u>TECHNICAL SPECIFICATION</u> - size: 8'x'4x16mm <u>GENERAL SPECIFICATION</u> - size: 8'x'4x16mm	
30	DGE109665		041559923141 2 / SHEET PLASTIC		4 / SHEET						<u>TECHNICAL SPECIFICATION</u> - Manfr/Tech.Sponcer Code reference: DTD 5592 <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			METHYL METHACRYLA TE PLAIN TRANSPAREN T L X W X THIC 48"X48"X0. 250"								<u>SPECIFICATION - Manfr/Tech.</u> Sponcer Code reference:DTD 5592	
31	DGB819 67		027759910623 1 / SPANNER O/JAW FXD D. E 0.625X0.688" W0.563X0.625" L MAX12X10. 25		14 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
32	DGT111 665	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	53 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moasture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moasture contents: 06 % to 18%	
33	DGE798 64	havana	711070524754 1 / master havana high back chair		3 / EACH/N UMBER	NIL					<u>TECHNICAL SPECIFICATION -</u> BACK: 24" ARM: 27 SEAT: 21.5" HEIGHT: 20" BACK HEIGHT: 47" A. CHROME BASE B. CHROME ARMS <u>GENERAL SPECIFICATION -</u> BACK: 24" ARM: 27 SEAT: 21.5" HEIGHT: 20" BACK HEIGHT: 47" A. CHROME BASE B. CHROME ARMS	
34	DGE111 645	3000	451070522641 4 / SINGLE LEVER SINK MIXER	SINK MIXER	8 / EACH/N UMBER	ARTICLE 3000		FAISAL SANITARY FITTING INDUSTRY G.T ROAD GUJRANWALA.	FASISAL SANITAR Y FITTING INDUSTR Y		<u>TECHNICAL SPECIFICATION -</u> ITEM IS USED IN PAINTRY, GALLEY AND SCULLERY WASHING BASIN/SINK. <u>GENERAL SPECIFICATION -</u> ITEM IS USED IN PAINTRY, GALLEY AND SCULLERY WASHING BASIN/SINK.	
35	DGE111 505	B2315512	471070517796 0 / FLEXIBLE	CNA LAN NETWORK	1800 / METER			ADAMJEE PAKISTAN	ADAMJEE		<u>TECHNICAL SPECIFICATION -</u> ADAMJEE PAKISTAN M/S INBOX	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PIPE 1 INCH DIA						PAKISTAN		TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter <u>GENERAL SPECIFICATION - ADAMJEE PAKISTAN M/S INBOX</u> TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter	
36	DGE111700		0330509427267 / FLANNELETTE CLOTH WHITE GROUND WITH RED STRIPT 4"X50 YARDS	SMALL ARMS CLEANING	500 / METER						<u>TECHNICAL SPECIFICATION - BOOK REF DEF STAN 83 - 48/2</u> 1977 Size: 4" x 2". Width: 10 cm. Material: 100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural. <u>GENERAL SPECIFICATION - BOOK REF DEF STAN 83 - 48/2</u> 1977 Size: 4" x 2". Width: 10 cm. Material: 100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural.	
37	DGE110097	BS2052, DEF STAN 40-3	0350595713246 / SPUN YARN SISAL S TWIST R. FROOFED 4/20 YARN LENGTH PER COIL 608-5% (FM)		10 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 1.</u> Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor) <u>GENERAL SPECIFICATION - 1.</u> Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor)	
38	DGE102001	nil	0350595713121 / Rope Nylon, Hawser laid, White, 3- Strand, Cir: 1-Inch, Diameter: 8-MM		200 / FATHOM						<u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
39	DGB111683		0283595711430 / ROD NAVAL BRASS HEX		12 / METER						<u>TECHNICAL SPECIFICATION -</u> SIZE: A/F 0.82" WT/Ft 2.170 (lb) Specs: BS EN 12163 Material Condition: 'M' Running Length: 03 Mtr ACCEPTANCE CRITERIA: AS PER SIZE AND SPECIFICATIONS, OR ITEM SAMPLE MAY BE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SHARED WITH MACHINE SHOP (C. NO. 205) FOR ACCEPTANCE OR OTHERWISE. <u>GENERAL SPECIFICATION - SIZE: A/F 0.82" WT/Ft 2.170 (lb) Specs: BS EN 12163 Material Condition: 'M' Running Length: 03 Mtr ACCEPTANCE CRITERIA: AS PER SIZE AND SPECIFICATIONS, OR ITEM SAMPLE MAY BE SHARED WITH MACHINE SHOP (C. NO. 205) FOR ACCEPTANCE OR OTHERWISE.</u>	
40	DGB111686	as per 320 d	028359571143 4 / ROD NAVAL BRASS HEX SIZE ACROSS FLATS 1.20 inch(dia HEXAGONSHA PED) 2-3 meter lenght, weight/ft: 4.580 (lb)		3.9 / METER						<u>TECHNICAL SPECIFICATION - BS EN 12163 OF 2011 MATERIAL GRADE: CW 712 R(M) RUNNING LENGTH: 1-2 METER</u> <u>GENERAL SPECIFICATION - BS EN 12163 OF 2011 MATERIAL GRADE: CW 712 R (M) RUNNING LENGTH: 1-2 METER</u>	
41	DGB111684		028359571144 2 / ROD NAVAL BRASS RD DIA.9.525 MM WT PER MTR 0.615 KG		6 / METER						<u>TECHNICAL SPECIFICATION - standard BSEN 12163 of 1998 Grade 712 (M)</u> <u>GENERAL SPECIFICATION - standard BSEN 12163 of 1998 Grade 712 (M)</u>	
42	DGB111685		028359571144 7 / ROD NAVAL BRASS RD DIA 01 INCH	GENERAL USE	2 / METER						<u>TECHNICAL SPECIFICATION - BS EN 12163 OF 2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98LBS, R-LENGTH-03 METERS (EACH)</u> <u>GENERAL SPECIFICATION - BS EN 12163 OF 2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98 LBS, R-LENGTH-03 METERS (EACH)</u>	
43	DGH111694		021159923019 6 / SHEET GI ZINC COATED 2430 ± 10 mm		24 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm),								SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346:2015 Steel Grade: S275JR Mass Coating: 120-275 g/m2 (Standard for Structural repair works) Tensile Strenght: 270-500 Mpa Yield Strenght: Minimum 140 Mpa 1. dETIALS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 :2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)GENERAL SPECIFICATION - Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346: 2015 Steel Grade: S275JR Mass Coating: 120-275 g/m2 (Standard for	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Structural repair works) Tensile Strength: 270-500 Mpa Yield Strength: Minimum 140 Mpa 1. DETAILS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)	
44	DGB111 277		026759923534 3 / Tee pipe equal galvanized (three sides equal) black		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - INNER DIA: 45 MM, OUTSIDE DIA: 58 MM, THICKNESS: 6.5 MM, THREADS: 11, BS 1740/71 CORROSION RESISTING STEEL/FERROUS ALLOY, WITH LAYER OF MOLTEN ZINC MTC OF ITEM IS REQUIREDGENERAL SPECIFICATION - INNER DIA: 45 MM, OUTSIDE DIA: 58 MM, THICKNESS: 6.5 MM, THREADS:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											11, BS 1740/71 CORROSION RESISTING STEEL/FERROUS ALLOY, WITH LAYER OF MOLTEN ZINC MTC OF ITEM IS REQUIRED	
45	DGB111 271		026759923534 9 / TEE PIPE EQUAL (GALVANISED) 03.00IN		80 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5 mm GENERAL SPECIFICATION - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5mm	
46	DGE106 973		033059571326 6 / TWINE HEMP PACKING MEDIUM 3STRD POLISHE MIN BKG STRGTH 100LB		30 / KILOGR AMME						TECHNICAL SPECIFICATION - (1) 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses. GENERAL SPECIFICATION - (1) 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											chemical free from harmful substances & making it safe for various uses.	
47	DGE108286	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		1500 / EACH/NUMBER						TECHNICAL SPECIFICATION - TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014. GENERAL SPECIFICATION - TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2014.	
48	DGB111 270	TPI 14	530571503899 6 / SCREW SELF TAPPING S/STEEL CSK HD 14 TPISZ 2.000X0.250" LOCAL	REPAIR FOR GRP BOATS	500 / TEN						<u>TECHNICAL SPECIFICATION</u> - material: stainless steel grade: 316 HD 14 Dimension: diameter: 14mm Thread per inch: 2.000x0.250" <u>GENERAL SPECIFICATION</u> - material: stainless steel grade: 316 HD 14 Dimension: diameter: 14mm Thread per inch: 2.000x0.250"	
49	DGB111 265	NO DATA AVAILABL E	473070503853 5 / band pipe m/s 2.5 inch	DUMP BARGE COUNSTRUCT ION	80 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - Material: Mild Steel Grade JR275 Size: 2.5 inch x 4.775 mm thick Schedule: 40 OEM: Pakistan/China Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload) <u>GENERAL SPECIFICATION</u> - Material: Mild Steel Grade JR275 Size: 2.5 inch x 4.775 mm thick Schedule: 40 OEM: Pakistan/China Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload)	
50	DGE723 89	NO DATA AVAILABL E	042250000003 4 / CARPET WOOLEN DARK GRAY B-92		200 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
51	DGE111 972		033054600356 5 / FLANNELETTE CLOTH CREAM GRD W/RED WEFT BARS 4"X50 YARDS		700 / METER						<u>TECHNICAL SPECIFICATION</u> - 2 Size: 4" x 2". 2 Width: 10 cm. 2 Material: 100% Softness Cotton and Gun Care Cleaning Products. 2 Colour: Cream. <u>GENERAL SPECIFICATION</u> - 2 Size: 4" x 2". 2 Width: 10 cm. 2 Material: 100% Softness Cotton and Gun Care Cleaning Products. 2 Colour: Cream.	
52	DGE111 647	ITD/SP- GCF/ tpt400- f1755 (DITD)	830559533484 7 / GLASS CLOTH FIBER, PLAIN WEAVE, COLOUR NATURAL		90 / METER	SP-GCF/ TPT400- F1755					<u>TECHNICAL SPECIFICATION</u> - SPECIFICATIONS: 1. WIDTH= 01- METER (± 1.5%), 2. LENGTH= 50-60 (METER PER ROLL), 3. THICKNESS= 1.0±0.3 MM (AS PER ISO 2589), 4. MATERIAL GRADE=	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FOR LAGGING PURPOSE								AS PER DEFSTAN NES 801 PART-2, 5. WEIGHT GSM= 800±10% G/M² : (AS PER ISO 3801) 6. DETAILS SPECIFICATIONS IS ATTACHMENT. <u>GENERAL SPECIFICATION</u> - SPECIFICATIONS: 1. WIDTH= 01-METER (± 1.5%), 2. LENGTH= 50-60 (METER PER ROLL), 3. THICKNESS= 1.0±0.3 MM (AS PER ISO 2589), 4. MATERIAL GRADE= AS PER DEFSTAN NES 801 PART-2, 5. WEIGHT GSM= 800±10% G/M² : (AS PER ISO 3801) 6. DETAILS SPECIFICATIONS IS ATTACHMENT.	
53	DGT111 666	NO DATA AVAILAB E	934070514992 3 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB TO 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	6 / SHEET	NO DATA AVAILAB LE		PK		SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.	TECHNICAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB <u>GENERAL SPECIFICATION</u> - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	
54	DGD111 746	HS CODE 29161900	156073519303 9 / HEXAMINE SOLID FUEL TABLETS	N/A	150 / PACK	N/A	N/A	HOT MEAL TECH CO LTD, 42-54 SINHUNG, SINPYEENG, DANGJI, CHUNGNAM# 343-816 KOREA TELE NO 008241 3632020	HOT MEAL TECH		TECHNICAL SPECIFICATION - ITEM IS ESSENTIAL FOR MEAL READY TO EAT <u>GENERAL SPECIFICATION</u> - ITEM IS ESSENTIAL FOR MEAL READY TO EAT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
55	DGE107 607	honey/mk/ 22	597070526728 8 / Honey Comb Hole matt rubber 20"x36"x1/2"		20 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
56	DGE111 406	14.02.0012	035059923357 7 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED. GENERAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED.	
57	DGE107 806		041459923091 1 / PACKING MATERIAL HEMP FOR FURNACE FUEL, SIZE= 1/4" SQ		20 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DGE958	BRUSH	047659943041		20 /						TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	17	LEG 4.375"	1 / BRUSH PAINT SQARE EDGE ONE KNOT GROUND WD. 2.500" TH. 0.625"		EACH/N UMBER						DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DGE107 603		034059923627 2 / CANVAS DAY SIGNAL MARINE BALL BLACK FITTED DIA 2FT		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Length 12 Inch (1 Feet) b. Width 08 Inch c. Cloth CanvasGENERAL SPECIFICATION - a. Length 12 Inch (1 Feet) b. Width 08 Inch c. Cloth Canvas	
60	DGH111 446		021159923017 3 / STAINLESS STEEL SHEET SIZE 2500X1250X1 MM	COLD ROLLED TENSILE TESTED ZINC COATED	10 / EACH/N UMBER						TECHNICAL SPECIFICATION - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC) GENERAL SPECIFICATION - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC)	
61	DGB954 41		021259923280 2 / BAR STEEL CORROSION RESISTING H/R RD 1.25" WT PER FT 4.209LBS		1 / METER						TECHNICAL SPECIFICATION - minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D) GENERAL SPECIFICATION - minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D)	
62	DGH108 551		021159923019 6 / SHEET GI ZINC COATED 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm),		-15 / EACH/N UMBER						TECHNICAL SPECIFICATION - Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346:2015 Steel Grade: S275JR Mass Coating: 120-275 g/m2 (Standard for Structural repair works) Tensile Strenght: 270-500 Mpa Yield Strenght: Minimum 140 Mpa 1. dETIALS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 :2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)<u>GENERAL SPECIFICATION</u> - Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346: 2015 Steel Grade: S275JR Mass Coating: 120-275 g/m2 (Standard for Structural repair works) Tensile Strength: 270-500 Mpa Yield Strength: Minimum 140 Mpa 1. DETAILS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)	
63	DGH108 360		021159923019 6 / SHEET GI ZINC COATED 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm),		60 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346:2015 Steel Grade: S275JR Mass Coating: 120- 275 g/m2 (Standard for Structural repair works) Tensile Strenght: 270- 500 Mpa Yield Strenght: Minimum 140 Mpa 1. dETIALS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 :2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)GENERAL SPECIFICATION - Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346: 2015 Steel Grade: S275JR Mass Coating: 120-275 g/m2 (Standard for Structural repair works) Tensile Strength: 270-500 Mpa Yield Strength: Minimum 140 Mpa 1. DETAILS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)	
64	DGB105 648	1A2672	027579910547 3 / PICK HEAD, DIGGING TYPE , CHISEL&POIN T SZ.4.50LBS EYE, UNIVERSAL NO2		15 / EACH/N UMBER						TECHNICAL SPECIFICATION - STANDARD/SPECIFICATION=BS14 21TABLE-2(AS PER BR320D) GENERAL SPECIFICATION - STANDARD/SPECIFICATION=BS14 21TABLE-2(AS PER BR320D)	
65	DGE107 176	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sSTRAND, Z- LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	120 / FATHO M						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
66	DGB963 63	SPEC BS 2874 C 107-0	028359961098 2 / ROD COPPER RD ANNEALED DIA 0.75 INCH (WEIGHT/ FOOT 1.710 LB		10 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
67	DGB991 10		027379000411 4 / CUTTER INSULATION REMOVING DIAMETER CAPACITY 0.744IN	USE; PYROTENAX CABLE	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
68	DGE107 053	NO DATA AVAILABLE	033054600448 4 / HEAVING LINE 06MM L50MM 466MS	MSI	1260 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - length :06MM L50MM 466MS material : nylon <u>GENERAL SPECIFICATION</u> - length :06MM L50MM 466MS material : nylon	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
69	DGE72300	C-134	0851580000076 / DEFENCER EAR C-134 62TD		57 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DGE111701	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		2500 / EACH/NUMBER						TECHNICAL SPECIFICATION - TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014. GENERAL SPECIFICATION - TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ACCORDANCE WITH ISO 13935-1: 2014.	
71	DGE107 985	NIL	402099923713 3 / ROPE NYLON, HAWSERLAID, CIRC: 5-INCH, DIA: 40MM, Z- LAY, 3- STRAND,		440 / METER						TECHNICAL SPECIFICATION - a. 3 stand 40mm in Color white Nylon rope length 220 Mtr. b. Material quality top nylon fibers. c. Thickness and diameter 40mm or 5 inch. d. Length 220 Mtr commercial bulk coil. e. 3-strand or 3-ply twisted rope. f. Breaking strength 28,000 kg to 30,000 kg g. High temperature resistance then polypropylene – working temperature up-to 100c (soften temperature 170c melting temperature 215c) h. A very strong and soft to touch synthetic fiber rope which has excellent shock absorption properties for use as a towing, mooring and as berthing hawser. j. High in strength and abrasion resistance, or elongation and absorbs moisture. 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 220 meter. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - a. 3 stand 40mm in Color white Nylon rope length 220 Mtr. b. Material quality top nylon fibers. c. Thickness and diameter 40mm or 5 inch. d. Length 220 Mtr commercial bulk coil. e. 3-strand or 3-ply twisted rope. f. Breaking strength 28,000 kg to 30,000 kg g. High temperature resistance then polypropylene – working temperature up-to 100c (soften temperature 170c melting temperature 215c) h. A very strong and soft to touch synthetic fiber rope which has excellent shock absorption properties for use as a towing, mooring and as berthing hawser. j. High in strength and abrasion resistance, or elongation and absorbs moisture. 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 220 meter. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
72	DGE99892		5330006183221 / PACKING		10 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MATERIAL SIZE 3/16".								SPECIFICATION - NO DATA AVAILABLE	
73	DGE99002		5330006183221 / PACKING MATERIAL SIZE 3/16".		10 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DGT111670	NO DATA AVAILABLE	5530705042933 / PLY WOOD NATURAL TEAK FINISH ONE SIDE (NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W=4' TH=03mm to 04mm	PRESENTATION BOXES FOR WVIPS	160 / SQ FEET						TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm GENERAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm	
75	DGE99264	MIL-P-15280	5640002374827 / INSULATION SLEEVING THERMAL		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
76	DGE98114		8135705064882 / TAPE TRANSPARENT ADHESIVE	GENERAL USE.	131 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WATER PROOFED WD.12 MM LG. 66 MTR.									
77	DGT96698	NO DATA AVAILABLE	0100000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	48 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
78	DGE111359	32B1296	8135992203363 / TUBING PLASTIC POLYETHYLENE TYPE -1 LAY FLAT WD. 36 THICKNESS 0.010 INCH		40 / KILOGRAMME						TECHNICAL SPECIFICATION - AS AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll(no need of packing) locally available GENERAL SPECIFICATION - AS AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll (no need of packing) locally available	
79	DGE107425		8340705089249 / CAMOUFLAGE NET, SIZE: 30X25FT FOR COVER 12.7-MM GUNS	TO COVER COMOUFLAGE TE 12.7MM GUNS	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM : 1. 100% POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH G1 COATED 300 G/SQ METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438 <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM : 1. 100% POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH G1 COATED 300 G/SQ METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438	
80	DGE107 773		834070508924 9 /	TO COVER COMOUFLAG	2 / EACH/N						<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION OF ITEM : 1. 100%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CAMOUFLAGE NET, SIZE: 30X25FT FOR COVER 12.7-MM GUNS	E TE 12.7MM GUNS	UMBER						POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH G1 COATED 300 G/SQ METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438 <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM : 1. 100% POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (855949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET, ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS. WITH G1 COATED 300 G/SQ METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438	
81	DGE111426	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	2 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					<u>TECHNICAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
82	DGT111667	NO DATA AVAILAB LE	0100500000029 / Ply wood, Marine All Shesham, 13-Ply, GD-II, (WBP, Treated with Preservative) Size: L=8FT, W=4FT, TH=25MM,		224 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METERGENERAL SPECIFICATION - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(Core inner plies & veneer) (Wood Should be all Shesham)									
83	DGT111666	NIL	9330992246097 / PLASTIC SHEET, LAMINATED, DECORATIVE		14 / SHEET						TECHNICAL SPECIFICATION - 1. SIZE= 8' X 4' X 1MM, 2. SHADE TRU TEAK WOOD) 3. MATERIAL= PVC/HPL GENERAL SPECIFICATION - 1. SIZE= 8' X 4' X 1MM, 2. SHADE TRU TEAK WOOD) 3. MATERIAL= PVC/HPL	
84	DGE111646	Is219004pk	8415761003378 / HELMET CRASH VIP ESCORT RIDER W/SUN VISER, NYL/BELT FOAM COAT		24 / EACH/NUMBER	ff353 rapid single mono					TECHNICAL SPECIFICATION - colour: gloss white (2) Serial No 1003378 size: xdl carton no. 102-57 W/Sun Viser, Size 23.23"-23.62" NYL/Belt Foam (56-60 cm) GENERAL SPECIFICATION - colour: gloss white (2) Serial No 1003378 size: xdl carton no. 102-57 W/Sun Viser, Size 23.23"-23.62" NYL/Belt Foam (56-60 cm)	
85	DGH107065		9535705043161 / SHEET STEEL CARBON 2500X1250X2 MM	FOR SHIPS STRUCTURE	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - BSEN 10025, Grade S-275 JRG GENERAL SPECIFICATION - BSEN 10025, Grade S-275 JR	
86	DGE111468		7110705114888 / master AURA LOW BACK REVOLVING CHAIR	MASTER OFFICE CHAIR	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240 <u>GENERAL SPECIFICATION</u> - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
87	DGD107552		7320705013214 / TOASTER TWO SLOT 220V 50HZ 01 PHASE 920W	FOR DOMASTIC USE	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - a. Make/ Model / Brand/ Equivalent be endorsed: Panasonic/ Dawlance/ West point a. Make/ Model of item Moulinex LT 140827 Black & Decker ET 222 Philips HD 2637/90 b. OEM COC/ authorized dealer certificate/ mill test certificate (MTC): Not required <u>GENERAL SPECIFICATION</u> - a. Make/ Model / Brand/ Equivalent be endorsed: Panasonic/ Dawlance/ West point a. Make/ Model of item Moulinex LT 140827 Black & Decker ET 222 Philips HD 2637/90 b. OEM COC/ authorized dealer certificate/ mill test certificate (MTC): Not required	
88	DGE96030	BS 419/156	0559546005362 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		40 / ROLL						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
89	DGE95820	BS 419/156	0559546005362 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		35 / ROLL						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
90	DGE111699		0330546003565 / FLANNELETTE CLOTH CREAM GRD W/RED WEFT BARS 4"X50 YARDS		400 / METER						<u>TECHNICAL SPECIFICATION</u> - $\hat{z}$ Size: 4" x 2". $\hat{z}$ Width: 10 cm. $\hat{z}$ Material: 100% Softness Cotton and Gun Care Cleaning Products. $\hat{z}$ Colour: Cream. <u>GENERAL SPECIFICATION</u> - $\hat{z}$ Size: 4" x 2". $\hat{z}$ Width: 10 cm. $\hat{z}$ Material: 100% Softness Cotton and Gun Care Cleaning Products. $\hat{z}$ Colour: Cream.	
91	DGE98108	NO DATA AVAILABLE	0559780000187 / SLEEVE PLASTIC DIA		5 / ROLL	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S.NO. 5) 40MM,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			0.5CM								32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black <u>GENERAL SPECIFICATION</u> - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S, NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black	
92	DGE96241	1900gsr-2usb	7025015913120 / honey well 1900 bar code scanner		2 / EACH/NUMBER	xeon 1900					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
93	DGD111947	MJ-DJ31	7330705270665 / PANASONIC JUICER BLENDER 3 IN 1		1 / EACH/NUMBER	MJ-DJ31					<u>TECHNICAL SPECIFICATION</u> - BRAND PANASONIC, CAPACITY: 1LTR, VOLTAGE: 800W, JAR MATERIAL TYPE GLASS, OPERAING MODE MANUAL, SKLI 227669609, PK-1447852121, 2 LTR CAPACITY <u>GENERAL SPECIFICATION</u> - BRAND PANASONIC, CAPACITY: 1LTR, VOLTAGE: 800W, JAR MATERIAL TYPE GLASS, OPERAING MODE MANUAL, SKLI 227669609, PK-1447852121, 2 LTR CAPACITY	
94	DGD111711	29161900	6505705193058 / FUEL TABLETS	MRE PACKS (04 IN ONE PACKET)	175 / PACKET	N/A	N/A	PANA FORCE FOODS ASC NOWSHEHRA KPK		PANA FORCE FOODS	<u>TECHNICAL SPECIFICATION</u> - ARTICLE NAME AND DETAILS Solid Fuel Tablet Specifications Physical Characteristics Diameter: 2 inches Shape: Cylindrical Cross Mark: For breaking into 4 equal pieces Weight: 28-30 Grams per tablet Burning Time: 17-20 minutes per tablet ash proof 1. 1 Tablet: Boil 1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											liter of water 2. 1/2 Tablet: Boil 3 cups of water or make 3 cup of tea 3. 1/4 Tablet: Make 1 Cup of tea Burning Time for Fractions 1. 1/2 Tablet: Approximately 14 Minutes 2. 1/4 Tablet: Approximately 09 Minutes 1. Number of tablets: 5 in One Bottle 2. Total Burning time: Approximately 1 Hours <u>GENERAL SPECIFICATION</u> <u>ARTICLE NAME AND DETAILS</u> Solid Fuel Tablet Specifications Physical Characteristics Diameter: 2 inches Shape: Cylindrical Cross Mark: For breaking into 4 equal pieces Weight: 28-30 Grams per tablet Burning Time: 17-20 minutes per tablet ash proof 1. 1 Tablet: Boil 1 liter of water 2. 1/2 Tablet: Boil 3 cups of water or make 3 cup of tea 3. 1/4 Tablet: Make 1 Cup of tea Burning Time for Fractions 1. 1/2 Tablet: Approximately 14 Minutes 2. 1/4 Tablet: Approximately 09 Minutes 1. Number of tablets: 5 in One Bottle 2. Total Burning time: Approximately 1 Hours	
95	DGT111 935	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	70 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
96	DGT111 760	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	70 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
97	DGT111 583	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	48 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
98	DGE111 987		042270515841 1 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	2550 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI & M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTICS, SADDAR KARACHI		<u>TECHNICAL SPECIFICATION</u> - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM <u>GENERAL SPECIFICATION</u> - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
99	DGT111 965	NIL	723070513291 0 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	3500 / FOOT	NO DATA AVAILABLE		PK	TAWAKAL BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		<u>TECHNICAL SPECIFICATION</u> - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required <u>GENERAL SPECIFICATION</u> - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
100	DGE111 802	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED	DECK	1300 / EACH/NUMBER	SSP-01-LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTAN		<u>TECHNICAL SPECIFICATION</u> - AS PER LETTER ATTACH <u>GENERAL SPECIFICATION</u> - AS PER LETTER ATTACH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PROCELAIN TILES (MASTER)									
101	DGH111 911		021159923019 6 / SHEET GI ZINC COATED 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm),		32 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346:2015 Steel Grade: S275JR Mass Coating: 120- 275 g/m2 (Standard for Structural repair works) Tensile Strenght: 270- 500 Mpa Yield Strenght: Minimum 140 Mpa 1. dETIALS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 :2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346: 2015 Steel Grade: S275JR Mass Coating: 120-275 g/m2 (Standard for Structural repair works) Tensile Strength: 270-500 Mpa Yield Strength: Minimum 140 Mpa 1. DETAILS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)	
102	DGH112 130		021159923019 6 / SHEET GI ZINC COATED 2430 ± 10 mm		32 / EACH/N UMBER						TECHNICAL SPECIFICATION - Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm),								SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346:2015 Steel Grade: S275JR Mass Coating: 120-275 g/m2 (Standard for Structural repair works) Tensile Strenght: 270-500 Mpa Yield Strenght: Minimum 140 Mpa 1. dETIALS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 :2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)<u>GENERAL SPECIFICATION</u> - Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346: 2015 Steel Grade: S275JR Mass Coating: 120-275 g/m2 (Standard for	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Structural repair works) Tensile Strenght: 270-500 Mpa Yield Strenght: Minimum 140 Mpa 1. dETIALS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)	
103	DGH112 141		028150281167 0 / BACK PLATE		14 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material : Metal Sheet Length : 10 Feet Width : 5.2 Feet Mounting Type : Back Mount Color : Gray Features : Quick in installation, Helpful in partitioning of storage pace, Robust & Durable, High grade Oil Paint Construction. GENERAL SPECIFICATION - Material : Metal Sheet Length : 10 Feet Width : 5.2 Feet Mounting Type : Back Mount	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Color : Gray Features : Quick in installation, Helpful in partitioning of storage pace, Robust & Durable, High grade Oil Paint Construction.	
104	DGE111 949	NO DATA AVAILABL E	033054600448 4 / HEAVING LINE 06MM L50MM 466MS	MSI	600 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - length :06MM L50MM 466MS material : nylonGENERAL SPECIFICATION -length :06MM L50MM 466MS material : nylon	
105	SGB111 282	NO DATA AVAILABL E	512073100065 4 / SCREW DRIVER FLAT PIONT 8PCS SET INTERCHANG EABLE(CHINA MADE)		20 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DGD111 951	LG-MP- 9482 SR	731073511893 9 / MICROWAVE OVEN-LG SHARP WAVES/DAWL ANCE & TOSHIBA	MICROWAVE OVEN LG	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - capacity: 36 LITTERs GENERAL SPECIFICATION - capacity: 36 LITTERs	
107	DGE111 950	NO DATA AVAILABL E	043250000000 6 / DUST RESPIRATOR		100 / EACH/N UMBER	M 511- N95					TECHNICAL SPECIFICATION - packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size: Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95 China (GB 2626-2006) Filtering Rate: = 95%GENERAL SPECIFICATION - packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size: Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95 China (GB 2626-2006) Filtering Rate: = 95%	
108	DGE112 009	32B1296	813599220336 3 / TUBING PLASTIC		100 / KILOGR AMME						TECHNICAL SPECIFICATION - AS AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			POLYETHYLENE TYPE -1 LAY FLAT WD. 36 THICKNESS 0.010 INCH								ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll(no need of packing) locally availableGENERAL SPECIFICATION -AS AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll (no need of packing) locally available	
109	DGT112 193	NO DATA AVAILAB LE	010050000002 1 / Ply wood GD-II, 3 ply (core and inner plies of Popular SIZE: L=8' W=4' TH=03MM		912 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - DESCRIPTION/ SIZES Ply wood GD-II, 3 ply (core and inner plies of Popular and both face and back veneer of Mersawa (0.6MM) type of bond INT (phenolic/ aminoplastic), treated with preservative. Size: L = 8? W = 4? Th = 03 MM BS EN 322 : 1993 2. Bonding Quality: 1. BS 314-1 : 2004 2. BS EN 314-2: 1993 3. Glue: BS 1203 : 1979 4. Preservation: BS 4072 : 1999 5. Physical evaluation: BS 6566-6 : 1985 6. Density: BS EN 323 : 1993 GENERAL SPECIFICATION - DESCRIPTION/ SIZES Ply wood GD-II, 3 ply (core and inner plies of Popular and both face and back veneer of Mersawa (0.6MM) type of bond INT (phenolic/ aminoplastic), treated with preservative. Size: L = 8? W = 4? Th = 03 MM BS EN 322 : 1993 2. Bonding Quality: 1. BS 314-1 : 2004 2. BS EN 314-2: 1993 3. Glue: BS 1203 : 1979 4. Preservation: BS 4072 : 1999 5. Physical evaluation: BS 6566-6 : 1985 6. Density: BS EN 323 : 1993	
110	DGH111 926	NO DATA AVAILAB LE	951550501792 1 / PLATE STEEL carbon (SIZE 6000X1500X8 MM.)		4 / EACH/N UMBER						TECHNICAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025.STEEL GRADE: s 275 JR. Tolerance Limit: BSEN 10029-1991 "Class-C". ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. standardized list of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											plats uploaded GENERAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025. STEEL GRADE: s 275 JR. Tolerance Limit: BSEN 10029-1991 "Class-C". ALL INFORMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. standarized list of plats uploaded	
111	DGE111707		711070511488 8 / master AURA LOW BACK REVOLVING CHAIR	MASTER OFFICE CHAIR	6 / EACH/N UMBER						TECHNICAL SPECIFICATION - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240 GENERAL SPECIFICATION - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240	
112	DGB108 541	TBS-01	733070527066 4 / SS WORKING TABLE W/CENTER & BOTTOM SHELVES		3 / EACH/N UMBER	TBS-01					TECHNICAL SPECIFICATION - DIMENSION: 72"X30"X34", S/S TOP 1.5MM, S/S SHELVES 1.2MM, SS/ SQ. PIPE 1 1/2" X 1 1/2", S/S ADJUSTABLE LEGS Steel Grade-201 GENERAL SPECIFICATION - DIMENSION: 72"X30"X34", S/S TOP 1.5MM, S/S SHELVES 1.2MM, SS/ SQ. PIPE 1 1/2" X 1 1/2", S/S ADJUSTABLE LEGS Steel Grade-201	
113	DGB108 506	DBS-01	731070527066 3 / DOUBLE BOWL SINK		2 / EACH/N UMBER	DBS-01					TECHNICAL SPECIFICATION - DIMENSION: 72X28X34INCH, BOWL S/S 304 1.2MM, TP S/S 304 1.5MM, S/S S. PIPER 1 1/2"X1 1/2" X 1.5"MM, STAINLESS STEEL ADJUSTABLE LEGS GENERAL SPECIFICATION - DIMENSION: 72X28X34INCH, BOWL S/S 304 1.2	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MM, TP S/S 304 1.5MM, S/S S. PIPER 1 1/2"X1 1/2" X 1.5"MM, STAINLESS STEEL ADJUSTABLE LEGS	
114	DGH105 296	LNKPN201 510	3020PK520265 1 / PINS	RACK	100 / UNIT			3RD FLOOR 83C,PHASE 2, EXTENSION,MAIN NATIONAL HIGHWADEFENCE KARACHIY.,021538726		HABIB & SONS	<u>TECHNICAL SPECIFICATION -</u> YEILD STRENGTH:245MPA16MM MATERIAL:SS400 TENSILE STRENGTH:400-510MPA THICKNESS:1.3MM SURFACE FINISH:GALVANIZED/POWDER COATED HEXAGONE NUT AND BOLT:M10*80*2 <u>GENERAL SPECIFICATION -</u> YEILD STRENGTH:245MPA16MM MATERIAL:SS400 TENSILE STRENGTH:400-510MPA THICKNESS:1.3MM SURFACE FINISH:GALVANIZED/POWDER COATED HEXAGONE NUT AND BOLT:M10*80*2	
115	DGB105 501	44	203079527084 6 / 26 X 28 US FEDERAL SPECIFICATIO N DEE SHACKLE		4 / EACH/N UMBER	44					<u>TECHNICAL SPECIFICATION -</u> 26 X 28 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD: 17 TON <u>GENERAL SPECIFICATION -</u> 26 X 28 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD: 17 TON	
116	DGE108 322	ORCA-828	801079520819 8 / FABRIC 1300 GSM MILITARY GREY (HYPALONE)	RHIB BOAT	45 / METER		NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX,TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk		HENSHA W INFLATA BLES LTD	<u>TECHNICAL SPECIFICATION -</u> 1. TDS IS ENCLOED WITH RWIMS 2. VALID OEM/ MANUFACTURER COC IS REQUIRED. 3. PACKING: 50 METER PER ROLL. WRAPPED IN WATERPROOF MATERIAL AND WOUND ON A RIGID CORE TO PREVENT DEFORMATION. PACKING SHALL PROTECT AGAINST MOISTURE, DUST, ABRASION AND MECHANICAL DAMAGE. EACH ROLL SHOULD BE MARKED WITH OEM NAME, PART/ PATTERN NO, MATERIAL, COLOR, WEIGHT BATCH/ LOT NO. <u>GENERAL SPECIFICATION -</u> 1. TDS IS ENCLOED WITH RWIMS 2.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											VALID OEM/ MANUFACTURER COC IS REQUIRED. 3. PACKING: 50 METER PER ROLL. WRAPPED IN WATERPROOF MATERIAL AND WOUND ON A RIGID CORE TO PREVENT DEFORMATION. PACKING SHALL PROTECT AGAINST MOISTURE, DUST, ABRASION AND MECHANICAL DAMAGE. EACH ROLL SHOULD BE MARKED WITH OEM NAME, PART/ PATTERN NO, MATERIAL, COLOR, WEIGHT BATCH/ LOT NO.	
117	DGE108 697		034059923627 2 / CANVAS DAY SIGNAL MARINE BALL BLACK FITTED DIA 2FT		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Length 12 Inch (1 Feet) b. Width 08 Inch c. Cloth Canvas GENERAL SPECIFICATION - a. Length 12 Inch (1 Feet) b. Width 08 Inch c. Cloth Canvas	
118	DGB104 545		021259571028 3 / BAR STEEL CARBON HOT ROLLED FLAT 04"X3/8"WT PER FT 5.10 LBS		10 / METER						TECHNICAL SPECIFICATION - RELEVANT SPECS i,e BS 970 EN 3A GENERAL SPECIFICATION - RELEVANT SPECS i,e BS 970 EN 3A	
119	DGH104 320		021159230669 5 / SHEET STEEL CARBON 2440X910X5M M		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
120	DGB104 676		021259571026 9 / BAR STEEL CARBON HOT ROLLED FLAT 03"X1/4"WT PER FT 2.55 LBS		125 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
121	DGB105 385		025770128378 2 / BOLT MACHINE BRASS BSW HEX HD TPI 8 SZ 1.000X3.		12 / DOZEN						TECHNICAL SPECIFICATION - material grade of brass is naval brass (c46400) 60 % copper, 39.2% zinc and 0.8% tin GENERAL SPECIFICATION - material grade of brass is naval brass (c46400) 60 %	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			000X2.000 IN								copper, 39.2% zinc and 0.8% tin	
122	DGB105997	(SIM)	0257709411504 / NUT-PLAIN-HEXAGON (BRASS) THREAD UNF SZ .375"LH .350"		32 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
123	DGE100432	NO DATA AVAILABLE	0330546004484 / HEAVING LINE 06MM L50MM 466MS	MSI	660 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - length :06MM L50MM 466MS material : nylon GENERAL SPECIFICATION - length :06MM L50MM 466MS material : nylon	
124	DGH100893		0561595218492 / CABLE, power, ELECT ELASTOMERICALFH , 3 cores, cond276/0.40 440 v, 160 amp, 100 lg.		100 / METER						TECHNICAL SPECIFICATION - 3 CORES, COND276/0.40 440 V, 160 AMP, 100 LG. DEFSTAN 02-526 GENERAL SPECIFICATION - 3 CORES, COND276/0.40 440 V, 160 AMP, 100 LG. DEFSTAN 02-526	
125	SGB104142	BR3013-SHEET3.1.2	4730995311379 / FLANGE PIPE STEEL ROUND 2		45 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Specification: flange pipe steel round 2, bore 2 inch. b. Dimension: Inner Dia 2 inch (51 mm), c. Outer Dia: 5 inch (125 mm) and d. thickness: 13 mm. GENERAL SPECIFICATION - a. Specification: flange pipe steel round 2, bore 2 inch. b. Dimension: Inner Dia 2 inch (51 mm), c. Outer Dia: 5 inch (125 mm) and d. thickness: 13 mm.	
126	DGE101725	MIL-P-15280	5640002374827 / INSULATION SLEEVING THERMAL		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
127	DGE105892	NO DATA AVAILABLE	042250000003 / CARPET WOOLEN.		429.4 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm <u>GENERAL SPECIFICATION -</u> (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm	
128	DGE100598	NO DATA AVAILABLE	0461500000024 / PAPER ABRASIVE 9" X11" WATERPROOF MATERIAL EMERY GRADE P-120D		20 / SHEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
129	DGT105343	NO DATA AVAILABLE	0100000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	30 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
130	DGT101975	NO DATA AVAILABLE	0100000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	217 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
131	DGE102290	10MM	5970705133476 / GLASS SLEEVING 10MM	MOTOR WINDING FOR CABLE	12 / EACH/NUMBER	NO DATA AVAILABLE		PK	GREEN WAY ELECTRIC STORE SHOP NO.1-5 ARAMBA GH		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									KARACHI			