

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 21-10-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGH105921		023159571524 3 / WIRE ROPE STEEL EXTRA SPECIAL GALVA LAY OF ROPE RH CIRC 3/8"		100 / METER						<u>TECHNICAL SPECIFICATION -</u> Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39) <u>GENERAL SPECIFICATION -</u> Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39)	
2	DGD99216	NO DATA AVAILAB LE	003550000031 8 / Aluminium covers for utensil cooking (Large) O/D 25.50" TH 10 SWG.		14 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers. <u>GENERAL SPECIFICATION -</u> Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.	
3	DGH101880		021159230669 5 / SHEET STEEL CARBON 2440X910X5M M		100 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
4	DGE102005	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sTRAND, Z- LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	120 / FATHO M						<u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE</u></u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
5	DGE106667	NO DATA AVAILABLE	0350599237130 / ROPE NYLON HAWSERLAID, DIA: 28-MM, 3-STRAND	MIN BRKG STRENGTH 15.500 TONS UNIT OF	1000 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.<u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
6	DGB100963	SKF 6208Z	0269599500114 / BEARING BALL JOURNAL SKF 6208Z 040X080X18MM	SUPPLY&EXH AUST FAN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
7	DGB88582		0257704195039 / NUT-PLAIN-WING-TH-SZ-0.25"WG.HT0.718(BRASS) WING-SPRD 1.187"		48 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
8	DGE101520	NO DATA AVAILAB L E	0330546004484 / HEAVING LINE 06MM L50MM 466MS	MSI	1620 / METER	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - length :06MM L50MM 466MS material : nylon GENERAL SPECIFICATION - length :06MM L50MM 466MS material : nylon	
9	DGE101568	NO DATA AVAILAB L E	0476546005949 / BRUSH WRITING NO-6		15 / EACH/NUMBER	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
10	DGE106614		0472594259799 / WHALER 27FT DROP REEL		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
11	DGE101305		4020999237137 / ROPE NYLON HAWSERLAID, 3-STRND, Z-LAY, TYPE-1, NOM DIA: 64-MM, CIRC: 08-INCH,	NOR-SHIPS-USE-NASAR	120 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
12	DGB69001	BD 531	5130765016393 / SAW JIG ELECTRIC	USE IN KNIFE CUTTER	2 / EACH/NUMBER	4327M					TECHNICAL SPECIFICATION - 220V 350 WATS 3000RMP MODEL BD 531 Country Origin : Japan Make : MAKITA <u>GENERAL SPECIFICATION - 220V 350 WATS 3000RMP MODEL BD 531</u> Country Origin : Japan Make : MAKITA	
13	DGB102163	NO DATA AVAILABLE	0268500000061 / SCALE-SPRING-BALANCE-20-STONE-280-LBS		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow <u>GENERAL SPECIFICATION - Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow</u>	
14	DGE105641	NIL	9340731000995 / E-GLASS FIBER (POWDER) CHOPPED STRAND MAT	GRP BOATS	50 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2 <u>GENERAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2</u>	
15	DGD106922	NO DATA AVAILABLE	0032500000119 / BASIN SUGAR STAINLESS STEEL		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
16	DGE87137	FEC 1735511	6532705172593 /	PCB FABRICATION	10 / EACH/N			M/sDF Technologies & Services (Pvt)Ltd Building	GERMANY		TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LIGHTWEIGHT ESD COMPLAINT LAB COATS.		UMBER			No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4			(combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION</u> - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
17	DGE101442	NO DATA AVAILABLE	0451594510013 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	55 / METER						<u>TECHNICAL SPECIFICATION</u> - AS PER STOCK SAMPLE HELD BY CINS <u>GENERAL SPECIFICATION</u> - AS PER STOCK SAMPLE HELD BY CINS	
18	DGH109928		9520705136051 / Angle Steel Bulb Bar	DOCK,S HULL	80 / METER	NO DATA AVAILABLE		PK	M/S RUBY TRADER S IRON & STEEL SHERSH AH RD KARACHI -2573339		<u>TECHNICAL SPECIFICATION</u> - Material specification is AH36. BS EN 10025-06 of 2019 + A1:2022. length/Height: 6 Meters, width: 200 mm, Flange/ web thickness: 09 mm. <u>GENERAL SPECIFICATION</u> - Material specification is AH36. BS EN 10025-06 of 2019 + A1:2022. length/Height: 6 Meters, width: 200 mm, Flange/ web thickness: 09 mm.	
19	DGH110204		9520705136051 / Angle Steel Bulb Bar	DOCK,S HULL	150 / METER	NO DATA AVAILABLE		PK	M/S RUBY TRADER S IRON & STEEL SHERSH AH RD KARACHI		<u>TECHNICAL SPECIFICATION</u> - Material specification is AH36. BS EN 10025-06 of 2019 + A1:2022. length/Height: 6 Meters, width: 200 mm, Flange/ web thickness: 09 mm. <u>GENERAL SPECIFICATION</u> - Material specification is AH36. BS EN 10025-06 of 2019 + A1:2022.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									-2573339		length/Height: 6 Meters, width: 200 mm, Flange/ web thickness: 09 mm.	
20	DGE109 917	12MM	597070513347 7 / GLASS SLEEVING 12MM	MOTOR WINDING FOR CABLE	50 / EACH/NUMBER	NO DATA AVAILABLE		PK	GREEN WAY ELECTRIC STORE SHOP NO.1-5 ARAMBA GH KARACHI		<u>TECHNICAL SPECIFICATION --</u> <u>GENERAL SPECIFICATION --</u>	
21	DGE110 873	LOCAL MADE	042270516014 7 / CARPET RUNNER JAI NAMAZ	JAI NAMAZ SUF	15 / FOOT			LOCAL SOURCE:BOLTON MARKET KARACHI.	LOCAL SOURCE: BOLTON MARKET KARACHI		<u>TECHNICAL SPECIFICATION -</u> LOCAL SOURCE:BOLTON MARKET KARACHI. Carpet Runner Jai Namaz (authorized quantity 200 running feet) 01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand. <u>GENERAL SPECIFICATION -</u> LOCAL SOURCE:BOLTON MARKET KARACHI. Carpet Runner Jai Namaz (authorized quantity 200 running feet) 01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand.	
22	DGE110 323	LOCAL MADE	042270516014 7 / CARPET RUNNER JAI NAMAZ	JAI NAMAZ SUF	50 / FOOT			LOCAL SOURCE:BOLTON MARKET KARACHI.	LOCAL SOURCE: BOLTON MARKET		<u>TECHNICAL SPECIFICATION -</u> LOCAL SOURCE:BOLTON MARKET KARACHI. Carpet Runner Jai Namaz (authorized quantity 200 running feet)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand. <u>GENERAL SPECIFICATION - LOCAL SOURCE:</u> BOLTON MARKET KARACHI. Carpet Runner Jai Namaz (authorized quantity 200 running feet) 01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand.	
23	DGE110886	NIL	5430705134177 / FLEXIBLE FUEL TANK 250 GALLONS	-	4 / EACH/NUMBER	NO DATA AVAILABLE		PK	M/S SAMAD RUBBER WORKS (PVT) LTD 409 FEROZE PUR ROAD LAHORE		<u>TECHNICAL SPECIFICATION - LENGTHXWIDTHXHEIGHT</u> 13'-6" X13'-6"X2'-8"(APPROXIMATELY) <u>GENERAL SPECIFICATION - LENGTHXWIDTHXHEIGHT</u> 13'-6" X13'-6"X2'-8"(APPROXIMATELY)	
24	DGE109983	lc-08-ssp-01	5620705227651 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	1000 / EACH/NUMBER	SSP-01-LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTAN		<u>TECHNICAL SPECIFICATION - AS PER LETTER ATTACH</u> <u>GENERAL SPECIFICATION - AS PER LETTER ATTACH</u>	
25	DGE110095	lc-08-ssp-01	5620705227651 / DUST	DECK	1000 / EACH/NUMBER	SSP-01-LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES		<u>TECHNICAL SPECIFICATION - AS PER LETTER ATTACH</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PRESSED, UNGLAZED PROCELAIN TILES (MASTER)		UMBER				PAKISTA N		SPECIFICATION - AS PER LETTER ATTACH	
26	DGH109 933	LUKUF901 052100M	712570520625 7 / FRAME 10' X 3.5'	Racking	30 / EACH/N UMBER	NA		M/s Habib & Sons 3rd Floor, 83-C, Phase II Extension, Main National Highway, Defense Housing Society Karachi-Pakistan	M/s Habib & Sons		TECHNICAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder CoatedGENERAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated	
27	DGE110 884	6402	451070522640 9 / QUARTER ROUND WALL SHOWER	shower	8 / EACH/N UMBER	ARTICLE 6402		FAISAL SANITARY FITTING INDUSTRY g.t road gujranwala.	FAISAL SANITAR Y FITTING INDUSTR Y		TECHNICAL SPECIFICATION - item is used in bathroom.GENERAL SPECIFICATION - item is used in bathroom.	
28	DGH109 929	LCKHB108 1182B	302070520258 0 / BEAM PR 2740X240	RACKS	90 / EACH/N UMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5GENERAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
29	DGE110 123	Nil	841570522801 7 / PARACHUTE CLOTH FOR WEAPONS	Cloth	70 / METER	NIL		AL MUSTAFA TRADERS F-41/F-42, Iqbal Center, M. A. Jinnah Road, Karachi-74200	AL MUSTAF A TRADER S		TECHNICAL SPECIFICATION - Type of cloth: Parachute Cloth Code: D-16-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof. with good	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			AND SENSORS								quality gauge to withstand humid and hot environment. <u>GENERAL SPECIFICATION</u> - Type of cloth: Parachute Cloth Code: D-16-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof. with good quality gauge to withstand humid and hot environment.	
30	DGE110105	D95	6508705231849 / D95 FACE MASK DESTO	SELF	30 / EACH/NUMBER	D95		DEFENCE SCIENCE AND TECHNOLOGY ORGANIZATION CHAKLALA CANTT, RAWALPINDI.	DEFENCE SCIENCE & TECHNOLOGY ORG		<u>TECHNICAL SPECIFICATION</u> - d95 FACE MASK DESTO <u>GENERAL SPECIFICATION</u> - d95 FACE MASK DESTO	
31	DGE110885	B2315512	4710705177960 / FLEXIBLE PIPE 1 INCH DIA	CNA LAN NETWORK	100 / METER			ADAMJEE PAKISTAN	ADAMJEE PAKISTAN		<u>TECHNICAL SPECIFICATION</u> - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter <u>GENERAL SPECIFICATION</u> - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter	
32	DGB99555		0277794334644 / TOOL BOX PORTABLE 18X6X 1-15/16IN STEEL ENAM		4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
33	DGB102641	BS1476/NE 8-M	0283705711226 / ALUMINIUM ALLOYANGLE EQUALSIDED RT ANGLE LG 1.50"X1.50" X1/8"		300 / METER						<u>TECHNICAL SPECIFICATION</u> - Item Specification:BSEN-573-3 OF 1995 (CHEMICAL COMPOSITION)BSEN-485-2 OF 1995(MECHANICAL PROPERTIES) GRADE ENAW 5083 <u>GENERAL SPECIFICATION</u> - Item Specification:BSEN-573-3 OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											1995(CHEMICAL COMPOSITION) BSEN-485-2 OF 1995(MECHANICAL PROPERTIES) GRADE ENAW 5083	
34	DGE110 262	14.02.0012	035059923357 7 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32- MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED. <u>GENERAL SPECIFICATION - 1.</u> SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32- MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED.	
35	DGB109 987		028370923350 4 / ZINC INGOT 99.995% PURITY LG 16",BREADTH 8",HT 1.75"		600 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - BS</u> EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005% <u>GENERAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005%</u>	
36	DGB106 748	BS-1471-NT4	028259571197 6 / TUBE, ALUMINIUM ALLOY,EXT DIA 2"TH 0.060"WDG 60 SPE BS 1471		30 / METER						<u>TECHNICAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades)</u> <u>GENERAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades)</u>	
37	DGB106 457		028359571143 2 / ROD NAVAL BRASS HEX A/F 1.01" WT PER FT 3.244 LB, (RUNNING LENGTH: MINIMUM 6 FT)	SERVICE PUMP	2 / METER						<u>TECHNICAL SPECIFICATION - BSEN 12163 OF 2016 GRADE CW 712 (R) M RUNNING LENGTH: minimum 6 ft</u> <u>GENERAL SPECIFICATION - BSEN 12163 OF 2016 GRADE CW 712 (R) M RUNNING LENGTH: minimum 6 ft</u>	
38	DGE977 06		043359924862 6 / KNIFE, DIVERS (SHEATH 7" & HANDLE 5)	OEM: USA, ITALY(SS MATERIAL, MAGNETIC TYPE)	1 / EACH/N UMBER	RC 556000					<u>TECHNICAL SPECIFICATION - Material Stainless Steel Blade Length: 17.8 cm/7.01 inch Overall Length: 30 cm/11.82 inch Blade Width: 32mm/1.25 inch Blade Thickness: 5.5mm/0.22 inch Knife Weight: 450gm/0.99 LB Weight with Seaboard: 600gm/1.32 LB</u> <u>GENERAL SPECIFICATION - Material Stainless Steel Blade Length: 17.8 cm/7.01 inch Overall Length: 30 cm/11.82 inch Blade Width: 32mm/1.25 inch Blade Thickness: 5.5mm/0.22 inch Knife</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Weight: 450gm/0.99 LB Weight with Seaboard: 600gm/1.32 LB	
39	DGE110114	0461-931-8996	0460599318996 / TAPE COTTON ADHASIVE COMPOUND WIDTH 3" THICK 0.038" LG.10 MTR.	30 MM GUN.	40 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
40	DGB101742		0283595711467 / ROD NAVAL BRASS RD DIA 5.125 INCH WT PER FT 76.98 LB		4 / METER						TECHNICAL SPECIFICATION - BS EN-12163 OF 2024 DESIGNATION : CW-712R CONDITION: M RUNNING LENGTH: 05FT GENERAL SPECIFICATION - BS EN-12163 OF 2024 DESIGNATION : CW-712R CONDITION: M RUNNING LENGTH: 05FT	
41	DGB106752		0283595711474 / SHEET-NAVAL-BRASS-ANNEALED 48		1.75 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340 GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
42	DGE110880		0415599231408 / PLASTIC SHEET METHYL METHACRYLATE TRANSPARENT 48"X36"X0.0625		12 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
43	DGH109926		0211592044553 / SHEET STEEL STAINLESS SIZE 3050X1220X3 MM	DEEP FRYER 2PAN	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MM GENERAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
44	DGH110203		021159204455 3 / SHEET STEEL STAINLESS SIZE 3050X1220X3 MM	DEEP FRYER 2PAN	5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MM <u>GENERAL</u> SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0. 25MM	
45	DGH110202		021159923019 6 / SHEET GI ZINC COATED 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm),		34 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346:2015 Steel Grade: S275JR Mass Coating: 120- 275 g/m2 (Standard for Structural repair works) Tensible Strenght: 270- 500 Mpa Yield Strenght: Minimum 140 Mpa 1. dETIALS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 :2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)GENERAL SPECIFICATION - Item: SHEET GI ZINC COATED Dimension: 2430+10MM X 1220+10MM X 2MM EQUIVALENT SIZE: Approx. 8 feet x 2mm Material Standard: EN 10346: 2015 Steel Grade: S275JR Mass Coating: 120-275 g/m2 (Standard for Structural repair works) Tensile Strenght: 270-500 Mpa Yield Strenght: Minimum 140 Mpa 1. dETIALS SIZE: 2430 ± 10 mm x1220 ± 10 mm x 2mm (i.e. 8ft x 4ft x 2mm), WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B). EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)	
46	DGB96817	BS 1421	027570910547 4 / PICK HEAD DIGGING TYPE CHISEL AND POINT 07LBS EYE 3" X3"		40 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
47	DGH109372		023159571524 3 / WIRE ROPE STEEL EXTRA SPECIAL GALVA LAY OF ROPE RH CIRC 3/8"		50 / METER						<u>TECHNICAL SPECIFICATION</u> - Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39) <u>GENERAL SPECIFICATION</u> - Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39)	
48	DGB106751	SPEC BSS 2874 CZ 112 M	028370571144 9 / ROD NAVAL BRASS RD DIA 1.25" WT PER FT 4.58LB		20 / METER						<u>TECHNICAL SPECIFICATION</u> - sPECIFICATION:BSEN/2/63 OF 1998 mATERIAL gRADE: CW712R <u>GENERAL SPECIFICATION</u> - SPECIFICATION: BSEN/2/63 OF 1998 mATERIAL gRADE: CW712R	
49	DGB109885	SPEC; BS1769	026659001603 1 / WASHER FLAT ROUND MILD STEEL O/D1.625"/I/D0. 792"THICK0. 128"		20 / KILOGR AMME						<u>TECHNICAL SPECIFICATION</u> - Spec: BS-970 EN 3A <u>GENERAL SPECIFICATION</u> - Spec: BS-970 EN 3A	
50	DGE110099	NO DATA AVAILABL E	055979900469 9 / INSULATION- SLEEVING- BLUE-6.5MM		12 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
51	DGH110222	DGS 212	056159521828 8 / CABLE ELECT 3 CORE BUTYL CSP SHEATHED		200 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			C/7/0.670 440V 33AMP									
52	DGE110 186	13213E54 56-12	422000275315 6 / LIFE BOUY (RING BOUY LIFE SAVING) ROUND ORANGE OUTER (COMD8)		16 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
53	DGE103 239	ORCA KNIFE	422050508458 9 / KNIFE DIVERS ORCA KNIFE DIVERS WITH LEG CLASP		6 / EACH/N UMBER	/Cressi orca, black					TECHNICAL SPECIFICATION - TECHNICAL FEATURES • Blade Length: 17.8 cm – 7.01 Inch • Total Length: 30 cm – 11.82 Inch, • Blade Width: 32 mm – 1.25 Inch, • Blade Thickness: 5.5 cm – 0.22 inch, • Knives-only weight: 450 gr – 0.99 lb • Weight with Sheath: 600 gr – 1.32 lb • (NMCRL NSN: 4220-14-381-4117) • OEM ADDRESS: CRESSI SUB S.P. A, VIA GELASIO ADAMOLI, 501-16165, GENOVA, ITALY, PHONE: +39 345 37 84 402 GENERAL SPECIFICATION - TECHNICAL FEATURES • Blade Length: 17.8 cm – 7.01 Inch • Total Length: 30 cm – 11.82 Inch, • Blade Width: 32 mm – 1.25 Inch, • Blade Thickness: 5.5 cm – 0.22 inch, • Knives-only weight: 450 gr – 0.99 lb • Weight with Sheath: 600 gr – 1.32 lb • (NMCRL NSN: 4220-14-381-4117) • OEM ADDRESS: CRESSI SUB S.P.A, VIA GELASIO ADAMOLI, 501-16165, GENOVA, ITALY, PHONE: +39 345 37 84 402	
54	DGE110 822	9-27017	4220PK508036 1 / LIGHT, CHEMILUMINE SCENT GREEN FOR UNDER WATER 12HR	DC LOCKERS	130 / EACH/N UMBER	Cyalume Chem light					TECHNICAL SPECIFICATION - IPC IS ENCLOSED GENERAL SPECIFICATION - IPC IS ENCLOSED	
55	DGE110 881	NIL	533070505816 9 /	FOR AIR CONDITION	135 / EACH/N						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INSULATION MATERIAL FOAM TYPE SUPERLON, SIZE= 3/8 X 1-1/16 X 72 INCH		UMBER						null	
56	DGE109 909	NO DATA AVAILABLE	562050504233 5 / TILES CERAMIC GLAZED COLOUR WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")	DECK COVERING	1000 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DGE110 876	MIL-P-15280	564000237482 7 / INSULATION SLEEVING THERMAL		165 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
58	DGE109 910	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		31 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
59	DGE110 107	NO DATA AVAILAB LE	041478000021 0 / INSULATING RUBBER GLOVES	MSI	8 / PAIR	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - ELASTOMER= NATURAL RUBBER,, THICKNESS= 1.5MM, LINING= UNLINED CHLORINATED, FORMER= PLAIN SMOOTH, CUFF TYPE= STRAIGHT, EXERIOR= CHLORINATED, TENSILE STRENGTH= 16.0 MPA (MIN), TENSION SET= 15% (MAX), ELONGATION AT BREAK= 600% (MIN), MAX USE VOLTAGE AC= 7500V, PROOF TEST VOLTAGE AC= 10000V,GENERAL SPECIFICATION - ELASTOMER= NATURAL RUBBER,, THICKNESS= 1.5MM, LINING= UNLINED CHLORINATED, FORMER= PLAIN SMOOTH, CUFF TYPE= STRAIGHT, EXERIOR= CHLORINATED, TENSILE STRENGTH= 16.0 MPA (MIN), TENSION SET= 15% (MAX), ELONGATION AT BREAK= 600% (MIN), MAX USE VOLTAGE AC= 7500V, PROOF TEST VOLTAGE AC= 10000V,	
60	DGE109 805	NO DATA AVAILAB LE	033050000013 9 / TWINE FLEX FINE 0.50 LBS.	LOAD=26 LBS, 2PLY	30 / KILOGRAMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - a. Specifications of Item Material: Synthetic fiber/ polypropylene thread Shape: Twisted multi-strand rope Flexibility: Highly flexible for easy layout and marking Usage: used for ground marking, layout marking in industrial areas b. Dimensions/ Sizes and etc Length: 50 meter in roll form Thickness: 01 mmGENERAL SPECIFICATION - a. Specifications of Item Material: Synthetic fiber/ polypropylene thread Shape: Twisted	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											multi-strand rope Flexibility: Highly flexible for easy layout and marking Usage: used for ground marking, layout marking in industrial areas b. Dimensions/ Sizes and etc Length: 50 meter in roll form Thickness: 01 mm	
61	DGD109844	MS-3443-A/DW-136G	7310705121904 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	1 / EACH/N UMBER	DW-136G					<u>TECHNICAL SPECIFICATION</u> - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI <u>GENERAL SPECIFICATION</u> - brand name: (i.e. WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI	
62	DGD110549	MS-3443-A/DW-136G	7310705121904 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	1 / EACH/N UMBER	DW-136G					<u>TECHNICAL SPECIFICATION</u> - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI <u>GENERAL SPECIFICATION</u> - brand name: (i.e. WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI	
63	DGD110068	MS-3443-A/DW-136G	7310705121904 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	2 / EACH/N UMBER	DW-136G					<u>TECHNICAL SPECIFICATION</u> - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI <u>GENERAL SPECIFICATION</u> - brand name: (i.e. WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI	
64	DGD110044		7730705048075 / plate Dinner 23cm blue crested (as per stock sample)		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material:PORCELINGENERAL SPECIFICATION - Material: PORCELIN	
65	DGE103451	NO DATA AVAILABLE	0432500000027 / HELMET PROTECTIVE DESPATCH RIDER WITH VISOR SIZE 6 3/4		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218) GENERAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218)	
66	DGE109918	NO DATA AVAILABLE	0432500000028 / HELMET PROTECTIVE WITH VISOR COLOUR WHITE (FULL HEAD)		20 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
67	DGT109913	NO DATA AVAILABLE	01005000000021 / Ply wood GD-II, 3 ply (core and inner plies of Popular SIZE: L=8' W=4' TH=03MM		300 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - DESCRIPTION/ SIZES Ply wood GD-II, 3 ply (core and inner plies of Popular and both face and back veneer of Mersawa (0.6MM) type of bond INT (phenolic/ aminoplastic), treated with preservative. Size: L = 8? W = 4? Th = 03 MM BS EN 322 : 1993 2. Bonding Quality: 1. BS 314-1 : 2004 2. BS EN 314-2: 1993 3. Glue: BS 1203 : 1979 4. Preservation: BS 4072 : 1999 5. Physical evaluation: BS 6566-6 : 1985 6. Density: BS EN 323 : 1993 GENERAL SPECIFICATION - DESCRIPTION/ SIZES Ply wood GD-II, 3 ply (core and inner plies of Popular and both	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											face and back veneer of Mersawa (0.6MM) type of bond INT (phenolic/ aminoplastic), treated with preservative. Size: L = 8' W = 4' Th = 03 MM BS EN 322 : 1993 2. Bonding Quality: 1. BS 314-1 : 2004 2. BS EN 314-2: 1993 3. Glue: BS 1203 : 1979 4. Preservation: BS 4072 : 1999 5. Physical evaluation: BS 6566-6 : 1985 6. Density: BS EN 323 : 1993	
68	DGE110 226	NO DATA AVAILAB L E	8415PK506744 2 / CLOTH PARASHUTE GRAY		300 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
69	DGE110 122	NO DATA AVAILAB L E	8415PK506744 2 / CLOTH PARASHUTE GRAY		500 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
70	DGE110 102	NO DATA AVAILAB L E	933070505435 4 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PN CREST	6 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	DGT104 323	NIL	933099224609 7 / PLASTIC SHEET, LAMINATED, DECORATIVE		12 / SHEET						TECHNICAL SPECIFICATION - 1. SIZE= 8' X 4' X 1MM, 2. SHADE TRU TEAK WOOD) 3. MATERIAL= PVC/HPL GENERAL SPECIFICATION - 1. SIZE= 8' X 4' X 1MM, 2. SHADE TRU TEAK WOOD) 3. MATERIAL= PVC/HPL	
72	DGE110 101	NIL	934073100099 5 / E-GLASS FIBER	GRP BOATS	220 / KILOGR AMME						TECHNICAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(POWDER) CHOPPED STRAND MAT								REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2 <u>GENERAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen</u> a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2	
73	DGD110052		734070510187 4 / Cruets Complete Small	MESS UTENSILS, OFFICER WARD PNS SHIFA	1 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - As per existing Stock, Make/Brand is Regal China with Blue Shell & PN Crest embossed on item</u> <u>GENERAL SPECIFICATION - As per existing Stock, Make/Brand is Regal China with Blue Shell & PN Crest embossed on item</u>	
74	DGD109086	MS-563XD LG	734070511750 1 / MICROWAVE OVEN LG 56 LTRS		1 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
75	DGD110468	MS-563XD LG	734070511750 1 / MICROWAVE OVEN LG 56 LTRS		2 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
76	DGD110055		003550000045 7 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		6 / EACH/ NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG</u> <u>GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG</u>	
77	DGD110051	NO DATA AVAILAB LE	003250000014 0 / KNIFE FISH EATING S/STEEL		10 / EACH/ NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - Grade 304, non magnetic & non reactive , food grade, pn crested</u> <u>GENERAL SPECIFICATION - Grade</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											304, non magnetic & non reactive , food grade, pn creasted	
78	DGD110067	NO DATA AVAILAB E	0035500000273 / BOARD CHOPPING		10 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - make/brand ken wood size ; 12" x 6" x 1/2" material; fiber/nylon ref haibat/03/7765652 GENERAL SPECIFICATION - make/brand ken wood size ; 12" x 6" x 1/2" material; fiber/nylon ref haibat/03/7765652	
79	DGD110066	NO DATA AVAILAB E	0035500000274 / BOARD KNIFE		15 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952 GENERAL SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952	
80	DGD110054	NO DATA AVAILAB E	0035500000294 / CHOPPER COOK OR MEAT		15 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - size ; 10" material; 100% steel stainless with hand grip country of origin pakistan make/brand kiwi ref haibat 03/7766015 GENERAL SPECIFICATION - size ; 10" material; 100% steel stainless with hand grip country of origin pakistan make/brand kiwi ref haibat 03/7766015	
81	DGD98945		0035546000614 / POT ALU 15/7" WITH COVER		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - 200 TO 250 LBS GENERAL SPECIFICATION - 200 TO 250 LBS	
82	DGD105615		0035546000615 / Pot Aluminum 18/9" With COVER		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - 18 Gauge Aluminum Pot having Capacity of 250 lbs Aluminum grade (as food grade and lead free) GENERAL SPECIFICATION - 18 Gauge Aluminum Pot having Capacity of 250 lbs Aluminum grade (as food grade and lead free)	
83	DGD74168		0035546000615 / Pot Aluminum 18/9" With COVER		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - 18 Gauge Aluminum Pot having Capacity of 250 lbs Aluminum grade (as food grade and lead free) GENERAL SPECIFICATION - 18 Gauge Aluminum Pot	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											having Capacity of 250 lbs Aluminum grade (as food grade and lead free)	
84	DGD98956		0035546000616 / POT ALU 20X10"WITH COVER		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - 200 TO 250 LBS CAPACITY GENERAL SPECIFICATION - 200 TO 250 LBS CAPACITY	
85	DGD110050	NO DATA AVAILABLE	0032500000133 / Fork Table Medium Common S/Steel		25 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - PN Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS-316 (Food Grade) & PN Crest . GENERAL SPECIFICATION - PN Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS-316 (Food Grade) & PN Crest .	
86	DGD110043	NO DATA AVAILABLE	0032500000155 / POTS TEA STAINLESS STEEL MEDIUM SIZE		3 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Stainless Steel grade (Food Grade) Material (Food Grade) Lead Free. GENERAL SPECIFICATION - Stainless Steel grade (Food Grade) Material (Food Grade) Lead Free.	
87	DGD110063	NO DATA AVAILABLE	0035500000366 / KNIFE COOK 6 INCH		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Blade Length = 6 inch Total Length = 11-11.5 inch Blade Material = SS 420 Handle = Full Steel Thickness = 2.2 mm Weight = 140-160 g Finish = Mirror Polish, plain Usage = Kitchen/ Commercial GENERAL SPECIFICATION - Blade Length = 6 inch Total Length = 11-11.5 inch Blade Material = SS 420 Handle = Full Steel Thickness = 2.2 mm Weight = 140-160 g Finish = Mirror Polish, plain Usage = Kitchen/ Commercial	
88	DGD110064	NO DATA AVAILABLE	0035500000367 / KNIFE COOK 8 INCH		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
89	DGD110065	NO DATA AVAILABLE	0035500000368 / KNIFE COOK 10 INCH		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
90	DGE110 883	d000-004	8440735270720 / cotton gloves (pack of 12 gloves)		15 / PAIR	na					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
91	DGH110 611		6145705332829 / electrical cable 30mm 4 core flexible cu/ pvc/ pvc,		50 / METER	4 CORE FLEXIBLE CABLE					TECHNICAL SPECIFICATION - ELECTRICAL CABLE 30MM 4 CORE FLEXIBLE CU/ PVC/ PVC GENERAL SPECIFICATION - ELECTRICAL CABLE 30MM 4 CORE FLEXIBLE CU/ PVC/ PVC	
92	DGE110 485	YCR105 or 1260	8305785163090 / CERAMIC FIBER CLOTH	GENRAL USE	10 / METER	YCR105		OEM:CHINA MANUFACTURERS NINGBO RUIFENG SEALING MATERIAL COMPANY LTD KUANGVAN TOWN CIXI : 86-574-63531211.63531433.	PANASONIC SADDAR KARACHI. TECHNO POWER SYSTEM		TECHNICAL SPECIFICATION - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, tempErature resistance= 700 °C (degree centigrade), max thermal conDuctivity= 0.16 w/m.K GENERAL SPECIFICATION - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, tempErature resistance= 700 °C (degree centigrade), max thermal conDuctivity= 0.16 w/m.K	
93	DGE110 110	565665	5340705246111 / leatherite for wallpaper		350 / SQ FEET	565665					TECHNICAL SPECIFICATION - leatherite wallpaper sheets GENERAL SPECIFICATION - leatherite wallpaper sheets	
94	DGE110 686	NO DATA AVAILAB L E	0350595713119 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 0.750", DIA: 0.21875" (1/4") (6MM), TYPE 1		240 / FATHO M	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - 1. ISO 2004(E) FOR COMPLY SPECIFICATIONS WITH ISO 1140 OF 2004, 2. ISO 9554: 2005 (E) CLAUSES 3.3.2 REFERS, 3. MARKING LABELLING OF ROPE AS PER ISO 9554 OF 2005 (E), 4. INSTRUCTION FOR USE / MAINTENANCE IS TO BE PROVIDED AS PER STANDARD 9554 OF 2005 (E), 5. TESTED AS PER ISO 2307 OF 2005, 6. OEM WILL PROVIDED CERTIFICATE OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 7. OEM COC WILL REQUIRED, 8. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 9. OEM OF ROPE MUST BE APPROVED BY MOD (UK), 10. LENGTH PER COIL: 120 FATHOM. <u>GENERAL SPECIFICATION - 1.</u> ISO 2004(E) FOR COMPLY SPECIFICATIONS WITH ISO 1140 OF 2004, 2. ISO 9554: 2005 (E) CLAUSES 3.3.2 REFERS, 3. MARKING LABELLING OF ROPE AS PER ISO 9554 OF 2005 (E), 4. INSTRUCTION FOR USE / MAINTENANCE IS TO BE PROVIDED AS PER STANDARD 9554 OF 2005 (E), 5. TESTED AS PER ISO 2307 OF 2005, 6. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 7. OEM COC WILL REQUIRED, 8. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 9. OEM OF ROPE MUST BE APPROVED BY MOD (UK), 10. LENGTH PER COIL: 120 FATHOM.	
95	DGE110 683		035059571313 0 / ROPE NYLON, HAWSERLAID, 3-STRAND, CIRC: 3-1/2 INCH, NOM DIA: 24MM, TYPE-1,	TOWING & BERTHING ROPE	200 / METER						<u>TECHNICAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY. 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION</u> - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY. 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
96	DGH109927		0211599230173 / STAINLESS STEEL SHEET SIZE 2500X1250X1 MM	COLD ROLLED TENSILE TESTED ZINC COATED	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC) <u>GENERAL SPECIFICATION</u> - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC)	
97	DGD110048		0032500032017 / SPOON SALT FOR		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Size: 2.5 to 3 ml Color: Silverware Length: 6.7" Diameter: 1.1" Width: 1"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OCNS								Made with stainless steel Material S/S 304/316 FOOD GRADE NON Magnetic (LOCAL) size and material grade: ss 304/316 (food grade) <u>GENERAL SPECIFICATION</u> - Size: 2.5 to 3 ml Color: Silverware Length: 6.7" Diameter: 1.1" Width: 1" Made with stainless steel Material S/S 304/316 FOOD GRADE NON Magnetic (LOCAL) size and material grade: ss 304/316 (food grade)	
98	DGE109 914	NO DATA AVAILABL E	047259523774 4 / Life Bouy Ring (Orange) with SOLAS Reflective Tape	FOR SHIPS/BOATS	4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM – Internal dia 44.5 CM Thickness 11.5CM Buoyancy Rating:181N. <u>GENERAL SPECIFICATION</u> - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM – Internal dia 44.5 CM Thickness 11.5 CM Buoyancy Rating:181N.	
99	DGE110 471	NO DATA AVAILABL E	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949).	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
100	DGE110402	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
101	DGE110862	NIL	402099923712 1 / ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00", DIA 0.3125" (8MM)	NGTH 1.330 TONS UNIT OF AVAILABILITY	240 / FATHO M						<u>TECHNICAL SPECIFICATION -</u> Local good quality as per stock sample is also acceptable specifications: ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00" DIA 0.3125" (8MM) <u>GENERAL SPECIFICATION -</u> Local good quality as per stock sample is also acceptable specifications: ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00" DIA 0.3125" (8MM)	
102	DGE109920	NO DATA AVAILABL E	562050504233 5 / TILES CERAMIC GLAZED COLOUR	DECK COVERING	1000 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")									
103	DGE110 111	SA9-27077PF.	626001178556 0 / LIGHT, CHEMILUMINE SCENT 6inch BLUE	REPLENISHMENT LIGHT	90 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
104	DGE109 916	NO DATA AVAILABLE	597070504085 6 / SLEEVING GLASS DIA 25 MM THICKNESS 1.1MM	D/GENERATER STATER	50 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DGD109 367	LG-MP-9482 SR	731073511893 9 / MICROWAVE OVEN-LG SHARP WAVES/DAWLANCE & TOSHIBA	MICROWAVE OVEN LG	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - capacity: 36 LITTERs GENERAL SPECIFICATION - capacity: 36 LITTERs	
106	DGE109 915	IS8021	047654600478 5 / Coated Rigger Gloves with Rubberized Cuff		10 / PAIR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DGD110 057	NO DATA AVAILABLE	003550000049 6 / SPOON SERVING S/STEEL		200 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - stainless steel m/grade 316 (food grade) & pn crest GENERAL SPECIFICATION - stainless steel m/grade 316 (food grade) & pn crest	
108	DGD110 062	NO DATA AVAILABLE	003550000031 8 / Aluminium covers for utensil cooking (Large) O/D 25.50" TH 10 SWG.		12 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											steel recommended for cooking. c. Magnet test Magnet should not stick to the covers. <u>GENERAL SPECIFICATION</u> - Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.	
109	DGD110 046	NO DATA AVAILABL E	00345000022 5 / Cup eggs with stand PN Blue crested and shell on edge of cup.		20 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - Height 6.5cm Octer Dia 4cm Base Dia 4cm <u>GENERAL SPECIFICATION</u> - Height 6.5cm Octer Dia 4cm Base Dia 4cm	
110	DGD110 061	NO DATA AVAILABL E	00355000037 9 / LADLE S/S HANDLE (L-13") WITH WOODEN GRIP,POT WD 3.5".		10 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
111	DGE110 109	NOT KNOWN	792070518127 1 / BROOM SCRUBBING DECK (FOR DECONTAMIN ATION)	NIL	10 / EACH/N UMBER		NIL	LOCAL MARKET	NIL		<u>TECHNICAL SPECIFICATION</u> - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21 <u>GENERAL SPECIFICATION</u> - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table 1 (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21	
112	DGD109 586	BMF-01	733070526968 0 / BROASTER MACHINE		1 / EACH/NUMBER	BMF-01					TECHNICAL SPECIFICATION - EGO GERMANY THERMOSTAT, HIGHLY EFFICIENT BURNER (160,000 BTU), ITALIAN VALVE ASSY, VOLTAGE AND POWER 220V/200W, DIMENSION: 28X42X42 INCH GENERAL SPECIFICATION - EGO GERMANY THERMOSTAT, HIGHLY EFFICIENT BURNER (160,000 BTU), ITALIAN VALVE ASSY, VOLTAGE AND POWER 220V/200W, DIMENSION: 28X42X42 INCH	
113	DGD109 649	DDS-10	733070527066 1 / FRYER SINGLE TANK 2 BASKETS 4 TUBE		1 / EACH/NUMBER	DDS-10					TECHNICAL SPECIFICATION - S/S 304TOP 1.5MM, S/S BODY 1MM, DIMENSION: 44X34X34 (DDS) & 17X34X34 (SD), OIL CAPACITY PER TANK 22LTRS, HIGHLY EFFICIENT BURNERS 120,000BTU, EUROPEAN SOLENOID VALVE, ITALIAN VALE ASSY GENERAL SPECIFICATION - S/S 304TOP 1.5 MM, S/S BODY 1MM, DIMENSION: 44X34X34 (DDS) & 17X34X34 (SD), OIL CAPACITY PER TANK 22LTRS, HIGHLY EFFICIENT BURNERS 120,000BTU, EUROPEAN SOLENOID VALVE, ITALIAN VALE ASSY	
114	DGD109 659	MM-32	731070526967 3 / MEAT MINCER		1 / EACH/NUMBER	mm-32					TECHNICAL SPECIFICATION - capacity: 200kg/hr, power: .90 kw GENERAL SPECIFICATION - capacity: 200kg/hr, power: .90 kw	
115	DGD109 662	D-205	513370527063 8 / BBQ COUNTER PIT 6' WITH CANOPY AND SLIDING DOOR		1 / EACH/NUMBER	D-205					TECHNICAL SPECIFICATION - TOP S/S 1.5 MM, BODY S/S 1 MM, PIT M/S PAINTED 4MM, CANOPY S/S 1MM, OUTER 1828X700X860MM Steel Grade-201 Inner Pit M/S GENERAL SPECIFICATION - TOP S/S 1.5 MM,	

S. No	LPR.No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BODY S/S 1 MM, PIT M/S PAINTED 4MM, CANOPY S/S 1MM, OUTER 1828X700X860MM Steel Grade-201 Inner Pit M/S	
116	DGD109 657	d-523	731070526967 9 / CUTTING BOARD		5 / EACH/NUMBER	d-523					<u>TECHNICAL SPECIFICATION</u> - hard polypropylene material, thickness: 2cm Dimension of Item: 26"x13"x 1/2" <u>GENERAL SPECIFICATION</u> - hard polypropylene material, thickness: 2cm Dimension of Item: 26"x13"x 1/2"	
117	DGE111 281	large 94.2 ltrs 300 plus	811570525959 7 / coleman ice boxes or EQUIVALENT (LARGE) 94.2 LTRS 300 (PLUS)		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM) <u>GENERAL SPECIFICATION</u> - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)	
118	DGD109 655	D-392	731070527066 8 / AIR FRYER		1 / EACH/NUMBER	D-392					<u>TECHNICAL SPECIFICATION</u> - CAPACITY: 800G, POWER: 1425W, ADJUSTABLE THERMOSTAT, NET WEIGHT: 07KG, DIMENSION: 287X315X384MM <u>GENERAL SPECIFICATION</u> - CAPACITY: 800G, POWER: 1425W, ADJUSTABLE THERMOSTAT, NET WEIGHT: 07KG, DIMENSION: 287X315X384MM	
119	DGE111 308	YCR105 or 1260	830578516309 0 / CERAMIC FIBER CLOTH	GENRAL USE	60 / METER	YCR105		OEM:CHINA MANUFACTURERS NINGBO RUIFENG SEALING MATERIAL COMPANY LTD KUANGVAN TOWN CIXI : 86-574-63531211.63531433.	PANASONIC SADDAR KARACHI. TECHNO POWER SYSTEM		<u>TECHNICAL SPECIFICATION</u> - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, temperature resistance= 700 °C (degree centigrade), max thermal conductivity= 0.16 w/m.K <u>GENERAL SPECIFICATION</u> - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											colour = white, tempErature resistance= 700 °C (degree centigrade), max thermal conDuctivity= 0.16 w/m.K	
120	DGE110 646	GGG-H-142	841500935190 6 / SAFETY HELMET YELLOW	PERSONAL PROTECTION	27 / EACH/N UMBER			FEDERAL SPECIFICATIONS UNITED STATES CAGE CODE 81348	FEDERAL SPECIFIC ATIONS		TECHNICAL SPECIFICATION - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000GENERAL SPECIFICATION - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000	
121	DGE109 908	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	1000 / EACH/N UMBER	SSP-01- LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTA N		TECHNICAL SPECIFICATION - AS PER LETTER ATTACHGENERAL SPECIFICATION - AS PER LETTER ATTACH	
122	DGE109 919	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	1000 / EACH/N UMBER	SSP-01- LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTA N		TECHNICAL SPECIFICATION - AS PER LETTER ATTACHGENERAL SPECIFICATION - AS PER LETTER ATTACH	
123	DGE111 269	14.02.0012	035059923357 7 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32- MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED. GENERAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED.	
124	DGE111051	14.02.0012	035059923357 7 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED. GENERAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
125	DGE107675		046279125518 8 / TUBING PLASTICS POLYETHYLENE (LOW DENSITY) FLIM LAY FLAT		15 / KILOGRAMME						TECHNICAL SPECIFICATION - DEFSTAN = 93-116/2 OF 2007 THICKNESS=.0.005" (Double Side) WIDTH = 24". WEIGHT OF ROLL = 48 LBS (APPROX 21.77 KG) LENGTH PER ROLL= 500 FT TYPE = 1 ADVANCE SAMPLE TO BE APPROVED BY CINS GENERAL SPECIFICATION - DEFSTAN = 93-116/2 OF 2007 THICKNESS=.0.005" (Double Side) WIDTH = 24". WEIGHT OF ROLL = 48 LBS (APPROX 21.77 KG) LENGTH PER ROLL= 500 FT TYPE = 1 ADVANCE SAMPLE TO BE APPROVED BY CINS	
126	DGE110687	NIL	035059571312 6 / ROPE NYLON, HAWSERLAID WHITE, 3- STRAND, CIRC: 02- INCH, DIA: 16MM (5/8"),		120 / FATHOM	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL. 3. OEM: COTESI UK GENERAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL. 3. OEM: COTESI UK	
127	DGE109904	TYRE 10X03	041159000692 0 / TRUCK HAND PLATFORM 4- WHEELED TURNABLE 60X36X15" CAP2240LBS		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
128	DGE109832	NO DATA AVAILABLE	033054600448 4 / HEAVING LINE 06MM L50MM 466MS	MSI	800 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - length :06MM L50MM 466MS material : nylon GENERAL SPECIFICATION - length :06MM L50MM 466MS material : nylon	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
129	DGE110 680		046259220336 3 / TUBING PLASTIC POLYETHYLE NE LAY FLAT THICK .010" WIDTH 36" ROLL PACKING.		100 / METER						<u>TECHNICAL SPECIFICATION -</u> Color: Transparent Size: 0.010" x 36" Denomination: Yard/ meter <u>GENERAL SPECIFICATION -</u> Color: Transparent Size: 0.010" x 36" Denomination: Yard/ meter	
130	DGE110 113		422000275315 5 / LIFE BOUY ROUND COLOUR RED OUTER DIA 18"INNER DIA 8"		12 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Inner Dia 45 cm Outer Outer Dia 72 cm Circumference 39 cm Life buoy should have water proof light and recovery line attached to it <u>GENERAL SPECIFICATION -</u> Inner Dia 45 cm Outer Outer Dia 72 cm Circumference 39 cm Life buoy should have water proof light and recovery line attached to it	
131	DGB108 402	66694	451099761024 5 / MIXER SHOWER UNIT 1/2" DUPLEX MIX FITTING TOP OUTLEY FOR 15MM	INLETS CHROME PLATED(COLD &WARM WATER)	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA</u> AVAILABLE	
132	DGE111 062	NO DATA AVAILABL E	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
133	DGE110098	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
134	DGE111 309	073000300 0000A/622 0-02	422071506012 7 / FINS STRAP RUBBER SIZE, LENGTH= 20- INCH (51-CM) , WD= 01-INCH (24 CM)	FOR FINS USE	10 / PAIR						<u>TECHNICAL SPECIFICATION - 1.</u> RUBBER PROFESSIONAL FINS COLOR= BLACK, 2. ADJUSTABLE STRAPS FOR A PERFECT ADAPTATION TO THE DIVER'S FEET, 3. DESIGNED TO COMBINE COMFORT AND PERFORMANCE ROCKET ARE VERY POPULAR AMOUNG PROFESSIONAL AND MILITARY DIVERS, 4. METAL BUCKLES VERSION<u>GENERAL</u> <u>SPECIFICATION - 1.</u> RUBBER PROFESSIONAL FINS COLOR=	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BLACK, 2. ADJUSTABLE STRAPS FOR A PERFECT ADAPTATION TO THE DIVER'S FEET, 3. DESIGNED TO COMBINE COMFORT AND PERFORMANCE ROCKET ARE VERY POPULAR AMONG PROFESSIONAL AND MILITARY DIVERS, 4. METAL BUCKLES VERSION	
135	DGE110 685	NIL	402099923712 1 / ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00", DIA 0.3125" (8MM)	NGTH 1.330 TONS UNIT OF AVAILABILITY	720 / FATHO M						<u>TECHNICAL SPECIFICATION -</u> Local good quality as per stock sample is also acceptable specifications: ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00" DIA 0.3125" (8MM) <u>GENERAL SPECIFICATION -</u> Local good quality as per stock sample is also acceptable specifications: ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00" DIA 0.3125" (8MM)	
136	DGE111 278	nil	533000038292 2 / PACKING- MATERIAL	FUEL OIL SERVICE PMP	100 / METER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C <u>GENERAL SPECIFICATION -</u> SPECIFICATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON-ASBESTOS, TEM UPTO: 400 °C	
137	DGE111 280	MIL-P-15280	564000237482 7 / INSULATION SLEEVING THERMAL		60 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - mil-p-15280</u> Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. <u>GENERAL SPECIFICATION - mil-p-15280</u> Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
138	DGH110 475	REPR0V3 268B	566099200309 4 / BARBED WIRE STEEL ZINC COATED 4 POINTS		500 / KILOGRAMME	Concertina Razor Wire					<u>TECHNICAL SPECIFICATION - 1.</u> Coil outside diameter should be minimum 450 mm. 2. Barbed length minimum 10 mm. 3. Wire gauge 2.5 mm. 4. Razor barbed type is cross. 5. Material is galvanized iron wire. 6. Barbed distance is to be minimum 26 mm. 7. Blade thickness is minimum 0.4 mm. 8. Blade width is minimum 15 mm. <u>GENERAL SPECIFICATION - 1.</u> Coil outside diameter should be minimum 450 mm. 2. Barbed length minimum 10 mm. 3. Wire gauge 2.5 mm. 4. Razor barbed type is cross. 5. Material is galvanized iron wire. 6. Barbed distance is to be minimum 26 mm. 7. Blade thickness is minimum 0.4 mm. 8. Blade width is minimum 15 mm.	
139	DGE109 901	9-27052	626001074423 0 / LIGHT CHEMILUMINESCENT		83 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
140	DGD109 823		773070504806 8 / POT MILK 6 OZ GOLDEN CRESTED		8 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 6 OZ GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u> <u>GENERAL SPECIFICATION - 6 OZ GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u>	
141	DGE111 163	NO DATA AVAILABLE	033050000013 8 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	178 / KILOGRAMME	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - material: lint free Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) CALICO CLOTH BLEACHED: PURE COTTON GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<u>SPECIFICATION</u> - material: lint free Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) CALICO CLOTH BLEACHED: PURE COTTON	
142	DGD109065		7730705048057 / DISH FLAT 12INCH DOLDEN CRESTED		3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
143	DGE111267	NO DATA AVAILABLE	0461500000086 / GOGGLE CHIPPING		215 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band. <u>GENERAL SPECIFICATION</u> - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.	
144	DGE110 657		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
145	DGE110 465		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
146	DGE110 688		834070508791	GENERAL PURPOSE	1 / EACH/N						TECHNICAL SPECIFICATION - 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT		UMBER						SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
147	DGE110613	32B1296	813599220336 3 / TUBING PLASTIC POLYETHYLENE TYPE -1 LAY FLAT WD. 36 THIKNESS 0.010 INCH		185 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - AS</u> AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll(no need of packing) locally available<u>GENERAL SPECIFICATION</u> _AS AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll (no need of packing) locally available	
148	DGE111064	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	5 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAGE					<u>TECHNICAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI- SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
149	DGD107550		734070508044		40 / EACH/N						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			9 / TABLE SPOON		UMBER						Length = 190-200 mm Material = SS 304 food grade base s with golden color. Thickness = 2.5- 3.0 mm Weight = 45- 55 g Finish = Mirror polish with handle design. Edge = Smooth rounded, No sharp edges Packing= VIP single poly/ velvet box Standard= Food grade, lead/nickel free <u>GENERAL SPECIFICATION</u> - Length = 190-200 mm Material = SS 304 food grade base s with golden color. Thickness = 2.5- 3.0 mm Weight = 45- 55 g Finish = Mirror polish with handle design. Edge = Smooth rounded, No sharp edges Packing= VIP single poly/ velvet box Standard= Food grade, lead/nickel free	
150	DGD109 066		733071502328 2 / POT SUGAR		3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
151	DGD111 345		003550000052 0 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		4 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER <u>GENERAL SPECIFICATION</u> - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
152	DGD109 364	NO DATA AVAILAB LE	003550000031 8 / Aluminium covers for utensil cooking (Large) O/D 25.50" TH 10 SWG.		4 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers. <u>GENERAL SPECIFICATION</u> - Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.	
153	DGD107863	NO DATA AVAILAB E	0035500000274 / BOARD KNIFE		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952 <u>GENERAL SPECIFICATION</u> - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952	
154	DGD109365	NO DATA AVAILAB E	0035500000454 / UTENSIL COOKING ALUMINIUM WITH COVER O/D 16-17", INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESSS 10 SWG		8 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) <u>GENERAL SPECIFICATION</u> - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD)	
155	DGD108308		0031546000265 / Glasses Claret cut stem		160 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - Glass Water Drinking Crystal Clear <u>GENERAL SPECIFICATION</u> - Glass Water Drinking Crystal Clear	
156	DGE110659		8345705119862 / SATTON	PRESENTATIO N VIP ITEM	40 / METER						<u>TECHNICAL SPECIFICATION</u> - Length = 20 Meter/Yard Width = 48	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CLOTH WHITE								to 60 Inches <u>GENERAL SPECIFICATION</u> - Length = 20 Meter/Yard Width = 48 to 60 Inches	
157	DGD107545	NO DATA AVAILABLE	0033500000200 / JUGS WATER GLASS 1 QT		3 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - Capacity = 946 ml Material = Borosilicate glass with gold crusted Glass Thickness = 3-5 mm Finish = Clear glass with gold crusted borer, hand decorated. Packing= VIP premium velvet/ gift box Standard= Food grade gold, lead/nickel free <u>GENERAL SPECIFICATION</u> - Capacity = 946 ml Material = Borosilicate glass with gold crusted Glass Thickness = 3-5 mm Finish = Clear glass with gold crusted borer, hand decorated. Packing= VIP premium velvet/ gift box Standard= Food grade gold, lead/nickel free	
158	DGD109650	SWE-01	7330705269667 / SOUP WARMER/BAIN MARIE		2 / EACH/NUMBER	SWE-01					<u>TECHNICAL SPECIFICATION</u> - SIMPLE TEMPERATURE CONTROL KNOB, 220Vac, 50/60hz, 380w has ce certificate, capacity: 10.0l <u>GENERAL SPECIFICATION</u> - SIMPLE TEMPERATURE CONTROL KNOB, 220Vac, 50/60hz, 380w has ce certificate, capacity: 10.0l	
159	DGD109644	PGD-01	7310705270667 / PININI GRILL DOUBLE		1 / EACH/NUMBER	CHZ-810-2					<u>TECHNICAL SPECIFICATION</u> - VOLTAGE"220V-240V/50HZ OR 110V/60HZ, POWER: 3600W, TOP PLATE:210X215MMX2, BOTTOM SIZE:480X230MM, NET WEIGHT: 24.5 KG, PACKING SIZE: 620X395X250MM, TEMPERATURE: 50-300C, MATERIAL:stainless steel 201 body <u>GENERAL SPECIFICATION</u> - VOLTAGE"220V-240V/50HZ OR 110V/60HZ, POWER: 3600W, TOP PLATE: 210X215MMX2, BOTTOM SIZE: 480X230MM, NET WEIGHT: 24.5 KG, PACKING SIZE: 620X395X250MM, TEMPERATURE: 50-300C, MATERIAL:stainless steel 201 body	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
160	DGD109 645	cfmv-01	732070526966 5 / COFFEE VENDING MACHINE		1 / EACH/NUMBER	CFMV-01					<u>TECHNICAL SPECIFICATION</u> - heating fast: 5min, great water qty flow: max. 400ml/cup, dispense great powder qty: max. 100g/cup, continuously dispense cups: above 100cups. power/output:ac 220v/50hz: 1600w, water and capacity: 3canisters, 1600g, boiler capacity: 4.3l <u>GENERAL SPECIFICATION</u> - heating fast: 5min, great water qty flow: max. 400ml/cup, dispense great powder qty: max. 100g/cup, continuously dispense cups: above 100cups. power/output:ac 220v/50hz: 1600w, water and capacity: 3canisters, 1600g, boiler capacity: 4.3l	
161	DGD109 626	MJ-DJ31	733070527066 5 / PANASONIC JUICER BLENDER 3 IN 1		1 / EACH/NUMBER	MJ-DJ31					<u>TECHNICAL SPECIFICATION</u> - BRAND PANASONIC, CAPACITY: 1LTR, VOLTAGE: 800W, JAR MATERIAL TYPE GLASS, OPERAING MODE MANUAL, SKLI 227669609, PK-1447852121, 2 LTR CAPACITY <u>GENERAL SPECIFICATION</u> - BRAND PANASONIC, CAPACITY: 1LTR, VOLTAGE: 800W, JAR MATERIAL TYPE GLASS, OPERAING MODE MANUAL, SKLI 227669609, PK-1447852121, 2 LTR CAPACITY	
162	DGD109 648	pp-01	732070526966 6 / POTATO PEELER		1 / EACH/NUMBER	pp-01					<u>TECHNICAL SPECIFICATION</u> - capacity: 15kg, power: 1500w, voltage: 220v/50hz, net weight: 62kg, dimension: 18x30x26 inch, heavy duty full load 1.5hp motor <u>GENERAL SPECIFICATION</u> - capacity: 15kg, power: 1500w, voltage: 220v/50hz, net weight: 62kg, dimension: 18x30x26 inch, heavy duty full load 1.5hp motor	
163	DGB111 274		027670910659 2 / VICE ENGINEERS WIDTH OF JAW 4.5", NOM	JAW 3-1/4" PARALLEL, QUICK RELEASE	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Jaw Opening: 5.5 Inch Depth of Jaw: 3 Inch Weight with stationary base: 91.1 kg Make/ Model: England <u>GENERAL SPECIFICATION</u> - Jaw	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OPENING 5-1/2",								Opening: 5.5 Inch Depth of Jaw: 3 Inch Weight with stationary base: 91.1 kg Make/ Model: England	
164	DGE110842	item grade 18-swg	7125705245959 / PERSONAL LOCKERS CUM ALMIRAH STEEL DIMENSIONS HEIGHT 05 x foot '11" inch FRONT WIDTH 01 x foot '06" inch SIDE WIDTH 01 x foot '08" inch		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
165	DGE87587	RB10002 local	6150705264085 / INSULATION RUBBER MAT		25 / FOOT	NA					TECHNICAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm. GENERAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm.	
166	DGD110053	NO DATA AVAILABLE	0032500000171 / SPOON TABLE MEDIUM S/STEEL		100 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - pn crest is to be embossed. specs : stainless steel grade 316 GENERAL SPECIFICATION - pn crest is to be embossed. specs : stainless steel grade 316	
167	DGB111273	H 2956	0276709106593 / VICE ENGINEER WIDTH OF JAW 6"NOM OPENING 7.250 D OF JAW 04IN	7-1/4", PARALLEL QUICK RELEASE	2 / EACH/NUMBER	63302					TECHNICAL SPECIFICATION - dimension: (l x w x h): 18 x 8.7 x 9.7 brand: wilton tools material: cast iron. manufacture: jpw industries inc wilton uk GENERAL SPECIFICATION - dimension: (l x w x h): 18 x 8.7 x 9.7 brand: wilton tools material: cast iron manufacture: jpw industries inc wilton uk	
168	DGE78765	ITD	0413599238926 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		17 / KILOGRAMME						TECHNICAL SPECIFICATION - COMPLETE SPECIFICATION (PN/TECH SPECS/RSSN/03/2026) IS ATTACHED WITH LETTER (PN/DID/PROJECTS/6761360 DATED 17 AUG 2026). GENERAL SPECIFICATION - COMPLETE SPECIFICATION (PN/TECH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECS/RSSN/03/2026) IS ATTACHED WITH LETTER (PN/DID/PROJECTS/6761360 DATED 17 AUG 2026).	
169	DGB111 276	SPECIFIC ATION BS 887	027459910007 7 / CALIPER VERNIER ENG&MM COMB IN&EXT W/CASE 0-TO9"(0-TO-225MM)	MEASURING TOOL	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION BS 887GENERAL SPECIFICATION - SPECIFICATION BS 887	
170	DGB111 275	1A1155	027470910496 6 / FILE ENGINEER THREE SQUARE D- CUT SMOOTH 4" LG,11 MM WIDTH		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - TRIANGLE FILE SIZE: 5 INCHGENERAL SPECIFICATION - TRIANGLE FILE SIZE: 5 INCH	
171	DGE111 048	NO DATA AVAILAB LE	035059923713 0 / ROPE NYLON HAWSERLAID, DIA: 28-MM, 3-STRAND	MIN BRKG STRENGTH 15.500 TONS UNIT OF	120 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
172	DGE108 944	NIL	035059923713 1 / ROPE NYLON HAWSERLAID, 3-STRAND, Z- LAY TYPE-I, SIZE: CIRC 4", NOM DIA: 32MM	BRKG STRENGTH UNIT OF AVAILABILITY 322LB	120 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
173	DGD110 049		0032500032008 / KNIVES BUTTER FOR CNS		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - MATERIAL S/S 304 /316 FOOD GRADE NON MAGNETIC (LOCAL) PN CREST ENGRAVED ON KNIFE STAINLESS STEEL M/GRADE SS 304/316 (FOOD GRADE) LENGTH 21 TO 23 CM <u>GENERAL SPECIFICATION</u> - MATERIAL S/S 304 /316 FOOD GRADE NON MAGNETIC (LOCAL) PN CREST ENGRAVED ON KNIFE STAINLESS STEEL M/GRADE SS 304/316 (FOOD GRADE) LENGTH 21 TO 23 CM	
174	DGE106	CM6538-	597070504435		45 /						<u>TECHNICAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	278	000	2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		EACH/NUMBER						Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes <u>GENERAL SPECIFICATION</u> - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
175	DGB107600	NO DATA AVAILABLE	026850000004 4 / SALTER-COUNTER-SCALE-MODLE250-CAP-15-KG		2 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
176	DGD107530		773070504805 9 / DISH BUTTER GOLDEN CRESTED		9 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Capacity = 250 -300 g butter Weight = 550- 600 g approx Size = L 20 x W 13 x H 10 cm Base tray- SS 304 mirror finish Grade = VIP Standard Lid/ Cover = High Clear lead - free glass, sheesha Lid knob = Golden crusted designer knob Glass Thickness = 4 mm toughened Steel Thickness = 0.8 mm heavy Finish = Mirror steel + gold crust, clear glass Packing = VIP gift box with foam <u>GENERAL SPECIFICATION</u> - Capacity = 250 -300 g butter Weight = 550- 600 g approx Size = L 20 x W 13 x H 10 cm Base tray- SS 304 mirror finish Grade = VIP Standard Lid/ Cover = High Clear lead - free glass, sheesha Lid knob = Golden crusted designer knob Glass Thickness = 4 mm toughened Steel Thickness = 0.8 mm heavy Finish =	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Mirror steel + gold crust, clear glass Packing = VIP gift box with foam	
177	DGE111353	NO DATA AVAILABLE	834050503926 1 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		4 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: gold. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos <u>GENERAL SPECIFICATION - 1.</u>Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: gold. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos	
178	DGB108688	NO DATA AVAILABLE	4510590010754 / WASH BASIN CEREMIC.		5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
179	DGD99094	NO DATA AVAILABLE	0035500000318 / Aluminium covers for utensil cooking (Large) O/D 25.50" TH 10 SWG.		8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers. GENERAL SPECIFICATION - Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.	
180	DGH95530	NO DATA AVAILABLE	5305ZO6568045 / LAWN MOVER MACHINE		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
181	DGH95573	NO DATA AVAILABLE	5305ZO6568045 / LAWN MOVER		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MACHINE									
182	DGD107163	29161900	6505705193058 / FUEL TABLETS	MRE PACKS (04 IN ONE PACKET)	175 / PACKET	N/A	N/A	PANA FORCE FOODS ASC NOWSHEHRA KPK	PANA FORCE FOODS		TECHNICAL SPECIFICATION - ARTICLE NAME AND DETAILS Solid Fuel Tablet Specifications Physical Characteristics Diameter: 2 inches Shape: Cylindrical Cross Mark: For breaking into 4 equal pieces Weight: 28-30 Grams per tablet Burning Time: 17-20 minutes per tablet ash proof 1. 1 Tablet: Boil 1 liter of water 2. 1/2 Tablet: Boil 3 cups of water or make 3 cup of tea 3. 1/4 Tablet: Make 1 Cup of tea Burning Time for Fractions 1. 1/2 Tablet: Approximately 14 Minutes 2. 1/4 Tablet: Approximately 09 Minutes 1. Number of tablets: 5 in One Bottle 2. Total Burning time: Approximately 1 Hours GENERAL SPECIFICATION - ARTICLE NAME AND DETAILS Solid Fuel Tablet Specifications Physical Characteristics Diameter: 2 inches Shape: Cylindrical Cross Mark: For breaking into 4 equal pieces Weight: 28-30 Grams per tablet Burning Time: 17-20 minutes per tablet ash proof 1. 1 Tablet: Boil 1 liter of water 2. 1/2 Tablet: Boil 3 cups of water or make 3 cup of tea 3. 1/4 Tablet: Make 1 Cup of tea Burning Time for Fractions 1. 1/2 Tablet: Approximately 14 Minutes 2. 1/4 Tablet: Approximately 09 Minutes 1. Number of tablets: 5 in One Bottle 2. Total Burning time: Approximately 1 Hours	